

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Product Data Sheet

MARATHON® SPECIAL PRODUCTS
A REGAL-BELOIT Company



F30AXSP

Replace “X” with 1, 2 or 3 for number of poles

Class H Fuse Holder
30 Amps, 250 Volts AC/DC

Wire Range:
#10 - #14 AWG Cu

Holds fuse size 9/16” diameter X 2”

Commonly used fuses in this holder: A2Y, CRN, NLN, NON, NRN, OT, OTN, RLN, RF

See tables below for wire sizes.

Electrical Ratings:
• 0 - 30A max (amperage rating based on maximum fuse rating for that physical size)
• Copper wire only
• 250 Volts AC/DC
• Approved for 10,000 Amp Withstand Rating

Mechanical Ratings:
• Insulator base temperature rating: -40°C/F to 125°C (257°F) UL RTI
• Flammability rating of insulator base: UL 94V-0
• Touch protection: IP-20 (IEC 60529) with optional cover CHR230 (See accessories)
- Use outside these ratings needs to be judged in the end-use application.

Materials:
• Fuse Clip: Copper alloy, tin plated
• Insulator base: Glass filled polycarbonate (thermoplastic)
• Straddle plate thread forming #10-32 screws: Steel, tin plated
• Fuse Clip anchor screws: Steel, zinc plated

Agency Approvals:
• UL Listed, Fuseholder standards UL 4248-1 and UL 4248-6.
• UL File No. IZLT.E35113
• CSA Certified, CSA C22.2 No. 39 – M1987, File No. LR21455
• CE compliant to IEC 60947-1
• RoHS Compliant


Wire Approvals:

Wire	Torque		Copper Wire Stranding Classes - Number of Strands		
Size	N-m	**In. lbs.**	Solid	Class B	Class C
10	2.8	25	1	1	1
12	2.8	25	1	1	1
14	2.8	25	1	1	1

- Wire strip length – 7/16”
- Panel mountable: #10 fastener, torque to 25-30 in. lbs. (2.8 - 3.4 N-m)

Accessories:

- Cover: CHR230. Glass-filled polycarbonate (thermoplastic). 125°C (UL RTI), Flammability rating UL 94 V-0, UL Listed File No. JDVS2.181825.
- DIN Rail Adapter: Din R-1



WWW.MARATHONSP.COM
1-419-352-8441

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP