

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

marathon™
Special Products

High SCCR with Fuse Protection





UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1321570	1	175	(1) 2/0 - 14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322570	2						2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1323570	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1321572	1	175	(1) 2/0 - 14	(1) 2/0 - 14			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322572	2						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1323572	3																	
1321574	1	175	(1) 2/0 - 14	(1) 1/4 - 20 x 1/2			2/0-6	2/0-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322574	2						2/0-10	8-10	B, C	150	150	100	30	60	30	100,000 A		
1323574	3						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1321580	1	175	(1) 2/0 - 14	(6) 4 - 14			2/0-6	4-12	B, C	200	200	100	60	60	30	100,000 A	Recognized	XCFR2.E62806
1322580	2						2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1323580	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1321970	1	175	(1) 2/0 - 14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322970	2						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1323970	3																	
1321972	1	175	(1) 2/0 - 14	(1) 2/0 - 14			2/0-6	2/0-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1322972	2						1-6	6-14	G, H, I	150	150	100	30	60	30	100,000 A		
1323972	3																	
1331320	1	510	(2) 250 - 1/0	(2) 250 - 1/0			250-1/0	250-1/0	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332320	2						3/0-1/0	3/0-1/0	G, H, I	500	500	400	200	60	30	100,000 A		
1333320	3																	
1331360	1	420	(1) 600 - 2	(1) 600 - 2			600-2	600-2	B, C	600	600					50,000,A	Recognized	XCFR2.E62806
1332360	2						600-2	600-2	B, C	400	400	400	200	60	30	100,000,A		
1333360	3						350-2	350-2	G, H, I	400	400	400	200	60	30	100,000,A		
1331552	1	335	(1) 400 - 6	(4) 2 - 14			400-3/0	2-8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332552	2						400-6	2-8	B, C	200	200	200	100	60	30	100,000 A		
1333552	3						250-1/0	1-6	G, H, I	150	150	100	30	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection







UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS													
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) (2)			Overcurrent Protection Fuse Required Class/Max Amp Rating (3)										
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1331554	1	310	(1) 350 - 6	(2) 2/0 - 14			350-3/0	2/0-1	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332554	2						350-6	2/0-10	B, C	200	200	200	100	60	30	100,000 A		
1333554	3						250-1/0	1-10	G, H, I	150	150	100	30	60	30	100,000 A		
1331555	1	350	(2) 2/0 - 14	(6) 4 - 14			2/0-2	4-8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332555	2						2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A		
1333555	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1331559	1	310	(1) 350 - 6	(1) 3/8 - 16 x 1 1/4			350-4	350-4	B, C	400	400	400	100	60	30	65,000 A	Recognized	XCFR2.E62806
1332559	2						250-4	250-4	G, H, I	300	300	200	100	60	30	65,000 A		
1333559	3																	
1331575	1	420	(1) 600 - 2	(4) 2/0 - 14			600 - 2	2/0 - 10	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332575	2																	
1333575	3																	
1331585	1	420	(1) 600 - 2	(8) 2 - 14			600-3/0	2-8	B, C	400	400	400	200	60	30	100,000,A	Recognized	XCFR2.E62806
1332585	2						600-2	2-10	B, C	200	200	200	100	60	30	100,000,A		
1333585	3						350-2	4-10	G, H, I	150	150	100	30	60	30	100,000,A		
1331587	1	380	(1) 500 - 4	(3) 2 - 14			500-3/0	350-6	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332587	2						500-4	2-10	B, C	200	200	200	100	60	30	100,000 A		
1333587	3			(1) 350 - 6			350-2	1-6	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	1-10	G, H, I	200	200	200	100	60	30	100,000 A		
1331588	1	420	(1) 600 - 2	(6) 2 - 14			600-3/0	1/0-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332588	2						600-2	1/0-10	B, C	200	200	200	100	60	30	100,000 A		
1333588	3			(3) 1/0 - 14			350-2	1-8	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	1-10	G, H, I	200	200	200	100	60	30	100,000 A		
1331595	1	420	(1) 600 - 2	(12) 4 - 14			600-3/0	4-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1332595	2						600-2	4-10	B, C	200	200	200	100	60	30	100,000 A		
1333595	3						350-2	6-10	G, H, I	150	150	100	30	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection



UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1331596	1	510	(2) 250 - 6	(12) 4 - 14			250-1/0	4-10	B, C	450	450	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332596	2						3/0-1/0	6-14	G, H, I	150	150	100	30	60	30	100,000 A		
1333596	3																	
1331597	1	510	(2) 250 - 1/0	(8) 2 - 14			250-1/0	2-8	B, C	350	350	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332597	2						3/0-1/0	4-14	G, H, I	150	150	100	30	60	30	100,000 A		
1333597	3																	
1331953	1	380	(1) 500 - 4	(6) 2 - 14			500-3/0	2-10	B, C	400	400	400	100	60	30	100,000,A	Recognized	XCFR2.E62806
1332953	2						500-4	2-10	B, C	200	200	200	100	60	30	100,000,A		
1333953	3						350-2	4-10	G, H, I	150	150	100	30	60	30	100,000,A		
1331955	1	350	(2) 2/0 - 14	(6) 4 - 14			2/0-2	4/8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1332955	2						2/0-6	4-10	B, C	200	200	200	60	60	30	100,000 A		
1333955	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1402401	2	175	(1) 2/0 - 14	(6) 4 - 14			2/0-6	4-14	B, C	200	200	100	100	60	30	100,000 A	Recognized	XCFR2.E62806
							2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1403401	3						1-10	6-14	G, H, I	60	60	60	30		30	100,000 A		
1402402	2	175	(1) 2/0 -14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1403402	3						1-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1402404	2	310	(1) 350 - 6	(6) 4 - 14			350-3/0	4-8	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							350-6	4-10	B, C	250	250	200	100	60	30	100,000 A		
1403404	3						250-6	6-10	G, H, I	150	150	100	30	60	30	100,000 A		
1411300	1	115	(1) 2 - 14	(1) 2 - 14			2-6	2-6	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1412300	2						2-10	2-10	B, C	100	100	100	30	60	30	100,000 A		
1413300	3						2-10	2-10	B, C	125	125	60	30	60	30	65,000 A		
1414300	4						4-10	4-10	G, H, I	150	150	100	30	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection







UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1411400	1	115	(1) 2 - 14	(4) 10 - 16			2-6	10	B, C	200	200	200	60	60	30	100,000 A	Recognized	XCFR2.E62806
1412400	2						2-10	10-14	B, C	150	150	100	30	60	30	100,000 A		
1413400	3						2-12	10-14	B, C	60	60	30		50	30	100,000 A		
1414400	4						4-10	10-14	G, H, I	150	150	100	30	60	30	100,000 A		
1421120	1	175	(1) 2/0 - 14	(1) 2/0 - 14			2/0-6	2/0-6	B, C	300	300	200	100	60	30	65,000 A	Recognized	XCFR2.E62806
1422120	2						1-6	1-6	G, H, I	300	300	200	100	60	30	65,000 A		
1423120	3																	
1421121	1	150	(1) 1/0 - 18	(1) 1/0 - 18			1/0-6	1/0-6	B, C	175	175	100	60	60	30	100,000 A	Recognized	XCFR2.E62806
1422121	2						1-6	1-6	G, H, I	175	175	100	60	60	30	100,000 A		
1423121	3																	
1421552	1	115	(1) 2 - 14	(1) 2 - 14			2-6	2-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1422552	2						2-10	2-10	B, C	150	150	100	30	60	30	100,000 A		
1423552							2-10	2-10	B, C	200	200	100	30	60	30	65,000 A		
	3						4-10	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1421553	1	175	(1) 2/0 - 14	(1) 1/4-20 X 1/2			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1422553	2						2/0-10	2/0-10	B, C	100	100	100	30	60	30	100,000 A		
1423553	3						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1421570	1	175	(1) 2/0 - 14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1422570	2						2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1423570	3						(1) 6	(2) 12 or 14	B, C	225	225	100	60	60	30	100,000 A		
							1-6	6-12	G, H, I	150	150	100	30	60	30	100,000 A		
1421572	1	175	(1) 2/0 - 14	(1) 2/0 - 14			2/0-6	2/0-6	B, C	300	300	200	100	60	30	65,000 A	Recognized	XCFR2.E62806
1422572	2						1-6	1-6	G, H, I	300	300	200	100	60	30	65,000 A		
1423572	3																	
1421574	1	175	(1) 2/0 - 14	(1) 1/4-20 X 1/2			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1422574	2						2/0-10	2/0-10	B, C	100	100	100	30	60	30	100,000 A		
1423574	3						1-6	1-6	G, H, I	150	150	100	30	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection












UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) (2)			Overcurrent Protection Fuse Required Class/Max Amp Rating (3)								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1421970	1	175	(1) 2/0 - 14	(4) 4 - 14			2/0-6	4-10	B, C	200	200	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1422970	2						2/0-10	4-14	B, C	150	150	100	30	60	30	100,000 A		
1423970	3						1-6	6-12	G, H, I	150	150	100	30	60	30	100,000 A		
1431123	1	255	(1) 250 - 6	(1) 250 - 6			250-6	250-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1432123	2						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
1433123	3																	
1431124	1	255	(1) 250 - 6	(1) 250 - 6			250-6	250-6	B, C	300	300	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
1432124	2						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
1433124	3																	
1431126	1	310	(1) 350 - 6	(1) 350 - 6			350-1/0	350-1/0	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1432126	2						350-6	350-6	B, C	300	300	200	100	60	30	100,000 A		
1433126	3						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
1431552	1	335	(1) 400 - 6	(4) 2 - 14			400-3/0	2-6	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1432552	2						400-6	2-10	B, C	300	300	200	100	60	30	100,000 A		
1433552	3						250-1/0	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1431553	1	335	(1) 400 - 6	(6) 2 - 14			400-3/0	2-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1432553	2						400-6	2-10	B, C	350	350	200	100	60	30	100,000 A		
1433553	3						(1) 6	(2) 12	B, C	350	350	200	100	60	30	100,000 A		
							250-1/0	4-10	G, H, I	150	150	100	30	30	60	100,000 A		
1431554	1	310	(1) 350 - 6	(2) 2/0 - 14			350-3/0	2/0-3	B, C	450	450	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1432554	2						350-6	2/0-6	B, C	300	300	200	100	60	30	100,000 A		
1433554	3						250-1/0	1-6	G, H, I	150	150	100	30	60	30	100,000 A		
1431555	1	350	(2) 2/0 - 14	(6) 4 - 14			2/0-2	4-8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1432555	2						2/0-6	4-8	B, C	350	350	200	100	60	30	100,000 A		
1433555	3						2/0-6	4-10	B, C	250	250	200	60	60	30	100,000 A		
							(1) 6	(2) 12	B, C	225	225	100	60	60	30	100,000 A		
							1-6	6-14	G, H, I	150	150	100	30	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection












UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1431559	1	310	(1) 350 - 6	(1) 3/8 - 16 x 1 1/8			350-4	350-4	B, C	400	400	400	100	60	30	65,000 A	Recognized	XCFR2.E62806
1432559	2						250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	65,000 A		
1433559	3																	
1431587	1	380	(1) 500 - 4	(3) 2 - 14			500-3/0	350-6	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1432587	2						500-4	350-10	B, C	200	200	200	100	60	30	100,000 A		
1433587	3			(1) 350 - 6			350-2	250-1/0	G, H, I	150	150	100	30	60	30	100,000 A		
							350-2	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1431953	1	380	(1) 500 - 4	(6) 2 - 14			500-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1432953	2						500-4	2-10	B, C	300	300	200	100	60	30	100,000 A		
1433953	3						250-1/0	4-10	G, H, I	150	150	100	30	60	30	100,000 A		
1431955	1	350	(2) 2/0 - 14	(6) 4 - 14			2/0-2	4-8	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1432955	2						2/0-6	4-8	B, C	350	350	200	100	60	30	100,000 A		
1433955	3						4-10	10-14	G, H, I	150	150	100	30	60	30	100,000 A		
1441551	1	380	(1) 500 - 4	(6) 2 - 14			500-3/0	2-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1442551	2						500-4	2-10	B, C	200	200	200	100	60	30	100,000 A		
1443551	3						350-2	4-14	G, H, I	150	150	100	30	60	30	100,000 A		
1441560	1	335	(1) 400 - 6	(8) 2 - 14			400-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1442560	2						400-6	2-10	B, C	200	200	200	100	60	30	100,000 A		
1443560	3						250-1/0	4-14	G, H, I	150	150	100	30	60	30	100,000 A		
1441557	1	420	(1) 600 - 4	(1) 600 - 4			600-2	600-2	B, C	600	600	-	-	-	-	50,000 A	Recognized	XCFR2.E62806
1442557	2						600-2	600-2	B, C	400	400	400	200	60	30	100,000 A		
1443557	3						350-2	350-2	G, H, I	400	400	400	200	60	30	100,000 A		
1451129	1	620	(2) 350 - 4	(2) 350 - 4			350-4	350-4	B, C	450	450	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
1452129	2						350-4	350-4	B, C	600	600	-	-	-	-	50,000 A		
1453129	3						250-2	250-2	G, H, I	600	600	-	-	-	-	50,000 A		
							250-2	250-2	G, H, I	450	450	400	200	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection








UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) (2)			Overcurrent Protection Fuse Required Class/Max Amp Rating (3)								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1451301 1452301 1453301	1 2 3	760	(2) 500 - 4	(2) 500 - 4			500-4	500-4	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							350-2	350-2	G, H, I	500	500	400	200	60	30	100,000 A		
1451552 1452552 1453552	1 2 3	380	(1) 500 - 4	(12) 2 - 14			500-3/0	2-6	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	2-10	B, C	250	250	200	100	60	30	100,000 A		
							350-2	4-6	G, H, I	400	400	400	200	60	30	100,000 A		
							350-2	4-10	G, H, I	250	250	200	200	60	30	100,000 A		
1451579 1452579 1453579	1 2 3	380	(1) 500 - 4	(6) 2/0 - 14			500-3/0	2/0-6	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	2/0-10	B, C	200	200	200	100	60	30	100,000 A		
							350-2	1-6	G, H, I	400	400	400	100	60	30	100,000 A		
							350-2	1-10	G, H, I	250	250	200	100	60	30	100,000 A		
1451586 1452586 1453586	1 2 3	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	600	600	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	2/0-10	B, C	350	350	200	100	60	30	100,000 A		
							350-250	1-4	G, H, I	600	600	400	200	60	30	100,000 A		
							350-4	6-10	G, H, I	350	350	200	100	60	30	100,000 A		
1451592 1452592 1453592	1 2 3	760	(2) 500 - 4	(12) 4 - 14			500-250	4-8	B, C	400	400	200	100	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	4-10	B, C	350	350	200	100	60	30	100,000 k		
							350-250	6-8	G, H, I	400	400	200	100	60	30	100,000 k		
							350-4	6-10	G, H, I	350	350	200	100	60	30	100,000 k		
1451594 1452594 1453594	1 2 3	380	(1) 500 - 4	(8) 2 - 14			500-3/0	2-8	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	2-10	B, C	300	300	200	100	60	30	100,000 A		
							350-3/0	4-8	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	4-10	G, H, I	300	300	200	100	60	30	100,000 A		
1451599 1452599 1453599	1 2 3	760	(2) 500 - 4	(2) 3/8 - 16 x 1 5/16			500-4/0	500-4/0	B, C	600	600	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	500-4	B, C	400	400	400	100	60	30	100,000 A		
							350-4/0	350-4/0	G, H, I	600	600	400	200	60	30	100,000 A		
							350-2	350-2	G, H, I	400	400	400	100	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1451986 1452986 1453986	1 2 3	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	500	500	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							500-4	2/0-6	B, C	450	450	400	200	60	30	100,000 A		
							350-250	1-4	G, H, I	500	500	400	200	60	30	100,000 A		
							350-2	1-6	G, H, I	450	450	400	200	60	30	100,000 A		
1451992 1452992 1453992	1 2 3	760	(2) 500 - 4	(12) 2 - 14			500-4	2-10	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							500-250	2-8	B, C	600	600	-	-	-	-	50,000 A		
							350-2	4-10	G, H, I	400	400	400	200	60	30	100,000 A		
							350-250	4-8	G, H, I	600	600	-	-	-	-	50,000 A		
EPBAP71	1	510	(2) 250 - 6	(2) 250 - 6			250-1/0	250-1/0	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							250 - 1/0	250 - 1/0	B, C	600	600	-	-	-	-	50,000 A		
							250-6	250-6	B, C	400	400	400	100	60	30	100,000 A		
							250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
EPBAP74	1	335	(1) 400 - 6 (1) 2/0 - 14	(8) 2 - 14			400-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							400-6	2-10	B, C	200	200	200	100	60	30	100,000 A		
							400-6	2-10	G, H, I	300	300	200	100	60	30	100,000 A		
EPBCP71	1	510	(2) 250 - 6	(2) 250 - 6			250-1/0	250-1/0	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							250 - 1/0	250 - 1/0	B, C	600	600	-	-	-	-	50,000 A		
							250-6	250-6	B, C	400	400	400	100	60	30	100,000 A		
							250-1/0	250-1/0	G, H, I	300	300	200	100	60	30	100,000 A		
EPBCP74	1	335	(1) 400 - 6 (1) 2/0 - 14	(8) 2 - 14			400-3/0	2-8	B, C	400	400	400	200	60	30	100,000 A	Recognized	XCFR2.E62806
							400-6	2-10	B, C	200	200	200	100	60	30	100,000 A		
							(1) 6	(2) 12	B, C	225	225	100	60	60	30	100,000 A		
							400-6	2-10	G, H, I	300	300	200	100	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection




UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS													
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]										
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
BFPB	2	1605	Lugs or Flexibar				750 - 350 kcmil			1200	600	1200	600	600		100,000 A	Recognized	XCFR2.E62806
	3						10x100x1 - 4x32x1			1200	600	1200	600	600		100,000 A		
	4						750 - 350 kcmil			No Over-Current Protection Device Required						35,000 A		
	5						10x100x1 - 4x32x1			No Over-Current Protection Device Required						35,000 A		
	6						Applicable lugs/Flexibar			No Over-Current Protection Device Required						10,000		
EPBAD21	1	115	(1) 2 - 14	(1) 2 - 14			2-14	2-14	B, C	175	225	100	60	60	30	100,000 A	Listed	QPQS.E309401
							4 - 14 (class G,H,I,K)	4 - 14 (class G,H,I,K)	G, H, I	175	225	100	60	60	30	100,000 A		
EPBAD24	1	115	(1) 2 - 14	(4) 10 - 14			2 - 10	10 - 14	B, C	125	200	100	30	60	30	65,000 A	Listed	QPQS.E309401
							4- 10 (class G,H,I,K)	10 - 14 (class G,H,I,K)	G, H, I	125	200	100	30	60	30	65,000 A		
EPBAD42	1	175	(1) 3/0 - 14	(1) 3/0 - 14			3/0-8	3/0-8	B, C	225	225	200	60	60	30	100,000 A	Listed	QPQS.E309401
EPBAP42							2/0-8	2/0-8	G, H, I	300	300	200	100	60	30	100,000 A		
EPBCD42							3/0-8	3/0-8	B, C	225	225	200	60	60	30	100,000 A		
EPBCP42							2/0-8	2/0-8	G, H, I	300	300	200	100	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection





UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) (2)			Overcurrent Protection Fuse Required Class/Max Amp Rating (3)								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
EPBAD45	1	175	(1) 3/0 - 14	(4) 2 - 14			3/0-8	2-8	B, C	225	225	200	60	60	30	100,000 A	Listed	QPQS.E309401
							3/0-8	8-14	B, C	100	110	100	30	60	30	100,000 A		
							2/0-8	4-8	G, H, I	225	225	200	60	60	30	100,000 A		
							2/0-8	8-12	G, H, I	100	110	100	30	60	30	100,000 A		
							3/0-10	2-14	G, H, I	60	60	30		50	30	100,000 A		
							(1) 8	(2) 14	G, H, I	225	225	100	60	60	30	100,000 A		
EPBAP45							3/0-8	2-8	B, C	225	225	200	60	60	30	100,000 A		
							3/0-8	8-14	B, C	100	110	100	30	60	30	100,000 A		
							2/0-8	4-8	G, H, I	225	225	200	60	60	30	100,000 A		
							2/0-8	8-12	G, H, I	100	110	100	30	60	30	100,000 A		
EPBCD45							3/0-8	2-8	B, C	225	225	200	60	60	30	100,000 A		
							3/0-8	8-12	B, C	100	110	100	30	60	30	100,000 A		
EPBCP45							2/0-8	4-8	G, H, I	225	225	200	60	60	30	100,000 A		
							2/0-8	8-12	G, H, I	100	110	100	30	60	30	100,000 A		
EPBAP81	1	760	(2) 500 - 4	(2) 500 - 4			500-4	500-4	B, C	600	600	600	200	60	30	100,000 A	Listed	QPQS.E309401
							350-2	350-2	G, H, I	600	600	600	200	60	30	100,000 A		
EPBAP84	1	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	600	600	400	200	60	30	100,000 A	Listed	QPQS.E309401
							500-4	2/0-10	B, C	350	350	200	100	60	30	100,000 A		
							350-250	1-4	G, H, I	600	600	600	200	60	30	100,000 A		
							350-4	1-8	G, H, I	350	350	200	100	60	30	100,000 A		
EPBCP84	1	760	(2) 500 - 4	(8) 2/0 - 14			500-250	2/0-4	B, C	600	600	600	200	60	30	100,000 A	Listed	QPQS.E309401
							500-4	2/0-10	B, C	350	350	200	100	60	30	100,000 A		
							350-250	1-4	G, H, I	600	600	600	200	60	30	100,000 A		
							350-4	1-8	G, H, I	350	350	200	100	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection






UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1351605 1352605 1353605	1 2 3	950	(2) 600 - 2	(4) 350 - 6			600 - 2	2/0-10	B, C	400	400	400	100	60	30	100,000 A	Recognized	XCFR2.E62806
1351701 1352701 1353701	1 2 3	475	750 - 1/0	750 - 1/0			750-1/0 535-1/0	750-1/0 535-1/0	B, C G, H, I	600 600	1200 700	600 600	400 200	60 60	- -	100,000 A 100,000 A	Listed	QPQS.E309401
1351702 1352702 1353702	1 2 3	950	(2) 750 - 1/0	(2) 750 - 1/0			750-1/0 535-1/0	750-1/0 535-1/0	B, C G, H, I	600 600	1200 700	600 600	400 200	60 60	- -	100,000 A 100,000 A	Listed	QPQS.E309401
1351703 1352703 1353703	1 2 3	950	(2) 750 - 1/0	(6) 250 - 6			750-1/0 750-1/0 535-1/0 535-1/0	250-2 250-6 3/0-2 3/0-6	B, C B, C G, H, I G, H, I	600 300 600 300	700 300 700 300	600 200 600 200	200 100 200 100	60 60 60 60	- - - -	100,000 A 100,000 A 100,000 A 100,000 A	Listed	QPQS.E309401
1351704 1352704 1353704	1 2 3	950	(2) 750 - 1/0	(10) 2/0 - 6			750-1/0 750-1/0 535-1/0 535-1/0	2/0-2 2/0-6 1-2 1-6	B, C B, C G, H, I G, H, I	600 300 600 300	700 300 700 300	600 200 600 200	200 100 200 100	60 60 60 60	- - - -	100,000 A 100,000 A 100,000 A 100,000 A	Listed	QPQS.E309401
1351705 1352705 1353705	1 2 3	950	(2) 750 - 1/0	(3) 250 - 6 (12) 2 - 14			750-1/0 750-1/0 750-1/0 535-1/0 535-1/0 535-1/0	250-2 250 - 6 2 - 6 (#2 opening) 3/0-2 3/0-6 4 - 6 (#2 opening)	B, C B, C B, C G, H, I G, H, I G, H, I	600 300 300 600 300 300	700 300 300 700 300 300	600 200 200 600 200 200	200 100 100 200 100 100	60 60 60 60 60 60	- - - - - -	100,000 A 100,000 A 100,000 A 100,000 A 100,000 A 100,000 A	Listed	QPQS.E309401

marathon™
Special Products

High SCCR with Fuse Protection




UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS										
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) [2]			Overcurrent Protection Fuse Required Class/Max Amp Rating [3]							
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
1351706	1	950	(2) 750 - 1/0	(5) 250 - 6 (4) 2 - 14			750-1/0	250-2	B, C	600	600	600	200	60	-	100,000 A	Listed	QPQS.E309401
1352706	2						750-1/0	250 - 6	B, C	300	300	200	100	60	-	100,000 A		
1353706	3						750-1/0	2 - 6 (#2 opening)	B, C	300	300	200	100	60	-	100,000 A		
							535-1/0	3/0-2	G, H, I	600	600	600	200	60	-	100,000 A		
							535-1/0	3/0-6	G, H, I	300	300	200	100	60	-	100,000 A		
							535-1/0	4 - 6 (#2 opening)	G, H, I	300	300	200	100	60	-	100,000 A		
1351707	1	950	(2) 750 - 1/0	(4) 3/0 - 6 (12) 2 - 14			750-1/0	3/0-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
1352707	2						750-1/0	3/0 - 6	B, C	300	300	200	100	60	-	100,000 A		
1353707	3						750-1/0	2 - 6 (#2 opening)	B, C	300	300	200	100	60	-	100,000 A		
							535-1/0	2/0-2	G, H, I	500	500	400	200	60	-	100,000 A		
							535-1/0	2/0-6	G, H, I	300	300	200	100	60	-	100,000 A		
							535-1/0	4 - 6 (#2 opening)	G, H, I	300	300	200	100	60	-	100,000 A		
1351708	1	950	(2) 750 - 1/0	(8) 3/0 - 6			750-1/0	3/0-2	B, C	600	700	600	200	60	-	100,000 A	Listed	QPQS.E309401
1352708	2						750-1/0	3/0 - 6	B, C	300	300	200	100	60	-	100,000 A		
1353708	3						535-1/0	3/0-2	G, H, I	500	500	400	200	60	-	100,000 A		
							535-1/0	2/0-6	G, H, I	300	300	200	100	60	-	100,000 A		
FPB23570	3	175	2/0-6	4-14													Listed	QPQS.E309401
							2/0-6	4-14	B, C	200	200	200	100	60	30	100,000 A		
FPB23572	3	175	2/0-6	2/0-6													Listed	QPQS.E309401
							2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A		
FPB23574	3	175	2/0-6 2/0-10	2/0-6 2/0-10			2/0-6	2/0-6	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401
							8-10	8-10	B, C	100	100	100	30	60	30	100,000 A		

marathon™
Special Products

High SCCR with Fuse Protection

UL 1059
XCFR2 - E62806

POWER BLOCK DESCRIPTION							HIGH SCCR CONDITIONS											
			Rated Wire Range (openings) kcmil/AWG		Configuration		Suitable Conductors (kcmil/AWG) (2)			Overcurrent Protection Fuse Required Class/Max Amp Rating (3)								
Marathon Catalog #	Poles	Amps	Line	Load		Load	Line	Load	Wire Class	J	T	RK1	RK5	G	CC	SCCR, RMS SYM Amps (1)	UL	FILE UL FILE NO
FPB23580	3	175	2/0-6	4-10														
							2/0-6	4-14	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401
FPB33553	3		400-3/0 2/0-2	2-8 2-14														
							400-3/0	2-8	B, C	400	400	400	100	60	30			
							2/0-6	2-14	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401
FPB33588	3	420	600-3/0 600-2	1/0-8 1/0-10														
							600-3/0	1/0-8	B, C	450	450	400	100	60	30			
							2/0-2	2-14	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401
FPB33595	3	420	600-3/0 600-2	4-8 4-10														
							600-3/0	4-8	B, C	450	450	400	100	60	30			
							2/0-2	4-12	B, C	200	200	200	100	60	30	100,000 A	600	QPQS.E309401

(1) Short-circuit current ratings may be marked on the block or instructions provided with the terminal block
(2) Size range of conductors suitable to maintain noted SCCR
(3) Maximum size of line side overcurrent protection to provide noted SCCR

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP