ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Max Fuss GmbH ZDK 400/800-33* at our website: *Click HERE*

Zwischenkreisdrosseln / DC-bus-reactors

Technische Daten / Technical Data

Bemessungsspannung / Rated voltage	800 V DC
Umgebungstemperatur / Ambient temperatur	max. 40°C
Schutzart / Protection index	IP00
Anschlüsse / Terminals	Berührungsgeschützte Klemmen Finger-Safe Screwing Terminals



Zwischenkreisdrosseln zur Einhaltung der Grenzwerte für Oberschwingungsströme nach EN61000-3-12, Rsce=120

DC-bus-chokes to conform limits for harmonic currents defined in EN61000-3-12 for Rsce=120

für einphasige Wechselrichter / for single-phase inverters

Typ Type	Bemessungsstrom Rated current A	Induktivität Inductance mH	Kupfergewicht Copperweight kg	Gewicht Weight kg
ZKD200/800-5,4	5,4	8	0,18	0,90
ZKD200/800-12	12	4,2	0,45	2,90
ZKD200/800-18	18	3	0,55	3,00
ZKD200/800-36	36	1	0,71	4,00
ZKD200/800-72	72	0,5	1,15	6,80

für dreiphasige Wechselrichter / for three-phase inverters

Typ Type	Bemessungsstrom Rated current A	Induktivität Inductance mH	Kupfergewicht Copperweight kg	Gewicht Weight kg
ZKD400/800-3,2	3,2	28	0,18	0,95
ZKD400/800-5,7	5,7	11	0,25	1,00
ZKD400/800-10	10	10	0,60	2,90
ZKD400/800-12	12	6,3	0,65	4,00
ZKD400/800-20	20	4,1	1,18	6,00
ZKD400/800-23	23	3,6	1,00	6,00
ZKD400/800-27	27	2,7	1,30	6,00
ZKD400/800-33	33	1,9	1,40	6,10
ZKD400/800-36	36	1,8	1,35	6,80
ZKD400/800-45	45	1,6	1,85	7,80
ZKD400/800-53	53	1,2	1,85	7,80
ZKD400/800-70	70	1,0	2,35	10,0
ZKD400/800-86	86	0,8	2,23	12,4
ZKD400/800-104	104	0,6	2,75	16,7
ZKD400/800-180	180	0,33	5,00	17,8
ZKD400/800-230	230	0,26	5,80	19,7
ZKD400/800-450	450	0,15	14,0	46,0

Kontakt
Ing. Max Fuss GmbH & Co. KG
Johann-Hittorf-Straße 6
12489 Berlin, Germany
Tel.: +49 30 404 40 04
Fax: +49 30 404 31 50
E- Mail: info@fuss-emv.de
Web: www.fuss-emv.de

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Zwischenkreisdrosseln zur Einhaltung der Grenzwerte für Oberschwingungsströme nach EN61000-3-2

DC-bus-chokes to conform limits for harmonic currents defined in EN61000-3-2

für einphasige Wechselrichter / for single-phase inverters

Typ Type	Bemessungsstrom Rated current A	Induktivität Inductance mH	Kupfergewicht Copperweight kg	Gewicht Weight kg
ZKD200/800-3,5.300	3,5	30	0,25	0,7
ZKD200/800-6,7.250	6,7	25	0,65	3,0

für dreiphasige Wechselrichter / for three-phase inverters


Typ Type	Bemessungsstrom Rated current A	Induktivität Inductance mH	Kupfergewicht Copperweight kg	Gewicht Weight kg
ZKD400/800-2,7.125	2,7	12,5	0,12	0,55

Abmessungen / Dimensions

Angaben in mm. / Values in mm.

Drosseltyp	Länge	Breite	Tiefe	Bef.-Maße		Befest.
Choke	Length	Width	Depth	Mounting		Hole
	L	B	T	D	E	ø
ZKD200/800-5,4	66	67	82	50	52	M4
ZKD200/800-12	96	87	114	84	70	M5
ZKD200/800-18	96	87	114	84	70	M5
ZKD200/800-36	96	96	96	84	84	M5
ZKD200/800-72	120	160	100	90	90	M5

Ab 36 A Profildraht, Breite + 15 mm für Anschlüsse




Kontakt Johann-Hittorf-Straße 6 Tel.: +49 30 404 40 04 E- Mail: info@fuss-emv.de
Ing. Max Fuss GmbH & Co. KG 12489 Berlin, Germany Fax: +49 30 404 31 50 Web: www.fuss-emv.de

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Abmessungen / Dimensions

Angaben in mm. / Values in mm.

Drosseltyp	Länge	Breite	Tiefe	Bef.-Maße		Befest.
Choke	Length	Width	Depth	Mounting		Hole
	L	B	T	D	E	ø
ZKD400/800-3,2	66	67	82	50	52	M4
ZKD400/800-5,7	78	69	90	56	54	M4
ZKD400/800-10	96	87	114	84	70	M5
ZKD400/800-12	96	87	114	84	70	M5
ZKD400/800-20	96	100	114	84	84	M5
ZKD400/800-23	105	101	111	84	85	M5
ZKD400/800-27	120	110	120	90	90	M5
ZKD400/800-33	120	103	120	90	82	M5
ZKD400/800-36	120	121	120	90	102	M5
ZKD400/800-45	135	116	133	104	97	M5
ZKD400/800-53	135	123	133	104	107	M5
ZKD400/800-70	150	175	130	122	101	M6
ZKD400/800-86	150	200	130	122	127	M6
ZKD400/800-104	174	149	150	135	116	M6
ZKD400/800-180	174	220	135	135	136	M6
ZKD400/800-230	174	220	135	135	136	M6
ZKD400/800-450	240	218	305	144	140	M8



Anschluss bis 53A an Klemme, ab 70A an Kabelschuh.

Drosseltyp	Länge	Breite	Tiefe	Bef.-Maße		Befest.
Choke	Length	Width	Depth	Mounting		Hole
	L	B	T	D	E	ø
ZKD200/800-3,5.300	66	67	82	50	52	M4
ZKD200/800-6,7.250	96	87	114	84	70	M5
ZKD400/800-2,7.125	60	70	78	84	83	M3

29.4.09

Kontakt Johann-Hittorf-Straße 6 Tel.: +49 30 404 40 04 E- Mail: info@fuss-emv.de
Ing. Max Fuss GmbH & Co. KG 12489 Berlin, Germany Fax: +49 30 404 31 50 Web: www.fuss-emv.de

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP