ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Measurement Computing / ComputerBoards CIO-DAS16/330* at our website: *Click HERE*

SPECIFICATIONS

CIO-DAS16/330

Analog Input & Digital I/O



Revision 4, October, 2001

© Copyright 2001, MEASUREMENT COMPUTING CORPORATION

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Power Consumption

+5V:	900 mA typical, mA max

Analog Input Section

A/D converter type	AD7800
Resolution	12 bits
Number of channels	8 differential or 16 single-ended, switch-selectable
Programmable ranges	±10V, ±5V, ±2.5V, ±1.25V , ±0.625V, 0 to 10V, 0 to 5V, 0 to 2.5V, 0 to 1.25V, 0 to 0.625V, fully programmable
Polarity	Unipolar/Bipolar, software-selectable
A/D pacing	Programmable: internal counter or external source (DIG. IN 0 / TRIGGER, rising edge) or software-polled
A/D Trigger sources	External hardware/software (DIG. IN 0 / TRIGGER, active high)
A/D Triggering Modes	
Digital:	Gated pacer, software-polled. (Gate must be disabled by software after trigger event.)
Data transfer	From 512 sample FIFO via REPINSW, interrupt, DMA or software polled
DMA	Channel 1 or 3, switch-selectable
A/D conversion time	3 µs
Throughput	330 kHz
Absolute accuracy	0.01% of reading ±1 LSB
Differential Linearity error	±1 LSB
Integral Linearity error	±1 LSB
Differential Linearity error	±1 LSB
No missing codes guaranteed	12 bits
Gain drift (A/D specs)	±25 ppm/°C
Zero drift (A/D specs)	±10 ppm/°C
Common Mode Range	±10V
CMRR @ 60 Hz	–72dB
Input leakage current	200 nA (@25 Deg C)
Input impedance	10 MegOhms min
Absolute max. input voltage	±35V

Digital Input / Output

Digital type:	
Input:	74LS367
Output:	74LS197
Configuration	Two ports, 4 input bits and 4 output bits
Input low voltage	0.8V max
Input high voltage	2.0V min
Output low voltage	0.5V max (IOL = 8 mA)
Output high voltage	2.7V min (IOH = –0.4 mA)
Absolute max. input voltage	–0.5V, +7V

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Interrupts	2 through 7, 10 and 11, programmable
Interrupt enable	Programmable
Interrupt sources	A/D End-of-conversion, A/D FIFO-half-full, Residual counter, DMA terminal count

Counter Section

Counter type	82C54
Configuration	Two 82C54 devices, 3 down-counters each device; 16 bits each.

82C54A:

Counter 0 - Independent, available to user

Source: 100 kHz on board clock or external (CTR 0 Clock In)
Gate: External (Dig In 2 / CTR 0 Gate)
Output: Available at user connector (CTR 0 Out)

Counter 1 - ADC Pacer Lower Divider

Source: 1 or 10 MHz oscillator, jumper-selectable
Gate: Tied to Counter 2 gate, programmable source (internal or external (Dig In 0 / Trigger).
Output: Chained to Counter 2 Clock.

Counter 2 - ADC Pacer Upper Divider

Source: Counter 1 Output.
Gate: Tied to Counter 1 gate, programmable source: internal or external (Dig In 0 / Trigger).
Output: ADC Pacer clock, available at user connector (CTR 2 Out)

82C54B:

Counter 0 - Total samples (residual) counter upper divider

Source: Counter 1 output (total samples lower divider)
Gate: Internal
Output: Internal

Counter 1 - Total samples (residual) counter lower divider

Source: ADC conversion complete
Gate: Tied to Counter 2 gate, internal source.
Output: Counter 0 input (total samples upper divider)

Counter 2 - Trigger index counter

Source: ADC conversion complete
Gate: Tied to Counter 1 gate, internal source.
Output: Not used

Clock input frequency	10 MHz max
High pulse width (clock input)	30 ns min
Low pulse width (clock input)	50 ns min
Gate width high	50 ns min
Gate width low	50 ns min
Input low voltage	0.8V max
Input high voltage	2.0V min
Output low voltage	0.4V max
Output high voltage	3.0V min
Crystal Oscillator Frequency	10 MHz
Frequency accuracy	100 ppm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Environmental

Operating temperature range	0 to 50°C
Storage temperature range	–20 to 70°C
Humidity	0 to 90% non-condensing

Measurement Computing Corporation
16 Commerce Boulevard,
Middleboro, Massachusetts 02346

(508) 946-5100

Fax: (508) 946-9500

E-mail: info@measurementcomputing.com
www.measurementcomputing.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP