ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Measurement Computing PCI-DDA04/12* at our website: ***Click HERE***

SPECIFICATIONS

PCI-DDA08/12
PCI-DDA04/12
PCI-DDA02/12

Analog Output Boards



Revision 2, August, 2001

© Copyright 2001, MEASUREMENT COMPUTING CORPORATION

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Typical for 25°C unless otherwise specified.

Power Consumption

+5V Operating	
PCI-DDA08/12	1.6A typical, 2.6A max
PCI-DDA04/12	1.5A typical, 2.4A max
PCI-DDA02/12	1.4A typical, 2.2A max
+12V	
PCI-DDA08/12	24 mA typical, 48 mA max
PCI-DDA04/12	12 mA typical, 24 mA max
PCI-DDA02/12	6 mA typical, 12 mA max
–12V	
PCI-DDA08/12	16 mA typical, 25 mA max
PCI-DDA04/12	8 mA typical, 12 mA max
PCI-DDA02/12	4 mA typical, 6 mA max

Analog Output

D/A converter type	AD7837B
Resolution	12 bits
Number of channels	
PCI-DDA08/12	8
PCI-DDA04/12	4
PCI-DDA02/12	2
Output Ranges	±10V, ±5V, ±2.5V, 0 to 10V, 0 to 5V, 0 to 2.5V. Each channel is independently programmable.
Data transfer	Programmed I/O.
Offset error (calibrated)	±(300 µV +¼LSB)
Gain error (calibrated)	±(300 µV +¼LSB)
Differential nonlinearity	±1 LSB max
Integral nonlinearity	±1 LSB max
Monotonicity	12 bits
D/A Gain drift	±2 ppm/°C
D/A Offset drift	±5 µV/°C
Throughput	PC dependent
Settling time (20V step to ±½ LSB)	6 µs typ, 10 µs max
Slew Rate	5V/µs
Current Drive	±5 mA
Output short-circuit duration	25 mA indefinite
Output coupling	DC
Output impedance	0.1 Ohms max
Miscellaneous	Double buffered output latches Update DACs individually or simultaneously (software-selectable) On power-up and reset, all DAC's are cleared to 0 volts, ±210mV

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Digital Input / Output

Digital Type (main connector)	82C55 mode 0 emulation
Output:	74S244
Input:	74LS373
Configuration	4 banks of 8, 4 banks of 4; programmable by bank as input or output
Number of channels	48 I/O
Output High	2.4 volts min @ –15mA
Output Low	0.5 volts max @ 64 mA
Input High	2.0 volts min, 7 volts absolute max
Input Low	0.8 volts max, –0.5 volts absolute min
Power-up / reset state	Input mode (high impedance)

Environmental

Operating temperature range	0 to 70°C
Storage temperature range	–40 to 100°C
Humidity	0 to 90% non-condensing

Measurement Computing Corporation
16 Commerce Boulevard,
Middleboro, Massachusetts 02346

(508) 946-5100

Fax: (508) 946-9500

E-mail: info@measurementcomputing.com
www.measurementcomputing.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP