ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Melles Griot 13AMP007* at our website: *Click HERE*

PhotoIntSphAmCh4_FINAL_Manual.qxd 12/23/2004 10:36 PM Page 4.12



High-Frequency Amplifier

The 13 AMP 007 is a low-noise ac-coupled high-frequency voltage or current amplifier.

- High-frequency response ranges from 4 kHz to >300 MHz.
- The amplifier accepts input currents up to 160 mA and input voltages up to 8 mV.

SPECIFICATIONS:
HIGH-FREQUENCY AMPLIFIER

Frequency Response: 4 kHz to >350 MHz (−3dB)
Maximum Output Voltage: 1 V p-p into 50 Ω
Input and Output Connector type: BNC
Input and Output Impedance: 50 Ω
Transimpedance Mode:
Transimpedance Gain: 6250 V/A
Maximum Input Current: 160 μA
Output Noise: 3.2 mV rms
Input-Referred Noise: 24 pA/Hz$^{1/2}$
Bias Adjustment: −20 V to +20 V
Voltage Amplification Mode:
Voltage Gain: 125
Maximum Input Voltage: 8 mV
Output Noise: 3.2 mV rms
Input Referred Noise: 1.2 nV/Hz$^{1/2}$
Power Requirements:
Voltage:
115 Vac +10/−20% and 230 Vac ±10%
rear panel switch selectable
Frequency: 50–60 Hz
Power: 3 W
Temperature:
Operating Temperature: +10°C to +35°C
Storage Temperature: −40°C to +55°C
Dimensions (W × H × D):
91 × 48.3 × 143 mm (3.6 × 1.9 × 5.6 in.)


High-Frequency Amplifier

	PRODUCT NUMBER
High-Frequency Amplifier	13 AMP 007

Performance Variation with Detector Type[1]

Rise Time[2] at −9 Vdc (nsec)	NEP[2] at −9 Vdc (nsec)	DETECTOR PRODUCT NUMBER
1.0	48×10^{-12}	13 DAH 001
1.25	48×10^{-12}	13 DAH 003
1.5	48×10^{-12}	13 DAH 005

1 Combined performance for Melles Griot high-speed silicon photodiodes and the 13 AMP 007.
2 Rise-time and noise equivalent power values are for a transimpedance gain of 6250 V/A and a detector responsivity of 0.5 A/W.



Typical frequency response of the 13 AMP 007 high-frequency amplifier

OEM ASK ABOUT OUR CUSTOM CAPABILITIES

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP