

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Symmetricom

CsIII

Cesium Frequency Standard
Model 4310B

KEY FEATURES

- Third Generation Cesium Technology
- 2U Compact Rack Mount
- AC & DC inputs
- Remote Monitoring & Control
- 5 & 10MHz Outputs
- 1PPS Sync input
- 1PPS Output
- 30 Minute Warm-Up to Full Specifications
- <30 lbs

OPTIONAL FEATURES

- T1/E1 Outputs
- Portability Kit

OVERVIEW

Symmetricom's CsIII is a lightweight, compact, economical cesium frequency standard. The technology developed for the CsIII is an evolutionary step forward in the quest for higher stability, lower phase noise and longer life. An ever-increasing base of demanding users in communications, timing, synchronization and other applications take advantage of this performance.

The CsIII is configured with 5 and 10MHZ sinewave outputs, a 10MHz TTL output a 1PPS sync input and a 1PPS timing output. All monitoring and control of the unit is done via the serial interface and Symmetricom's proprietary Monitor3 software.

Packaged in a 2U, 19-inch rack mounted chassis, the CsIII weighs less than 30 lbs. An optional portability kit and T1/E1 synthesizer are available for added functionality and versatility.

The CsIII comes standard with a 2-year electronics warranty and 12-year tube warranty.

The CsIII is ideal for SATCOM, Calibration, Metrology and many other Test & Measurement applications that required cesium stability and accuracy.



CsIII Cesium Frequency Standard

CsIII Specifications

ELECTRICAL SPECIFICATIONS

- Frequency outputs

Frequency:	1 each 5 MHz and 10 MHz
Format:	Sine
Amplitude:	1 Vrms
Harmonic:	<-40dBc
Non harmonic:	<-80dBc
Connector:	BNC
Load impedance:	50Ω
Location:	rear panel
Frequency:	10 MHz
Format:	TTL
Amplitude:	>2.2V
Load impedance:	50Ω
Location:	rear panel
Connector:	BNC

- Timing outputs

Format:	1PPS
Amplitude:	>3.0V into 50Ω (TTL compatible)
Pulse width:	20µs positive pulse
Rise time:	<5ns
Jitter:	<1ns rms
Connector:	BNC
Load impedance:	50Ω
Location:	rear panel

- Timing inputs

Sync input:	1PPS
Amplitude:	>3.0V into 50Ω (TTL compatible)
Pulse width:	20µs positive pulse
Rise time:	<5ns
Jitter:	<1ns rms
Connector:	BNC
Load impedance:	50Ω
Location:	rear panel

REMOTE SYSTEM INTERFACE AND CONTROL

RS-232-C (DTE Configuration)
Complete remote control and interrogation of all instrument functions and parameters

Connector	
RS-232-C:	9-pin male rectangular D subminiature type
Location:	rear panel
Alarm (Relay):	9-pin female rectangular D subminiature type
Location:	rear panel

- Performance parameters

Accuracy:	±1.0E-12
Warm-up time (typical):	30 minutes
Reproducibility:	±2.0E-13
Settability	
Range:	±1.0E-9
Resolution:	1.0E-15
Control:	Via RS-232 port

- Stability

Averaging Time(s)	Allan Deviation
1	<1.2E-11
10	<8.5E-12
100	<2.7E-12
1,000	<8.5E-13
10,000	<2.7E-13
100,000	<8.5E-14
floor	<5.0E-14

- SSB Phase noise

Offset (Hz)	5MHz output
1	<-95dBc
10	<-130dBc
100	<-145dBc
1,000	<-155dBc
10,000	<-155dBc
100,000	<-160dBc

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

- General Environment

Temperature	
Operating:	0°C to 50°C
Non-operating:	-40°C to 70°C
Humidity:	95% up to 50°C
Magnetic field:	0 to 2 gauss
Altitude (operating):	0 to 50,000 feet

- AC Power requirements

Operating voltage:	100 to 240 VAC +/-10%
Frequency:	47 to 63 Hz
Power	
Operating:	<65W
Warm-up:	<90W

- DC Power requirements

22 to 36 VDC
36 to 75 VDC
30W 1.3A @ 24V (Operating)
65W 2.7A @ 24V (Warm Up)

- Dimensions/Weight

Height:	3.50" (89.9mm)
Width	
Front panel:	19.00" (483mm)
Instrument	17.31" (440mm)
Depth:	15.0" (381mm)
Weight:	<30lbs (13.5kg)
MTBF:	>130,000 hrs.

ORDERING INFORMATION

	Part No.
• 24VDC, 12 Yr. Warranty	14534-110
• 48VDC, 12 Yr. Warranty	14534-109



CsIII connections

SYMMETRICOM, INC.
2300 Orchard Parkway
San Jose, California
95131-1017
tel: 408.433.0910
fax: 408.428.7896
info@symmetricom.com
www.symmetricom.com

©2009 Symmetricom. Symmetricom and the Symmetricom logo are registered trademarks of Symmetricom, Inc. All specifications subject to change without notice. DS/CSIII/D/031109/PDF

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP