

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *MEN Micro / Mikro Elektronik M27* at our website: ***Click HERE***

Embedded Solutions

M27 - 16 Binary Outputs



- **16 outputs 8..36 V**
- **500 mA output current per channel**
- **Thermal and short-circuit protection**
- **Load on supply voltage**
- **Optical isolation**

The M27 with its open-collector outputs can be used in process I/O applications (cf. M28 with open-emitter outputs). If there are currents of above 500mA an intelligent power switch guarantees that the respective transistor is switched off. The M-Module™ is equipped with suppressor diodes for protection against overvoltage caused by inductive loads. The output registers can be read back.
The M27 is based on the M-Module™ ANSI mezzanine standard. It can be used as an I/O extension in any type of bus system, i.e. CPCI, PXI™, VME or on any type of stand-alone SBC. Appropriate M-Module™ carrier cards in 3U, 6U and other formats are available from MEN or other manufacturers.

mikro elektronik gmbh • nürnberg

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Technical Data

Output Voltage
- 8..36V; 10µA max. (open)
- 2V max.; 500mA (closed)

Output Current
- Max. 500mA per channel
- No derating

Miscellaneous
- Load on supply voltage
- Thermal and short circuit protection

Peripheral Connections
- Via front panel on a shielded 25-pin D-Sub receptacle connector
- Via carrier board (rear I/O)

M-Module™ Characteristics
- A08, D16, IDENT

Electrical Specifications
- Isolation voltage:
  - 500V DC between isolated side and digital side
  - Voltage between the connector shield and isolated ground is limited to 180V using a varistor; AC coupling between connector shield and isolated ground through 47nF capacitor
- Supply voltage/power consumption: +5V (4.85V..5.25V), 100mA typ.
- MTBF: 58,000h @ 50°C (derived from MIL-HDBK-217F)

Mechanical Specifications
- Dimensions: conforming to M-Module™ Standard
- Weight: 84g

Environmental Specifications
- Temperature range (operation):
  - 0..+60°C
  - Industrial temperature range on request
  - Airflow: min. 10m³/h
- Temperature range (storage): -40..+85°C
- Relative humidity range (operation): max. 95% non-condensing
- Relative humidity range (storage): max. 95% non-condensing
- Altitude: -300m to + 3,000m
- Shock: 15g/11ms
- Bump: 10g/16ms
- Vibration (sinusoidal): 2g/10..150Hz
- Conformal coating on request

Safety
- PCB manufactured with a flammability rating of 94V-0 by UL recognized manufacturers

EMC
- Tested according to EN 55022 (radio disturbance), IEC1000-4-2 (ESD) and IEC1000-4-4 (burst) with regard to CE conformity


Software Support
- MEN Driver Interface System (MDIS™ for Windows®, Linux, VxWorks®, QNX®, RTX, OS-9®)
- For more information on supported operating system versions and drivers see Software.

mikro elektronik gmbh • nürnberg

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Embedded Solutions

Diagram



mikro elektronik
gmbh • nürnberg

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Embedded Solutions

Ordering Information

Standard Hardware

04M027-00 16 binary sink outputs, 0..+60°C

Miscellaneous

05M000-00 M-Module™ cable, 2m, with 25-pin D-Sub plug/housing to pig tail

05M000-17 25 mounting screw sets to fix M-Modules™ on carrier boards

Software: OS independent

13M027-06 MDIS4/2004 low-level driver sources (MEN) for M27, M28 and M81

Software: Windows

13M027-70 MDIS4™/2004 Windows® driver (MEN) for M27, M28 and M81

Documentation

20M000-00 M-Module™ Draft Specification, Rev. 3.0

20M027-00 M27 User Manual

For the most up-to-date ordering information and direct links to other data sheets and downloads, see the M27 online data sheet under » www.men.de.

Germany
MEN Mikro Elektronik GmbH
Neuwieder Straße 5-7
90411 Nuremberg
Phone +49-911-99 33 5-0
Fax +49-911-99 33 5-901
E-mail info@men.de
www.men.de

France
MEN Mikro Elektronik SA
18, rue René Cassin
ZA de la Châtelaine
74240 Gaillard
Phone +33 (0) 450-955-312
Fax +33 (0) 450-955-211
E-mail info@men-france.fr
www.men-france.fr

USA
MEN Micro, Inc.
24 North Main Street
Ambler, PA 19002
Phone (215) 542-9575
Fax (215) 542-9577
E-mail sales@menmicro.com
www.menmicro.com

The date of issue stated in this data sheet refers to the Technical Data only. Changes in ordering information given herein do not affect the date of issue.
All brand or product names are trademarks or registered trademarks of their respective holders.
Information in this document has been carefully checked and is believed to be accurate as of the date of publication; however, no responsibility is assumed for inaccuracies. MEN Mikro Elektronik accepts no liability for consequential or incidental damages arising from the use of its products and reserves the right to make changes on the products herein without notice to improve reliability, function or design. MEN Mikro Elektronik does not assume any liability arising out of the application or use of the products described in this document.
The products of MEN Mikro Elektronik are not suited for use in nuclear reactors and for application in medical appliances used for therapeutical purposes. Application of MEN's products in such plants is only possible after the user has precisely specified the operation environment and after MEN Mikro Elektronik has consequently adapted and released the product.
Copyright © 2007 MEN Mikro Elektronik GmbH. All rights reserved.

mikro elektronik
gmbh • nürnberg

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP