

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

FIXED ATTENUATORS 50 & 75Ω Coaxial

UP TO 2W 0.5 to 40 dB, DC to 6000 MHz



CAT

MODEL NO.	FREQ. RANGE MHz f_L-f_U	ATTENUATION dB Nom.	FLATNESS, Max. L	M	U	VSWR (:1) Max. L	M	U	POWER W	CASE STYLE Note B	CONNECTION	PRICE $ Qty. (1-9)
CAT-1	DC-1500	1±0.2	0.3	0.4	0.5	1.3	1.5	1.7	1	FF55	-	16.95
CAT-2	DC-1500	2±0.2	0.3	0.4	0.8	1.3	1.5	1.7	1	FF55	-	16.95
CAT-3	DC-1500	3±0.2	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
■ CAT-3-75	DC-500	3±0.2	0.9	—	—	2.0	—	—	1	FF55	-	16.95
CAT-4	DC-1500	4±0.2	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
CAT-5	DC-1500	5±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
CAT-6	DC-1500	6±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
■ CAT-6-75	DC-500	6±0.3	1.0	—	—	2.0	—	—	1	FF55	-	16.95
CAT-7	DC-1500	7±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
CAT-8	DC-1500	8±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
CAT-9	DC-1500	9±0.4	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
CAT-10	DC-1500	10±0.4	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
■ CAT-10-75	DC-500	10±0.4	1.0	—	—	2.0	—	—	1	FF55	-	16.95
CAT-12	DC-1500	12±0.4	0.3	0.6	1.0	1.3	1.5	1.7	1	FF55	-	16.95
CAT-15	DC-1500	15±0.4	0.4	0.7	1.1	1.3	1.5	1.7	1	FF55	-	16.95
■ CAT-15-75	DC-500	15±0.4	0.8	—	—	1.5	—	—	1	FF55	-	16.95
CAT-20	DC-1500	20±0.5	0.4	0.8	1.3	1.3	1.6	1.8	1	FF55	-	16.95
■ CAT-20-75	DC-500	20±0.5	1.1	—	—	2.0	—	—	1	FF55	-	16.95
CAT-25	DC-2000	25±0.5	0.4	0.8	1.3*	1.3	1.6	2.0**	1	FF55	-	16.95
CAT-30	DC-1000	30±0.5	0.5	1.0	—	1.3	1.6	—	1	FF55	-	16.95
CAT-40	DC-500	40±0.6	1.0	—	—	1.5	—	—	1	FF55	-	16.95

L = DC-500 MHz M = DC-1000 MHz U = DC-f_U

NOTES:

■ Denotes 75 ohm models. For coax connector models 75 ohm BNC connectors are standard.

* Attenuation Flatness over DC-2000 MHz:
CAT-25, NAT-25, 0.75 dB typ.; NAT-1-2W, 0.20 dB typ.;
NAT-2-2W, 0.40 dB typ.; NAT-3-2W, 0.50 dB typ.
NAT-4-2W, 0.8 dB typ.; NAT-5-2W, 0.9 dB typ.; NAT-6-2W, 1.0 dB typ.

** VSWR over DC-2000 MHz:
CAT-25, NAT-25, 1.45 (typ.)
NAT-2W models, 1.25 (typ.)

A. General Quality Control Procedures, Environmental Specifications, Hi-Rel and MIL description are given in General Information (Section 0).

B. Connector types and case mounted options, case finishes are given in section 0, see "Case styles & outline drawings".


C. Prices and specifications subject to change without notice.

NSN GUIDE


MCL NO.	NSN
CAT-3	5985-01-447-0901
CAT-5	5985-01-299-9258
CAT-6	5985-01-300-0481
CAT-10	5985-01-380-3801
CAT-15	5985-01-299-9257
CAT-20	5985-01-265-0338
CAT-30	5985-01-296-0943
NAT-3	5985-01-298-0747
NAT-10	5985-01-291-5548
NAT-30	5985-01-298-0746
SAT-3	5985-01-418-0247
SAT-6	5985-01-237-5343
SAT-10	5985-01-250-4812
SAT-15	5985-01-418-0250
SAT-20	5985-01-454-7333
SAT-30	5985-01-190-6838



SAT



NAT



TAT (Consult factory)

MODEL NO.	FREQ. RANGE MHz f_L-f_U	ATTENUATION dB Nom.	FLATNESS, Max. L	M	U	VSWR (:1) Max. L	M	U	POWER W	CASE STYLE Note B	CONNECTION	PRICE $ Qty. (1-9)
SAT-0.5	DC-1500	0.5±0.1	0.2	0.3	0.3	1.2	1.2	1.3	1	FF56	-	20.95
SAT-1	DC-1500	1±0.2	0.3	0.4	0.5	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-2	DC-1500	2±0.2	0.3	0.4	0.8	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-2.5	DC-1500	2.5±0.2	0.2	0.4	0.7	1.2	1.2	1.3	0.25	FF56	-	20.95
SAT-3	DC-1500	3±0.2	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-4	DC-1500	4±0.2	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-5	DC-1500	5±0.3	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-6	DC-1500	6±0.3	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-7	DC-1500	7±0.3	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-8	DC-1500	8±0.3	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-9	DC-1500	9±0.4	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-10	DC-1500	10±0.4	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-12	DC-1500	12±0.4	0.3	0.6	1.0	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-15	DC-1500	15±0.4	0.4	0.7	1.1	1.3	1.5	1.7	0.5	FF56	-	20.95
SAT-20	DC-1500	20±0.5	0.4	0.8	1.3	1.3	1.6	1.8	0.5	FF56	-	20.95
SAT-30	DC-1000	30±0.5	0.5	1.0	—	1.3	1.6	—	0.5	FF56	-	20.95
SAT-40	DC-500	40±0.6	1.0	—	—	1.5	—	—	0.5	FF56	-	20.95
NAT-1	DC-1500	1±0.2	0.3	0.4	0.5	1.3	1.5	1.7	1	FF57	-	23.95
NAT-1-2W	DC-2000	1±0.2	0.2	0.3	0.5*	1.3	1.4	1.5**	2	FF57	-	26.95
NAT-2	DC-1500	2±0.2	0.3	0.4	0.8	1.3	1.5	1.7	1	FF57	-	23.95
NAT-2-2W	DC-2000	2±0.2	0.2	0.4	0.7*	1.3	1.4	1.5**	2	FF57	-	26.95
NAT-3	DC-1500	3±0.2	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-3-2W	DC-2000	3±0.2	0.3	0.4	0.7*	1.3	1.4	1.5**	2	FF57	-	26.95
NAT-4	DC-1500	4±0.2	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-4-2W	DC-2000	4±0.2	0.2	0.5	1.2*	1.3	1.4	1.5**	2	FF57	-	26.95
NAT-5	DC-1500	5±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-5-2W	DC-2000	5±0.2	0.2	0.5	1.2*	1.3	1.4	1.5**	2	FF57	-	26.95
NAT-6	DC-1500	6±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-6-2W	DC-2000	6±0.2	0.2	0.5	1.5*	1.3	1.4	1.5**	2	FF57	-	26.95
NAT-7	DC-1500	7±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-8	DC-1500	8±0.3	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-9	DC-1500	9±0.4	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-10	DC-1500	10±0.4	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-12	DC-1500	12±0.4	0.3	0.6	1.0	1.3	1.5	1.7	1	FF57	-	23.95
NAT-15	DC-1500	15±0.4	0.4	0.7	1.1	1.3	1.5	1.7	1	FF57	-	23.95
NAT-20	DC-1500	20±0.5	0.4	0.8	1.3	1.3	1.6	1.8	1	FF57	-	23.95
NAT-25	DC-2000	25±0.5	0.4	0.8	1.3*	1.3	1.6	1.8**	1	FF57	-	23.95
NAT-30	DC-1000	30±0.5	0.5	1.0	—	1.3	1.6	—	1	FF57	-	23.95
NAT-40	DC-500	40±0.6	1.0	—	—	1.5	—	—	1	FF57	-	23.95
			L_1	M_1	U_1	L_1	M_1	U_1				
NAT-1-60	DC-6000	1±0.2	0.4	0.8	1.1	1.2	1.5	1.5	1	FF57	-	26.95
NAT-2-60	DC-6000	2±0.2	0.4	0.8	1.2	1.2	1.4	1.4	0.9	FF57	-	26.95
NAT-3-60	DC-6000	3±0.2	0.4	1.0	1.4	1.2	1.4	1.4	0.65	FF57	-	26.95
NAT-4-60	DC-6000	4±0.2	0.4	1.0	1.5	1.2	1.3	1.5	0.5	FF57	-	26.95
NAT-5-60	DC-6000	5±0.2	0.4	0.9	1.2	1.2	1.3	1.5	0.5	FF57	-	26.95
NAT-6-60	DC-6000	6±0.2	0.4	0.7	0.9	1.15	1.25	1.5	0.5	FF57	-	26.95
NAT-7-60	DC-6000	7±0.2	0.3	0.7	0.9	1.2	1.3	1.4	0.45	FF57	-	26.95
NAT-8-60	DC-6000	8±0.2	0.2	0.5	1.0	1.2	1.3	1.4	0.35	FF57	-	26.95
NAT-9-60	DC-6000	9±0.2	0.2	0.7	1.3	1.2	1.2	1.45	0.225	FF57	-	26.95
NAT-10-60	DC-6000	10±0.2	0.3	0.9	1.9	1.2	1.2	1.5	0.225	FF57	-	26.95
NAT-12-42	DC-4200	12±0.2	0.3	0.8	1.8	1.2	1.2	1.2	0.25	FF57	-	26.95
NAT-15-30	DC-3000	15±0.2	0.3	0.8	1.5	1.2	1.2	1.2	0.2	FF57	-	26.95
NAT-20-21	DC-2100	20±0.3	0.3	0.9	1.6	1.15	1.15	1.15	0.2	FF57	-	26.95
NAT-25-21	DC-2100	25±0.3	0.4	1.0	1.9	1.2	1.2	1.2	0.175	FF57	-	26.95
NAT-30-15	DC-1500	30±0.3	0.5	0.9	1.7	1.15	1.2	1.25	0.15	FF57	-	26.95

L = DC-500 MHz M = DC-1000 MHz U = DC-f_U

L_1 = DC-(1/3)f_U M_1 = DC-(2/3)f_U U_1 = DC-f_U

The Design Engineers Search Engine
Provides Actual Data Instantly
At: http://www.minicircuits.com

In Stock... Immediate Delivery
For Custom Versions Of Standard Models
Consult Our Applications Dept.
Available Tape & Reel

FF57 (inch mm)


A	B	C	D	E	F	G	H	J
	0.67 17.018		2.90 73.660	.82 20.828				

K	L	M	N	P	Q	R	S	T	wt. grams.
									90

Tolerance: .x ± .1 .xx ± .03 .xxx ± .015 inch.

Notes:

- Material and Finish:
  - Case material: Stainless steel, passivated.
- Connectors:
  - Connectors: Male N, Female N standard. Combinations with BNC, SMA, TNC available on request, consult factory.



Back

FF56(inch mm)


A	B	C	D	E	F	G	H	J
	.43 10.922		1.70 43.180	.312 7.925				

K	L	M	N	P	Q	R	S	T	wt. grams.
									18

Tolerance: .x ± .1 .xx ± .03 .xxx ± .015 inch.

Notes:

- Material and Finish:
  - Case material: brass. Finish: nickel plate.
- Connectors:
  - Connectors: Male SMA. Female SMA only.



Back

FF55 (inch / mm)


A	B	C	D	E	F	G	H	J
	0.54 13.716		2.59 65.786					

K	L	M	N	P	Q	R	S	T	wt. grams.
									40

Tolerance: .x ± .1 .xx ± .03 .xxx ± .015 inch.

Notes:

- Material and Finish:
  - Case material: Stainless steel, passivated.
- Connectors:
  - Connectors: Male BNC, Female BNC standard. Other combinations with SMA, TNC available on request, consult factory.



Back

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP