

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

DC Pass

Power Splitter/Combiner

8 Way-0° 50Ω 800 to 2000 MHz

ZB8PD-2000+



Generic photo used for illustration purposes only

SMA version shown
CASE STYLE: Z41

Connectors	Model
SMA	ZB8PD-2000-S+
N-TYPE	ZB8PD-2000-N+

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	10W max.
Internal Dissipation	0.875W max.
DC Current	1.8A(225mA for each port)

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

SUM PORT	S
PORT 1,2,3,4,5,6,7,8	1,2,3,4,5,6,7,8


Features

- wideband, 800 to 2000 MHz
- low insertion loss, 0.8 dB typ.
- good isolation, 26 dB typ.
- up to 10W power input
- rugged, shielded case

Applications

- cellular
- PCS/DCS
- communication systems
- GPS

Outline Drawing




Outline Dimensions (inch / mm)

A	B	C	D	E	F	G	H
7.06	3.13	.88	.250	1.750	5.310	6.810	.250
179.32	79.50	22.35	6.35	44.45	134.87	172.97	6.35

J	K	L	M	N	P	wt
2.875	.144	3.53	.44	.415	.89	grams
73.03	3.66	89.66	11.18	10.54	22.61	800

Electrical Schematic



Electrical Specifications at 25°C


Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		800		2000	MHz
Insertion Loss (above theoretical 9.0 dB)	800 - 2000	—	0.8	1.6	dB
Isolation	800 - 2000	20	26	—	dB
Phase Unbalance	800 - 2000	—	3	7	Degree
Amplitude Unbalance	800 - 2000	—	0.3	0.7	dB
VSWR (Port S)	800 - 2000	—	1.25	1.7	:1
VSWR (Port 1-8)	800 - 2000	—	1.1	1.35	:1

Typical Performance Data


Freq. (MHz)	Total Loss[1] (dB)						Amplitude Unbalance (dB)	Isolation (dB)				Phase Unbalance (deg.)	VSWR		
	S-1	S-2	S-3	S-4	S-6	S-8		1-2	2-3	3-4	5-6		S	1	8
800	9.52	9.56	9.55	9.54	9.49	9.49	0.07	32.53	33.61	32.18	31.04	1.34	1.39	1.09	1.11
850	9.46	9.50	9.50	9.48	9.44	9.43	0.07	32.07	32.95	31.29	30.12	1.39	1.24	1.09	1.10
900	9.43	9.48	9.48	9.45	9.42	9.41	0.07	30.29	31.11	29.75	28.56	1.42	1.12	1.08	1.09
950	9.44	9.49	9.49	9.45	9.43	9.41	0.08	29.09	30.16	29.09	27.59	1.43	1.06	1.08	1.09
1000	9.45	9.51	9.51	9.46	9.45	9.43	0.08	28.39	29.88	29.07	27.08	1.42	1.08	1.09	1.09
1100	9.49	9.55	9.55	9.50	9.50	9.47	0.08	26.10	27.60	27.29	25.35	1.40	1.14	1.09	1.08
1200	9.55	9.63	9.63	9.57	9.58	9.53	0.10	24.83	25.88	25.50	24.21	1.37	1.25	1.07	1.05
1300	9.56	9.65	9.68	9.60	9.60	9.53	0.14	27.34	27.61	27.22	26.57	1.25	1.24	1.05	1.03
1400	9.59	9.69	9.74	9.66	9.66	9.56	0.18	31.09	28.70	29.19	31.39	1.10	1.29	1.07	1.04
1500	9.62	9.73	9.80	9.71	9.72	9.60	0.20	35.80	30.92	31.91	37.65	1.13	1.36	1.06	1.04
1600	9.55	9.66	9.73	9.63	9.65	9.52	0.22	35.33	47.41	43.64	33.62	1.22	1.12	1.08	1.07
1700	9.64	9.76	9.83	9.72	9.73	9.59	0.23	26.54	29.26	29.04	26.22	1.47	1.28	1.16	1.15
1800	9.70	9.82	9.90	9.78	9.80	9.65	0.25	27.41	30.48	30.36	27.09	1.80	1.36	1.16	1.17
1900	9.60	9.72	9.83	9.69	9.73	9.56	0.27	41.34	45.00	42.05	39.29	2.27	1.07	1.10	1.11
2000	9.75	9.87	10.01	9.86	9.91	9.69	0.32	32.69	29.55	29.70	35.35	2.77	1.42	1.12	1.13

1. Total Loss = Insertion Loss + 9dB splitter loss.


ZB8PD-2000-S+
TOTAL LOSS



ZB8PD-2000-S+
ISOLATION



ZB8PD-2000-S+
VSWR



Notes
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP