

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

MAILING ADDRESS:
P.O. Box 115
SHIPPING ADDRESS:
100 Interpower Avenue
Oskaloosa, IA 52577 (USA)
E-MAIL: info@interpower.com

US, CAN, PR, VI:
Call Toll-free: (800) 662-2290
Fax Toll-free: (800) 645-5360
INTERNATIONAL:
Phone: (641) 673-5000
Fax: (641) 673-5100

United Kingdom

10 Kelvin Drive | Knowlhill, Milton Keynes | Buckinghamshire, MK5 8NH | U.K. | uk@interpower.com
UK, Ireland, Germany, Switzerland, Austria
Freephone: 00800 5566 5566 | Freefax: 00800 5655 5655
International: Phone: +44 (0)1908 295 300 | Fax: +44 (0)1908 295301

Part Number: 83545010
Description: 5 Function Double Fuse Filtered Screw Mount Module



Specifications

(Specifications subject to change without notice)
Part Number: **83545010**
Int'l Current Rating: **10A**
Int'l Voltage Rating: **250VAC**
N.A. Current Rating: **10A**
N.A. Voltage Rating : **120/250VAC**
Temperature Rating: **-10ºC to 40ºC**
Flammability Rating: **See Remarks**
Operating Frequency: **50/60Hz**
Class: **Class I**
Quick Disconnects: **5/4.8mm**
Terminal Material: **Various Copper Alloy**
Power Inlet: **yes**
Access Outlet: **no**
Sheet Style: **C14**
Switch: **yes**
Fuse: **yes**
Number of Fuses: **2(not included)**
Fuse Size: **¼ x 1¼" / 5x20mm**
Voltage Selector: **yes**
Voltage Selector Settings: **115,230**
Circuit Breaker: **no**
Filter: **yes**
Leak Current Value: **0.25mA/0.50mA**
Filtering Bandwidth : **150KHz to 30MHz**
Mounting Style: **Screw Mount**

General Material: **PBT**
Color: **Black**
CE Marking: **no**

Approvals: CSA VDE MISC UR

Remarks: Flammability: UL 94 V-0; IEC 60127-6:2014 compliant, Glow Wire Ignition Temp.= 775°ºC, Glow Wire Flammability Index = 850°ºC.

Last Modification: 09/29/21 • 11:23:15 • netui *Specifications subject to change without notice

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP