

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PMC-1553


Multi-Channel 1553 Interface for PMC Carriers/SBCs



Cable Assemblies Optional (DB 50 for I/O Shown)

Alta Data Technologies' PMC-1553 interface modules (PCI Mezzanine Card for Carriers and Single Board Computers) are multi-channel (1-4) 1553 cards supported by the latest software technologies. These PMC cards are based on the industry's most advanced 32-bit 1553 FPGA protocol engine, ***AltaCore***™, and by a feature-rich application programming interface, ***AltaAPI***™, which is a multi-layer ANSI C, C++, Windows .NET, Linux and most RTOSes. This hardware and software package provides increased system performance and reduces integration time.

AltaCore-1553 is guaranteed 1553A/B/C Notice II & IV compliant and all cards are manufactured to the highest IPC-Level 3 standards and ISO processes. Cards are available in dual-function (BC/Mon or multi-RT/Monitor) or full-function (BC, mRT and Mon) configurations. Playback and Signal Generation are part of BC operations. Alta is committed to a risk-free integration and will be glad to help with any level of your system development.



Alta's Advanced Software Architecture

Key Features:

- One to Four Independent, Dual Redundant MIL-STD-1553 Channels
- Dual Function (BC/Mon or mRT/Mon) or Full Function (BC/mRT/Mon)
- One Mbyte of Memory per Channel
- Fully Compliant to MIL-STD-1553A/B/C Notice II/IV, MIL-STD-1760 and Link-16
- **One of the Most Popular 1553 Cards in the Market with 1000s Deployed**
- Commercial or Industrial Extended Temperature Parts, Conduction Cooled and Rear Panel Optional
- Advanced 32-bit BC, RT and Monitor FPGA Design – Full 32 bit Memory.
- BC Framing/Subframing/Aperiodic
- Common Data Packets (CDP) for BC, RT and Monitor – Complete Message Info
- Advanced, Multi-layer ***AltaAPI*** Provided at No Cost with Source Code
- Windows, Linux, RTOS, LabVIEW & RT
  - .NET Managed DLLs
  - Contact Factory for Latest RTOS Support
- True HW Playback – HW Sync Channels
- Industry First: 20ns Signal Generation
  - Bit Construction – 1553 PHY TX
  - Supports RT Validation Testing
- IRIG-B RX PAM or RX/TX PPS Ext Clock
- Avionics Level & RS-485 Discretes/Clk
  - 1760 Ext RT Addressing
- Advanced BIT Features and Dual Temperature Sensors
- Full HW Interrupt Features
- PCI 32 Bit, 33/66MHz & PCI-X Compatible

www.altadt.com

4901 Rockaway Blvd., Building A Rio Rancho, NM 87124 USA
(In US): 888-429-1553 (Outside US): 505-994-3111 Fax: 805-504-8588

Multi-Channel (1-4)
PMC-1553 Specifications

General

- 32-Bit PCI 33/66MHz/PCI-X Compatible
  - PCI-SIG PCI 2.1 Compliant
  - ANSI/VITA 20-2001 Compliant
- One Megabyte RAM per Channel
- Common Data Packets (CDPs) for all BC, RT and Monitor Functions – Industry First
- MIL-STD-1553A/B/C Notice II & IV
  - MIL-STD-1760,1553A and Link-16
- Weight: 4oz/120grams
- Power (Estimated @ Max Bandwidth)
  - 1CH@5.5W, 2CH@6.5W, 3CH@7.5W, 4CH@8.5W
- Parts Temp (C) : -55 to +120 Storage, 0 to +70 Commercial, -40 to +85 Extended
- SCSI 3 Cable Assembly with 1553 3-Plug Stub Cables Provided. DB50 Optional for Trig/Clk/IO.
- 14 Avionics and Two RS-485 Discretes
- 1 Channel 1760 Ext RT Address Power-Up
- Loop-Back & User BIT, Dual Temp Sensors
- IRIG-B RX PAM and TX/RX PPS Time Sync
- IPC Class 3 and ISO 9001:2008 Processes

BC Features

- Simple One-Shot Lists to Advanced Message Framing and Subframing
- Message Timing with 100 nSec Accuracy
- Infinite Linked CDP Data Buffers
  - 64-Bit, 20 ns Time Tags, Interrupts, Triggers
- Low and High Priority Aperiodic Messages
- Multi Branching Per Message, No-Ops, Delays, Ext Trigger In/Out, Interrupts etc…
- Up to 15 Retries Per Message
- Legal and Reserved Mode Codes
- 1553A and 1553B Support
- Full Error Injection/Detection

Playback/Signal Vector PHY TX

- Real Hardware Playback from Archive Files
- Multi Channel and Multi Card Playback Clock Synchronization - 100 nSec Accuracy
- Signal Vector Generation at 20 nsecs **INDUSTRY FIRST**
  - Construct 1553 Bit Signals at 20 nsecs
  - **AS4111 5.2 RT Val Protocol Capability
  - Advanced BC, RT or any 1553 PHY Signal TX

RT Features

- Infinite Linked CDP Data Buffers
  - 64-Bit, 20 ns Time Tags, Interrupts, Triggers
- Legal and Reserved Mode Codes
  - 1553A and 1553B Support
  - Full Buffering of All Mode Codes
- Full Error Injection/Detection

Monitor

- Sequential and RT Mapped Monitoring with Infinite Linked CDP Data Buffers
  - Available with All Card Models
  - 64-Bit, 20 ns Time Tags, Interrupts, Triggers
  - Full Error Detection

Software: *AltaAPI*, *AltaView*, *AltaRTVal*

- Multi-Layer ***AltaAPI*** Architecture to Support Windows and ANSI C Linux, VxWorks, Integrity, etc…
  - Contact Factory For RTOS Platforms
  - LabVIEW & RT Support
- Optional ***AltaView*** is Based on the Latest Windows MS Office User Interface Style with Ribbon-Bar
  - Full Analyzer Integration Tool
- Optional ***AltaRTVal*** provides full AS4111/4112 5.2 RT Validation GUI and Reports

Part Numbers

Dual Function Models: BC/Mon or mRT/Mon

- **PMC-1553-1D/2D/3D/4D-T**

Full Function Models: BC, mRT and Monitor

- **PMC-1553-1F/2F/3F/4F-T**

Options: -E for Ext Temp Parts (-40 to +85C), -C for Ext Temp, Conduction Cooled/Conformal Coated/Rear Panel, -R for Rear Panel P4 Commercial, -A for AltaView and –B for AltaRTVal. Ask factory about cable options.

5 Year Limited Warranty!

EU and China RoHS Compliant

Contact Alta for Special Lead Build Configurations

AltaAPI Software with ANSI C Source, .Net Managed DLLs and LabVIEW & LabVIEW-RT Provided at No Cost.

Alta Data Technologies LLC
4901 Rockaway Blvd., Building A
Rio Rancho, NM 87124 USA
888-429-1553 (in US)
505-994-3111 (outside US)
alta.sales@altadt.com
www.altadt.com

Information in this data sheet is subject to change without notice. Alta is not responsible for errors or omissions. All trademarks are reserved by their respective owners. AltaCore, AltaAPI, AltaView and AltaRTVal are trademarks of Alta Data Technologies.2301 – Page 2/2

Alta dt data technologies

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP