

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Mercury Computer Systems / Momentum Computer Leopard-A500* at our website: ***Click HERE***

Leopard-A500

500 MHz UltraSPARC™ IIe CompactPCI Single Board Computer

momentum COMPUTER



Two Gigabit Ethernet for PICMG 2.16, High Performance, Low Power, 2 PMC Slots

Leopard-A500 is a CompactPCI 6U form factor Single Board Computer that is designed for high performance embedded applications. It utilizes the Sun Microsystems UltraSPARC IIe processor and supports up to 2 Gbytes of SDRAM memory.

The Leopard-A500 occupies a single system or non-system slot in a standard CompactPCI chassis. The board automatically detects whether it is installed in a system or non-system slot and configures itself accordingly.

The board has two Gigabit Ethernet (copper) ports implementing PICMG 2.16, and has a full 64-bit PCI interface to a rear I/O module for virtually unlimited I/O capability. Two PMC slots are provided for user hardware expansion, one with rear I/O PIM support.

FEATURE SET:

- Sun Microsystems UltraSPARC-IIe (V9 architecture with VIS instruction set) operating at 500 MHz. The CPU has 16 Kbytes of L1 instruction cache, 16 Kbytes of L1 data cache, and an internal 256 Kbytes L2 unified cache (all caches 4-way set associative).
- Single slot 6U CompactPCI (PICMG 2.0 R3.0) board supporting auto-sensing of system or non-system slot functionality.
- Hot Swappable (PICMG 2.1 R2.0).
- BMC or Standard Node capability per PICMG 2.9 R1.0 System Management Specification.
- Temperature and voltage sensors provide real time feed back for critical applications.
- 2 level Watchdog timer.
- Compact PCI connector J4 not populated to avoid conflict with H.110 Computer Telephony bus.
- Open boot firmware.
- Power on Self-Test (POST).
- One LED for POST results and one user controlled LED.
- Solaris version 2.8

MEMORY AND STORAGE:

- Up to 2 Gbytes SDRAM with ECC running at 108 MHz. Up to 1 Gbyte SDRAM is soldered directly to the baseboard. An additional 1 Gbyte SDRAM can be added with a Momentum Expansion Memory Module (MEMM). (The MEMM module shares its location with one of the two PMC slots: see below).
- Two socketed 512K byte Flash PROMs. Both are selectable as boot device via a jumper. One is reserved for Open Firmware; the other is free for user data, programs or NVRAM data backup.
- 32 Kbytes of NVRAM and Real Time Clock.


VERSATILE I/O:

on main board:

- Two 10/100/1000 BaseT Gigabit Ethernet ports routed to PICMG 2.16 packet switched backplane connection on J3.
- Two 64-bit, 33 MHz, PMC slots (IEEE P1386 / P1386.1). One PMC slot has rear I/O PIM support. The other PMC slot shares its location with the memory mezzanine so going beyond 2G of SDRAM prevents the use of the second PMC slot.
- 64-bit PCI interface to rear I/O module for virtually unlimited I/O options. Rear I/O modules are currently available with SCSI, Ethernet and serial ports.
- RS-232 communication port interfaces to front panel RJ11 connector or J3 for rear I/O.

Leopard-A500

500 MHz UltraSPARC™ IIe CompactPCI Single Board Computer



The Leopard-A650 Version with 650 MHz UltraSPARC IIi+: Leopard-A is also available with the UltraSPARC IIi+ running at 650 MHz. This version of Leopard-A has 512 Kbytes of L2 cache and supports 4 Gbytes of SDRAM: 2 Gbytes on the baseboard plus a 2 Gbyte SDRAM mezzanine. With the 650 MHz UltraSPARC-IIi+, the SDRAM runs at 108 MHz. For complete details, see the Leopard-A650 data sheet.

If the Leopard-A500 doesn't fit your specific requirements: Momentum Computer specializes in quick turn custom development and production of high performance processor boards and I/O boards.

Custom designs give you a competitive edge by providing the unique features needed for a leading market position.

Custom designs by Momentum Computer are accomplished so rapidly that time-to-market targets can be met with confidence.

We're ready to work for you.

momentum COMPUTER

Momentum Computer, Inc.
1815 Aston Avenue, Suite 107, Carlsbad, CA 92008-7310
Tel: 760.431.8663 • Fax: 760.431.7571 • e-mail: info@momenco.com
www.momentum-computer.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP