

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Mountain Engineering & Technology ME-1001* at our website: ***Click HERE***

Mountain Engineering & Technology

ME-1001

Long Line Simulator, #22AWG



Features

- Simulates #22AWG (0.7mm) PIC unshielded twisted-pair (UTP) telephone transmission line
- Selectable attenuations levels 0dB to -48dB @ 772kHz (1.544Mb/s) in 1dB steps and from 0dB to -55.7dB @ 1024kHz (2.048Mb/s) in 1.16dB steps
- Selectable line impedance: 100Ω , 120Ω , or 75Ω BALUN
- Accurate over a 3 decade frequency range, from 10kHz to 10MHz
- Convenient front panel controls and displays, calibrated in kFeet, Meters, and dB of Attenuation at 772/1024kHz
- Remote control of all functions via standard RS-232 port
- Accepts standard BNC, Bantam, and 310 connectors

Compatibility

- US and European AMI-PCM codes:

  T1 - 1.544Mb/s
  T1C - 3.152Mb/s
  T2 - 6.312Mb/s
  CEPT - 2.048Mb/s
  CEPT - 8.448Mb/s

- ISDN Primary rate standards, 1.544Mb/s and 2.048Mb/s

Applications

- Design and evaluation of serial data receivers and repeaters
- Replaces 11kft (3.3km) of transmission line in laboratory experiments
- Allows automated testing of telecommunications, PBX, and LAN equipment

General Description

The ME-1001 Line Simulator is a highly accurate, programmable filter designed to simulate the attenuation versus frequency characteristics of the #22AWG (0.7mm) unshielded twisted-pair transmission wire commonly used in long distance telephone trunk lines in the US and around the world. The same wire is also found in office buildings and industrial complexes where it forms the backbone of PBX and LAN communication systems. By simulating 11kft (3.3km) of transmission line in 230ft (70m) increments, the ME-1001 offers a convenient and practical method of developing and testing communications equipment intended for use on this wire.

Easy to use front panel controls set the ME-1001's simulated line length displayed in kFeet, Meters, or dB of Attenuation at either 772kHz for 1.544Mb/s applications or 1024kHz for 2.048Mb/s applications. Input and output line terminations are also user-selectable to correctly match the characteristic impedances

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

- Japan's CMI code standard, 2.048Mb/s
- Manchester coded data from 100kb/s to 10Mb/s

of either 100Ω or 120Ω twisted-pair wire systems. A 75Ω BALUN connection is also provided. All ME-1001 functions can be computer controlled via a standard RS-232 serial port for automated test applications. Options include 19" rack mount chassis, battery back-up, and an internal noise mixer.

Operating Specifications

(Valid at all attenuation settings, test signal (f_o) = 772kHz and 0°C < $T_{ambient}$ < 50°C unless otherwise stated)

Input

Terminating Impedance 100Ω/120Ω/75Ω, ą5%

Recommended Frequency Range ..... 10kHz to 10MHz

Maximum Balanced Input Voltage,
Zero to Peak ą6V

Maximum Balanced DC Input Current,
Input Center-Tap to Output Center-Tap .. 70mA

Output

Sourcing Impedance 100Ω/120Ω/75Ω, ą5%

Maximum Rise/Fall Time At 0dB,
$V_{IN} = 3V_{PEAK}$ ..... < 40nsec

Maximum Overshoot At 0dB,
$V_{IN} = 3V_{PEAK}$ ..... < 10%

Short Circuit Tolerance ..... Continuous

Attenuation Characteristics

Attenuation range at f_o with display setting:

f_o = 772kHz ..... 0dB to -48.0dB
f_o = 1024kHz ..... 0dB to -55.7dB

Frequency dependent attenuation simulates that of #22AWG (0.7mm) unshielded twisted-pair wire at 20şC. The following indicates the relative attenuation (A_R) verses frequency normalized at f_o =772kHz.

Freq. (kHz)	10	20	30	50	70	100	200	300
A_R (dB)	.225	.260	.291	.332	.359	.393	.495	.602
Freq. (MHz)	.500	.772	1.024	2.0	3.0	5.0	7.0	10.0
A_R (dB)	.785	1.0	1.16	1.62	1.98	2.62	3.21	4.04


The attenuation at any frequency, A(f), can be calculated as a function of the attenuation setting at f_o=772kHz as follows:

$$A(f) = A_R(f) \times A(f_o)$$

.

Attenuation adjustment step size with display setting:

f_o = 772kHz 1.00dB
f_o = 1024kHz (Displayed to nearest 0.1dB) ... 1.16dB




CLICK ON GRAPH TO ENLARGE

Attenuation Accuracy

Attenuation tolerance at f_o with display setting:

f_o = 772kHz ..... ą 0.25dB
f_o = 1024kHz ..... ą 0.30dB

Attenuation tolerance at all other frequencies relative to f_o is given by the following graph:




CLICK ON GRAPH TO ENLARGE

General Specifications

Power input voltage:
- Option A ..... 105V to 130V
- Option B ..... 210V to 250V
- Option J ..... 90V to 110V

Power input frequency ..... 45Hz to 66Hz
Power consumption 10W
Dimensions (w x h x d in inches) ..... 17 x 3.5 x 14
Weight ..... 13 lbs
Storage temperature ..... -40°C to 85°C

Ordering Information



Back to Products Page

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP