ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Myricom M2M-PMC32A* at our website: ***Click HERE***


M2M-PMC32C

32-bit, 33MHz, Myrinet-SAN/PCI interface in the PMC form factor

Many single-board Computers (SBCs) accept PCI devices in a standard form factor called "PMC" -- the PCI Mezzanine Card (IEEE P1386.1).




M2M-PMC32C, Myrinet-SAN/PCI interface in the PCI Mezzanine Card (PMC) form factor



M2M-PMC32 interface on a Motorola MVME1603e SBC.
The Myrinet-SAN-port end of the PMC interface fits into the VME front panel.

This PMC Myrinet-SAN/PCI interfaces is functionally identical to the M2M-PCI32C PCI-short-card version except that it adheres to the (single-width) PMC form factor. The small, very flexible, Myrinet-SAN cables that plug into Myrinet-SAN ports are ideal for in-chassis connections on the front-panel side of VME systems. 6U VME SBCs can be clustered using a 6U-VME-form-factor Myrinet-SAN switch.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com



Block diagram of the M2M-PMC32B&C

Specifications

PCI-bus Interface: 32-bit, 33MHz, supports all burst modes and write-invalidate, master or slave. Sustained DMA performance at 33MHz with large blocks exceeds 120 MB/s peer mode, or to/from system memory on platforms with good PCI implementations.

Interface processor: LANai-4 RISC operating at the PCI-clock rate.

Interface memory: 1MB (256Kx4B). The interface memory operates at double the PCI-clock rate. With a 33MHz PCI clock, 264 MB/s of memory bandwidth is available to support the Myrinet link, the host DMA, and the RISC processor.

Myrinet-SAN port: 1.28+1.28 Gb/s on the A link; B link unused.

Physical characteristics: PCI Mezzanine Card; ~4 Watts.

Myricom-supported software: Both GM and MyriAPI software, which can be downloaded from the Software & Customer Support page.

Last updated: 1 July 1999

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP