ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *National Instruments PXI-7853R* at our website: *Click HERE*

NI R Series Multifunction RIO Specifications

This document lists the specifications of the NI 781*x*R/783*x*R/784*x*R/785*x*R. These specifications are typical at 25 °C unless otherwise noted.

Français Deutsch 日本語 한국어 简体中文

ni.com/manuals

Analog Input (NI 783*x*R/784*x*R/785*x*R Only)

Input Characteristics

Number of channels

- NI 7830R 4
- NI 7831R/7833R/7841R/7842R/7851R/7852R/7853R/7854R 8

Input modes ..... DIFF, RSE, NRSE (software-selectable; selection applies to all channels)

Type of ADC ..... Successive approximation

Resolution ..... 16 bits, 1 in 65,536

Conversion time

- NI 783*x*R/NI 784*x*R ..... 4 µs
- NI 785*x*R ..... 1 µs

Maximum sampling rate

- NI 783*x*R/784*x*R ..... 200 kS/s (per channel)
- NI 785*x*R ..... 750 kS/s (per channel)

Input impedance

- Powered on ..... 10 GΩ in parallel with 100 pF
- Powered off/overload ..... 4.0 kΩ min

Input signal range ..... ±10 V

Input bias current

- NI 783*x*R ..... ±2 nA
- NI 784*x*R/785*x*R ..... ±5 nA

Input offset current

- NI 783*x*R ..... ±1 nA
- NI 784*x*R/785*x*R ..... ±5 nA

Input coupling ..... DC

Maximum working voltage (signal + common mode) ..... Inputs should remain within ±12 V of ground

Overvoltage protection

- Powered on ..... ±42 V
- Powered off ..... ±35 V

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Accuracy Information

NI 783*x*R

Nominal Range (V)		Absolute Accuracy							Relative Accuracy	
		% of Reading			Noise + Quantization (µV)				Resolution (µV)	
Positive Full Scale	Negative Full Scale	24 Hours	1 Year	Offset (µV)	Single Point	Averaged	Temp Drift (%/°C)	Absolute Accuracy at Full Scale (±mV)	Single Point	Averaged
10.0	–10.0	0.0496	0.0507	2,542	1,779	165	0.0005	7.78	2,170	217

Note: Accuracies are valid for measurements following an internal calibration. Averaged numbers assume dithering and averaging of 100 single-channel readings. Measurement accuracies are listed for operational temperatures within ±1 °C of internal calibration temperature and ±10 °C of external or factory-calibration temperature.

NI 784*x*R/785*x*R

Nominal Range (V)		Absolute Accuracy							Relative Accuracy	
		% of Reading			Noise + Quantization (µV)				Resolution (µV)	
Positive Full Scale	Negative Full Scale	24 Hours	1 Year	Offset (µV)	Single Point	Averaged	Temp Drift (%/°C)	Absolute Accuracy at Full Scale (±mV)	Single Point	Averaged
10.0	–10.0	0.0186	0.0228	1,591	1,029	91.6	0.0005	3.97	1,205	121

Note: Accuracies are valid for measurements following an internal calibration. Averaged numbers assume dithering and averaging of 100 single-channel readings. Measurement accuracies are listed for operational temperatures within ±1 °C of internal calibration temperature and ±10 °C of external or factory-calibration temperature.

DC Transfer Characteristics

INL

NI 783*x*R.....±3 LSB typ, ±6 LSB max

NI 784*x*R/785*x*R .....±1 LSB typ, ±3 LSB max

DNL

NI 783*x*R.....–1.0 to +2.0 LSB max

NI 784*x*R/785*x*R .....±0.4 LSB typ, ±0.9 LSB max

No missing codes

NI 783*x*R.....16 bits typ, 15 bits min

NI 784*x*R/785*x*R .....16 bits guaranteed

CMRR, DC to 60 Hz .....–86 dB

Dynamic Characteristics

Bandwidth

NI 783*x*R

Small signal (–3 dB).....650 kHz

Large signal (1% THD).....55 kHz

NI 784*x*R/785*x*R

Small signal (–3 dB) ..... 1 MHz

Large signal (1% THD) ..... 500 kHz

Settling Time

Device	Step Size	Accuracy		
		±16 LSB	±4 LSB	±2 LSB
NI 783*x*R	±20.0 V	7.5 µs	10.3 µs	40 µs
	±2.0 V	2.7 µs	4.1 µs	5.1 µs
	±0.2 V	1.7 µs	2.9 µs	3.6 µs
NI 784*x*R/ 785*x*R	±20.0 V	2.1 µs	4.2 µs	8 µs
	±2.0 V	1.3 µs	1.6 µs	1.8 µs
	±0.2 V	0.8 µs	1.1 µs	1.2 µs

Crosstalk ..... –80 dB, DC to 100 kHz

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Analog Output (NI 783*x*R/784*x*R/785*x*R Only)

Output Characteristics

Output type ..... Single-ended, voltage output

Number of channels

NI 7830R 4

NI 7831R/7833R/7841R/7842R/ 7851R/7852R/7853R/7854R 8

Resolution..... 16 bits, 1 in 65,536

Update time ..... 1.0 µs

Maximum update rate..... 1 MS/s

Type of DAC..... Enhanced R-2R

Accuracy Information

Nominal Range (V)		Absolute Accuracy				Absolute Accuracy at Full Scale (mV)
		% of Reading				
Positive Full Scale	Negative Full Scale	24 Hours	1 Year	Offset (µV)	Temp Drift (%/°C)	
10.0	–10.0	0.0335	0.0351	2366	0.0005	5.88

Note: Accuracies are valid for analog output following an internal calibration. Analog output accuracies are listed for operation temperatures within ±1 °C of internal calibration temperature and ±10 °C of external or factory calibration temperature. Temp Drift applies only if ambient is greater than ±10 °C of previous external calibration.

DC Transfer Characteristics

INL..... ±0.5 LSB typ, ±4.0 LSB max

DNL ..... ±0.5 LSB typ, ±1 LSB max

Monotonicity..... 16 bits, guaranteed

Voltage Output

Range ..... ±10 V

Output coupling ..... DC

Output impedance

NI 783*x*R ..... 1.25 Ω

NI 784*x*R/785*x*R..... 0.5 Ω

Current drive..... ±2.5 mA

Protection ..... Short-circuit to ground

Power-on state..... User configurable

Dynamic Characteristics

Settling time

Step Size	Accuracy		
	±16 LSB	±4 LSB	±2 LSB
±20.0 V	6.0 µs	6.2 µs	7.2 µs
±2.0 V	2.2 µs	2.9 µs	3.8 µs
±0.2 V	1.5 µs	2.6 µs	3.6 µs

Slew rate..... 10 V/µs

Noise..... 150 μV_{rms}, DC to 1 MHz

Glitch energy
at midscale transition..... ±200 mV for 3 µs

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Digital I/O

Number of channels

- NI 781*x*R 160
- NI 7830R 56
- NI 7831R/7833R/7841R/7842R/7851R/7852R/7853R/7854R 96

Compatibility ..... TTL

Digital logic levels

Level	Min	Max
Input low voltage (V_{IL})	0.0 V	0.8 V
Input high voltage (V_{IH})	2.0 V	5.5 V
Output low voltage (V_{OL}), where I_{OUT} = –4 mA	0 V	0.4 V
Output high voltage (V_{OH}), where I_{OUT} = 4 mA	2.4 V	3.3 V

Output current

- Source ..... 4.0 mA
- Sink ..... 4.0 mA

Input leakage current ..... ±10 µA

Power-on state ..... Programmable, by line

Protection

- Input
  - NI 781*x*R/783*x*R ..... –0.5 to 7.0 V, single line
  - NI 784*x*R/785*x*R ..... –20.0 to 20.0 V, single line
- Output ..... Short-circuit (up to eight lines may be shorted at a time)

Minimum pulse width

- Input ..... 25 ns
- Output ..... 12.5 ns

Minimum sampling period ..... 5 ns

Reconfigurable FPGA

NI 7811R/7830R/7831R

- FPGA type ..... Virtex-II V1000
- Number of flip-flops 10,240
- Number of 4-input LUTs 10,240
- Number of 18 × 18 multipliers ... 40
- Embedded block RAM ..... 720 kbits

NI 7813R/7833R

- FPGA type ..... Virtex-II V3000
- Number of flip-flops 28,672
- Number of 4-input LUTs 28,672
- Number of 18 × 18 multipliers ... 96
- Embedded block RAM ..... 1,728 kbits

NI 7841R/7851R

- FPGA type Virtex-5 LX30
- Number of flip-flops 19,200
- Number of 6-input LUTs 19,200
- Number of DSP48 slices (25 × 18 multipliers) 32
- Embedded block RAM ..... 1,152 kbits

NI 7842R/7852R

- FPGA type Virtex-5 LX50
- Number of flip-flops 28,800
- Number of 6-input LUTs 28,800
- Number of DSP48 slices (25 × 18 multipliers) 48
- Embedded block RAM ..... 1,728 kbits

NI 7853R

- FPGA type Virtex-5 LX85
- Number of flip-flops 51,840
- Number of 6-input LUTs 51,840
- Number of DSP48 slices (25 × 18 multipliers) 48
- Embedded block RAM ..... 3,456 kbits

NI 7854R

- FPGA type Virtex-5 LX110
- Number of flip-flops 69,120
- Number of 6-input LUTs 69,120
- Number of DSP48 slices (25 × 18 multipliers) 64
- Embedded block RAM ..... 4,608 kbits

Timebase ..... 40, 80, 120, 160, or 200 MHz

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Timebase reference sources

NI PCI-781*x*R/783*x*R ..... Onboard clock only

NI PCIe-784*x*R/785*x*R ..... Onboard clock only

NI PXI-78*xx*R..... Onboard clock, phase-locked to PXI 10 MHz clock

Timebase accuracy, onboard clock..... ±100 ppm, 250 ps peak-to-peak jitter

Phase locked to PXI 10 MHz Clock (NI PXI-78*xx*R only)..... Adds 350 ps peak-to-peak jitter

Additional frequency-dependent peak-to-peak jitter

NI 781*x*R/783*x*R

- 40 MHz ..... None
- 80 MHz ..... 400 ps
- 120 MHz ..... 720 ps
- 160 MHz ..... 710 ps
- 200 MHz ..... 700 ps

NI 784*x*R/785*x*R

- 40 MHz ..... None
- 80 MHz ..... 460 ps
- 120 MHz ..... 172 ps
- 160 MHz ..... 172 ps
- 200 MHz ..... 152 ps

Calibration (NI 783*x*R/784*x*R/785*x*R Only)

Recommended warm-up time ..... 15 minutes

Calibration interval ..... 1 year

Onboard calibration reference

DC level..... 5.000 V (±3.5 mV) (actual value stored in Flash memory)

Temperature coefficient ..... ±5 ppm/°C max

Long-term stability ..... ±20 ppm/$\sqrt{1{,}000\ \text{h}}$

Note Refer to *Calibration Certificates* at `ni.com/calibration` to generate a calibration certificate for the NI 78*xx*R.

Bus Interface

PCI/PCIe/PXI .....Master, slave

Data transfers.....DMA, interrupts, programmed I/O

Number of DMA channels 3

Power Requirement

+5 VDC (±5%)[1]

- NI 781*x*R.....9 mA typ
- NI 7830R/7831R.....330 mA typ
- NI 7833R.....364 mA typ
- NI PXI-7841R/7851R .....125 mA typ
- NI PXI-7842R/7852R .....136 mA typ
- NI 7853R.....460 mA typ
- NI 7854R.....484 mA typ

+3.3 VDC (±5%)[2]

- NI 7811R.....650 mA typ
- NI 7813R.....850 mA typ
- NI 7830R/7831R.....462 mA typ
- NI 7833R.....727 mA typ
- NI PCIe-7841R/7851R .....847 mA typ
- NI PCIe-7842R/7852R .....984 mA typ
- NI PXI-7841R/7851R .....525 mA typ
- NI PXI-7842R/7852R .....604 mA typ
- NI 7853R.....640 mA typ
- NI 7854R.....843 mA typ

+12 V

- NI 784*x*R/785*x*R .....0.5 A

–12 V

- NI PXI-784*x*R/785*x*R .....0.25 A

+5V terminal

- Connector 0.....0.5 A max[3]
- Connector 1.....0.5 A max[3]
- Connector 2.....0.5 A max[3]
- All connectors .....1.5 A max[3, 4]

---

[1] Does not include current drawn from the +5 V line on the I/O connectors.

[2] Does not include current sourced by the digital outputs.

[3] **(NI PCIe-78*xx*R only)** Total maximum terminal current for all connectors is 100 mA unless disk drive connector is attached.

[4] **(NI 784*x*R/785*x*R only)** The NI 784*x*R/785*x*R has a user-replaceable socketed fuse that opens when current exceeds the current specification. Refer to the *NI R Series Multifunction RIO User Manual*, available at `ni.com/manuals`, for information about fuse replacement.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

To calculate the total current sourced by the digital outputs, use the following equation:

$$\sum_{i=1}^{j} \text{current sourced on channel } i$$

Power available at I/O connectors ... 4.50 to 5.25 VDC at 1 A total, 250 mA per I/O connector pin

Physical

Dimensions (not including connectors)

- NI PCI-781*x*R/783*x*R ... 17 cm by 11 cm (6.7 in. by 4.3 in.)
- NI PCIe-784*x*R/785*x*R ... 17 cm by 11 cm (6.7 in. by 4.3 in.)
- NI PXI-78*xx*R ... 16 cm by 10 cm (6.3 in. by 3.9 in.)

Weight

- NI PCI-781*x*R/783*x*R ... 112 g
- NI PCIe-784*x*R/785*x*R ... 127 g
- NI PXI-78*xx*R ... 152 g

I/O connectors

- NI 781*x*R ... Four 68-pin female high-density VHDCI type
- NI 7830R ... Two 68-pin female high-density VHDCI type
- NI 783*x*R/784*x*R/785*x*R ... Three 68-pin female high-density VHDCI type

Disk drive power connector (PCIe devices) ... Standard ATX peripheral connector (not serial ATA)

Maximum Working Voltage (NI 783*x*R/784*x*R/785*x*R Only)

Maximum working voltage refers to the signal voltage plus the common-mode voltage.

Channel-to-earth ... ±12 V, Measurement Category I

Channel-to-channel ... ±24 V, Measurement Category I

Caution Do *not* use the NI 783*x*R/784*x*R/785*x*R for connection to signals in Measurement Categories II, III, or IV.

Environmental

The NI 78*xx*R is intended for indoor use only.

Operating Environment

NI 781*x*R ... 0 °C to 55 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

NI 7830R, NI 7831R

- 40 MHz or 80 MHz timebase ... 0 °C to 55 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

NI PCI/PXI-7833R

- 40 MHz timebase ... 0 °C to 55 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.
- 80 MHz timebase ... 0 °C to 55 °C except the following: 0 °C to 45 °C when installed in an NI PXI-1000/B or NI PXI-101X, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

NI PXI-7841R/7842R/7851R/7852R/7853R/7854R

- 40 MHz timebase ... 0 °C to 55 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.
- 80 MHz timebase ... 0 °C to 55 °C except the following: 0 °C to 45 °C when installed in an NI PXI-1000/B or NI PXI-101X, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

NI PCIe-7841R/7842R/7851R/7852R

- 40 MHz or 80 MHz timebase ... 0 °C to 40 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

Relative humidity range ... 10% to 90%, noncondensing, tested in accordance with IEC-60068-2-56.

Altitude ... 2,000 m at 25 °C ambient temperature

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Storage Environment

NI PCI/PXI-781*x*R/783*x*R ..... –20 °C to 70 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

NI PCIe-784*x*R/785*x*R ..... –20 °C to 70 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

NI PXI-784*x*R/785*x*R ..... –40 °C to 70 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

Ambient temperature range ..... –20 °C to 70 °C, tested in accordance with IEC-60068-2-1 and IEC-60068-2-2.

Relative humidity range..... 5% to 95%, noncondensing, tested in accordance with IEC-60068-2-56.

Note Clean the device with a soft, non-metallic brush. Make sure that the device is completely dry and free from contaminants before returning it to service.

Shock and Vibration (for NI PXI-78*xx*R Only)

Operational shock ..... 30 g peak, half-sine, 11 ms pulse; tested in accordance with IEC-60068-2-27. Test profile developed in accordance with MIL-PRF-28800F.

Random vibration

Operating ..... 5 Hz to 500 Hz, 0.3 g_{rms}

Nonoperating ..... 5 Hz to 500 Hz, 2.4 g_{rms}, tested in accordance with IEC-60068-2-64. Nonoperating test profile exceeds the requirements of MIL-PRF-28800F, Class 3.

Safety

The NI 78*xx*R is designed to meet the requirements of the following standards of safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA 61010-1

Note For UL and other safety certifications, refer to the product label or the *Online Product Certification* section.

Electromagnetic Compatibility

The NI 78*xx*R is designed to meet the requirements of the following standards of EMC for electrical equipment for measurement, control, and laboratory use:

- EN 61326 (IEC 61326): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- AS/NZS CISPR 11: Group 1, Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions

Note For the standards applied to assess the EMC of this product, refer to the *Online Product Certification* section.

Note For EMC compliance, operate this device with shielded cabling.

CE Compliance CE

This product meets the essential requirements of applicable European Directives as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2004/108/EC; Electromagnetic Compatibility Directive (EMC)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit `ni.com/certification`, search by model number or product line, and click the appropriate link in the Certification column.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *NI and the Environment* Web page at `ni.com/environment`. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of their life cycle, all products *must* be sent to a WEEE recycling center. For more information about WEEE recycling centers and National Instruments WEEE initiatives, visit `ni.com/environment/weee.htm`.

电子信息产品污染控制管理办法 （中国 RoHS）



中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于 National Instruments 中国 RoHS 合规性信息，请登录 `ni.com/environment/rohs_china`。(For information about China RoHS compliance, go to `ni.com/environment/rohs_china`.)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Device Pinouts




Figure 1. NI 781*x*R Connector Pin Assignments and Locations

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com




Figure 2. NI 783*x*R/784*x*R/785*x*R Connector Pin Assignments and Locations

National Instruments, NI, ni.com, and LabVIEW are trademarks of National Instruments Corporation. Refer to the *Terms of Use* section on `ni.com/legal` for more information about National Instruments trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at `ni.com/patents`.

© 2008–2009 National Instruments Corporation. All rights reserved.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP