ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *National Instruments SCXI-1190* at our website: *Click HERE*

Specifications for the NI SCXI™-1190

1.3 GHz Quad 4x1 50 Ω Multiplexer

This document lists specifications for the NI SCXI-1190 multiplexer module. All specifications are subject to change without notice. Visit `ni.com/manuals` for the most current specifications.

Configuration ..... Quad 4x1 multiplexers

RF Performance Characteristics

Characteristic impedance (Z_0)..... 50 Ω nominal

Insertion loss

- ≤100 MHz ..... <0.4 dB
- ≤500 MHz ..... <0.9 dB
- ≤1.3 GHz..... <1.5 dB
- ≤2 GHz..... <3 dB

VSWR

- ≤100 MHz ..... <1.15
- ≤500 MHz ..... <1.35
- ≤1.3 GHz..... <1.5
- ≤2 GHz..... <2.5

Channel-to-channel isolation

- ≤500 MHz ..... >60 dB
- ≤1.3 GHz..... >50 dB
- ≤2 GHz..... >30 dB

Propagation delay..... <3 ns

Rise time ..... <300 ps

National Instruments™, NI™, ni.com™, and SCXI™ are trademarks of National Instruments Corporation. Product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your CD, or `ni.com/patents`.

April 2003
323480A-01

© 2003 National Instruments Corp. All rights reserved.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Input Characteristics

All input characteristics are DC, AC_{rms}, or a combination unless otherwise specified.

Maximum switching voltage .....24 V
(channel-to-channel and channel-to-ground)

Maximum switching current.....1 A
(per channel)

Maximum carry current .....1 A
(per channel)

Maximum switching power .....24 W
(per channel)

Note National Instruments recommends against switching active RF signals. As a relay actuates, the channel is momentarily unterminated. Some RF sources can be damaged by reflections if their outputs are not properly terminated. Consult your RF source documentation for more information.

Maximum RF carry power .....10 W up to 900 MHz
(per channel)

DC path resistance

Initial.....<0.1 Ω

End of life .....>1 Ω

Path resistance is a combination of relay contact resistance and trace resistance. Contact resistance typically remains low for the life of a relay. At the end of relay life, the contact resistance rises rapidly above 1.0 Ω.

Dynamic Characteristics

Relay operate time (at 20 °C) .....15 ms

Release time (at 20 °C).....15 ms

Expected relay life

Mechanical .....5,000,000 cycles

Electrical.....100,000 cycles
(maximum load)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Physical Characteristics

Relay type ..... Electromechanical, non-latching

I/O connectors ..... 20 SMB jacks

Contact material ..... Gold-clad silver

Dimensions (W × H × D) ..... 3.0 cm × 17.3 cm × 19.6 cm
(1.2 in. × 6.7 in. × 7.6 in.)

Weight ..... 925 g
(2 lb, 1 oz)

Environment

Operating temperature ..... 0 °C to 50 °C

Storage temperature ..... –20 °C to 70 °C

Relative humidity ..... 5% to 85% noncondensing

Pollution Degree 2




Figure 1. NI SCXI-1190 Power-On State

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Compliance and Certifications

Safety

This product is designed to meet the requirements of the following standards of safety for electrical equipment for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 3111-1, UL 61010B-1
- CAN/CSA C22.2 No. 1010.1

Note For UL and other safety certifications refer to the product label or visit `ni.com`.

Electromagnetic Compatibility

Emissions	EN 55011 Class A at 10 m FCC Part 15A above 1 GHz
Immunity	EN 61326:1997 + A2:2001, Table 1
EMC/EMI	CE, C-Tick, and FCC Part 15 (Class A) Compliant

Note For EMC compliance, you *must* operate this device with shielded cabling.

CE Compliance

This product meets the essential requirements of applicable European Directives, as amended for CE Marking, as follows:

Low-Voltage Directive (safety)	73/23/EEC
Electromagnetic Compatibility Directive (EMC)	89/336/EEC

Note Refer to the Declaration of Conformity (DoC) for this product for any additional regulatory compliance information. To obtain the DoC for this product, click **Declarations of Conformity Information** at `ni.com/hardref.nsf/`.

323480A-01 Apr03

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP