



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Model 3150

Advanced High-Power Temperature Controller



- 15 A/23 V, low noise, bipolar output
- Extremely stable, long term drift <math><0.001^{\circ}\text{C}</math>
- Multiple sensors supported: thermistors, RTD, AD590/592, and LM335
- Complete characterization of TE cooler (I_{TE} and V_{TE}) versus temperature
- Automatic power management and failsafe shutdown

The **Model 3150 Temperature Controller** provides a 350 W bipolar output for operation with thermoelectric (TE) coolers. Active power management of the output DC power supply reduces unnecessary power dissipation resulting in increased temperature stability and higher reliability. Full 16-bit control and characterization of the TE module and temperature sensor is attainable via the IEEE-488 or RS-232 interfaces. LabVIEW drivers are included with the computer interfaces as a standard feature.

All pertinent TE cooler parameters I_{TE} , V_{TE} , temperature sensor ($^{\circ}\text{C}$, R, Amp, or Volts) are measured and simultaneously presented on the four line alphanumeric LCD display. All standard temperature sensors including thermistors, platinum RTD, AD590/592 and LM335 IC sensors are supported without

the need for additional interface units. Sensor calibration constants are easily programmed for direct readout in $^{\circ}\text{C}$.

A proportional-integral (P-I) control circuit is implemented in the Model 3150 that meets all the temperature stabilization requirements for laser diode users.

During operation, the front panel controls can be disabled to prevent any changes in the output by accidental misadjustment of the control knob.

Protection features include: I_{TE} Limit, Hi and Lo Temperature Limits, Sensor Open and TE Open Detection. To prevent noise pickup, either by the output lines or the sensor inputs — resulting in undesirable temperature oscillations — shielded cables are also available.

Specifications

| | |
|--|---|
| LCD Display | |
| Display Type | 4-line by 20 character alphanumeric |
| Display Backlighting | Green LED |
| Display Controls | Brightness, contrast (optimizes viewing angle) |
| Chassis Ground | 4 mm banana jack |
| Power Requirements | 90–132 VAC, 198–250 VAC (6 Amp Max), 50–60 Hz |
| Size (H x W x D) [in. (mm)] | 3.5 (86) x 14 (356) x 14 (356) |
| Mainframe Weight [lb (kg)] | 14 (6.4) |
| Operating Temperature | 0 $^{\circ}\text{C}$ to 40 $^{\circ}\text{C}$ (<math><80\%</math> relative humidity non-condensing) |
| Storage Temperature Range | -20 $^{\circ}\text{C}$ to + 60 $^{\circ}\text{C}$ (<math><90\%</math> relative humidity non-condensing) |
| Connectors | |
| RS-232 | 9-pin, male D-Sub |
| GPIB | 24-pin, IEEE-488 |
| Output Connectors TE Module and Sensor | 7-pin, female D-Sub 7W2 |

Accessories

| Model | Description |
|------------------------|---|
| 3150-02 ⁽¹⁾ | Temperature Controller Cable |
| 3150-04 ⁽¹⁾ | Temperature Controller/Mount Cable |
| 300-16 | 10.0 k Ω Thermistor ($\pm 0.2^{\circ}\text{C}$) |
| 300-22 | AD592CN IC Sensor (-45 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$ Range) |
| LD1-RACK | Rack Mount Kit, Single |

1) Please see page 347 for Cable Diagrams

Ordering Information

| Model | Description |
|-------|--|
| 3150 | Advanced High-Power Temperature Controller |

POLARIZATION MEASUREMENT AND CONTROL

LASER DIODE CONTROL

LASER DIODE MOUNTS

FIBER OPTIC COMPONENTS

OPTICAL FIBERS AND ACCESSORIES

EDUCATIONAL KITS

Specifications

| TEC Output | |
|---|-----------------------------|
| Type | Bipolar, Low Noise |
| Maximum Current | 15A at 23V or 12.5A at 28 V |
| Maximum Power (W) | 350 |
| I _{TE} Current Resolution (mA) | 0.458 |
| I _{TE} Current Accuracy ⁽³⁾ | ±(3% setting + 50 mA) |
| Current Limit | |
| Range (A) | 0–15 |
| Accuracy (mA) | ±150 |
| Ripple/Noise (rms) (mA) | <10 |
| Short-Term Stability (1 h) (°C) | 0.0005 |
| Long-Term Stability (24 h) (°C) | 0.001 |
| Temperature Coefficient (°C/°C) | <0.05 |
| TEC Measurement Display | |
| Temperature (°C) | -100.00 to +240.00 |
| Resistance (10 μA) (kΩ) | 0.01–495 |
| Resistance (100 μA) (kΩ) | 0.001–49.5 |
| Range Resistance (RTD) (Ω) | 20–192 |
| Range TE Voltage (V) | 0.0 to + 30.0 |
| TE Current (A) | -15.00 to +15.00 |
| Range AD590 Current (μA) | 248–378 |
| Range LM335 Voltage (mV) | 2331–3731 |
| Temperature (°C) | 0.01 |
| Resistance (10 μA) (Ω) | 10 |
| Resistance (100 μA) (Ω) | 1 |
| Resolution Resistance (RTD) (Ω) | 0.01 |
| Resolution TE Voltage (V) | 0.1 |
| TE Current (mA) | 10 |
| Resolution AD590 Current (μA) | 0.01 |
| Resolution LM335 Voltage (mV) | 0.1 |
| Temperature (°C) ⁽⁴⁾ | Typical ±0.1 |
| Resistance (10 μA) ⁽³⁾ | ±(0.04% + 16Ω) |
| Resistance (100 μA) ⁽³⁾ | ±(0.05% + 8Ω) |
| Accuracy Resistance (RTD) ⁽³⁾ | ±(0.03% + 50 mΩ) |
| Accuracy TE Voltage ⁽³⁾ | ±(0.005% + 100 mV) |
| TE Current ⁽³⁾ | ±(0.50% + 30 mA) |
| Accuracy AD590 Current ⁽³⁾ | ±(0.005% + 0.5 μA) |
| Accuracy LM335 Voltage ⁽³⁾ | ±(0.09% + 1 mV) |

| Temperature Sensors | Thermistor (NTC 2-wire) | AD590 | LM335 | RTD (100Ω) ⁽¹⁾ |
|---|--|-------|-------|---------------------------|
| Temp. Sensor Control Resolution (°C) | | 0.01 | | |
| Temp. Sensor Control Accuracy | ±0.05 °C ⁽²⁾ | ±0.05 | ±0.05 | ±0.05 |
| Sensor Bias | 10/100 μA | +5 V | 1 mA | 1 mA |
| Temperature Computation and Calibration | | | | |
| Thermistor | $1/T = (C1 \times 10^{-3} + (C2 \times 10^{-4})(\ln R) + (C3 \times 10^{-7})(\ln R)^3)$ | | | |
| AD590 | $T = C1 + C2 \times (I_{AD590}/1 \mu A/K - 273.15)$ | | | |
| LM335 | $T = C1 + C2 \times (V_{LM335}/10 \text{ mV/K} - 273.15)$ | | | |
| RTD (100Ω) | $R_T = R_0 [1 + C1T + C2T^2]; T \geq 0^\circ\text{C},$ $R_0 = \text{resistance at } 0^\circ\text{C where } R_0 = 100\Omega \text{ for a } 100\Omega \text{ Pt RTD.}$ $R_T = R_0 [1 + C1T + C2T^2 + C3T^3(T - 100)]; T < 0^\circ\text{C}$ | | | |

- 1) Accuracy is with lead wire resistance calibrated out
- 2) Thermistor accuracy will degrade at temperatures above 25°C
- 3) ± (x% Reading + Fixed Error)
- 4) Temperature is a value derived from the sensor's parameter (resistance, voltage or current) using the above temperature computation equations. Accuracy can be computed by applying the sensor's parameter to the above equations at the temperature in question.



Model 3150 Rear Panel

Related Products

Our Model 5600 Advanced High-Power Laser Diode Drive and our Model 762 Series High-Power Temperature Controlled Mounts complement Newport's 3150 Temperature Controller in performance and value.



Model 762/762W High-Power Laser Diode Mounts



Model 5600 Advanced High-Power Laser Diode Driver



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com