

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PTS-OPM Series

Optical Power Meter Modules

Key Features

- *Free-space and fiber optic measurements*
- *Compatible with all of Newport's low-power 818 Series, semiconductor detectors, including 818-IS-1 integrating sphere based systems*
- *Wide power range—from 1 pW up to 2 W (-90 to +33 dBm)*
- *Wide wavelength range—190 nm to 1800 nm*
- *Analog output for connection to external instruments*



The PTS-OPM Series Optical Power Meter Modules give the Model 8800 and 8200 Photonics Test System mainframes the utility of a benchtop optical power meter along with the convenience of a modular platform.

Single and dual-channel versions of this module are available, featuring an analog output for monitoring the detector input directly with an oscilloscope or volt meter.

The **PTS-OPM** modules utilize any one of Newport's new **918 Series** low-power, semiconductor detectors.

This makes these meters extremely versatile for measuring free-space and fiber optic lights sources, with power levels from 1 pW (-90 dBm) up to 2 W (+33 dBm), and wavelengths in the 190 nm to 1800 nm regime. The modules are also backward compatible with Newport's full range of **818 Series** detectors, using the **818-ADAPT-OPM** adaptor cable (requires a calibration module).

The optical power meter modules are individually calibrated using NIST traceable, precision current sources, and are shipped with a certificate of calibration.

Ordering Information

Model	Module Type
PTS-OPM-1	Single-Channel
PTS-OPM-2	Dual-Channel

Specifications

Model	PTS-OPM-1	PTS-OPM-2
Module Type	Single-Channel	Dual-Channel
Signal Ranges	Up to 8 decades (detector dependent)	
Auto-Ranging Time (typ)	200 ms	
Maximum Detector Input Current (mA)	5	
Analog Output (into 1 MΩ)	0–2 V	
DC Accuracy	<±2 %	
Detector Input	14-pin circular connector	
Connector, Analog Output	Mini-SMA	
Dimensions (H x W x D) [in. (cm)]	5.23 (13.3) x 1.39 (3.5) x 9.09 (23.1)	
Weight [lb (kg)]	1.75 (0.8)	
Operating Temperature	0°C to 40°C	
Storage Temperature	-20°C to 60°C	

Module/Detector System Specifications

Detector Model	918-UV/818-UV	918-SL/818-SL	918-IR/818-IR	918-IG/818-IG	818-IS-1
Material	Silicon	Silicon	Germanium	Indium Gallium Arsenide	InGaAs/Si
Active Diameter (cm)	1.13	1.13	0.3	0.3	
Wavelength (nm)	190–1100	400–1100	780–1800	800–1650	400–1650
Power Range (dBm)	-83 to +23	-90 to +33	-70 to +21.5	-90 to +21.5	-70 to +23
Accuracy (w/o attenuator)	±2%	±2%	±3%	±2%	±2.5%
Linearity (%)	0.5%	0.5%	±0.5%	±0.5%	±0.5%
NEP @ 5 Hz and 1 A/W (fW/√Hz)	50	50	4	30	3[1]

1) 0.01 A/W for the 818-IS-1

Artisan Scientific - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisan-scientific.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP