ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Newport U100-A* at our website: ***Click HERE***

ULTIMA Series

High-performance Mirror and Platform Mounts





- **Clear quadrant design**
- **Removable actuators**
- **Adaptors for a large variety of optics**
- **Platform mounts for custom optics mounting**

ULTIMA® Kinematic Optical Mounts are designed for demanding research, development, and industrial OEM applications requiring a stable optical positioner. They are available in aperture versions for 0.5, 1.0, 1.18, 2.0, and 3.0 in. (12.7, 25.4, 30.0, 50.8, and 76.2 mm) diameter optics, as well as platform versions in 0.5, 1.0, and 2.0 in. (12.7, 25.4, and 50.8 mm) sizes for holding mounted mirrors, prisms, or cube beamsplitters. Thick front and rear plates and optimized, stiff springs improve the long-term stability and provide greater protection against vibrations. The patented clear quadrant design exposes the edge of the optic, allowing beams to pass close to the edge of a mounted optic. Actuators can be quickly changed to accommodate a broad selection of adjustment screws, micrometers, and motorized actuators.


U50-A, U100-A, U200-A, U300-A: The -A versions, with the clear quadrant design, offer a versatile positioning system for mounting 0.5 to 3.0 in. (12.7 to 76.2 mm) diameter mirrors. Adaptors UPA1-.5, UPA1-.75, and UPA2-1 allow smaller diameter 0.5, 0.75, and 1 in. (12.7, 19.05, and 25.4 mm) optics to be mounted in the U100-A and U200-A. A large array of additional accessories is available (see ULTIMA Accessories) for other optics and configurations.

U50-P, U100-P, U200-P: When -P versions are used with the optional Adaptors UPA-PA.5, UPA-PA1, or UPA-PA2 these mounts can be converted to a horizontal tip/tilt or tip/tilt and translation post-mounted platform for prisms, cube beamsplitters, and other components. When used with the optional Mirror Holders UPA.5, UPA.75, UPA1, or UPA2, these mounts provide a stable mounting platform for 0.5 to 2 in. (12.7 to 50.8 mm) diameter mirrors.






Clear Quadrant Design



Small 'd' – Small Ø

Conventional Design



Large 'd' – Large Ø

The patented clear quadrant design allows a beam to pass close to the edge of a mounted optic



U50-A with KD.37 knobs



U50-A (back) U50-A (front)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Ordering Information

Model	Optic Diameter [in. (mm)]	Adjustment Screw Thread	Drive Type[1]	Angular Range (°)	Sensitivity[2] (arc sec)	Translation[3] [in. (mm)]
0.5 in. (12.7 mm) Optical Mounts						
U50-A	0.5 (12.7)	80 TPI	Allen-Key	±5	10.4	0.15 (3.8)
U50-A1	0.5 (12.7)	100 TPI	Allen-Key	±5	8.3	0.15 (3.8)
U50-AL	0.5 (12.7)	80 TPI	Allen-Key	±5	10.4	0.15 (3.8)
U50-AL1	0.5 (12.7)	100 TPI	Allen-Key	±5	8.3	0.15 (3.8)
U50-P	See adaptors	80 TPI	Allen-Key	±5	10.4	0.15 (3.8)
U50-P1	See adaptors	100 TPI	Allen-Key	±5	8.3	0.15 (3.8)
U50-PL	See adaptors	80 TPI	Allen-Key	±5	10.4	0.15 (3.8)
U50-PL1	See adaptors	100 TPI	Allen-Key	±5	8.3	0.15 (3.8)
1 in. (25.4 mm) Optical Mounts						
U100-A	1.0 (25.4)					
U100-A-LH	1.0 (25.4)					
U100-A2K	1.0 (25.4)	100 TPI	Knob	±7	3.8	
U100-A-LH-2K	1.0 (25.4)	100 TPI	Knob	±7	3.8	
U100-A2K-NL	1.0 (25.4)	100 TPI	Knob	±7	3.8	
U100-A2H	1.0 (25.4)	100 TPI	Locking Allen-Key	±7	3.8	
U100-A-LH-2H	1.0 (25.4)	100 TPI	Locking Allen-Key	±7	3.8	
U100-A2H-NL	1.0 (25.4)	100 TPI	Allen-Key	±7	3.8	
U100-A3K	1.0 (25.4)	100 TPI	Knob	±7	3.8	0.38 (9.7)
U100-A-LH-3K	1.0 (25.4)	100 TPI	Knob	±7	3.8	0.38 (9.7)
U100-A3K-NL	1.0 (25.4)	100 TPI	Knob	±7	3.8	0.38 (9.7)
U100-A3H	1.0 (25.4)	100 TPI	Locking Allen-Key	±7	3.8	0.38 (9.7)
U100-A-LH-3H	1.0 (25.4)	100 TPI	Locking Allen-Key	±7	3.8	0.38 (9.7)
U100-A3H-NL	1.0 (25.4)	100 TPI	Allen-Key	±7	3.8	0.38 (9.7)
U100-P	See adaptors					
U100-P2K		100 TPI	Knob	±7	3.8	
U100-P2K-NL		100 TPI	Knob	±7	3.8	
U100-P2H		100 TPI	Locking Allen-Key	±7	3.8	
U100-P3K	See adaptors	100 TPI	Knob	±7	3.8	0.38 (9.7)
U100-P3K-NL	See adaptors	100 TPI	Knob	±7	3.8	0.38 (9.7)
U100-P3H	See adaptors	100 TPI	Locking Allen-Key	±7	3.8	0.38 (9.7)
1.18 in. (30 mm) Optical Mounts						
U100-A-30	1.18 (30)					
2 in. (50.8 mm) Optical Mounts						
U200-A	2.0 (50.8)					
U200-A-LH	2.0 (50.8)					
U200-A2K	2.0 (50.8)	100 TPI	Knob	±5	2.4	
U200-A2K-NL	2.0 (50.8)	100 TPI	Knob	±5	2.4	
U200-A2H	2.0 (50.8)	100 TPI	Locking Allen-Key	±5	2.4	
U200-A3K	2.0 (50.8)	100 TPI	Knob	±5	2.4	0.38 (9.7)
U200-A3K-NL	2.0 (50.8)	100 TPI	Knob	±5	2.4	0.38 (9.7)
U200-A3H	2.0 (50.8)	100 TPI	Locking Allen-Key	±5	2.4	0.38 (9.7)
U200-P	See adaptors					
U200-P2K	See adaptors	100 TPI	Knob	±5	2.4	
U200-P2H	See adaptors	100 TPI	Locking Allen-Key	±5	2.4	
U200-P3K	See adaptors	100 TPI	Knob	±5	2.4	0.38 (9.7)
U200-P3H	See adaptors	100 TPI	Locking Allen-Key	±5	2.4	0.38 (9.7)
3 in. (76.2 mm) Optical Mounts						
U300-A	3.0 (76.2)					
U300-A2K	3.0 (76.2)	100 TPI	Knob	±3.5	1.8	
U300-A3K	3.0 (76.2)	100 TPI	Knob	±3.5	1.8	0.38 (9.7)

U50-P







U100-P3K-NL

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Model U50-A and Model U50-P



Model U50-AL



Models U100/200/300-A and Models U100/200-P



Related Products



V100-CP CenterPoint™ Mount
(see page 872)



SR-series Magnetic Pedestal Rods



Ultrafast Laser Broadband 45° Mirrors
(see page 694)

Nominal Mount Width with Actuator

	Dimensions [in. (mm)]
Actuator	Nominal Width
AJS100-0.5H	C+.493 (12.52)
AJS100-0.5H-NL	C+.353 (8.97)
AJS100-0.5K	C+.778 (19.76)

	Dimensions [in. (mm)]							Thread		
Model	A	B[1]	C Nominal	D	E	F	G	H	I	J
U50A	1.00 (25.4)	0.82 (20.8)	0.70 (17.8)	0.375 (9.5)	0.50 (12.7)		0.18 (4.6)	8-32 (M4)		
U100-A2*	2.00 (50.8)	1.79 (45.5)	1.14 (29.0)	0.63 (15.9)	1.00 (25.4)		0.31 (7.9)	8-32 (M4)		
U100-A3*	2.00 (50.8)	1.79 (45.5)	1.14 (29.0)	0.63 (15.9)	1.00 (25.4)		0.31 (7.9)	8-32 (M4)		
U200-A2*	2.75 (69.9)	1.95 (49.5)	1.31 (33.3)	0.63 (15.9)	1.38 (35.1)		0.31 (7.9)	8-32 (M4)		
U200-A3*	2.75 (69.9)	1.95 (49.5)	1.31 (33.3)	0.63 (15.9)	1.38 (35.1)		0.31 (7.9)	8-32 (M4)		
U300-A2*	3.75 (95.3)	1.95 (49.5)	1.31 (33.3)	0.63 (15.9)	1.88 (47.8)		0.31 (7.9)	8-32 (M4)		
U300-A3*	3.75 (95.3)	1.95 (49.5)	1.31 (33.3)	0.63 (15.9)	1.88 (47.8)		0.31 (7.9)	8-32 (M4)		
U50-P	1.00 (25.4)	0.82 (20.8)	0.70 (17.8)	0.375 (9.5)	0.50 (12.7)		0.18 (4.6)	8-32 (M4)	1/4-20 (M6)	
U100-P2*	2.00 (50.8)	1.79 (45.5)	1.14 (29.0)	0.63 (15.9)	1.00 (25.4)	1.79 (45.5)	0.31 (7.9)	8-32 (M4)	1/4-20 (M6)	8-32 (M4)
U100-P3*	2.00 (50.8)	1.79 (45.5)	1.14 (29.0)	0.63 (15.9)	1.00 (25.4)	1.79 (45.5)	0.31 (7.9)	8-32 (M4)	1/4-20 (M6)	8-32 (M4)
U200-P2*	2.75 (69.9)	1.95 (49.5)	1.31 (33.3)	0.63 (15.9)	1.38 (35.1)	2.17 (55.1)	0.31 (7.9)	8-32 (M4)	1/4-20 (M6)	8-32 (M4)
U200-P3*	2.75 (69.9)	1.95 (49.5)	1.31 (33.3)	0.63 (15.9)	1.38 (35.1)	2.17 (55.1)	0.31 (7.9)	8-32 (M4)	1/4-20 (M6)	8-32 (M4)

Note: U50 models are supplied with precision 8-100 (TPI) hex adjustment screws.
Note: U300-A has 3 clearance holes with 0.50 in. (12.7 mm) spacing—see Dimension H callout.
[1]Nominal width based on AJS100-0.5K-NL adjustment screw. For width with other AJS100 models see Nominal Mount Width with Actuator table.

CAD *See our website for CAD files*

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP