

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

The Wayback Machine - https://web.archive.org/web/20150908100014/http://www.hytec-electronics.co.uk/DescriptionPages/DataSheet.aspx?prodI...

Sidebar

Technical Spec Table

Manual

Software Downloads

Ordering Options

Release Notes

Ask a Question

Product Catalogue

Related Products

VTB 8302 Digital Input/Output Transition Board

Features

VTB 8302



- VME64 extensions / Transition Board
- Full EMC shielding and insertion/extraction handles
- RP0 and RP2 connections
- Provides 64 buffered TTL input/output signals which can be configured as inputs or outputs by setting a PCB jumper, four output strobes and four input strobes when connected to the VCB 8001 Carrier Board.
- Connector pins allocated for back-to-back connection to the 8301.
- Four 50-way SCSI-2 sockets provide ease of connection to four groups of circuitry each with 16 outputs, input trigger and clock.

Product Description

The VTB 8302 is a 6U (double height) VME rear I/O transition board, which provides connection to the 8001 and 8002 Carrier Boards. It routes the signals from the carrier board to four 50-way SCSI sockets via the J0 and J2 connectors of the VME backplane. The board includes sites for fitting resistors and capacitors or diodes associated with each input/output.

Construction

The unit is constructed to the VME64x standard, with EMC rear panel, injector/ejector handles, guide pin and slot keying, static discharge protection, hot swap capability, 5-row RP0 and RP2 connectors.

Signal Path

A rear-mounted transition card with four high-density 50-way [SCSI2] connectors transmits/receives all I/O signals and provides direct or conditioned connection provided by pcb jumper settings. The signals connect to the main carrier board according to the VME64x Greenspring pinout for IP module carriers.

SCSI Connectors

Connector 1 (lowest connector) Inputs/Outputs 1-16, I/PStr1, O/PStr1
Connector 2 Inputs/Outputs 17-32, I/PStr2, O/PStr2
Connector 3 Inputs/Outputs 33-48, I/PStr3, O/PStr3
Connector 4 (top connector) Inputs/Outputs 49-64, I/PStr4, O/PStr4

Digital Output Connection Details

Signal	VME Connection	SCSI Connection
Signal High 1-16	RP2/A6-A21	Skt1/26-41
Signal Rtn 1-16	RP2/C6-C21	Skt1/1-16
Str-Out1 High	RP2/A23	Skt1/44
Str-Out1 Low	RP2/C23	Skt1/19
Str-In1 High	RP2/A25	Skt1/47
Str-In1 Low	RP2/C25	Skt1/22
N/C		Skt1/25
Gnd		Skt1/50

Signal High 17-32	RP2/D4, D5, Z7, D8, D9, Z11, D12, D13, Z15, D16, D17, Z19, D20, D21, Z23, D24	Skt2/26-41
Signal Rtn 17-32	RP2/Z5, D6, D7, Z9, D10, D11, Z13, D14, D15, Z17, D18, D19, Z21, D22, D23, Z25	Skt2/1-16
Str-Out2 High	RP2/Z27	Skt2/44
Str-Out2 Low	RP2/D27	Skt2/19
Str-In2 High	RP2/D29	Skt2/47
Str-In2 Low	RP2/D30	Skt2/22
N/C		Skt2/25
Gnd		Skt2/50
Signal High 33-48	RP0/A11, C11, E11, B12, D12, A13, C13, E13, B14, D14, A15, C15, E15, B16, D16, A17	Skt3/26-41
Signal Low 33-48	RP0/B11, D11, A12, C12, E12, B13, D13, A14, C14, E14, B15, D16, A16, C16, E16, B17	Skt3/1-16
Str-Out3 High	RP0/E17	Skt3/44
Str-Out3 Low	RP0/A18	Skt3/19
Str-In3 High	RP0/D18	Skt3/47
Str-In3 Low	RP0/E18	Skt3/22
N/C		Skt3/25
Gnd		Skt3/50
Signal High 49-64	RP0/A1, C1, E1, B2, D2, A3, C3, E3, B4, D4, A5, C5, E5, B6, D6, A7	Skt4/26-41
Signal Low 49-64	RP0/B1, D1, A2, C2, E2, B3, D3, A4, C4, E4, B5, D5, A6, C6, E6, B7	Skt4/1-16
Str-Out4 High	RP0/E7	Skt4/43
Str-Out4 Low	RP0/A8	Skt4/18
Str-In4 High	RP0/D8	Skt4/45
Str-In4 Low	RP0/E8	Skt4/20
N/C		Skt4/25
Gnd		Skt4/50

nqa
ISO 9001
Registered
Quality Management

Hytec Electronics have been providing control and data acquisition systems solutions for over 35 years. Our hardware engineers design and manufacture high specification analogue and digital instrumentation for the harshest of industrial and research environments. We build quality designs into modular instruments based on the stringent standards including CAMAC, VME, VME64x, PCI and Industry Packs. Our software engineers implement sophisticated system drivers in all the leading operating systems to support our hardware. Software application engineers consult, design and implement complex control and data acquisition solutions.

© HYTEC ELECTRONICS LTD 2012

Information on this web site is subject to change without notice. Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders. Send mail to Webmaster with questions or comments about this web site.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP