ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *National Instruments AT-DIO-32HS* at our website: *Click HERE*

NI 6533/6534 Specifications

This document lists features and specifications for the NI 6533/6534 family of devices and the NI PCI/PXI-7030/6533. The NI 6533/6534 family includes the following devices:

- NI PCI-6534
- NI PXI-6534
- NI PCI-6533 (PCI-DIO-32HS)
- NI PXI-6533
- NI DAQCard-6533
- NI AT-DIO-32HS

Note All NI 6533/6534 devices can be programmed with NI-DAQmx or NI-DAQ Traditional (Legacy), except for the NI DAQCard-6533 and NI AT-DIO-32HS, which are only supported with NI-DAQ Traditional (Legacy).

Specifications are typical at 25 °C unless otherwise noted. Specifications are subject to change without notice. For the most recent version of the specifications, visit `ni.com/manuals`.

Digital I/O

Number of channels ..... 32 input/output;
4 dedicated output and control;
4 dedicated input and status

Compatibility ..... TTL/CMOS (standard or open collector)

Hysteresis ..... 500 mV

Digital logic levels

Level	Minimum	Maximum
Input low voltage	0 V	0.8 V
Input high voltage	2 V	5 V

Level	Minimum	Maximum
Input low current for data lines (V_{in} = 0.4 V) DATA PULL† high DATA PULL low	 — —	 –70 µA –10 µA
Input high current for data lines (V_{in} = 2.4 V) DATA PULL high DATA PULL low	 — —	 10 µA 40 µA
Input low current for control lines (V_{in} = 0.4 V) CTRL PULL‡ high CTRL PULL low	 — —	 –2.5 mA –200 µA
Input high current for control lines (V_{in} = 2.4 V) CTRL PULL high CTRL PULL low	 — —	 200 µA 1.4 mA
Input low current for CTRL PULL/DATA PULL (V_{in} = 0.4 V)	—	4 µA
Input high current for CTRL PULL/DATA PULL (V_{in} = 2.4 V)	—	140 µA
Output low voltage (I_{OL} = 24 mA)	—	0.4 V
Output high voltage†† (I_{OH} = 24 mA)	2.4 V	—

† DATA PULL is represented as the DPULL signal in Traditional NI-DAQ (Legacy).

‡ CTRL PULL is represented as the CPULL signal in Traditional NI-DAQ (Legacy).

†† When configured as active drive output terminals. Drivers configured for open-collector drive type are in the high-impedance state when at logic high level.

Absolute maximum
input voltage range .....–0.3 to 5 V

Power-on state for output channels .....High-impedance, pulled up or down (selectable)

Pull-up/down resistors
CTRL PULL (for control lines).....2.2 kΩ
DATA PULL (for data lines) .....100 kΩ

Data transfers (all devices
except NI DAQCard-6533).....Interrupt, DMA

Memory

NI AT-DIO-32HS ..... 16 S

NI DAQCard-6533 for PCMCIA..... 16 S

NI PCI/PXI-6534 ..... 64 MB, two 32 MB modules on each NI 6534

NI PCI/PXI-7030/6533 ..... 16 S

NI PCI-DIO-32HS ..... 16 S

NI PXI-6533..... 16 S

Sample Timing Types

Sample Clock Timing[1]

Direction..... Input or output

Maximum sample rate (internally timed, for small transfers[2])..... 20 MHz

Minimum sample rate (internal clock rate) ..... 1 S/10 minutes

Change Detection

Change-detection resolution ..... 150 ns

Triggers

Start and Reference[3] Triggers

Compatibility ..... TTL/CMOS

Trigger types ..... Rising or falling edge, or digital pattern

Minimum pulse width for edge triggers ..... 10 ns

[1] Sample clock timing is described as Pattern I/O in NI-DAQ Traditional (Legacy).

[2] Small transfer size is the size of the FIFO.

[3] Reference triggers are called Stop triggers in NI-DAQ Traditional (Legacy).

Pattern trigger detection capabilities ..... Detect pattern match or mismatch on user-selected data lines

Pattern trigger resolution ..... 60 ns or one Sample clock[1] period, depending on pattern I/O mode

RTSI Triggers (PCI, PXI, AT)

Trigger lines 7

Bus Interfaces

NI PCI-DIO-32HS/PXI-6533/PCI-6534/PXI-6534 ..... PCI master and target with onboard linking (scatter-gather) DMA

AT-DIO-32HS type ..... AT slave with dual DMA

NI DAQCard-6533 for PCMCIA type ... PCMCIA slave

Power

Power Requirements

+5 VDC (±5%) (with light output load)

- NI PCI-DIO-32HS, NI PXI-6533 .... 1.3 A
- NI PCI-6534 and NI PXI-6534 ..... 2.0 A
- NI DAQCard-6533 for PCMCIA .... 500 mA

Power Available at I/O Connector

NI PCI-DIO-32HS, NI PXI-6533, NI AT-DIO-32HS, NI PCI-6534, and NI PXI-6534 ..... +4.65 to +5.25 VDC at 1 A

NI DAQCard-6533 for PCMCIA ..... +4.65 to +5.25 VDC at 250 mA

[1] Sample clock is represented by the REQ signal in NI-DAQ Traditional (Legacy).

Physical

Dimensions, not including connectors

- NI DAQCard-6533 for PCMCIA ... 8.6 by 5.3 cm (3.4 by 2.1 in.)
- NI AT-DIO-32HS/ PCI-6533/6534 ... 17.5 by 10.7 cm (6.9 by 4.2 in.)
- NI PXI-6533/6534 ... 16.3 by 9.9 cm (6.4 by 3.9 in.)

I/O connector

- NI PCI-DIO-32HS, NI PXI-6533, NI AT-DIO-32HS, NI PCI-6534, and NI PXI-6534 ... 68-pin male SCSI-II type
- NI DAQCard-6533 for PCMCIA ... 68-pin female PCMCIA connector

Environment

Operating temperature ... 0 to 55 °C

Storage temperature ... –20 to 70 °C

Relative humidity ... 5 to 90% noncondensing

Functional shock ... MIL-T-28800 E Class 3 (per Section 4.5.5.4.1) Half-sine shock pulse, 11 ms duration, 30 g peak, 30 shocks per face

Operational random vibration (PXI only) ... 5 to 500 Hz, 0.31 g_{rms}, 3 axes

Nonoperational random vibration (PXI only) ... 5 to 500 Hz, 2.5 g_{rms}, 3 axes

Note Random vibration profiles were developed in accordance with MIL-T-28800E and MIL-STD-810E Method 514. Test levels exceed those recommended in MIL-STD-810E for Category 1 (Basic Transportation, Figures 514.4-1 through 514.4-3).

National Instruments, NI, ni.com, and LabVIEW are trademarks of National Instruments Corporation. Refer to the *Terms of Use* section on `ni.com/legal` for more information about National Instruments trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering National Instruments products, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your CD, or `ni.com/patents`.

© 2005 National Instruments Corporation. All rights reserved.

374163A-01 Nov05

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP