



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Low-Cost Stepper Motion Controllers

NI 7330 Series

- Up to 4 axes of stepper motion
- 3D linear interpolation
- PXI (cPCI) and PCI versions available

Models

- NI PCI-7334
- NI PXI-7334

Operating Systems

- Windows 2000/NT/XP

Recommended Software

- LabVIEW
- NI Motion Assistant
- LabWindows/CVI
- Measurement Studio
- Motion Control Module for Measurement Studio

Other Compatible Software

- Visual Basic
- C/C++

Driver Software (included)

- NI-Motion



Overview and Applications

NI 7330 series devices are low-cost stepper motion controllers for point-to-point applications. These low-cost motion controllers provide new solutions for machine builders who need simple, straightforward motion control without a lot of extra features.

Unlike other low-cost motion controllers, NI 7330 controllers still have a variety of powerful features including:

- Linear interpolation for coordinating multiple axes.
- Real-time system integration for directly communicating with data acquisition or image acquisition boards
- High-performance stepper generation for ensuring smooth motion at high velocities.

NI-Motion Driver Software

NI 7330 devices use the NI-Motion driver. The advantage of this is that if your application needs change in the future, you can easily upgrade your hardware without having to change your code. You can also take advantage of any firmware updates with the field-upgradable firmware.

Integration Capabilities

Like other NI Motion controllers, NI 7330 controllers offer powerful integration capabilities with both data acquisition and machine vision. One of the most powerful is the RTSI bus or PXI trigger bus capability that you can use to communicate directly with other devices without extra wiring and without consuming bandwidth on the host bus. An NI 7330 is ideal when using stepper motors for applications where only simple motion is required.

Feature	NI 7330 Series
Maximum number of axes	4 axes
Closed loop stepper control	✓
Linear interpolation	✓
Configurable auxiliary DIO	✓
RTSI	✓
S-curve	✓
Configurable move complete criteria	✓
Software limits	✓
High-speed capture	✓
Blending	✓
Upgradeable firmware	✓
NI Motion software API	✓
Number of axes per 62.5 microsecond PID rate	1
Static PWM outputs	2
DIO	32 bits
Analog-to-digital converter	12-bit A/D
Stepper output rate	4 MHz maximum
Encoder rate	20 MHz maximum
PCI	✓
PXI	✓

Figure 1. NI 7330 Series Features

Low-Cost Stepper Motion Controllers

Low-Cost Stepper Controller

Motion

Technical Support for Motion Software

As a complement to your motion software product, consider:

Technical Support – FREE through applications engineers worldwide, Web resources, and Premier Support – ni.com/support

Motion Control Fundamentals Training – Instructor-led courses – ni.com/training

Professional Services – Feasibility, consulting, and integration through our Alliance Program members – ni.com/alliance

For more information on NI services and support, visit ni.com/services

Ordering Information

NI PCI-7334 (4-axis stepper)778417-01
 NI PXI-7334 (4-axis stepper)778444-01
 Includes hardware and NI-Motion software, libraries, and examples

Accessories

NI Motion Assistant778553-01
 Universal Motion Interfacessee page 640
 Drivessee page 642
 Cablessee page 645

BUY ONLINE!

Visit ni.com/info and enter *pxi7334*, *pci7334*.

Specifications

Trajectory update rate range.....	62.5 to 500 μ s/sample
Maximum update rate.....	62.5 μ s/axis
4-axis update rate.....	250 μ s total
Multi-axis synchronization.....	< 1 update sample
Trajectory parameters	
Position range.....	$\pm 2^{31}$ steps
Maximum relative move size.....	$\pm 2^{31}$ steps
Velocity range.....	1 to 4,000,000 steps/s
Acceleration/deceleration.....	61 to 128,000,000 steps/s ²

System Safety

Watchdog timer function.....	Resets board to startup state
Shutdown input.....	Disable all axes and command outputs

Motion I/O

Stepper outputs	
Maximum pulse rate.....	4 MHz (full, half, and microstep)
Step output mode.....	Step and direction or CW/CCW
Encoder inputs.....	Quadrature, incremental, single-ended
Maximum count rate.....	20 MHz
Forward, reverse, and home inputs	
Number of inputs.....	3 per axis
Control.....	Individual enable/disable, stop on input, prevent motion, find home
Trigger inputs.....	1 per axis
Maximum repetitive capture rate.....	150 Hz
Breakpoint outputs	
Number of outputs.....	1 per axis, programmable polarity
Inhibit/enable output	
Number of outputs.....	1 per axis, programmable polarity
Analog inputs.....	12-bit resolution, ± 10 V range, 50 μ s scan rate

Digital I/O

Ports.....	4, 8-bit TTL ports, bit configurable, sink or source 24 mA
Open-loop PWM outputs	
Number of PWM outputs.....	2
Clock sources.....	Internal or external

Power Requirements

+5 VDC ($\pm 3\%$).....	1 A
+12 VDC ($\pm 3\%$).....	30 mA
-12 VDC ($\pm 3\%$).....	30 mA
Power consumption.....	5.7 W, maximum

Physical

PCI.....	17.5 by 9.9 cm (6.9 by 3.9 in.)
PXI.....	16 by 10 cm (6.3 by 3.9 in.)
Connectors	
Motion I/O connector.....	68-pin female high-density VHDCI type
Digital I/O connector.....	68-pin female high-density VHDCI type

Environment

Operating temperature.....	0 to 55 °C
Storage temperature.....	-20 to 70 °C
Relative humidity range.....	10 to 90% (noncondensing)



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com