ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *National Instruments SCXI-1104C* at our website: *Click HERE*

SCXI Thermocouple Input Modules

NI SCXI-1102, NI SCXI-1112

- Hardware scanning of cold-junction sensors
- 2 Hz lowpass filtering per channel
- Overvoltage protection to ±42 V
- 333 kS/s maximum sampling rate
- NI measurement services software that simplifies configuration and measurements

SCXI-1102

- Programmatic input range of ±100 mV or ±10 V per channel
- Thermocouple, millivolt, volt, and current input

SCXI-1112

- Instrumentation amplifier per channel
- Random scanning
- Onboard calibration reference
- Open-thermocouple detection LEDs
- Cold-junction compensation per channel

Operating Systems

- Windows 2000/NT/XP

Recommended Software

- LabVIEW
- LabWindows/CVI
- Measurement Studio

Measurement Services Software

- NI-DAQmx driver software
- VI Logger Lite data-logging software



Module	Channels	Thermocouple	RTD	±100 mV	±10 V	0 to 20 mA
SCXI-1102	32	✓	✓[1]	✓	✓	✓
SCXI-1112	8	✓	–	–	–	–

[1] With SCXI-1581

Table 1. Signal Compatibility

Overview

The National Instruments SCXI-1102 and SCXI-1112 are designed for high-accuracy thermocouple measurements. The SCXI-1102 also can acquire millivolt, volt, 0 to 20 mA, and 4 to 20 mA current input signals, as well as signals from RTDs when the SCXI-1581 provides excitation. Each input channel includes an instrumentation amplifier and a 2 Hz lowpass filter. The SCXI-1112 incorporates open-thermocouple detection circuitry on each input channel. LEDs on the front of the module indicate the presence of an open thermocouple.

Ordering Information

NI SCXI-1102 776572-02
NI SCXI-1112 776572-12

Accessories
SH96-96 shielded cable 1 m 183228-01
R96-96 ribbon cable 1 m 183425-01

For information on extended warranty and value-added services, go to **ni.com/signalconditioning**.

BUY NOW!

For complete product specifications, pricing, and accessory information, call (866) 265 9891 (U.S. only) or go to **ni.com/scxi**.

Terminal Block	Part Number	Type	CJ Sensor	Compatible Modules	Cabling	Special Functions
SCXI-1300	777687-00	Screw terminals Front-mounting	✔	SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1104C, SCXI-1100	_	IC sensor for CJC
SCXI-1303	777687-03	Screw terminals Front-mounting	✔	SCXI-1102B, SCXI-1102C, SCXI-1100	_	Isothermal construction Pluggable ground referencing
SCXI-1308	777687-08	Screw terminals Front-mounting	–	SCXI-1102B, SCXI-1102C, SCXI-1100	_	249 Ω precision shunt resistor for current measurements
TC-2095	777509-01	Thermocouple, plugs Rack-mounted	✔	SCXI-1100, SCXI-1102B, SCXI-1102C	SH96-96 or R96-96	Isothermal construction Prewired ground referencing
TBX-1303	777207-03	Screw terminals	✔	SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1104C, SCXI-1100	SH96-96 or R96-96	DIN-rail mount Isothermal construction Pluggable ground referencing 3 terminals per channel
TBX-96	777264-01	Screw terminals DIN-rail mount	–	SCXI-1100, SCXI-1102B, SCXI-1102C, SCXI-1104,	SH96-96 or R96-96	DIN-rail mount 3 terminals per channel
SCXI-1310	777687-10	Solder pins Front-mounting	–	SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1100	–	Low-cost connector and shell assembly

Table 2. Terminal Block Options for SCXI-1102

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

SCXI Thermocouple Input Modules

Specifications

Complete Accuracy Table

			Percent of Reading[1]			System Noise (peak, 3 sigma)[1]				Temperature Drift	
						Single Point		Average			
Module	Nominal Range[1]	Overall Gain[1]	Typical	Maximum	Offset (µV)	4 Hz (µV)	10 kHz or FBW (µV)	4 Hz (µV)	10 kHz or FBW (µV)	Percent of Reading/°C	Offset (µV/°C)
SCXI-1100	±10 V	1	0.03	0.05	250	600	600	15.0	15.0	0.002	24.0
	±5 V	2	0.1	0.15	175	400	400	15.0	15.0	0.002	14.0
	±2 V	5	0.1	0.15	100	200	200	15.0	15.0	0.002	8.0
	±1 V	10	0.1	0.15	75	100	100	10.0	11.0	0.002	6.0
	±500 mV	20	0.1	0.15	65	50	50	10.0	11.0	0.002	5.0
	±200 mV	50	0.1	0.15	50	30	30	10.0	11.0	0.002	4.5
	±100 mV	100	0.1	0.15	50	10	10	5.0	6.0	0.002	4.5
	±50 mV	200	0.1	0.15	50	10	10	5.0	6.0	0.002	4.5
	±20 mV	500	0.1	0.15	45	10	10	5.0	6.0	0.002	4.0
	±10 mV	1000	0.1	0.15	45	1.5	1.5	0.5	1.5	0.002	4.0
	±5 mV	2000	0.1	0.15	45	1.5	1.5	0.5	1.5	0.002	4.0

[1]Absolute Accuracy (15 to 35 °C). To calculate the absolute accuracy for the SCXI-1100, 1102, 1102B, 1102C, 1104, 1104C, and/or 1112, visit **ni.com/accuracy**.

			Percent of Reading[1]			System Noise (peak, 3 sigma)[1]		Temperature Drift	
Module	Nominal Range[1]	Overall Gain[1]	Typical	Maximum	Offset (µV)	Single Point	Average (µV)	Percent of Reading/°C	Offset (µV/°C)
SCXI-1102	±10 V	1	0.025	0.035	500	600 µV	50	0.0010	20
	±100 mV	100	0.015	0.02	25	20 µV	5	0.0005	1
SCXI-1102B	±10 V	1	0.025	0.035	500	600 µV	50	0.0010	20
	±100 mV	100	0.015	0.02	25	20 µV	5	0.0005	1
SCXI-1102C	±10 V	1	0.025	0.035	500	600 µV	70	0.0010	20
	±100 mV	100	0.015	0.02	25	30 µV	10	0.0005	1
SCXI-1104	±60 VDC	0.1	0.035	0.05	800	900 µV	200	0.0020	50
SCXI-1104C	±42 VAC	0.1	0.035	0.05	800	1 mV	300	0.0020	50
SCXI-1112	±100 mV	100	0.015	0.02	25	20 µV	5	0.0005	1

[1]Absolute Accuracy (15 to 35 °C). To calculate the absolute accuracy for the SCXI-1100, 1102, 1102B, 1102C, 1104, 1104C, and/or 1112, visit **ni.com/accuracy**.

Input Characteristics

Module	Number of Channels
SCXI-1100, SCXI-1102, SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1104C	32 differential
SCXI-1112	8 differential

Input signal ranges..... See accuracy table
Input coupling..... DC

Maximum working voltage

Module	Maximum Working Voltage (Signal + Common Mode)
SCXI-1100, SCXI-1102, SCXI-1102B, SCXI-1102C	±10 V
SCXI-1104, SCXI-1104C	30 V_{rms} or ±42 VAC peak or 60 VDC
SCXI-1112	±10 V

Overvoltage protection

Module	Powered On	Powered Off
SCXI-1100	±25 V	±15 V
SCXI-1102, SCXI-1102B, SCXI-1102C	±42 V	±42 V
SCXI-1104, SCXI-1104C	30 V_{rms} or ±42 VAC peak or 60 VDC	
SCXI-1112	±42 V	±42 V

Inputs with Overvoltage Protection	
SCXI-1100, SCXI-1104, SCXI-1104C	CH0..CH31
SCXI-1102, SCXI-1102B, SCXI-1102C	CH0..CH31, CJ Sensor
SCXI-1112	CH0..CH7, CJ Sensor

Offset error..... See accuracy table
Gain error..... See accuracy table

Transfer Characteristics

Nonlinearity

Module	Percentage of Full Scale Range
SCXI-1100	±0.008
SCXI-1102, SCXI-1102B, SCXI-1102C	±0.005
SCXI-1104, SCXI-1104C	±0.01
SCXI-1112	±0.005

Amplifier Characteristics

Input impedance

Module	Normal Powered On	Powered Off/Overload
SCXI-1100	>1 GΩ	1.6 kΩ
SCXI-1102, SCXI-1102B, SCXI-1102C	>1 GΩ	10 kΩ
SCXI-1104, SCXI-1104C	1 MΩ	900 kΩ
SCXI-1112	>1 GΩ	10 kΩ

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

SCXI Thermocouple Input Modules

Specifications

Input bias current

Module	Current
SCXI-1100	±350 pA
SCXI-1102, SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1104C, SCXI-1112	±0.5 nA

Input offset current

Module	Current
SCXI-1100	±350 pA
SCXI-1102, SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1104C, SCXI-1112	±1.0 nA

No MMR

CMRR (Common Mode Rejection Ratio) (DC to 60 Hz)

Module	Range	Filter	CMRR (dB)
SCXI-1100	±10 V to ±2 V	4 Hz	98
	±1 V to ±5 mV	4 Hz	78
	±10 V to ±2 V	10 kHz or full bandwidth	110
	±1 V to ±5 mV	10 kHz or full bandwidth	90
SCXI-1102	±10 V to ±100 mV	2 Hz	110
SCXI-1102B	±10 V to ±100 mV	200 Hz	90
SCXI-1102C	±10 V to ±100 mV	10 kHz	90
SCXI-1104	±42 VAC/±60 VDC	2 Hz	70
SCXI-1104C	±42 VAC/±60 VDC	10 kHz	70
SCXI-1112	±100 mV	2 Hz	110

Output range ..... See accuracy table

No output impendance

Dynamic Characteristics

Input signal bandwidth

Module	Bandwidth
SCXI-1100	4 Hz, 10 kHz, full bandwidth
SCXI-1102	2 Hz
SCXI-1102B	200 Hz
SCXI-1102C	10 kHz
SCXI-1104	2 Hz
SCXI-1104C	10 kHz
SCXI-1112	2 Hz

Step response (10 V step)

			Accuracy		
Module	Filter Setting	Range	±0.012%[1]	±0.006%[2]	±0.0015%[2]
SCXI-1100	Full bandwidth	±10 V to ±100 mV	6 µs	10 µs	32 µs
	(No filter)	±50 mV	7.5 µs	10 µs	33 µs
		±20 mV	12 µs	25 µs	40 µs
		±10 mV	20 µs	26 µs	76 µs
		±5 mV	25 µs	30 µs	195 µs
	10 kHz	All ranges	150 µs	160 µs	200 µs
	4 Hz	All ranges	350 ms	400 ms	500 ms

			Accuracy	
Module	Filter Setting	Range	±0.01%	±0.01%
SCXI-1102	2 Hz	±10 V, ±100 mV	1 s	10 s
SCXI-1102B	200 Hz	±10 V, ±100 mV	10 ms	100 ms
SCXI-1102C	10 kHz	±10 V, ±100 mV	200 µs	1 ms
SCXI-1112	2 Hz	±100 mV	1 s	10 s

			Accuracy	
Module	Filter Setting	Range	±0.01%	±0.01%
SCXI-1104	2 Hz	± 42 VAC/± 60 VDC	1 s	10 s
SCXI-1104C	10 kHz	± 42 VAC/± 60 VDC	200 µs	1 ms

Multiplexer performance

	Scan Interval	
Module	Settle to ±0.012%[1]	Settle to ±0.006%[2]
SCXI-1100	(See step response)	(See step response)
SCXI-1102, SCXI-1102B, SCXI-1102C, SCXI-1104, SCXI-1104C, SCXI-1112	3 µs	10 µs

Filter Characteristics

Module	Filter Setting	Range	Noise Related to Input (μV_{rms})
SCXI-1100	Full bandwidth	±10 V	15
	(No filter)	±10 mV	6
	4 Hz	±10 V	15
		±10 mV	0.2
	10 kHz	±10 V	15
		±10 mV	1.5
SCXI-1102	2 Hz	±100 mV	5
		±10 V	50
SCXI-1102B	200 Hz	±100 mV	5
		±10 V	50
SCXI-1102C	10 kHz	±10 V	70
SCXI-1104	2 Hz	±100 mV	10
		±42 VAC, ±60 VDC	200
SCXI-1104C	10 kHz	±42 VAC, ±60 VDC	300
SCXI-1112	2 Hz	±100 mV	5

Type ..... RC

Cutoff Frequency (-3 dB)

SCXI-1100 ..... 4 Hz, 10 kHz, full bandwidth (jumper-selectable)

SCXI-1102, 1104, 1112 ..... 2 Hz

SCXI-1102B ..... 200 Hz

SCXI-1102C, 1104C ..... 10 kHz

Stability

Module	Input Range	Gain Temperature Coefficient (ppm/°C)	Offset Temperature Coefficient (µV/°C()
SCXI-1100	All ranges	20	20
SCXI-1102	±10 V	10	20
SCXI-1102B SCXI-1102C	±100 mV	10	1
SCXI-1104 SCXI-1104C	±42 VAC, ±60 VDC	20	50
SCXI-1112	±100 mV	10	1

Recommended warm-up time ..... 20 minutes

Physical

Dimensions ..... 3.0 by 17.3 by 30.3 cm
1.2 by 6.8 by 8.0 in.

I/O Connector

Rear ..... 50-pin male ribbon cable rear connector

Front

SCXI-1112 ..... 8 uncompensated minithermocouple connectors

Others ..... 96-pin male DIN C front connector

Environment

Operating temperature ..... 0 to 50 °C

Storage temperature ..... -55 to 150 °C

Relative humidity ..... 5 to 90% noncondensing

Certification and Compliance

European Compliance

EMC ..... EN 61326 Group I Class A, 10 m, Table 1 Immunity

Safety ..... EN 61010-1

North American Compliance

EMC ..... FCC Part 15 Class A using CISPR

Australia and New Zealand Compliance

EMC ..... AS/NZS 2064.1/2 (CISPR-11)

[1]Includes effects of NI 6052E with 1 or 2 m SCXI cable assembly.


[2]Includes effects of NI 6030E with 1 or 2 m SCXI cable assembly.

For a definition of specific terms, please visit ni.com/glossary.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

NI Services and Support

NI has the services and support to meet your needs around the globe and through the application life cycle – from planning and development through deployment and ongoing maintenance. We offer services and service levels to meet customer requirements in research, design, validation, and manufacturing. Visit ni.com/services.



Training and Certification

NI training is the fastest, most certain route to productivity with our products. NI training can shorten your learning curve, save development time, and reduce maintenance costs over the application life cycle. We schedule instructor-led courses in cities worldwide, or we can hold a course at your facility. We also offer a professional certification program that identifies individuals who have high levels of skill and knowledge on using NI products. Visit ni.com/training.

Professional Services

Our Professional Services Team is comprised of NI applications engineers, NI Consulting Services, and a worldwide National Instruments Alliance Partner program of more than 600 independent consultants and integrators. Services range from start-up assistance to turnkey system integration. Visit ni.com/alliance.

NATIONAL INSTRUMENTS™
Certified Alliance Partner

OEM Support

We offer design-in consulting and product integration assistance if you want to use our products for OEM applications. For information about special pricing and services for OEM customers, visit ni.com/oem.

Local Sales and Technical Support

In offices worldwide, our staff is local to the country, giving you access to engineers who speak your language. NI delivers industry-leading technical support through online knowledge bases, our applications engineers, and access to 14,000 measurement and automation professionals within NI Developer Exchange forums. Find immediate answers to your questions at ni.com/support.

We also offer service programs that provide automatic upgrades to your application development environment and higher levels of technical support. Visit ni.com/ssp.

Hardware Services

NI Factory Installation Services

NI Factory Installation Services (FIS) is the fastest and easiest way to use your PXI or PXI/SCXI combination systems right out of the box. Trained NI technicians install the software and hardware and configure the system to your specifications. NI extends the standard warranty by one year on hardware components (controllers, chassis, modules) purchased with FIS. To use FIS, simply configure your system online with ni.com/pxiadvisor.

Calibration Services

NI recognizes the need to maintain properly calibrated devices for high-accuracy measurements. We provide manual calibration procedures, services to recalibrate your products, and automated calibration software specifically designed for use by metrology laboratories. Visit ni.com/calibration.

Repair and Extended Warranty

NI provides complete repair services for our products. Express repair and advance replacement services are also available. We offer extended warranties to help you meet project life-cycle requirements. Visit ni.com/services.

NATIONAL INSTRUMENTS™

ni.com • (800) 813 3693

National Instruments • info@ni.com

© 2005 National Instruments Corporation. All rights reserved. CVI, LabVIEW, Measurement Studio, National Instruments, National Instruments Alliance Partner, NI, ni.com, NI-DAQ, and SCXI are trademarks of National Instruments. Other product and company names listed are trademarks or trade names of their respective companies. A National Instruments Alliance Partner is a business entity independent from NI and has no agency, partnership, or joint-venture relationship with NI.

2005_5612_321_101_D

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP