ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *NuAire NU-5500* at our website: ***Click HERE***

SPECIFICATIONS FOR NUAIRE DH AUTOFLOW NU-5500 DIRECT HEAT AUTOMATIC CO^2 INCUBATOR

This document is a concise statement of requirements for a quality Direct Heat CO^2 Incubator, which may be used to augment your purchase request/order.

A NuAire sales representative will be pleased to explain the importance of the performance and control affected by each of the following requirements. The DH AUTOFLOW NU-5500 meets all of the requirements in the following SPECIFICATION.

Overall Dimensions - Inches [mm]

Height:	Exterior:	39.5 [1003.3]
Width:		25.5 [647.7]
Depth:		26.5 [673.1]
Height:	Interior:	25.5 [647.7]
Width:		21.5 [546.1]
Depth:		21.0 [533.4]

Volume: 6.65 $ft.^3$ [188.5 liters]

1. The chamber walls are directly heated by foil heating elements attached to the sides, bottom, top and back of the chamber.
2. A space-age high-density insulation [rated R5.0] covers the complete outer surfaces of the incubator inner chamber.
3. Air is constantly circulating within the chamber using a continuous operating fan/ motor/blower within the upper air plenum and sidewall duct system. This airflow is distributed uniformly and at very low velocity.
4. A large replaceable 99.99% efficient HEPA filter cartridge continually filters the air that circulates in the chamber.
5. A state-of-the-art microcomputer based control system is specifically designed to service the precise control requirements of the chamber's environment.
6. The microcomputer is supported with Read Only Memory [ROM] containing executable software, Random Access Memory [RAM] for temporary storage, and Electronically Erasable Programmable Read Only Memory [EEPROM] for control set points and parameters. The EEPROM provides for indefinite storage of these values during periods of power off or power interruption. The microcomputer includes a complete internal diagnostic software package that permits fault isolation detection down to the failed component.
7. The direct heat incubator incorporates an integrated digital microprocessor-based, non-dispersive infrared CO^2 sensor. Advanced design provides a very stable drift-free output requiring less frequent calibration.
8. Incubator shall be listed by Underwriters Laboratory to meet the requirements of both the U.S. and Canada standards for electrical/mechanical integrity.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

9. The outer shell is cold-rolled steel with powder coat paint finish.
10. The inner chamber is 16 gauge, type 304 polished stainless steel using coved corner crevice-free construction.
11. All stainless steel shelves, shelf supports, guide rails, and air plenum are easily removable for decontamination.
12. Manually adjustable outer front door heater and front frame perimeter heater are duty cycle controlled to reduce condensation within the chamber.
13. Relative humidity level up to 95% is achieved in the incubator by the use of a stainless steel pan filled with distilled water and placed on the bottom of the chamber.
14. An air pump continuously introduces fresh air into the chamber at a variable rate to reduce condensation.
15. Incubator shall come with four [4] square polished stainless steel shelves, 8 ft. [2.5m] electrical power cord, utility side access port, and heavy-duty leg levelers.
16. Incubators are stackable.
17. Performance Parameters

Temperature Range:	5° C above ambient to 55°C
Temperature Sensitivity:	±0.125° C
Temperature Uniformity:	± 0.3° C @ 37° C
Temperature Accuracy:	± 0.1° C
CO^2 Range:	0.1 to 20%
CO^2 Accuracy:	± 0.1%
CO^2 Recovery:	Up to 5% ± 0.2% in 3 minutes
Temperature Recovery:	0.3° C/min.
Temperature Display Resolution:	0.1° C
CO^2 Uniformity:	± 0.1%
CO^2 Display Resolution:	0.1%
Door and Perimeter Heater Control Logic:	Proportional 0-100% [adjustable]
Temperature Sensor Type:	Precision Integrated Circuit
CO^2 Control Logic:	Fixed Algorithm/Manual Environmental Adaptable
CO^2 Sensor Type:	Infrared

RJ-11 Jack - on rear panel for remote alarm connection

18. The following optional equipment shall be available to support installation and user requirements:
    - Automatic CO^2 Tank Switch [Internal]
    - RS-232 Communication Output
    - Additional Shelves
    - Surge Protector
    - 4 Inner Lexan® Doors
    - Chart Recorder Outputs

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP