ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Bel Fuse / Power-One MAP55-4002* at our website: ***Click HERE***

AUTOFLOW



CO_2 INCUBATORS

NUAIRE

Best Products. Best Performance. Best Protection.

The Perfect Choice for Your Unique Application


NU-8500


NU-8700


NU-4750


NU-5500



NU-5510


NU-5100

	Model	Electronic Control System	Gas Control System	Temperature Control System	Humidity Control System	HEPA Filtration System	Configuration System
IR AutoFlow	NU-8500, NU-8700	Microprocessor	CO_2-Infrared	Water-Jacketed	Convection[6]	Air/Gas[4]	Single[3] Over-Under Double
US AutoFlow	NU-4750, NU-4850, NU-4950	Microprocessor	CO_2-Infrared[1] O_2 Fuel Cell[9]	Water-Jacketed	Convection[6] Sensor[2,8]	Air/Gas[4]	Single
DH AutoFlow	NU-5500	Microprocessor	CO_2-Infrared	Direct Heat	Convection[6]	Air/Gas[7]	Single[3]
DHD AutoFlow	NU-5510	Microprocessor	CO_2-Infrared	Direct Heat w/ Sterilization Cycles	Convection[6]	Air/Gas[7]	Single[3]
TC PureCell	NU-5100	Microprocessor	CO_2-Thermo-Conductivity	Direct Heat	Convection[6]	Air/Gas[7]	Single[3]

1] 2 or 3 gas control system
2] Monitors actual chamber humidity. Alarms in low humidity condition indicating that water reservoir requires filling
3] Right or left hand door swing – factory ordered
4] Internal recirculation system to ISO Class 5 clean air within 30 minutes
5] Right or left hand door swing – field reversible
6] Humidity pan (relative humidity to 95%)
7] Internal recirculation system to class 100 within 1 minute
8] Humidity control w / NU-4850, NU-4950
9] O_2 / N_2 control w / NU-4950

Registered to: ISO 9001:2000
ISO 13485:2003





- **The Sensitivity and Accuracy of Gas Control**
  The AutoFlow incubators use a microprocessor-based, non-dispersive, digital solid-state infrared [IR] CO_2 sensor. This advanced design provides a very stable, drift-free output requiring less frequent calibrations.
- **The Precision of Electronic Microprocessor Controls**
  AutoFlow incubators are run by a programmable microcontroller that samples input sensors, sets control outputs, and makes necessary corrections to the chamber environment. AutoFlow incubators provide quick and responsive recovery times.
- **The Long-Term Reliability and Protection of Automated and Redundant Back-Up Systems**
  AutoFlow incubators provide dual sensor probes where appropriate, solid-state analyzers, multiple HEPA filtration systems, and the status alarms / outputs create a dependable, long-lasting scientific instrument.
- **The Flexibility of Available Options and Add-On Expansion Built into the System**
  Additional shelves, RS-232 communication output, inner Lexan® doors, multi-signal analog outputs, tank switches, chart recorders, and moveable platforms are just a few of the available options and accessories.



Constant Contamination Control

- Unique HEPA Filter System
  - Filters Fresh Air Into the Pump
  - Filters CO_2 Gas from Tanks or House Systems
  - Filters Internal Chamber Continuously to ISO Class 5 Air Quality
  - Filters IR CO_2 Sensor Sample Air Returning to Chamber
  - Filters Air Between Air Pump and Inner Chamber
- Interior Chamber is Constantly Maintained at Positive Pressure Similar to an ISO Class 5 Cleanroom
- Dual Sterilization Cycle (DHD AutoFlow NU-5510 Only)
  - 95°C Humidified Decontamination
  - 145°C Dry Sterilization Cycle



NU-8700 / NU-8500

Specifications

Model	Chamber Volume (Ft.³ / Liters)	Electrical*	Chamber Dimensions (W x H x D)	Exterior Dimensions (W x H x D)	Weight
NU-8500	6.64 / 188	115 VAC / 60 Hz	21.5 x 25.5 x 21 in.	25.5 x 40.5 x 27 in.	**Dry:** 218 lbs. / 99 kg
		D: 100 VAC / 50-60 Hz	546 x 647 x 535 mm	648 x 1029 x 686 mm	**Full H_2O Jacket:** 385 lbs. / 175 kg
		E: 230 VAC / 50-60 Hz			**Shipping:** 287 lbs. / 130 kg
		G: 220 VAC / 50-60 Hz			
NU-8700	13.28 / 376	115 VAC / 60 Hz	21.5 x 25.5 x 21 in.	25.5 x 73.5 x 27 in.	**Dry:** 492 lbs. / 224 kg
		D: 100 VAC / 50-60 Hz	546 x 647 x 535 mm	648 x 1867 x 686 mm	**Full H_2O Jacket:** 826 lbs. / 375 kg
		E: 230 VAC / 50-60 Hz			**Shipping:** 561 lbs. / 255 kg
		G: 220 VAC / 50-60 Hz			

*Specify NU-8500 / 8700, NU-8500D / 8700D, NU-8500E / 8700E, or NU-8500G / 8700G

Features

Standard Features

- 100% Stainless Steel Coved Interior Chamber
- 20 gal. / 75.7 L Capacity Water Jacket
- Removable Stainless Steel Shelves (4) [21 maximum] 19.25 in.² [489 mm²]
- Remote Alarm Output Contacts
- CO_2 Sample Port
- Water Level Sensor
- Adjustable Leg Levelers
- Access Port
- Fill Port and Drain Valve
- NuAire Incubator Control Electronics
- Full Size Water Pan
- 8 ft. / 2.5 m Electrical Cord

Optional Features

- Automatic CO_2 Tank Switch
- Communications Interface (RS-232)
- Internal Coil for Chilled Water
- Multi-Signal Analog Outputs: 0-5 VDC, 0-10 VDC, 4-20 mA
- 4 Inner Lexan® Doors
- Humidity Display (RH)

Temperature Control System

- **Default Set Point:** 37˚C
- **Chamber Temperature Range:** 18˚C to 55˚C (5˚C Above Ambient to 30˚C Ambient Max)
- **Chamber Temperature Uniformity:** ± 0.2˚C at 37˚C
- **Temperature Sensitivity:** ± 0.0125˚C

Electrical Requirements

Model NU-8500:
115 VAC / 60 Hz
Startup Power: 625 Watts
Running Power: 250 Watts
Heat Rejected: 14 BTU/min.
[Other electrical voltages available.]

Model NU-8700:
115 VAC / 60 Hz
Startup Power: 1250 Watts
Running Power: 500 Watts
Heat Rejected: 28 BTU/min.
[Other electrical voltages available.]

CO_2 Control System

- **Default Set Point:** 5%
- **CO_2 Range:** 0% to 20%
- **CO_2 Accuracy:** ± 0.1%
- **CO_2 Recovery:** 5.0± 0.2% Within 3.5 Minutes
- **CO_2 Sensor Type:** Non-dispersive Digital Infrared CO_2 Sensor

Utility Connections

- **Gas Connections:** .25" (6.3 mm) Tubing Connections
- **Gas Input Pressure:** 20 PSIG (1.4 BAR) Input Pressures Maximum. Two-stage Gas Regulators Required.







NU-4750 NU-4850 NU-4950

Specifications

Model	Chamber Volume (Ft.³ / Liters)	Electrical*	Chamber Dimensions (W x H x D)	Exterior Dimensions (W x H x D)	Weight
NU-4750	6.64 / 188	115 VAC / 60 Hz	21.5 x 25.5 x 21 in.	31.0 x 34.0 x 25.5 in.	**Dry:** 222 lbs. / 101 kg
		D: 100 VAC / 50-60 Hz	546 x 647 x 535 mm	787 x 864 x 648 mm	**Full H_2O Jacket / RH system:** 392 lbs. / 178 kg
		E: 230 VAC / 50-60 Hz			**Shipping:** 291 lbs. / 132 kg
		G: 220 VAC / 50-60 Hz			
NU-4850	6.64 / 188	115 VAC / 60 Hz	21.5 x 25.5 x 21 in.	31.0 x 34.0 x 25.5 in.	**Dry:** 232 lbs. / 105 kg
		D: 100 VAC / 50-60 Hz	546 x 647 x 535 mm	787 x 864 x 648 mm	**Full H_2O Jacket / RH system:** 412 lbs. / 188 kg
		E: 230 VAC / 50-60 Hz			**Shipping:** 301 lbs. / 137 kg
		G: 220 VAC / 50-60 Hz			
NU-4950	6.64 / 188	115 VAC / 60 Hz	21.5 x 25.5 x 21 in.	31.0 x 34.0 x 25.5 in.	**Dry:** 232 lbs. / 105 kg
		D: 100 VAC / 50-60 Hz	546 x 647 x 535 mm	787 x 864 x 648 mm	**Full H_2O Jacket / RH system:** 412 lbs. / 188 kg
		E: 230 VAC / 50-60 Hz			**Shipping:** 301 lbs. / 137 kg
		G: 220 VAC / 50-60 Hz			

*Specify NU-4750, 4850, 4950 / NU-4750D, 4850D, 4950D / NU-4750E, 4850E, 4950E / NU-4750G, 4850G, 4950G

Features

Standard Features

- 100% Stainless Steel Coved Interior Chamber
- 20 gal. / 75.7 L Capacity Water Jacket
- Removable Stainless Steel Shelves (4) [21 maximum] 19.25 in.² [489 mm²]
- Remote Alarm Output Contacts
- CO_2 Sample Port
- Water Level Sensor
- Adjustable Leg Levelers
- Access Port
- Fill Port and Drain Valve
- NuAire Incubator Control Electronics
- Full Size Water Pan
- 8 ft. / 2.5 m Electrical Cord

Optional Features

- Automatic CO_2 Tank Switch
- Communications Interface (RS-232)
- Internal Coil for Chilled Water
- Multi-Signal Analog Outputs: 0-5 VDC, 0-10 VDC, 4-20 mA
- 4 Inner Lexan® Doors
- Humidity Display (RH) and control (NU-4850 and NU-4950)
- O_2 Control System (NU-4950)

Temperature Control System

Default Set Point: 37˚C

Chamber Temperature Range: 18˚C to 55˚C (5˚C Above Ambient to 30˚C Ambient Max)

Chamber Temperature Uniformity: ± 0.2˚C at 37˚C

Temperature Sensitivity: ± 0.0125˚C

Electrical Requirements

115 VAC / 60 Hz
Startup Power: 625 watts
Running Power: 250 watts, 60 Hz
Heat Rejected: 14 BTU/min.
[Other electrical voltages available.]

Utility Connections

Gas Connections: .25" (6.3 mm) Tubing Connections

Gas Input Pressure: 20 PSIG (1.4 BAR) Input Pressures Maximum. Two-stage Gas Regulators Required.

CO_2 Control Systems

CO_2 (NU-4750 / 4850 / 4950)

Default Set Point: 5%

CO_2 Range: 0 to 20%

CO_2 Accuracy: ± 0.1%

CO_2 Recovery: 5.0± 0.2%

CO_2 Sensor Type: Non-dispersive Digital Infrared CO_2 Sensor

RH (NU-4850 / 4950)

Default Set-Point: 90%

RH Range: 5% Above Ambient to 95%

RH Accuracy: ± 3%

RH Recovery: 95% ± 3%:

O_2 (NU-4950)

Default Set-Point: 21%

O_2 Range: 2 to 21%

O_2 Accuracy: ± 1.0%

O_2 Recovery: 5% ± 2%:



NU-5500

Specifications

Model	Chamber Volume (Ft.³ / Liters)	Electrical*	Chamber Dimensions (W x H x D)	Exterior Dimensions (W x H x D)	Weight
NU-5500	6.64 / 188	115 VAC / 60 Hz	21.5 x 25.5 x 21.0 in.	25.5 x 39.5 x 26 in.	208 lbs. / 94.35 kg
		E: 230 VAC / 50-60 Hz	546 x 648 x 533 mm	648 x 1003 x 660 mm	
		G: 220 VAC / 50-60 Hz			

*Specify NU-5500 / NU-5500E / NU-5500G

Features

Standard Features

- 100% Stainless Steel Coved Interior Chamber
- Foil Heaters Attached to Chamber Outer Walls
- Removable Stainless Steel Shelves (4) [17 maximum] 19.25 in.² [489 mm²]
- Remote Alarm Output Contacts
- CO_2 Sample Port
- Adjustable Leg Levelers
- Access Port
- Digital Infrared CO_2 Gas Sensor
- Water Pan
- Microcomputer-Based Controls
- Replaceable HEPA Filter
- Replaceable Fan Wheel
- 8 ft. / 2.5 m Electrical Cord

Optional Features

- Automatic CO_2 Tank Switch
- Communications Interface (RS-232)
- Multi-Signal Analog Outputs: 0-5 VDC, 0-10 VDC, 4-20 mA
- Additional Shelves
- Surge Protector

Temperature Control System

- **Temperature Range:** 18˚C to 55˚C (5˚C Above Ambient to 30˚C Ambient Max)
- **Temperature Sensitivity:** ± .125˚C
- **Temperature Uniformity:** ± 0.3˚C at 37˚C
- **Temperature Accuracy:** ± 0.1˚C
- **Temperature Recovery:** 0.3˚C / min. (Average)
- **Temperature Display Resolution:** 0.1˚C

Electrical Requirements

115 VAC / 60 Hz
Startup Power: 345 watts
Running Power: 175 watts
Heat Rejected: 10 BTU/min.
[Other electrical voltages available.]

Utility Connections

- **Gas Connections:** .25" (6.3 mm) Tubing Connections
- **Gas Input Pressure:** 20 PSIG (1.4 BAR) Input Pressures Maximum. Two-stage Gas Regulators Required.

CO_2 Control Systems

- **CO_2 Range:** 0.1 to 20%
- **CO_2 Accuracy:** ± 0.1%
- **CO_2 Recovery:** 5.0% ± 0.2% In Four Minutes
- **CO_2 Display Resolution:** ± 0.1%
- **CO_2 Sensor Type:** Non-dispersive Digital Infrared CO_2 Sensor







[A] A 99.98% efficient HEPA filter maintains Constant Contamination Control (C3) in the growth chamber.

[B] Dual temperature sensor probes, mounted just under the inflow to the HEPA filter controlling the chamber environment.



NU-5510

Specifications

Model	Chamber Volume (Ft.³ / Liters)	Electrical*	Chamber Dimensions (W x H x D)	Exterior Dimensions (W x H x D)	Weight
NU-5510	6.65 / 188.51	115 VAC / 60 Hz	21.5 x 25.5 x 21.0 in.	25.5 x 39.5 x 26 in.	208 lbs. / 94.35 kg
		E: 230 VAC / 50-60 Hz	546 x 648 x 533 mm	648 x 1003 x 660 mm	
		G: 220 VAC / 50-60 Hz			

*Specify NU-5510 / NU-5510E / NU-5510G

Features

Standard Features

- 100% Stainless Steel Coved Interior Chamber
- Foil Heaters Attached to Chamber Outer Walls
- Removable Stainless Steel Shelves (4) [17 maximum] 19.25 in.² [489 mm²]
- Remote Alarm Output Contacts
- CO_2 Sample Port
- Adjustable Leg Levelers
- Access Port
- Digital Infrared CO_2 Gas Sensor
- Water Pan
- Microcomputer-Based Controls
- Replaceable HEPA Filter
- Replaceable Fan Wheel
- 8 ft. / 2.5 m Electrical Cord
- **Dual Decontamination Cycles**
  - 95˚C Wet Decontamination Cycle
  - 145˚C Dry Decontamination Cycle

Optional Features

- Automatic CO_2 Tank Switch
- Communications Interface (RS-232)
- Multi-Signal Analog Outputs: 0-5 VDC, 0-10 VDC, 4-20 mA
- Additional Shelves
- Surge Protector

Temperature Control System

- **Temperature Range:** 18˚C to 55˚C (5˚C Above Ambient to 30˚C Ambient Max)
- **Temperature Sensitivity:** ± .125˚C
- **Temperature Uniformity:** ± 0.3˚C at 37˚C
- **Temperature Accuracy:** ± 0.1˚C
- **Temperature Recovery:** 0.3˚C / min. (Average)
- **Temperature Display Resolution:** 0.1˚C

Electrical Requirements

115 VAC, 50/60 Hz
Startup Power: 345 watts
Running Power: 175 watts
Heat Rejected: 10 BTU/min.
Decon. Cycle Power: 1150 watts
[Other electrical voltages available.]

Utility Connections

Gas Connections: .25" (6.3 mm) Tubing Connections

Gas Input Pressure: 20 PSIG (1.4 BAR) Input Pressures Maximum. Two-stage Gas Regulators Required.

CO_2 Control System

- **CO_2 Range:** 0.1 to 20%
- **CO_2 Accuracy:** ± 0.1%
- **CO_2 Recovery:** 5.0% ± 0.2% in Four Minutes.
- **CO_2 Display Resolution:** ± 0.1%
- **CO_2 Sensor Type:** Non-dispersive Digital Infrared CO_2 Sensor

Decontamination Cycles

95ºC Humidified Cycle

95ºC Humidified Decontamination Cycle Eradicates Contaminating Agents

Advanced Chamber Design Allows for Shorter Heat Up and Cool Down Cycles; Complete Cycle Takes 14 Hours to Run

Remote CO_2 IR Sensor Does Not Need to be Removed or Recalibrated

145ºC Dry Cycle Features

145ºC High Temperature Dry Decontamination Cycle Eradicates Contaminating Agents

Complete Cycle Takes 10 Hours to Run

Remote CO_2 IR Sensor Does Not Need to be Removed or Recalibrated



[A] Coved interior corners prevent contaminants from becoming trapped in the chamber.





NU-5100

Specifications

Model	Chamber Volume (Ft.³ / Liters)	Electrical*	Chamber Dimensions (W x H x D)	Exterior Dimensions (W x H x D)	Weight
NU-5100	4.4 / 125	115 VAC / 60 Hz	18.0 x 22.0 x 19.0 in.	23.0 x 30.0 x 23.4 in.	135 lbs. / 62.3 kg
		E: 230 VAC / 50-60 Hz	457 x 559 x 533 mm	584 x 762 x 595 mm	
		G: 220 VAC / 50-60 Hz			

*Specify NU-5100 / NU-5100E / NU-5100G

Features

Standard Features

- 100% Stainless Steel Coved Interior Chamber
- Foil Heaters Attached to Chamber Outer Walls
- Removable SST Shelves (3), Maximum Shelf Capacity (16)
- Remote Alarm Output Contacts
- CO_2 Sample Port
- Adjustable Leg Levelers
- Access Port
- Water Pan
- Microcomputer-Based Controls
- Replaceable HEPA Filter
- Replaceable Fan Wheel
- 8 ft. / 2.5 m Electrical Cord

Optional Features

- Automatic CO_2 Tank Switch
- Communications Interface (RS-232)
- Multi-Signal Analog Outputs: 0-5 VDC, 0-10 VDC, 4-20 mA
- Additional Shelves
- Surge Protector

Temperature Control System

- **Temperature Range:** 18˚C to 55˚C (5˚C Above Ambient to 30˚C Ambient Max)
- **Temperature Uniformity:** ± 0.5˚C at 37˚C
- **Temperature Accuracy:** ± 0.25˚C
- **Temperature Display Resolution:** 0.1˚C

Electrical Requirements

115 VAC, 50/60 Hz
Startup Power: 130 watts
Running Power: 72 watts
Heat Rejected: 4.1 BTU/min.
[Other electrical voltages available.]

Utility Connections

- **Gas Connections:** .25" (6.3 mm) Tubing Connections
- **Gas Input Pressure:** 20 PSIG (1.4 BAR) Input Pressures Maximum. Two-stage Gas Regulators Required.

CO_2 Control System

- **CO_2 Range:** 0.1 to 20%
- **CO_2 Accuracy:** ± 0.25%
- **CO_2 Display Resolution:** ± 0.1%
- **CO_2 Sensor Type:** Digital Thermo-conductivity



Accessories



NU-1555	Stainless Steel Water Pan (Water Jacket)
NU-5560	Stainless Steel Water Pan (Direct Heat)
NU-1556	Replacement Tubing Kit
NU-1557	Additional Stainless Steel Shelves



NU-1564	CO_2 Regulator, Two Stage
NU-1590	CO_2 Regulator, Single Stage
NU-3557	O_2 Regulator, Two Stage
NU-3556	N_2 Regulator, Two Stage



NU-1574	Platform w/ Leveling Casters
NU-1553	Stacking Rack (Single)



NU-1575	Moisture-Proof Duplex Outlet
NU-2568	Isobar® Surge Protector
SV-7008	15A/20A 2 Outlet Surge Protector
SV-7006	15A/20A 6 Outlet Surge Strip



NU-1550	Automatic Tank Switch
NU-1552	CO_2 Tank Alarm




NU-1559	CO_2 Analyzer Fyrite Kit
NU-1561	CO_2 Analyzer Fluid
NU-3550	O_2 Analyzer Fyrite Kit
NU-3551	O_2 Analyzer Fluid

Discover more accessories online at **www.nuaire.com**

Sales and Service Locator

Please visit the NuAire Web site at: www.nuaire.com and select the 'Sales / Service Locator' menu item. Information can be found there for global sales and service personnel.



Other NuAire Products



GLACIER

ULT Freezers



INVITROCELL ES

CO_2 Incubators



LABGARD ES CELLGARD ES

Biological Safety Cabinets

awel international™

Awel Centrifugation

(North and Latin America Only)





AIREGARD

Laminar Airflow Products

NuAire, Inc.

2100 Fernbrook Lane

Plymouth, MN 55447

U.S.A.

1.800.328.3352

www.nuaire.com



Process 20 - 1160DB Rev. 4 10/12

© 2012 NuAire, Inc.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP