ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *OMRON JZSP-VFP00-03* at our website: *Click HERE*

OMRON

SJDE-□-OY, SJME-□-OY

Junma Servo system



A new concept in drive simplicity
Save space, save wiring, save time


- Ultra compact drive size reduces panel space
- Tuning-less technology, no gain parameters need to be set
- Peak torque 300% of nominal for 3 seconds
- High response, high speed, high torque and high accuracy
- Drive version with MECHATROLINK-II port built-in
- MECHATROLINK-II simplifies wiring and reduces installation time
- MECHATROLINK-II provides access to the system from one point
- Pulse control Drive version available, fully "Parameter-less" just plug and run

Ratings


- 230 VAC Single-phase 100 W to 750 W (2.39 Nm)

System Configuration

Junma MECHATROLINK-II Servo Drive Configuration



Junma PULSE Servo Drive Configuration



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Motor Type Designation

SJME - 02 A M B 4 1 - OY

- JUNMA servomotor
- Capacity

Code	Output (W)
01	100
02	200
04	400
08	750

- Voltage
  A: 200 VAC
- Feedback specifications
  M : Analogue output encoder
- Design procedure
  B : Standard
- Shaft end specifications
  4 : Straight, key
- Brake specifications
  1 : No brake
  C : 24VDC brake
- OMRON YASKAWA Motion Control BV


Servomotor Specifications

Voltage			**230 V**			
Servomotor Model SJME- □			**01A**□	**02A**□	**04A**□	**08A**□
Rated Output *1		W	100	200	400	750
Rated Torque *1, *2		N·m	0.318	0.637	1.27	2.39
Instantaneous Peak Torque *1		N·m	0.955	1.91	3.82	7.16
Rated Current *1		Arms	0.84	1.1	2.0	3.7
Instantaneous Max. Current *1		Arms	2.5	3.3	6.0	11.1
Rated Speed *1		min^{-1}	3000			
Max. Speed *1		min^{-1}	4500			
Torque Constant		N·m/Arms	0.413	0.645	0.682	0.699
Rotor Moment of Inertia (JM)		$kg·m^2x10^{-4}$	0.0634	0.330	0.603	1.50
Allowable load inertia *3		$kg· m^2x10^{-4}$	0.6	3.0	5.0	10.0
Rated Power Rate		kW/s	16.0	12.3	26.7	38.1
Rated Angular Acceleration		rad/s^2	50200	19300	21100	15900
Encoder		Standard	Analogue output encoder			
Allowable radial load			78	245	245	392
Allowable thrust load			54	74	74	147
Approx. mass		kg (without brake)	0.5	0.9	1.3	2.6
		kg (with brake)	0.8	1.5	1.9	3.5
Brake specifications	Rated voltage		24 VDC ±10%			
	Holding Brake Moment of Inertia	$kg·m^2x10^{-4}$	0.0075	0.064		0.171
	Power consumption (at 20°C)	W	6	6.9		7.7
	Current consumption (at 20°C)	A	0.25	0.29		0.32
	Static friction torque	N·m (minimum)	0.318	1.27		2.39
	Rise time for holding torque	ms (max)	100			
	Release time	ms (max)	80			
Basic Specifications	Time Rating		Continuous			
	Thermal Class		Class B			
	Vibration Class		15 µm or below			
	Withstand Voltage		1500 VAC for one minute			
	Insulation resistance		500 VDC, 10 MΩ min.			
	Enclosure		Totally-enclosed, self-cooled, IP55 (excluding shaft opening and connectors)			
	Vibration Resistance		Vibration acceleration 49 m/s²			
	Usage / storage temperature		0 to +40° C / -20 to 60° C without freezing			
	Usage / storage humidity		20 to 80% RH (non-condensing)			
	Altitude		1000 m or less above sea level			
	Mounting		Flange-mounted			

Note: ***1.** These items and speed/torque characteristics quoted in combination with an SJDE servo drive are at an armature winding temperature of 100°C. Other values quoted at 20°C.
***2:** The rated torques listed here are the values for the continuous allowable torque at 40°C with an aluminium heatsink (250 mm x 250 mm x 6 mm) attached.
***3.** Value usig the appropriate SJDE drive without of external regeneration unit

Torque-Speed Charecteristics

(A : Continuous Duty Zone B : Intermittent Duty Zone)



Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Servomotor / Servo Drive Combination

Junma Servomotor						Junma servo drive	
	Voltage	Rated Torque	Capacity	Model without brake	Model with brake	MECHATROLINK-II	Pulse Control
SJME- (3000 min^{-1}) 	200 V	0.318 Nm	100 W	SJME-01AMB41-OY	SJME-01AMB4C-OY	SJDE-01ANA-OY	SJDE-01APA-OY
		0.637 Nm	200 W	SJME-02AMB41-OY	SJME-02AMB4C-OY	SJDE-02ANA-OY	SJDE-02APA-OY
		1.27 Nm	400 W	SJME-04AMB41-OY	SJME-04AMB4C-OY	SJDE-04ANA-OY	SJDE-04APA-OY
		2.39 Nm	750 W	SJME-08AMB41-OY	SJME-08AMB4C-OY	SJDE-08ANA-OY	SJDE-08APA-OY

Servo Drive Type Designation

SJDE - 02 A N A - OY

- JUNMA servo drive
- Applicable servomotor capacity

Code	Output (W)
01	100
02	200
04	400
08	750

- Power supply voltage
  A: 200 VAC
- Control Interface specification
  N: MECHATROLINK-II
  P: Pulse train input
- Design revision
  A: Standard
- OMRON YASKAWA Motion Control BV

Servo Drive Specifications

Junma MECHATROLINK-II Servo Drive

Servo Drive Type		SJDE- □	01ANA-OY	02ANA-OY	04ANA-OY	08ANA-OY
Applicable servomotor		SJME-□	01A□	02A□	04A□	08A□
Basic specifications	Max. Applicable Motor capacity	W	100	200	400	750
	Continuous output current	Arms	0.84	1.1	2.0	3.7
	Max. output current	Arms	2.5	3.3	6.0	11.1
	Input power supply (Main circuit and control circuit)	Voltage	Single-phase, 200 to 230 VAC, + 10 to -15% (50/60 Hz)			
		Capacity KVA	0.40	0.75	1.2	2.2
	Control Method		PWM control, sine wave current drive system			
	Feedback		Analogue incremental encoder (13 bits incremental equivalent)			
	Allowable load inertia*1	kg· m^2	0.6×10^{-4}	3.0×10^{-4}	5.0×10^{-4}	10.0×10^{-4}
	Usage / storage temperature		0 to +55° C / -20 to 70° C			
	Usage / storage humidity		90%RH or less (non-condensing)			
	Altitude		1000m or less above sea level			
	Vibration/shock Resistance		4.9m/s^2 (0.5G) / 19.6m/s^2 (2G)			
	Configuration		Base mounted			
	Approx. mass	Kg	1.0			1.4
Built-in functions	Dynamic brake (DB)		Operated at main power OFF, servo alarm, servo OFF.(OFF after motor stops; ON when motor power is off.)			
	Regenerative processing		Optional (If the regenerated energy is too large, install a regenerative unit JUSP-RG08D)			
	Over-travel (OT) prevention function		P_OT, N_OT			
	Emergency stop		Emergency stop (E-STP)			
	LED display		4 LEDs (PWR, RDY, COM, ALM)			
	MECHATROLINK-II monitor		MECHATROLINK-II under communication : COM LED (Light ON)			
	Servo ON/OFF monitor		At Servo OFF : RDY LED (Light OFF), at Servo ON : RDY LED (Light Blinks)			
	Power supply status monitor		Control / main-circuit power-supply OFF state: PWR LED (Light OFF) Control / main-circuit power-supply ON state: PWR LED (Light ON)			
	Electronic gearing		0,01< A/B<100			
	Protection		Overcurrent, overvoltage, undervoltage, overload, main circuit sensor error, board temperature error, excessive position error overflow, overspeed, encoder signal error, overrun protection, system error, parameter error			
	MECHATROLINK Communication	Comm. protocol	MECHATROLINK-II			
		Transmission rate	10 Mbps			
		Transmission cycle	1ms, 1.5ms, 2ms, 3ms, 4ms			
		Data length	17 byte and 32 byte			
	Command input	MECHATROLINK communication	MECHATROLINK-II commands (For sequence, motion, data setting/reference, monitor, adjustment, and other commands)			
	Sequence Input signal	Fixed input	5 points (fixed layout: external latch signal, zero return reduced speed signal, forward drive inhibiting signal, reverse run inhibiting signal, emergency stop signal)			
	Sequence Output signal	Fixed output	2 points (fixed layout: servo alarm, brake interlock)			

Note: *1. Value without external regeneration unit

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Junma Pulse Servo Drives

Servo Drive Type		SJDE-□	01APA-OY	02APA-OY	04APA-OY	08APA-OY
Applicable servomotor		SJME-□	01A□	02A□	04A□	08A□
Basic specifications	Max. Applicable Motor capacity	W	100	200	400	750
	Continuous output current	Arms	0.84	1.1	2.0	3.7
	Max. output current	Arms	2.5	3.3	6.0	11.1
	Input power supply (Main circuit and control circuit)	Voltage	Single-phase, 200 to 230 VAC, + 10 to -15% (50/60 Hz)			
		Capacity KVA	0.40	0.75	1.2	2.2
	Control Method		PWM control, sine wave current drive system			
	Feedback		Analogue incremental encoder (10000 steps per revolution)			
	Allowable load inertia*1	kg· m^2	0.6×10^{-4}	3.0×10^{-4}	5.0×10^{-4}	10.0×10^{-4}
	Usage / storage temperature		0 to +55° C / -20 to 70° C			
	Usage / storage humidity		90%RH or less (non-condensing)			
	Altitude		1000 m or less above sea level			
	Vibration/shock Resistance		$4.9m/s^2$ (0.5G) / $19.6m/s^2$ (2G)			
	Configuration		Base mounted			
	Cooling method		Forced cooling (built-in fan)			
	Approx. mass	Kg	0.5			1.0
Built-in functions	Dynamic brake (DB)		Operated at main power OFF, servo alarm, servo OFF.(OFF after motor stops; ON when motor power is off.)			
	Regenerative processing		Optional (If the regenerated energy is too large, install a regenerative unit JUSP-RG08D)			
	LED display		5 (PWE, REF, AL1, AL2, AL3)			
	Reference filter		Select one of eight levels with FIL switch			
	Protection		Speed errors, overload, encoder errors, voltage errors, overcurrents, disablement of the built-in cooling fan, system errors			
I/O Signals	Input signal for reference Designated pulse type and pulse resolution with PULSE switch.	Pulse type	Select one of the following signals: 1. CCW + CW 2. Sign + pulse train 3. CCW + CW (logic reversal) 4. Sign + pulse train (logic reversal)			
		Pulse resolution	Select one of the following signals: 1. 1000 pulses/rev (Open collector/line driver) 75 kpps max. 2. 2500 pulses/rev (Open collector/line driver) 187.5 kpps max. 3. 5000 pulses/rev (Line driver) 375 kpps max. 4. 10000 pulses/rev (Line driver) 750 kpps max.			
	Clear input signal		Clears the positioning error when turned ON			
	Servo ON input signal		Turns the servomotor ON or OFF			
	Alarm output signal		OFF if an alarm occurs. (Note: OFF for 2s when power is turned ON)			
	Brake output signal		External signal to control brakes. Turn ON to release the brake			
	Positioning completed output signal		ON if the current position is equal to the reference position ±10 pulses.External signal to control brakes.			
	Origin output signal		ON if the motor is at the origin. (Width: 1/500 rev) (Note:Use the pulse edge that changes the signal from OFF to ON)			

Note: *1. Value without external regeneration unit


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Dimensions

Junma servomotors

SJME-01 (200V, 100W)


Model	L	LL	Approx. Mass (kg)
SJME-01AMB41-OY	119	94	0.5
SJME-01AMB4C-OY	164	139	0.8



Units: mm

SJME-02, 04, 08 (200V, 200 to 750W)


Model	L	LL	LR	LG	LE	S	LB	LC	LD	LF	LA	LZ	QK	Approx. Mass (kg)
SJME-02AMB41-OY	125.5	95.5	30	6	3	$14^{0}_{-0.011}$	$50^{0}_{-0.039}$	60	-	-	70	5.5	20	0.9
SJME-02AMB4C-OY	165.5	135.5												1.5
SJME-04AMB41-OY	148.5	118.5							-	-				1.3
SJME-04AMB4C-OY	188.5	158.5												1.9
SJME-08AMB41-OY	173	133	40	8	3	$16^{0}_{-0.011}$	$70^{0}_{-0.046}$	80	35	20	90	7	30	2.6
SJME-08AMB4C-OY	216	176												3.5



Units: mm

Servomotor connectors

Encoder Connector Specifications



Plug:
5559-12P-210
Terminal:
5558T2(chained) or
5558T2L(detached)
(Manufacture: Molex Japan Co., Ltd)

1	PG5V	Red
2	PG0V(GND)	Black
3	Phase A+	Blue
4	Phase A-	Blue/White
5	Phase B+	Yellow
6	Phase B-	Yellow/White
7	Phase /Z	Purple
8	Phase U	Gray
9	Phase V	Green
10	Phase W	Orange
11	-	-
12	FG	Shield

Motor Connector Specifications




Plug:
5559-06P-210
Terminal (No.1 to 3, 5, 6):
5558T(chained) or 5558TL(detached)
Grounding Pin (No.4):
30490-2002(chained) or
30490-2012 (detached)
(Manufacture: Molex Japan Co., Ltd)

	No brake		With brake	
1	Phase U	Red	Phase U	Red
2	Phase V	White	Phase V	White
3	Phase W	Blue	Phase W	Blue
4	F G	Green/Yellow	F G	Green/Yellow
5	-	-	Brake	Red
6	-	-	Brake	Black

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Junma MECHATROLINK-II servo drives

SJDE-01, 02, 04ANA-OY (200V, 100 to 400W)




Model	Cooling Fan
SJDE-01ANA-OY	Not mounted
SJDE-02ANA-OY	Not mounted
SJDE-04ANA-OY	Mounted

Approx. mass : 1kg

Units in mm

SJDE-08ANA-OY (200V, 750W)




Approx. mass : 1.4 kg

Units in mm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Junma pulse control servo drives

SJDE-01, 02APA-OY (200V, 100 to 200W)




Approx. mass : 0.5 kg
Units in mm

SJDE-04APA-OY (200V, 400W)



Approx. mass : 0.5 kg
Units in mm

SJDE-08APA-OY (200V, 800W)




Approx. mass : 1 kg
Units in mm

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Ordering Information


Junma Servo Motor configuration

① **Junma Servo Motor**
3,000 rpm
(100-750 W)



④ Encoder cable







③ Power cable

(Refer to servo drive chapter)

② **Junma MECHATROLINK-II Servo Drive**





② **Junma Pulse Servo Drive**




Servomotors and Servo drives

Symbol	Specifications					① Servomotor model	② Servo drive model	
	Voltage	Encoder and Design		Rated Torque	Capacity		Mechatrolink-II	Pulse Control
①②	1 Phase 200 VAC	Analogue Incremental Encoder Straight shaft with key	Without brake	0.318 Nm	100 W	SJME-01AMB41-OY	SJDE-01ANA-OY	SJDE-01APA-OY
				0.637 Nm	200 W	SJME-02AMB41-OY	SJDE-02ANA-OY	SJDE-02APA-OY
				1.27 Nm	400 W	SJME-04AMB41-OY	SJDE-04ANA-OY	SJDE-04APA-OY
				2.39 Nm	750 W	SJME-08AMB41-OY	SJDE-08ANA-OY	SJDE-08APA-OY
			With brake	0.318 Nm	100 W	SJME-01AMB4C-OY	SJDE-01ANA-OY	SJDE-01APA-OY
				0.637 Nm	200 W	SJME-02AMB4C-OY	SJDE-02ANA-OY	SJDE-02APA-OY
				1.27 Nm	400 W	SJME-04AMB4C-OY	SJDE-04ANA-OY	SJDE-04APA-OY
				2.39 Nm	750 W	SJME-08AMB4C-OY	SJDE-08ANA-OY	SJDE-08APA-OY

Power cables

Symbol	Specifications			Model	Appearance
③	Power cable for Junma servomotors without brake SJME-0□AMB41-OY	Flexible cables (Standard) Shielded Cable Bending radius (Dynamic) > 10xDiameter Bending cycles > 5 Million	1.5 m	JZSP-CHM000-01-5E	
			3 m	JZSP-CHM000-03-E	
			5 m	JZSP-CHM000-05-E	
			10 m	JZSP-CHM000-10-E	
			15 m	JZSP-CHM000-15-E	
			20 m	JZSP-CHM000-20-E	
		Non flexible cables	3 m	R7A-CAZ003S	
			5 m	R7A-CAZ005S	
			10 m	R7A-CAZ010S	
	Power cable for Junma servomotors with brake SJME-0□AMB4C-OY	Flexible cables (Standard) Shielded Cable Bending radius (Dynamic) > 10xDiameter Bending cycles > 5 Million	1.5 m	JZSP-CHM030-01-5E	
			3 m	JZSP-CHM030-03-E	
			5 m	JZSP-CHM030-05-E	
			10 m	JZSP-CHM030-10-E	
			15 m	JZSP-CHM030-15-E	
			20 m	JZSP-CHM030-20-E	
		Non flexible cables	3 m	R7A-CAZ003B	
			5 m	R7A-CAZ005B	
			10 m	R7A-CAZ010B	

Encoder cables


Symbol	Specifications			Model (Flexible)	Appearance
④	Encoder cable for Junma servomotors SJME-0□AMB4□-OY	Flexible cables (Standard) Shielded Cable Bending radius (Dynamic) > 10xDiameter Bending cycles > 5 Million	1.5 m	JZSP-CHP800-01-5E	
			3 m	JZSP-CHP800-03-E	
			5 m	JZSP-CHP800-05-E	
			10 m	JZSP-CHP800-10-E	
			15 m	JZSP-CHP800-15-E	
			20 m	JZSP-CHP800-20-E	
		Non flexible cables	3 m	R7A-CRZ003C	
			5 m	R7A-CRZ005C	
			10 m	R7A-CRZ010C	

Connectors for power and encoder cables

Specifications			Model (Omron)	Model (Yaskawa)
Connectors for making power cables	Drive side (CNB)	Manufacturer: JST (04JFAT-SAYGF-N)	R7A-CNZ01A	JZSP-CHM9-2
	Motor side	Manufacturer: Molex (5557-06R-210)	R7A-CNZ02A	JZSP-CHM9-1
Connectors for making encoder cables	Drive side (CN2)	Manufacturers 3M and Molex	R7A-CNZ01R	JZSP-CHP9-2
	Motor side	Manufacturer: Molex (57026-5000)	R7A-CNZ02R	JZSP-CHP9-1

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Junma MECHATROLINK-II Servo Drive Configuration



Servomotors and Servo drives

Symbol	Specifications					① Servomotor model	② Servo drive model
	Voltage	Encoder and Design		Rated Torque	Capacity		
①②	1 Phase 200 VAC	Analogue Incremental Encoder Straight shaft with key	Without brake	0.318 Nm	100 W	SJME-01AMB41-OY	SJDE-01ANA-OY
				0.637 Nm	200 W	SJME-02AMB41-OY	SJDE-02ANA-OY
				1.27 Nm	400 W	SJME-04AMB41-OY	SJDE-04ANA-OY
				2.39 Nm	750 W	SJME-08AMB41-OY	SJDE-08ANA-OY
			With brake	0.318 Nm	100 W	SJME-01AMB4C-OY	SJDE-01ANA-OY
				0.637 Nm	200 W	SJME-02AMB4C-OY	SJDE-02ANA-OY
				1.27 Nm	400 W	SJME-04AMB4C-OY	SJDE-04ANA-OY
				2.39 Nm	750 W	SJME-08AMB4C-OY	SJDE-08ANA-OY

Power and encoder cables

Note: ③④ Refer to the Junma servo motor section for motor cables or connectors selection

Mechatrolink-II Motion controllers

Symbol	Name	Model
⑤	Position Controller Unit for CJ1 PLC	CJ1W-NCF71
	Position Controller Unit for CS1 PLC	CS1W-NCF71
	Trajexia stand-alone motion controller	TJ1-MC16

Mechatrolink-II cables

Symbol	Specifications		Model
⑥	Mechatrolink-II Terminator resistor		JEPMC-W6022
	Mechatrolink-II Cables	0.5 m	JEPMC-W6003-A5
		1 m	JEPMC-W6003-01
		3 m	JEPMC-W6003-03
		5 m	JEPMC-W6003-05
		10 m	JEPMC-W6003-10
		20 m	JEPMC-W6003-20
		30 m	JEPMC-W6003-30

Cables for I/Os (for CN1)

Symbol	Name	Compatible units		Model
⑦	Control cable	Cable for servo drive I/O signals	1 m	R7A-CPZ001S or JZSP-CHI003-01
			2 m	R7A-CPZ002S or JZSP-CHI003-02
			3 m	JZSP-CHI003-03

Filters

Symbol	Applicable servo drive	Rated current	Leakage current	Rated voltage	Filter model
⑧	SJDE-01ANA-OY SJDE-02ANA-OY SJDE-04ANA-OY	5A	1.7 mA	250 VAC 1- phase	R7A-FIZN105-BE
	SJDE-08ANA-OY	9A	1.7 mA		R7A-FIZN109-BE

Regenerative Unit Model (Option)

Symbol	Specifications	Model (Omron)	Model (Yaskawa)
⑨	External regenerative unit (Optional)	R88A-RG08UA	JUSP-RG08D

Connectors


Specification	Model (Omron)	Model (Yaskawa)
Control I/O connector (for CN1)	R7A-CNA01R	JZSP-CHI9-1
Power input connector (for CNB). (Included in drive the box)	R7A-CNZ01P	JZSP-CHG9-1

Computer Software

Specifications	Model
Configuration and monitoring software tool via ML2 (CX-Drive version 1.3 or higher)	CX-DRIVE
Complete Omron software package including CX-Drive (CX-One 2.0 or higher)	CX-ONE

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Junma Pulse Servo Drive Configuration



Servomotors and Servo drives

Symbol	Specifications					① Servomotor model	② Servo drive model
	Voltage	Encoder and Design		Rated Torque	Capacity		Pulse Control
①②	1 Phase 200 VAC	Analogue Incremental Encoder Straight shaft with key	Without brake	0.318 Nm	100 W	SJME-01AMB41-OY	SJDE-01APA-OY
				0.637 Nm	200 W	SJME-02AMB41-OY	SJDE-02APA-OY
				1.27 Nm	400 W	SJME-04AMB41-OY	SJDE-04APA-OY
				2.39 Nm	750 W	SJME-08AMB41-OY	SJDE-08APA-OY
			With brake	0.318 Nm	100 W	SJME-01AMB4C-OY	SJDE-01APA-OY
				0.637 Nm	200 W	SJME-02AMB4C-OY	SJDE-02APA-OY
				1.27 Nm	400 W	SJME-04AMB4C-OY	SJDE-04APA-OY
				2.39 Nm	750 W	SJME-08AMB4C-OY	SJDE-08APA-OY

Power and encoder cables

Note: ③④ Refer to the Junma servo motor section for motor cables or connectors selection

Control cables (for CN1)

Symbol	Name	Compatible units		Model
⑤	Servo relay unit	Units: CS1W-NC113/133, CJ1W-NC113/133, C200HW-NC113	-	XW2B-20J6-1B (1 axis)
		Units: CS1W-NC213/233/413/433, CJ1W-NC213/233/413/433, C200HW-NC213/413	-	XW2B-40J6-2B (2 axes)
		Units: CQM1H-PLB21 and CQM1-CPU43-V1	-	XW2B-20J6-3B (1 axis)
		Use with CJ1M-CPU21/22/23	-	XW2B-20J6-8A (1 axis)
			-	XW2B-40J6-9A (2 axes)
⑥	Cable to servo drive	For the servo relay unit XW2B-□□J6-□B, XW2B-20J6-8A, XW2B-40J6-9A	1 m	XW2Z-100J-B17
			2 m	XW2Z-200J-B17
⑦	Cable to position control unit	CQM1H-PLB21 and CQM1-CPU43-V1	0.5 m	XW2Z-050J-A3
			1 m	XW2Z-100J-A3
		CS1W-NC113 and C200HW-NC113	0.5 m	XW2Z-050J-A8
			1 m	XW2Z-100J-A8
		CS1W-NC213/413 and C200HW-NC213/413	0.5 m	XW2Z-050J-A9
			1 m	XW2Z-100J-A9
		CS1W-NC133	0.5 m	XW2Z-050J-A12
			1 m	XW2Z-100J-A12
		CS1W-NC233/433	0.5 m	XW2Z-050J-A13
			1 m	XW2Z-100J-A13
		CJ1W-NC113	0.5 m	XW2Z-050J-A16
			1 m	XW2Z-100J-A16
		CJ1W-NC213/413	0.5 m	XW2Z-050J-A17
			1 m	XW2Z-100J-A17
		CJ1W-NC133	0.5 m	XW2Z-050J-A20
			1 m	XW2Z-100J-A20
		CS1W-NC233/433	0.5 m	XW2Z-050J-A21
			1 m	XW2Z-100J-A21
		CJ1M-CPU21/22/23	0.5 m	XW2Z-050J-A26
			1 m	XW2Z-100J-A26

Symbol	Name	Compatible units		Model
⑧	Control cable	For general-purpose controllers	1 m	R7A-CPZ001S or JZSP-CHI003-01
			2 m	R7A-CPZ002S or JZSP-CHI003-02
			3 m	JZSP-CHI003-03
⑨	Connector terminal block cable	For general-purpose controllers	1 m	XW2Z-100J-B19
			2 m	XW2Z-200J-B19
	Connector terminal block		-	XW2B-20G5

Filters

Symbol	Applicable servo drive	Rated current	Leakage current	Rated voltage	Filter model
⑩	SJDE-01APA-OY SJDE-02APA-OY SJDE-04APA-OY	5A	1.7 mA	250 VAC 1- phase	R7A-FIZP105-BE
	SJDE-08APA-OY	9A	1.7 mA		R7A-FIZP109-BE

Regenerative Unit Model (Option)

Symbol	Specifications	Model (Omron)	Model (Yaskawa)
⑪	External regenerative unit (Optional)	R88A-RG08UA	JUSP-RG08D

Connectors

Specification	Model (Omron)	Model (Yaskawa)
Control I/O connector (for CN1)	R7A-CNA01R	JZSP-CHI9-1
Power input connector (for CNB). (Included in drive the box)	R7A-CNZ01P	JZSP-CHG9-1

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

OMRON EUROPE B.V. Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. Tel: +31 (0) 23 568 13 00 Fax: +31 (0) 23 568 13 88 www.omron-industrial.com

Austria
Tel: +43 (0) 1 80 19 00
www.omron.at

Belgium
Tel: +32 (0) 2 466 24 80
www.omron.be

Czech Republic
Tel: +420 234 602 602
www.omron.cz

Denmark
Tel: +45 43 44 00 11
www.omron.dk

Finland
Tel: +358 (0) 207 464 200
www.omron.fi

France
Tel: +33 (0) 1 56 63 70 00
www.omron.fr

Germany
Tel: +49 (0) 2173 680 00
www.omron.de

Hungary
Tel: +36 (0) 1 399 30 50
www.omron.hu

Italy
Tel: +39 02 326 81
www.omron.it

Middle East & Africa
Tel: +31 (0) 23 568 11 00
www.omron-industrial.com

Netherlands
Tel: +31 (0) 23 568 11 00
www.omron.nl

Norway
Tel: +47 (0) 22 65 75 00
www.omron.no

Poland
Tel: +48 (0) 22 645 78 60
www.omron.pl

Portugal
Tel: +351 21 942 94 00
www.omron.pt

Russia
Tel: +7 495 745 26 64
www.omron-industrial.ru

Spain
Tel: +34 913 777 900
www.omron.es

Sweden
Tel: +46 (0) 8 632 35 00
www.omron.se

Switzerland
Tel: +41 (0) 41 748 13 13
www.omron.ch

Turkey
Tel: +90 (0) 216 474 00 40
www.omron.com.tr

United Kingdom
Tel: +44 (0) 870 752 08 61
www.omron.co.uk

More Omron representatives
www.omron-industrial.com

Authorised Distributor:

Control Systems
• Programmable logic controllers • Human-machine interfaces • Remote I/O

Motion & Drives
• Motion controllers • Servo systems • Inverters

Control Components
• Temperature controllers • Power supplies • Timers • Counters • Programmable relays
• Digital panel indicators • Electromechanical relays • Monitoring products • Solid-state relays
• Limit switches • Pushbutton switches • Low voltage switch gear

Sensing & Safety
• Photoelectric sensors • Inductive sensors • Capacitive & pressure sensors • Cable connectors
• Displacement & width-measuring sensors • Vision systems • Safety networks • Safety sensors
• Safety units/relay units • Safety door/guard lock switches

KPP_JUNMA_01_EN_INT

Although we strive for perfection, Omron Europe BV and/or its subsidiary and affiliated companies do not warrant or make any representations regarding the correctness or completeness of the information described in this document. We reserve the right to make any changes at any time without prior notice.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP