ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Parker / Compumotor Q-510* at our website: *Click HERE*

Q series
MOTOR and DRIVES



Compumotor's Q-Series DC servosystem offers the simplicity of step motor/drive control in a DC servo positioning system. Ready to plug in and run, the new Q-Series system consists of a motor, microprocessor based driver, and brushless resolver feedback.

The Compumotor Q-Series drivers accept digital step and direction inputs to control positioning and velocity. The onboard microprocessor monitors both the pulse inputs and the resolver position feedback, then determines the proper voltage levels to apply to the motor. The Q-Series offers speeds to 3600 RPM and a maximum torque of 34 lb-in (540 oz-in) continuous and 100 lb-in (1600 oz-in) peak.

Closed loop performance is simplified by the microprocessor control and a sophisticated servo algorithm. All servo parameters are stored in non-volatile memory (EEPROM), eliminating analog potentiometer adjustments required in conventional servosystems. Q-Series motor/drives are supplied as packaged systems, factory compensated for typical loads and performance requirements.

Q-Series systems are readily installed and operated by personnel with little training in servo controls. In most applications, no adjustments will be required. A simple pushbutton adjustment is provided to alter factory set servo constants for special loads. In addition, an RS-232C interface port allows access to all servo parameters for applications requiring critical adjustment.

Compumotor's new Q-Series utilizes a proprietary hybrid power MOSFET module in the power amplifier section for high frequency (20 KHz) pulse width modulation current control. This Compumotor innovation improves efficiency and low speed smoothness, and results in virtually inaudible operation.

Features of the Q series include:

- DC brushed servomotor
- Brushless resolver feedback
- Speeds to 3600 RPM
- Torques to 100 lb-in (1600 oz-in)
- 4096 steps/rev resolution
- Microprocessor control: no drift, no analog pots to adjust
- Compact convection-cooled driver enclosure
- Inaudible 20 KHz PWM switching frequency
- Accepts digital step and direction inputs
- Servo parameters factory set and stored in non-volatile (EEPROM) memory
- High noise immunity due to opto and transformer isolation
- Pushbutton adjustment of servo compensation

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Specifications

Parameter	Value
Performance:	
Repeatability	±5 arc min. (.088°) Unloaded—one revolution returning to start point from same direction.
Accuracy	±14 arc min. (-0.23°) Unloaded—motor bearing and seal friction only.
Relative accuracy	±5 arc min. (.088°) Step to step, bidirectional
Resolution	
—R5	4,096 steps/rev
—R8	16,384 steps/rev (Maximum speed is 2100 RPM)

Power:	Single Phase	3 Phase	DC
Volts	105-125 VAC	105-125 VAC	100-160 VDC
Frequency	50/60 Hz	50/60 Hz	
Current	10A maximum	10A maximum	10A maximum

Inputs:	Optically isolated
Step	3.5-6.0 VDC
Direction	500 N. Sec. minimum pulse width
Shut Down	20 mA maximum source current required
Interface: RS-232C	
Baud Rate	1200
Data Bits	8
Stop Bits	2
Parity	None
Environmental:	
Operating	
Drive	32 to 122°F (0 to 50°C). Maximum heatsink temperature is 122°F (50°C).
Motor	255°F (125°C) Maximum motor case temperature
Storage	-40°F to 185°F (-40°C to 85°C).
Humidity	0 to 95% Non-condensing

Adjustment to Factory Preset Servo Parameters

Factory preset servo parameters will ensure optimum performance under most operating conditions. External pushbuttons provide easy "up/down" adjustment to meet more critical load/performance requirements. For extremely critical positioning needs, the following software commands can be used to redefine motor performance parameters. User defined parameters are simply entered over an RS-232C interface and stored in on-board non-volatile EEPROM memory. Factory settings can be recalled at any time.

Software Commands


AC	Average Current
CF	Define desired crossover frequency
DB	Dead band definition
ES	Enter setup mode
FE	Define maximum following error
MS	Motor enable
RE	Report error conditions
RF	Factory preset settings
RS	Reset drive system
RV	Report software revision
SC	Report average current
SE	Report the following error
SV	Save parameters in EEPROM

Setup Mode Commands

D	Decrease gain
E	Enter tuning process
S	Save new setup parameters
U	Increase gain
X	Exit setup mode


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Q-510



Maximum speed (2,100 RPM) with 16,384 (R-8) step/rev option

Q-530



Technical Data


	Q-510	Q-530
Continuous torque (at 77°F/25°C)		
lb-in	9	34
oz-in	150	540
(N-m)	(1.06)	(3.81)
Peak torque		
lb-in	48.8	100
oz-in	780	1,600
(N-m)	(5.51)	(11.29)
Rotor inertia		
oz-in²	9.3	141.7
(Kg-cm²)	(1.69)	(25.92)
Maximum speed		
rps	60	30
(rpm)	(3,600)	(1,800)
Maximum armature temperature		
°F	310	310
(°C)	(155)	(155)
Maximum allowable ambient temperature at driver		
°F	122	122
(°C)	(50)	(50)
Maximum driver input current at 120 VAC		
in Amps	10	10
Bearings:		
Radial load		
lbs.	40.0	150.0
(N)	(180)	(670)
Weight (Net)		
Motor + Cable + Connector		
lbs.	7.4	33.0
(Kg)	(3.4)	(15.0)
Total shipping weight (Net)		
Motor/Drive + Cables + Container		
lbs.	18.0	43.0
(Kg)	(8.2)	(19.5)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com


Dimensions

(—) denotes centimeters


Model Q-510




Model Q-530



Programming Key



Motor Drive



The drive should be mounted with the heat sink vertical. Allow a 6" vertical and 4" horizontal clearance for proper convection cooling.

Drive Connector Listing

RS-232C

25-Pin "D"

Pin No.	Signal
2	Receive Data
3	Transmit Data
7	GND

Motor

7-Pin Entrelec
(Shielding unnecessary)

Pin No.	Signal
1	Motor +
2	Strap
3	Motor –
4	Earth
5	Reserved
6	Reserved
7	Reserved

Power Connector

4-Pin Entrelec (Shielding unnecessary)

Pin No.	Signal		
	Single Phase	Three Phase	DC
1	Line	Phase 1	V+
2	Neutral	Phase 2	V–
3	—	Phase 3	—
4	Earth	Earth	Earth

Indexer

25-Pin "D"

Pin No.	Signal
1	Step +
2	Direction +
7	Fault reset +
9	Fault +
14	Step –
15	Direction –
16	Shutdown +
17	Shutdown –
19	Fault reset –
21	Fault –

Auxiliary

4-Pin Entrelec
(User responsible for shielding)

Pin No.	Signal
1	Pullup
2	Drive enable (Input)
3	Ground
4	Reserved

The drive should be mounted with the heat sink vertical. Allow a 6" vertical and 4" horizontal clearance for proper convection cooling.

Resolver

9-Pin "D"
Shielded from motor end

Programming Key

9-Pin "D"

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP