ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Parker / Compumotor RP-240-R* at our website: *Click HERE*

RP240

Operator Interface



Features


- Operates directly with Compumotor's ZETA6104, SX and ZX Indexer/Drives, 500, 6200 and 6201 Indexers, 6250 Servo Controller, and APEX6151/APEX6152/APEX6154 Controllers
- Communication through a three-wire RS-232C port (RX, TX Ground)
- Screw Terminal connections for easy wiring
- Sealed membrane keypad meets NEMA 12 specifications (NEMA 4 option available)
- Easy-to-read, 2-line, 40-character-per-line LCD display
- Adjustable contrast for the LCD display
- Numeric and Function key data entry
- Dedicated STOP key for program termination
- PAUSE and CONTINUE keys for temporary program halt
- 8 independent LEDs for user-selectable status indicators
- Power requirement of only 100 mA @ 5VDC (can be supplied from SX, ZX, 500, 6200, 6250, APEX6152, and APEX6154)
- Can be utilized by any controller capable of transmitting ASCII strings across RS-232C
- Low profile for easy panel mount configuration
- Optional flange for flush mounting and NEMA 4 sealed, keypad (RP240–NEMA 4) membrane

Summary of Command Set Functions


- Clear the display
- Enable/disable PAUSE and CONTINUE keys
- Turn RP240 LEDs on/off
- Position cursor
- Enable/disable STOP
- Display text data on RP240 LCD
- Display variable data on RP240 LCD

Dimensions (—) denotes millimeters

RP240



RP240-Nema 4



Specifications

Parameter	Value
Power	5VDC @ 100 mA
Serial Interface	RS-232C port, 3-wire, 9600 baud, 8 data bits, 1 stop bit, no parity
Environmental	
Operating Temp	36° to 122° F (5° to 50°C)
Storage Temp	–22° to 185°F (–30° to 85°C)
Humidity	0% to 95% non-condensing

RP240 Connections

Power & RS-232C, 4-pin

Pin No.	In/Out	Description
1	IN	Ground
2	IN	Receive (RX)
3	OUT	Transmit (TX)
4	IN	+5VDC

C Step Motor Systems

Parker Automation

Parker Hannifin Corporation
Compumotor Division
Rohnert Park, California

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP