



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com



P1P PowerStation

It's a perfect fit for applications that need high speed and high functionality in a compact hardware package!


The 6" P1P is a Pentium-based HMI workstation with advanced features, yet is small enough to fit almost any machine. It also sports an all-new look...with its sleek bezel design and graphical displays, bringing a modern, high tech look to any machine. The P1P not only offers a 6" STN display, but also provides a full VGA TFT option, which can run all of CTC's Interact software modules. This also means that the P1P can run applications developed for larger PowerStation workstations - on a smaller, more compact unit.

The P1P comes bundled with CTC's core Interact HMI software modules (panel tools, graphics, alarming and networking) and is a perfect companion to CTC's MachineLogic PC-based control software. All of this allows you to integrate HMI and machine control in a small, yet powerful, package.

Typically, smaller HMI workstations have slower processors, but the P1P delivers much higher speed with its Pentium processor. The P1P is an open architecture unit that offers expansion capabilities — it comes standard with a solid-state 16 MB Compact FLASH memory cartridge that is expandable to 128 MB. The removable Compact FLASH allows users to make changes to applications by simply dropping in an updated cartridge.

Ordering Information

(See MachineShop section for information about ordering development software.)



P1P Common Configurations	
Description	Model #
Color STN (1/4 VGA) Pentium - FLASH	P12-334DR-3
Color TFT (Full VGA) Pentium - FLASH	P12-434DR-3

Factory-Installed (or User-Installed) Hardware Accessories	
Description	Model #
PC/104 Installation Kit for a single PC/104 card	P11-PC104
PC/104 Installation Kit for two PC/104 cards	P12-PC104
PC/104 Installation Kit for three PC/104 cards	P13-PC104
Allen-Bradley 1771 Remote I/O Card and Driver	ABR-3205-A



P1P PowerStation

	Features	Values
Software		MachineShop with Interact Runtime PTM, AMM, GMM, NET
Display	Type Backlight Monochrome/Color Resolution Size	Flat Panel Cold Cathode Fluorescent Tube Color - LCD, TFT STN: 1/4 VGA (320 x 240) TFT: VGA (640 x 480) 5.7" (145 mm) Diagonal (LCD) 6.4" (163 mm) Diagonal (TFT)
CPU	Pentium	(consult factory for specific processor information)
System Memory	Standard	32 MB (minimum)
Storage Memory	Compact FLASH Floppy Disk Drive Hard Drive	16 MB compact FLASH (minimum) (Field replaceable FLASH Disk) N/A N/A
I/O Ports	Serial Ethernet Parallel Expansion Slots External Video	(1) RS232/422/485 (1) RS232 10/100 Base-T with RJ45 connector IBM Enhanced PC/104 (16 bit) N/A
User Interface	Function Key Numeric Key Touchscreen Select Key Cancel Key Keyboard Port Mouse	On Screen On Screen Analog Resistive N/A N/A IBM AT with Y-cable PS/2 with Y-cable
Package	Designed for Temperature Range Rel. Humidity (non-condensing) Vibration Shock Weight Overall Size (HxWxD)	NEMA 4, 4X 0-45 C 5-95% 10-150 Hz, 1G (Sin) 10-500 Hz 1.5G (RMS Random) 10G, 11 msec (operating) 30G, 11 msec (non-operating) 3.26 lbs. (1.48 Kg) 8.7" x 6.3" x 3.25" (221 mm x 160 mm x 82.5 mm)
Power Requirements	AC Maximum Power Consumption DC Maximum Power Consumption	90-260 VAC; 50/60 Hz; (Ext. Opt.) 50 Watts max. 18-28 VDC 25 Watts
Agency Approval	CE; UL/CUL	Class I Division 2 (DC units only)

For More Information on HMI & Machine Control Products, Call 1-800-233-3329.





Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com