

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PASTERNACK®
THE ENGINEER'S RF SOURCE



2 Way SMA Wilkinson Power Divider From 2 GHz to 4 GHz Rated at 10 Watts

Power Dividers Technical Data Sheet PE2014

Features

- 2-Way Power Divider
- Wilkinson Design
- 2 to 4 GHz Frequency Range
- Max Power 10 Watts (CW)
- Insertion Loss < 3.5 dB
- Isolation > 20 dB

Applications

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

Description

Pasternack carries a wide selection of power dividers to fit your needs. These components are essential in many systems, allowing the combination of multiple signals or splitting of a single signal into multiple signals with equal magnitude and phase. Pasternack's resistive and Wilkinson power dividers come with excellent performance featuring minimal loss, high isolation and low VSWR. They are available in both narrow and broad bandwidths with a variety of connector types such as 2.92mm, BNC, N and SMA.

The PE2014 is a 2-way Wilkinson power divider that operates from 2 to 4 GHz and can handle up to 10 Watts (CW) with 3.5 dB max insertion loss and 20 dB min isolation. The package interface uses SMA female connectors and is REACH and RoHS compliant.

Electrical Specifications

Design	Wilkinson
Number of Output Ports	2

Description	Minimum	Typical	Maximum	Units
Frequency Range	2		4	GHz
Impedance		50		Ohms
Input VSWR			1.3:1	
Output VSWR			1.3:1	
Insertion Loss			3.5	dB
Isolation	20			dB
Amplitude Balance			0.2	dB
Phase Balance			4	Degrees
Input Power (CW)			10	Watts

Electrical Specification Notes:
Max input power rated for load VSWR better than 2.0:1.
Insertion loss includes splitting loss.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2 Way SMA Wilkinson Power Divider From 2 GHz to 4 GHz Rated at 10 Watts PE2014

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

© 2017 Pasternack Enterprises All Rights Reserved

PASTERNACK®
THE ENGINEER'S RF SOURCE



2 Way SMA Wilkinson Power Divider From 2 GHz to 4 GHz Rated at 10 Watts

Mechanical Specifications

Size

Length	1.5 in [38.1 mm]
Width	1.5 in [38.1 mm]
Height	0.51 in [12.95 mm]
Weight	0.098 lbs [44.45 g]

Configuration

Package Type	Connectorized
Input Connector	SMA Female
Input Connector Specification	MIL-STD-348
Output Connectors	SMA Female
Output Connectors Specification	MIL-STD-348

Environmental Specifications

Temperature

Operating Range	-30 to +70 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

2 Way SMA Wilkinson Power Divider From 2 GHz to 4 GHz Rated at 10 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 2 Way SMA Wilkinson Power Divider From 2 GHz to 4 GHz Rated at 10 Watts PE2014

URL: https://www.pasternack.com/2-way-sma-reactive-power-divider-2-ghz-4-ghz-10-watts-pe2014-p.aspx


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

© 2017 Pasternack Enterprises All Rights Reserved

PE2014 CAD Drawing

2 Way SMA Wilkinson Power Divider From 2 GHz to 4 GHz Rated at 10 Watts



© 2017 Pasternack Enterprises All Rights Reserved

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP