

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*



powercom
complete power solution

ISO 9001

About Us | Products | Services | Sales | News | Contact Us

KIN-1500AP



GENERAL INFORMATION

Model Type	KING PRO
Model Name	KIN-1500AP
Power Rating	1500VA/900W

AC INPUT

AC Input Capacity on Battery	1500VA
AC Input Voltage	100V/110V/120 +/- 25%; 220V/230V/240V +/-25%
AC Input Frequency	50 or 60 Hz+/-10% (auto sensing)

OUTPUT

Output Voltage On Battery	100V/110/120V +/- 5%; 220V/230V/240V +/- 5%

AC OUTPUT

AC Output Voltage	Simulated sine ware
AC Output Frequency	50 or 60 Hz +/- 0.5%
AC Output Voltage Regulation	AVR automatically increase output voltage 15% above input voltage if -9% to -25% of nominal. AVR decrease output voltage 13% below input voltage if +9% to +25% of nominal
AC Output Transfer	2/4 milliseconds, including detection time

PROTECTION

Protection Spike	320 Joules, 2ms
Protection EMI/RFI	10dB at 0.15 MHz, 50 dB at 30 MHz
Protection Overload	UPS automatic shutdown if overload exceeds 110% nominal at 60 sec and 130% at 3 sec
Protection Unit	Fuse for overload & short circuit protection
Protection 10 BaseT	Network (UTP, RJ-45) compatible jacks
Protection Short Protection	UPS output cut off immediately or input fuse protection

BATTERY

Battery Type	Sealed, Maintenance-free lead acid, with 3 - 6 years typical lifetime
Battery Typical	4 hours (to 90% of full capacity)

Battery Protection	Automatic self-test & discharge protection, replace battery indicator

BACKUP TIME

Battery Backup Time Full Load	7 minutes
Battery Backup Time Half Load	15 minutes

PHYSICAL

Physical Weight kgs Tower	15.6
Physical Weight lbs Tower	34.3
Physical Dimension mm Tower	130x382x200
Physical Dimension inch Tower	5.1x15x7.9

INDICATOR

LED	LED

ALARM

Alarm Battery Backup	Slow beeping sound (about 0.47 Hz)
Alarm Battery Low	Rapid beeping sound (about 1.82Hz)
Alarm Overload	Continue beeping sound

INTERFACE

Interface RS-232	Bi-directional communication port

ENVIRONMENT

Environment Ambient	3,500 meters max. elevation, 0-95% humidity non-condensing, 0-40 deg c
Environment Audible	<40dBA (1 meter from surface)
ShowOrder	19

Copyright 2019 Powercom America Inc. 7550 Jurupa Avenue, Riverside, California 92504-1021 USA
Powered by GUS Networks, Inc.
All rights reserved.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP