



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

PYRIS 1 TGA

thermogravimetric analyzer

OPERATION

Instrument Design	The Pyris™ 1 TGA is a vertical design TGA that utilizes a high sensitivity balance and quick response furnace. The balance is located above the furnace and is thermally isolated from the furnace. A precision hangdown wire is suspended from the balance down into the furnace. At the end of the hangdown wire is the sample pan. The sample pan's position in the furnace is extremely reproducible.
Balance	<p>The balance is housed in a thermostatted chamber that isolates the balance from thermal effects. This design enhances sensitivity, accuracy, and weighing precision.</p> <p>Balance tare: Reproducible to $\pm 2 \mu\text{g}$</p> <p>Balance sensitivity: $0.1 \mu\text{g}$</p> <p>Balance accuracy: Better than 0.02%</p> <p>Balance weighing precision: 10 ppm (for a 100-mg sample)</p>
Hangdown Wires	Hangdown wires that suspend the sample pan from the balance are made of high temperature quartz, nichrome, or platinum.
Sample Pans	<p>The standard furnace sample pans are made of platinum or ceramic with a capacity of $60 \mu\text{L}$.</p> <p>The high temperature furnace uses sample pans made of platinum or ceramic with a capacity of $250 \mu\text{L}$.</p> <p>Additionally, disposable sample pan liners made of aluminum or stainless steel make cleanup easy.</p>
Standard Furnace	<p>The TGA standard furnace employs a microfurnace that has a low thermal mass for quick cooling and equilibration. The platinum heater element acts as a resistance temperature detector (PRTD) under tight feedback control. Accurate program temperature control reduces overshoot to 0.2°C at $100^\circ\text{C}/\text{minute}$, which results in stepwise analysis precision. The sample temperature is sensed by a chromel-alumel thermocouple.</p> <p>Standard furnace temperature range: Subambient to 1000°C</p> <p>Standard furnace scanning rates: $0.1^\circ\text{C}/\text{minute}$ to $200^\circ\text{C}/\text{minute}$</p> <p>Temperature precision: $\pm 2^\circ\text{C}$</p>
High Temperature Furnace	<p>An optional external furnace is constructed with a platinum/30% rhodium heating element. The sample temperature is sensed by a platinum/10% rhodium-platinum thermocouple.</p> <p>High temperature furnace temperature range: 50°C to 1500°C</p> <p>High temperature furnace scanning rates: $0.1^\circ\text{C}/\text{minute}$ to $50^\circ\text{C}/\text{minute}$</p> <p>Temperature precision: $\pm 5^\circ\text{C}$</p>
Sample Atmosphere	The sample atmosphere may be static or dynamic. Typical gases used are nitrogen, argon, helium, carbon dioxide, air, oxygen, or other inert or reactive gases. Analyses are done at normal pressure or at reduced pressures.
Control	The Pyris 1 TGA operates on Pyris Software for Windows®. This is the most comprehensive thermal analysis software available that offers high quality, reliability, and flexibility for operation, data analysis, and automation. Automation is controlled by Pyris Player, a standard feature of Pyris Software for Windows.

PERKIN ELMER*Look to us. And see more.*

Mass Spectrometer Coupling	It is possible to determine the reaction products from evolved gases during decomposition by using simultaneous gas analysis. Our TGA is compatible with most mass spectrometers.
FT-IR Coupling	Infrared spectroscopy is a proven gas analysis method especially for polymers. The Pyris 1 TGA can be coupled to most FT-IRs.
Autosampler	The Pyris 1 TGA Autosampler can run up to 20 samples unattended. It has the ability to be customized through Pyris Player to meet your analysis needs and increase productivity.
Gas Switching	Reduced furnace volume allows gas switching to be fast, thorough and efficient. The time to purge the sample area of ambient gases (remove 99% of oxygen) and replace the volume with an inert purge gas is less than 3 minutes. It takes 10 minutes to achieve a 99.99% oxygen-free environment.
Cooling	<p>The furnace is forced air cooled with an external fan and internal booster purge. All purge products are easily directed to the laboratory exhaust vent.</p> <p>Under normal operation the standard furnace cools down from 1000°C to 40°C in less than 15 minutes. The standard furnace temperature can be continuously monitored regardless of position.</p> <p>Under normal operation the high temperature furnace cools down from 1500°C to 100°C in less than 30 minutes.</p>
Bench Dimensions	<p>Height: 67 cm</p> <p>Width: 28 cm</p> <p>Depth: 60 cm</p>
Power Requirements	<p>100 to 240 volts</p> <p>50 or 60 Hz</p> <p>10 amps max</p>

Ordering Information:

PE Part Number	Description
N537-0742	Pyris 1 TGA with standard furnace
N537-0744	Pyris 1 TGA with standard furnace and autosampler
N537-0743	Pyris 1 TGA with high temperature furnace

For additional information about the Pyris 1 TGA, see Product Note D-5992.



Get MORE Connected.

The lines of advanced communication are OPEN. It's the Perkin-Elmer commitment to building relationships by sharing information and solving problems together. So no matter how far-reaching your needs, our worldwide support and service teams will take you where you need to go. Experience MORE of what PE can do for you. For the location nearest you, or a complete listing of our worldwide offices, visit us at www.perkin-elmer.com. E-MAIL us at info@perkin-elmer.com. Or, in the U.S., call 1-800-762-4000 or fax 1-203-762-4228.



PERKIN ELMER
Look to us. And see more.

U.S.A., The Perkin-Elmer Corporation, 761 Main Avenue, Norwalk, Connecticut 06859-0010 Tel: (800) 762-4000 or (203) 762-4000 Fax: (203) 762-4228
Perkin-Elmer is a registered trademark and Pyris is a trademark of The Perkin-Elmer Corporation.
Windows is a registered trademark of Microsoft Corporation.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com