ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Pickering 40-665-001* at our website: ***Click HERE***

40-660/665
Power Multiplexer Module

- 10-Channel Power Multiplexer, 1 or 2-Pole
- High Density 18-Channel Power Multiplexer, 1-Pole
- 10A Current Rating (1-Pole Versions)
  8A Current Rating (2-Pole Version)
- Hot Switch to 125VDC/250VAC, Cold Switch to 400VDC/250VAC
- VISA, IVI & Kernel Drivers Supplied for Windows XP/Vista/7/8
- Supported by PXI or LXI Chassis
- 3 Year Warranty



Pickering Interfaces have a range of power switching PXI modules, available in relay, matrix or multiplexer configurations.

Model 40-660 is a 10-Channel Power Multiplexer, suitable for switching inductive/capacitive loads up to 10A at 250VAC. It is available in 1-pole (10A) or 2-pole (8A) versions.

Model 40-665 is a higher density 18-Channel Power Multiplexer with the same specification as the 1-pole 40-660.


Power Multiplexer Modules are intended for switching heavy AC or DC loads or for slaving up to large external relays, contactors and solenoids.

The 40-660/665 Power Multiplexer Module is suitable for applications requiring switching of either AC mains or DC voltage.


Mating power connectors are supplied with all versions.

Power Relay Type


The 40-660/665 is fitted with electro-mechanical power relays, gold-flash over silver alloy. A **Spare Relay is** built onto the circuit board to facilitate easy maintenance with minimum downtime.



10-Channel 1-Pole Power Multiplexer 40-660-001



10-Channel 2-Pole Power Multiplexer 40-660-002




18-Channel High Density Power Multiplexer 40-665-001

ISSUE 7.0 MAY 2013


pickering

pickeringtest.com


Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com




40-660/665 Current/Voltage Curve - 1-Pole



40-660/665 Current/Operating Life Curve - 1-Pole



40-660-002 Current/Voltage Curve - 2-Pole



40-660-002 Current/Operating Life Curve - 2-Pole

Switching Specification

Contact Type:	Gold flash over silver alloy
Cold Switching Capacity	
Maximum Current:	10A (1-pole) 8A (2-pole)
Maximum Voltage:	400VDC/250VAC
Hot Switching Capacity	
Maximum Current:	10A (1-pole) 8A (2-pole)
Maximum Voltage:	125VDC/250VAC
Maximum Power:*	300W/2500VA (1-pole) 240W/2000VA (2-pole)
Min. Switching Capacity:	10mA, 5VDC
Initial Path Resistance, On:	<50mΩ
Path Resistance, Off:	>10^9Ω
Bandwidth:	>20MHz
Operate Time:	10ms typical
Expected Life (operations) - resistive load	
Mechanical Life:	>$5x10^7$
At Max. Switch Capacity:	>$1x10^5$

* For variation of maximum hot switching capacity of voltage with current refer to plot.

Power Requirements

+3.3V	+5V	+12V	-12V
0	360mA (typ 280mA)	0	0

Width and Dimensions

Single slot 3U PXI (CompactPCI card).
3D models for all versions in a variety of popular file formats are available on request.

Connectors

PXI bus via 32-bit P1/J1 backplane connector.
Signals via a front panel 20-way GMCT (MS-M) type male connector (40-660-001/665-001) or 2 x 20-way GMCT (MS-M) type male connectors (40-660-002).

Product Order Codes

10-Channel Power MUX, 1-Pole	**40-660-001**
10-Channel Power MUX, 2-Pole	**40-660-002**
18-Channel Power MUX, 1-Pole	**40-665-001**

Support Products

Spare Relay Kits

Kits of replacement relays are available for the majority of Pickering's PXI switching modules, simplifying servicing and reducing down-time. The relay kits for the 40-660 range are as follows:

91-100-071 kit for 40-660-001
91-100-052 kit for 40-660-002
91-100-071 kit for 40-665-001

For further assistance, please contact your local Pickering sales office.

Mating Connectors & Cabling

For connection accessories for the 40-660/665 modules please refer to the **90-014D** 20-way GMCT (MS-M) Connector Accessories data sheet where a complete list and documentation can be found for accessories, or refer to the Connection Solutions catalog.

pickering

pickeringtest.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Programming

Pickering provide kernel, IVI and VISA (NI and Agilent) drivers which are compatible with 32/64-bit versions of Windows including XP, Vista, 7 and 8 operating systems. The VISA driver is also compatible with Real-Time Operating Systems such as LabVIEW RT. For other RTOS support contact Pickering.

These drivers may be used with a variety of programming environments and applications including:

- **National Instruments** products (LabVIEW, LabWindows/CVI, Switch Executive, MAX, TestStand, etc.)
- **Microsoft Visual Studio** products (Visual Basic, Visual C+)
- **Agilent** VEE
- **Mathworks** Matlab
- **Geotest** ATE Easy
- **MTQ Testsolutions** Tecap

Drivers for popular Linux distributions are available, other environments are also supported, please contact Pickering with specific enquiries.

Operating/Storage Conditions

Operating Conditions

Operating Temperature:	0°C to +55°C
Humidity:	Up to 90% non-condensing
Altitude:	5000m

Storage and Transport Conditions

Storage Temperature:	-20°C to +75°C
Humidity:	Up to 90% non-condensing
Altitude:	15000m

PXI & CompactPCI Compliance

The module is compliant with the PXI Specification 2.2. Local Bus, Trigger Bus and Star Trigger are not implemented.

Uses 33MHz 32-bit backplane interface.

Safety & CE Compliance

All modules are fully CE compliant and meet applicable EU directives: Low-voltage safety EN61010-1:2001, EMC Immunity EN61000-6-1:2001, Emissions EN55011:1998.

PXI & LXI Chassis Compatibility

Compatible with all chassis conforming to the 3U PXI and 3U cPCI specification. Compatible with Legacy and Hybrid peripheral slots in a 3U PXI Express chassis.

Compatible with Pickering Interfaces LXI Modular Switching chassis. For information on driving your switching solution in an LXI environment refer to the LXI Product Guide.



Latest Details

Please refer to our Web Site for Latest Product Details.


www.pickeringtest.com



Please refer to the Pickering Interfaces "**Connection Solutions**" catalog for the full list of connector/cabling options, including drawings, photos and specifications. This is available in either print or as a download. Alternatively our web site has dynamically linked connector/cabling options, including pricing, for all Pickering PXI modules.



"**The Big PXI Catalog**" gives full details of Pickering's entire range of PXI switch modules, instrument modules and support products.
At over 500 pages, the Big PXI Catalog is available on request or can be downloaded from the Pickering website.



Ever wondered what PXI is all about?

Pickering Interfaces' "**PXImate**" explains the basics of PXI and provides useful data for engineers working on switch based test systems.

The PXImate is available free on request from the Pickering website.



The "**PXI Module Map**" - a simple fold-out selection guide to all Pickering's 600+ PXI Modules.

pickering

pickeringtest.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP