ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Pickering 40-860-222* at our website: ***Click HERE***

40-860
MEMS Optical Insert/Bypass Switch



- Single, Dual, Triple or Quad 2x2 Insert/Bypass Fiber Optic Switch
- High Density 1 or 2 Slot Width Modules
- FC/APC, FC/PC or SC/PC Connectors
- Small Form Factor Connectors LC or MU (mini SC)
- 1240 to 1640nm Single Mode
- 700 to 1700nm Multi-Mode
- Return Loss >55dB
- Long Operating Life >10^9 Operations with High Repeatability ± 0.01dB and Good Temperature Stability
- Crosstalk -60dB Typical
- 1ms Typical Switching Time
- VISA, IVI & Kernel Drivers Supplied for Windows
- Supported by PXI or LXI Chassis
- 3 Year Warranty

Pickering PXI Fiber Optic MEMS Switching modules are available in many high density formats with a choice of 5 different connector styles to suit most applications: FC/APC (for optimal performance), FC/PC and SC/PC for general applications and LC and MU for high density applications.

The fiber optic multiplexers connect the optical channel by redirecting the optical signal into a selected output fiber. This is achieved using Micro-Mechanical Mirrors driven by a highly precise mechanism and activated via an electrical control signal.

The range of MEMS (Micro-Electro-Mechanical-Systems) based optical switches is:

40-860-X12 – Single 2x2 Insert/Bypass Switch

40-860-X22 – Dual 2x2 Insert/Bypass Switch


40-860-X32 – Triple 2x2 Insert/Bypass Switch

40-860-X32 – Quad 2x2 Insert/Bypass Switch

Pickering will construct custom optical systems to customers precise requirements. We have a large range of electrical switching modules which can form a complete PXI based telecom switching solution.

MEMS technology offers many advantages over traditional Optical Prism Technology as used in module types 40-810/815/820. MEMS offer similar optical performance but with lower price, higher packing density, faster operate time and much longer operating life.

Block Diagram of 2x2 Insert/ Bypass Fiber Optic Switch (both Set and Reset states are shown)



Key Features

- Very fast operate time <1ms
- Very long life >10^9 operations
- Return loss greater than 55dB
- High repeatability over a broad range of environmental conditions
- High density

Applications

- Optical signal routing
- Fiber network configuration
- Fiber Optic Component Test

40-860-022 Fiber Optic Dual 2x2 Matrix



ISSUE 5.1 MAY 2017

General Specification (SM Versions)

Fiber Switch Type: **Internal Fiber Type:**	**MEMS** **SM 9/125**
Wavelength: Insertion loss (2x2): Return loss (APC version): Return loss (other versions): Polarization dependent loss (PDL): Repeatability: Crosstalk: Optical Input Power:	1240 to 1640nm 0.8dB Typ 60dB Min 55dB Min 0.05dB Max ±0.01dB Max -60dB Max 300mW Max
Thermal Stability: (-10 to 75°C insertion loss variation)	0.2dB Max
Expected Life:	>>10^9 operations
Maximum Switching Time: Cycle Rate:	1ms 500/sec
Module Weight:	<0.8Kg typ.

Additional Specification (MM Versions)

Fiber Switch Type: **Internal Fiber Type:**	**MEMS** **MM 62.5/125**
Wavelength: Insertion loss (2x2): Return loss (other versions): Polarization dependent loss (PDL):	700 to 1700nm 0.8dB Typ 55dB Min 0.05dB Max

Power Requirements

+3.3V	+5V	+12V	-12V
0	300mA (typ 220mA)	0	0

Mechanical Characteristics

All modules are either 1 or 2 slot as indicated in model list.

Module weight: 420g (40-860-222)

3D models for all versions in a variety of popular file formats are available on request.

Connectors

PXI bus via 32-bit P1/J1 backplane connector.
Signals via front panel fiber optic connectors (choice of FC/APC, FC/PC,SC/PC, MU or LC types).

Other Fiber Connector Styles

Pickering can manufacture Fiber Optic Switch modules with other connector styles, please contact sales office for further information.

Product Order Codes

2 x 2 Insert/Bypass Switch Versions	
FC/APC, 1240 to 1640nm, Single-Mode	
Single 2x2 Insert/Bypass Switch, 1 slot	**40-860-012**
Dual 2x2 Insert/Bypass Switch, 2 slot	**40-860-022**
FC/PC, 1240 to 1640nm, Single-Mode	
Single 2x2 Insert/Bypass Switch, 1 slot	**40-860-112**
Dual 2x2 Insert/Bypass Switch, 2 slot	**40-860-122**
SC/PC, 1240 to 1640nm, Single-Mode	
Single 2x2 Insert/Bypass Switch, 2 slot	**40-860-212**
Dual 2x2 Insert/Bypass Switch, 2 slot	**40-860-222**
MU (mini SC), 1240 to 1640nm, Single-Mode	
Single 2x2 Insert/Bypass Switch, 1 slot	**40-860-312**
Dual 2x2 Insert/Bypass Switch, 1 slot	**40-860-322**
Triple 2x2 Insert/Bypass Switch, 2 slot	**40-860-332**
Quad 2x2 Insert/Bypass Switch, 2 slot	**40-860-342**
LC, 1240 to 1640nm, Single-Mode	
Single 2x2 Insert/Bypass Switch, 1 slot	**40-860-412**
Dual 2x2 Insert/Bypass Switch, 1 slot	**40-860-422**
Triple 2x2 Insert/Bypass Switch, 2 slot	**40-860-432**
Quad 2x2 Insert/Bypass Switch, 2 slot	**40-860-442**
SC, 700 to 1700nm, Multi-Mode	
Single 2x2 Insert/Bypass Switch, 1 slot	**40-860-212-M**
Dual 2x2 Insert/Bypass Switch, 2 slot	**40-860-222-M**
ST, 700 to 1700nm, Multi-Mode	
Single 2x2 Insert/Bypass Switch, 1 slot	**40-860-512-M**
Dual 2x2 Insert/Bypass Switch, 2 slot	**40-860-522-M**



Pickering Interfaces Will Configure PXI Optical Switching Systems To Customers Exact Requirements Including Custom Cabling

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Programming

Pickering provide kernel, IVI and VISA (NI & Keysight) drivers which are compatible with all Microsoft supported versions of Windows and popular older versions. For a list of all supporting operating systems, please see: www.pickeringtest.com/os
The VISA driver is also compatible with Real-Time Operating Systems such as LabVIEW RT. For other RTOS support contact Pickering. These drivers may be used with a variety of programming environments and applications including:

- **Pickering Interfaces Switch Path Manager**
- **MTQ Testsolutions** Tecap Test & Measurement Suite
- **National Instruments** products (LabVIEW, LabWindows/CVI, Switch Executive, MAX, TestStand, VeriStand, etc.)
- **Microsoft Visual Studio** products (Visual Basic, Visual C+)
- **Keysight** VEE • **Mathworks** Matlab • **Marvin** ATEasy

Drivers for popular Linux distributions are available, other environments are also supported, please contact Pickering with specific enquiries.

Operating/Storage Conditions

Operating Conditions

Operating Temperature:	0°C to +55°C
Humidity:	Up to 90% non-condensing
Altitude:	5000m

Storage and Transport Conditions

Storage Temperature:	-20°C to +75°C
Humidity:	Up to 90% non-condensing
Altitude:	15000m

PXI & CompactPCI Compliance

The module is compliant with the PXI Specification 2.2. Local Bus, Trigger Bus and Star Trigger are not implemented.
Uses a 33MHz 32-bit backplane interface.

Safety & CE Compliance

All modules are fully CE compliant and meet applicable EU directives: Low-voltage safety EN61010-1:2001, EMC Immunity EN61000-6-1:2001, Emissions EN55011:1998.

PXI & LXI Chassis Compatibility

Compatible with all chassis conforming to the 3U PXI and 3U cPCI specification. Compatible with Legacy and Hybrid peripheral slots in a 3U PXI Express chassis.
Compatible with Pickering Interfaces LXI Modular Chassis. For information on driving your switching solution in an LXI environment refer to the LXI Product Guide.



Latest Details


Please refer to our Web Site for Latest Product Details.
www.pickeringtest.com




Please refer to the 200 page Pickering Interfaces "**Connection Solutions**" catalog for the full list of connector/cabling options, including drawings, photos and specifications. Available in either print or as a download.
Alternatively our web site has dynamically linked connector/cabling options, including pricing, for all Pickering PXI modules.




"**The Big PXI Catalog**" gives full details of Pickering's entire range of PXI switch modules, instrument modules and support products.
At over 500 pages, the Big PXI Catalog is available on request or can be downloaded from the Pickering website.



Ever wondered what PXI is all about?
Pickering Interfaces' "**PXImate**" explains the basics of PXI and provides useful data for engineers working on switch based test systems.
The PXImate is available free on request from the Pickering website.



The "**Cables & Connectors Map**" - outlines the cable and connector options available for all PXI Modules.



The "**PXI Module Map**" - a simple fold-out selection guide to all Pickering's 1000+ PXI Modules.

pickering

pickeringtest.com

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

© Copyright (2017) Pickering Interfaces. All Rights Reserved
Pickering Interfaces maintains a commitment to continuous product development, consequently we reserve the right to vary from the description given in this data sheet.

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP