

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PXI Instrumentation

41-100 RF Signal Analyzer (Frequancy Counter/Peak Power Meter)

41-100-001	RF Signal Analyzer, 100MHz to 3GHz, 50 Ohm	1 Slot
41-110-001	RF Signal Analyzer, 10kHz to 500MHz, 50 Ohm	1 Slot

- Frequency counter, time interval analyzer & peak-power meter.
- Continuous Wave or Pulsed Modulation
- -34dBm to +16 dBm Signal Range
- On-board Digital Signal Processor
- 32 Kbytes Memory for Multiple RF Pulse acquisition
- Choice of SMB or SMA Connectors

41-100
3GHz RF Signal
Analyzer





Typical Display From The 41-100
RF Signal Analyzer Soft Front Panel

41-180 3GHz Programmable Step Attenuator – Q1 2003 Release

41-180-011	Single Attenuator, 63 dB range, 1 dB Step, 0MHz to 3GHz. 50 Ohm SMB Connector	1 Slot
41-180-012	Dual Attenuator, 63 dB range, 1 dB Step, 0MHz to 3GHz. 50 Ohm SMB Connector	1 Slot
41-180-021	Single Attenuator, 63 dB range, 1 dB Step, 0MHz to 3GHz. 50 Ohm SMA Connector	1 Slot
41-180-022	Dual Attenuator, 63 dB range, 1 dB Step, 0MHz to 3GHz. 50 Ohm SMA Connector	1 Slot

- Choice of Connectors SMA (preferred for best performance) or SMB
- 1W Power Rating

41-200 6 1/2 Digit DMM


41-200-040	Basic 6 1/2 Digit DMM	1 Slot
41-200-042	Mid-Range 6 1/2 Digit DMM	1 Slot
41-200-044	High-End full featured 6 1/2 Digit DMM (adds frequency, timing, capacitance, Peak-to-Peak AC and temperature, event counting, external triggering and programmable level trigger.	1 Slot

- Flexible, full featured auto ranging DMM
- DC & AC Volts & Current
- 2-Wire & 4-Wire Ohms
- True AC RMS measurements, 10Hz to 100kHz
- Measure 1 µV to 330 V • Self-calibrating
- Up to 1000 readings per second
- 330V isolation barrier



Typical LabView Panel Display
From The 41-200, 6 $^{1}/_{2}$ Digi DMM

41-200-040
6$^{1}/_{2}$ Digit DMM



Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP