

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions


Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Digital Input

PSS DI, PSS1 DI



Digital input circuits with integral software algorithms and redundant design for safety-related functions.

Features

- Failsafe modules have type-approval
- Whole system is approved by BG and TÜV
- 32 digital inputs
- Galvanic isolation for a high level of noise suppression
- Integral protection circuits for trouble-free installation

Approvals

	PSS DI	PSS1 DI
BG	●	●
TÜV PRODUCT SERVICE	●	●
CASTEC	●	
UL LISTED	●	●
AIBV	●	

Technical Details	PSS DI	PSS1 DI
Function	Digital input	
Application Range	Failsafe applications conforming to EN 954-1, 11/94, DIN V 19 250, 01/89, DIN VDE 0116	
Electrical Data		
Supply Voltage	24 VDC	24 VDC
Tolerance Range	20 ... 30 VDC including residual ripple	
Galvanic Isolation	Yes (optocoupler)	Yes (optocoupler)
Connection Type	AWG 12 screw connectors	
Inputs		
Number	32	32
Potential Isolation	Yes (optocoupler)	Yes (optocoupler)
Signal Level at “0”	-3 ... +5 VDC	-3 ... +5 VDC
Signal Level at “1”	+15 ... +30 VDC	+15 ... +30 VDC
Input Current	Typ. 6 mA	Typ. 6 mA
Input Delay	E0 ... E15: 1 ms, E16 ... E31: 3 ms	
Status Indicator	LED	LED
Mechanical Data		
Size (H x W x D)	257 x 41 x 220 mm	265 x 41 x 218 mm
Space Requirement	1 slot	1 slot
Weight	840 g	450 g
Environmental Data		
Protection Type	IP 20, installed on module rack	
Ambient Temperature	0 ... +60 °C	0 ... +60 °C
Storage Temperature	-25 ... +70 °C	-25 ... +70 °C
Climatic Suitability	IEC 68-2-30, IEC 68-2-14	
Condensation	Not permitted	
Vibration to IEC 68-2-6	Frequency range: 10 ... 100 Hz Amplitude: 0.1 mm, max. 5 g	

Order References		
System	PSS 3000	PSS 3100
Description	PSS DI	PSS1 DI
Order Number	301 100	302 100

Description

The PSS 3000/PSS 3100 can process the status of inputs in bits, bytes or words. Each input has space available for inscription and a status LED.
The inputs are suitable for connecting:

- single-channel safety-related input devices, with or without test pulse
- dual-channel safety-related input devices, with or without test pulses

The PSS DIO T / PSS1 DIO T modules can be used to provide the test pulses. Input devices are connected via plug-in screw connectors. The module’s address is established by its slot number on the module rack.

For press

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP