ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *PMC DCX-VM300* at our website: *Click HERE*

DCX-VM 300 Series Specifications

Form Factor & Processor

- 6U double-width VME-bus card
- Modular multi-processor architecture
- Motherboard: Intel 32-bit CPU with 64-bit floating point co-processor
- Axis Modules: 40 MHz Texas Instruments DSP & FPGA on each module

Communication

- ASCII communication
- High speed binary communication via dual-ported RAM

Programming

- Programmable with easy-to-use motion command language
- Programmable in user units (mm, microns, ft./sec...etc.)
- Contact PMC for Operating System support

Motion Capabilities

- 1 to 6 control axes per card
- AC/DC servo and/or stepper motor control
- Point-to-point positioning
- Multi-axis synchronized & coordinated motion
- Trapezoidal, parabolic and S-curve velocity profiles
- Independent acceleration & deceleration
- Multi-axis linear & circular

Stepper Control Signals

- Pulse/direction or CW/CCW stepper control (DCX-MC360 Module)
- 5 MHz maximum step (pulse) rate each axis (up to 16 axes)
- Full step, half-step and microstepping control, full and half current
- 50% pulse train duty-cycle at all pulse rates
- Open or closed-loop stepper control

Position Feedback

- Quadrature incremental encoder with index
- 10 MHz encoder count rate for each axis (up to 16 axes)
- Single-ended or differential inputs (A+, A-, B+, B-, I+, I-)
- Digital noise filtering
- Auxiliary encoders
- 32-bit position resolution

Dedicated I/O (each axis)

- Axis inputs: Opto-isolated home, ± limits, amp fault
- Axis outputs: Opto-isolated amp enable, step direction
- Position capture input (less than 0.5 microsecond latency)
- Position compare output (less than 0.5 microsecond latency, 10 microsecond opto-isolator delay)

General Purpose I/O

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

interpolation
- High-resolution electronic gearing
- Position, velocity and gain control modes
- Backlash compensation
- Target, velocity, acceleration/deceleration & PID parameters can be changed on-the-fly
- Custom motion capabilities available upon request

Memory

- 64K user program memory
- 256 general purpose user registers (variables)

Dynamic Range

- Position: 64 bit floating point
- Velocity and acceleration: 64 bit floating point

Servo Control Signals

- ±10V command signal with 16-bit DAC resolution (DCX-MC300 Module)
- Pulse & direction signals for pulse-controlled servo drives: 5MHz maximum pulse rate each axis
- Sinusoidal output for commutation of AC servo motors (DCX-MC320 Module)

Servo Filter

- Proportional/Integral/Derivative with acceleration, deceleration & velocity feed forward (PID-FF)
- Custom notch filtering
- Selectable servo update rate 2, 4, & 8 KHz (up to 6 axes)

- 16 digital I/O on motherboard, individually software configurable as input/output
- Up to 128 additional configurable digital I/O via DCX-MC400 plug-in modules
- Up to 64 additional analog I/O, 12-bit resolution, via DCX-MC500 plug-in modules

Other Features

- Programmable in user units
- On-board memory for user program storage
- On-board watchdog timer with external or PC-bus reset
- Custom features or performance available upon request

Connections

- 26 pin dual-row IDC ribbon header for each axis module and I/O module
- Dual-row IDC ribbon header for on-board general-purpose digital I/O
- VME P2 connector can also be used for I/O connections
- External interconnection boards available with individually labeled screw terminals

Environmental & Mechanical

- Operating temperature: 0-55 ºC (32-131 ºF) R.H. non-condensing
- Size: 314mm x 107mm (12.3" x 4.2")

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP