

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PNEUMADYNE

Specification Sheet

4-Way Valves with 10-32 (F) Ports

Performance Data

Temperature Range	Media
-20° to 160° F	Compatible w/ seals

Product Number	Operating Pressure	Series	Cv	Flow (scfm) 50 psi	Flow (scfm) 125 psi	Fill sec/in3 0-90 psi	Exhaust sec/in3 100-10 psi	Actuation Force 50 psi	Actuation Force 125 psi
A4C-100-SR	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	3 lbs	3 lbs
A4N-100-SR	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	3 lbs	3 lbs
AP45-100-SR	0 to 125 psi	"45"	.23	7.8	17.3	.02	.02	5 lbs	8 lbs
AM45-100-SR	0 to 125 psi	"45"	.23	7.8	17.3	.02	.02	5 lbs	8 lbs
A4C-100-DP	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	16 oz	3 lbs
A4N-100-DP	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	16 oz	3 lbs
AP45-100-DP	0 to 125 psi	"45"	.23	7.8	17.3	.02	.02	16 oz	3 lbs
H4C-100-DT	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	16 oz	16 oz
H4N-100-DT	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	16 oz	16 oz
HP45--100-DT	0 to 125 psi	"45"	.23	7.8	17.3	.02	.02	16 oz	16 oz
HM45-100-DT	0 to 125 psi	"45"	.23	7.8	17.3	.02	.02	13 oz	13 oz
F4C-100-SR	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	16 oz	16 oz
F4N-100-SR	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	16 oz	16 oz
FP45-100-SR	0 to 125 psi	"45"	.23	7.8	17.3	.02	.02	16 oz	16 oz
A4C-100-PK	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	-	-
A4N-100-PK	0 to 125 psi	"4"	.13	5.1	10.9	.03	.05	-	-
S20U42-AP	0 to 125 psi	"20"	.15	5.8	12.1	.02	.05	15 psi	
S20M42-AP	0 to 125 psi	"20"	.15	5.8	12.1	.02	.05	15 psi	
S20U42-DP	0 to 125 psi	"20"	.15	5.8	12.1	.02	.05	15 psi	
S20M42-DT	0 to 125 psi	"20"	.15	5.8	12.1	.02	.05	15 psi	

When design makes data critical- contact factory for confirmation. All published information is based on usual manufacturing standards and product applications and is for general reference purposes. Supplied information is in no way a representation of a warranty for product.

Materials

"4" Series: *4C
Anodized Aluminum Body, Buna-N Seals, Brass Spool, Stainless Steel Stem and Stainless Steel Spring
"4" Series: *4N
Electroless Nickel Plated Aluminum Body, Buna-N Seals, Brass Spool, Stainless Steel Stem and Stainless Steel Spring

"45" Series
Anodized Aluminum Body, Buna-N Seals, Brass Stem and Stainless Steel Spring

"20" Series
Solenoid: Glass Filled Nylon Body, Buna-N Seals, Stainless Steel Springs, Copper Wire Coil
Valve Body: Anodized Aluminum Body, Buna-N Seals, Stainless Steel Spring, PTFE Aluminum Spool

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP