

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

HIGH DENSITY RECTANGULAR

Rectangular Connectors





Positronic®

an **Amphenol** company



















Qualified to:

MIL-C-28748/13 & MIL-C-28748/14


MIL-DTL-28748/7 & MIL-DTL-28748/8

SAE AS39029/34-440 & SAE AS39029/35-441









C-008 Rev. F2

Positronic Provides Complete Capability

Experience

- Founded in **1966**
- **Involvement** in the development of international connector specifications through EIA®, IEC and ISO as well as PICMG®.
- Introduction of new and **unique connector products** to the electronics industry.
- Patent holder for many **unique connector features and manufacturing techniques.**
- **Vertically integrated** manufacturing – raw materials to finished connectors.



Technology

- **Expertise** with solid machined contacts provides a variety of high reliability connectors including high current density power connectors.
- Quality Assurance lab is **capable of testing** to IEC, EIA, UL, CUL, military and customer-specified requirements.
- **In-house design and development** of connectors based on market need or individual customer requirements.
- **Internal manufacturing capabilities** include automatic precision contact machining, injection molding, stamping, plating operations and connector assembly.
- **Manufacturing locations** in southwest Missouri, U.S.A. (headquarters); France, China, Singapore, and India.



Support

- **Quality Systems:** Select locations qualified to ISO 9001, ISO 14001, AS9100, MIL-STD-790 and customer "dock to stock" programs. Applicable products qualified to MIL-DTL-24308, SAE AS39029, DSCC 85039, MIL-DTL-28748, Space D32, GSFC S-311-P-4 and GSFC S-311-P-10.
- Compliance to a variety of international and customer specific **environmental requirements.**
- Large **in-house inventory** of finished connectors. Customer specific **stocking programs.**
- Factory direct **technical sales support** in major cities worldwide.
- **One-on-one customer support** from worldwide factory locations.
- World class **web site**.
- **Value-added solutions** and willingness to **develop custom products** with reasonable price and delivery.



Manufacturing Facilities

Springfield, MO 

Auch, France 

Singapore 

Products described within this catalog may be protected by one or more of the following US patents:

#4,900,261* #5,255,580 #5,329,697 #6,260,268
#6,835,079 #7,115,002 #8,944,697 #9,304,263

* Patented in Canada, 1992 Other Patents Pending

Positronic Industries' **FEDERAL SUPPLY CODE** (Cage Code) FOR MANUFACTURERS is **28198**

Unless otherwise specified, dimensional tolerances are:


1) ±0.001 inches [0.03 mm] for male contact mating diameters.
2) ±0.003 inches [0.08 mm] for contact termination diameters.
3) ±0.005 inches [0.13 mm] for all other diameters.
4) ±0.015 inches [0.38 mm] for all other dimensions.

POSITRONIC® IS AN ITAR REGISTERED COMPANY

Information in this catalog is proprietary to Positronic and its subsidiaries. Positronic believes the data contained herein to be reliable. Since the technical information is given free of charge, the user employs such information at his own discretion and risk. Positronic assumes no responsibility for results obtained or damages incurred from use of such information in whole or in part.


The following trademarks are owned by Positronic Industries, Inc.: Positronic Industries, Inc.®, Positronic®, Connector Excellence®, P+ logo®, PosiBand®, PosiShop®, Optik-D™, and The Science of Certainty®. The color blue as it appears on various connectors is a trademark of Positronic Industries, Inc., Registered in U.S. Patent and Trademark Office.

CONNECTOR DESCRIPTIONS




SGMC SERIES

High density rectangular connectors with size 22 **removable contacts.** Industrial performance or MIL-C-28748/13, MIL-C-28748/14, SAE AS39029/34 and SAE AS39029/35. Eleven connector variants, 4 through 104 contacts. Crimp, solder cup, straight solder and compliant press-in printed board mount terminations. Thermocouple contact options available.



SGM SERIES

High density rectangular connectors with size 22 **straight printed circuit boart mount / solder cup contacts.** Industrial performance or MIL-DTL-28748/7 and MIL-DTL-28748/8. Twelve connector variants, 4 through 50 contacts. Solder cup, wrap post, straight solder and compliant press-in printed board mount terminations. Thermocouple contact options available.



SMPL SERIES

High density rectangular connectors with size 22 **right angle printed circuit board mount contacts.** Industrial performance or conformance to MIL-DTL-28748. Twelve connector variants, 4 through 50 contacts. Right angle (90º) solder printed board mount terminations. Thermocouple contact options available.

Visit our website for the latest catalog updates and supplements at https://www.connectpositronic.com/catalogs/

RoHS Compliant options available!

Positronic
connectpositronic.com

TABLE OF CONTENTS

High Density Rectangular

GENERAL INFORMATION

What makes Positronic's new "PosiBand®" contact interface a significant improvement? 1
The PosiBand® contact system has many advantages over the legacy split tine design 2
Temperature Rise Curves 2
Mating Dimensions and Exploded View of Typical Mated Connector Assemblies 3
Connector Component Description and Terminology 4

SGMC SERIES

Technical Characteristics 5-6
Connector Insert Dimensions 7-8
Contact Hole Dimensions and Printed Board Hole Pattern for Contact Variants 75 and 104 8
Removable Contact Ordering Assistance Chart 9
Ordering Information 10

REMOVABLE CONTACTS

Technical Characteristics 11
Size 22 Removable Crimp Contact 11
Size 22 Removable Military Crimp Contact 12
Size 22 Removable Thermocouple Crimp Contact 12
Size 22 Removable Solder Cup Contact 13
Size 22 Removable Straight Solder Printed Board Mount Contact 13
Size 22 Removable Compliant Press-In Printed Board Mount Contact 14
Mounting Hardware for Printed Board Mount Connectors 14

SGM SERIES

Technical Characteristics 15-16
Connector Insert Dimensions for SGM and SMPL Series 17-18
Straight Solder Printed Board Mount Termination 18
Solder Cup Termination 19
Wrap Post Termination 20
Compliant Press-In Printed Board Mount Termination 20
Contact Hole Dimensions and Printed Board Hole Pattern for SGM and SGMC Series 21
Ordering Information 22

SMPL SERIES

Technical Characteristics 23-24
Right Angle (90°) Printed Board Mount Termination 25
Mounting Bracket 25

continued on next page. . . .

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

S M P L S E R I E S

continued from previous page. . . .

Alignment Bar Dimensions 25
Right Angle (90º) Printed Board Hole Pattern 26
Ordering Information 27

U N I Q U E F E A T U R E S

Introduction 28
Low Profile Space Saving High Reliability Mezzanine Connector 28
Customer Specified Contact Termination Length 29
Flush Panel Connector Mounting Brackets 29
Polarization & Coding (Keying) Options 30

A C C E S S O R I E S

Panel Cut-Out Dimensions..... 30
Polarizing Guides 31
Fixed and Rotating Jackscrew Systems 31
Polarizing Guide and Jackscrew Thread Availability Chart 31
Polarizing Guide 32
Jackscrew System 33
Connector Housing (Shells) 34
Aluminum Backshell..... 35
Aluminum Backshell with Jackscrew System 35
Full Access Aluminum Backshell with Jackscrew System 36
Quick Disconnect Locking Device 36

A P P L I C A T I O N T O O L S

Introduction 37
Contact Application Tools Cross Reference List 38
Compliant Press-In Connector Installation Tools 39

P C B P R I N T E D H O L E S I Z E

Suggested Printed Board Hole Sizes for Compliant Press-In Connectors 40

S P E C I A L O P T I O N S

Modifications (MOS) 41


M I L Q U A L I F I E D P R O D U C T S

Positronic offers a wide variety of QPL connector products 42

What Makes Positronic's "PosiBand®" Contact Interface a Significant Improvement?


High reliability connectors utilize female **closed entry contacts** that provide an unbroken ring of solid material at the face of the contact. The closed entry feature is **crucial in preventing damage** to female contacts used in harsh environments, repeated mating cycles, blind mate applications and applications requiring highest reliability.

FIGURE 1



The most common **closed entry design** utilized by connector manufacturers is a split tine and sleeve concept. **See figure 1.** With this design, both the mechanical forces and electrical interface are provided only at the tip of the female contact.

FIGURE 2



Positronic's **PosiBand technology** takes a unique approach for closed entry female contacts. **PosiBand** contacts utilize a two-piece contact design. **See figure 2.** Each piece serves a separate function, providing a more mechanically robust contact and more consistent electrical performance.

The main body of the **PosiBand** contact provides a true closed entry opening to enhance robustness. The **PosiBand** spring clip provides normal force on the male contact. Consistent electrical performance is supported through a larger area of contact interface between the male and female contact along the entire "floor" of the contact body. **PosiBand** contacts are QPL listed under **SAE AS39029** and **MIL-DLT-24308** specifications. **PosiBand** is also qualified under **GSFC S-311-P4/08 Rev C** and **GSFC S-311-P4/10 Rev C** to the higher 40 gram contact separation test requirement.

continued on next page . . .

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

continued from previous page . . .


The PosiBand® contact system has many advantages over the legacy split tine design.


- **PosiBand** is more robust than split tine contact, which can be pried open in harsh environments, resulting in reduced normal force and degradation of electrical performance.
- **PosiBand** has greater surface area at the male and female contact interface, resulting in more consistent electrical performance.
- **PosiBand** has lower average insertion forces, resulting in greater ease in mating, especially in larger high density connectors. The average lower insertion force is accomplished while meeting or exceeding performance requirements.
- The **PosiBand's** contact body does not require annealing of the crimp barrels, as does the split tine design. This eliminates concern of unintentionally heat-treating the mating end of the contact, which can cause electrical failure.
- **PosiBand** is qualified under **SAE AS39029** and **MIL-DTL-24308** specifications. **PosiBand** is also qualified under **GSFC S-311-P4/08 Rev C** and **GSFC S-311-P4/10 Rev C** to the higher 40 gram contact separation test requirement.
- **PosiBand** is protected by US Patent 7,115,002.

For more details about the ***advantages of the PosiBand®*** system, please view the detailed white paper at ***www.connectpositronic.com/posiband/*** or visit our website at ***www.connectpositronic.com.***

TEMPERATURE RISE CURVES

Test conducted in accordance with UL1977.






Size 22 PosiBand Contacts

Initial Contact Resistance: 0.004 ohms, maximum.
Curve developed with contacts terminated to size 22 AWG wire.


DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

MATING DIMENSIONS


FULLY MATED




SGMC TO SGMC




SGMC TO SGM




SGMC TO SMPL



SGM TO SGM




SGM TO SMPL



SMPL TO SMPL

EXPLODED VIEWS OF TYPICAL MATED CONNECTOR ASSEMBLIES



FOR DESCRIPTION AND TERMINOLOGY, SEE PAGE 4.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

CONNECTOR COMPONENT DESCRIPTION AND TERMINOLOGY

See "Supplemental Definitions" for clarification of "italicized" terms.

FOR ILLUSTRATIONS, SEE PAGE 3.

A1 – Connector contact: The primary electrically conductive element of connectors. The contact system is comprised of a *male contact* and a *female contact.* In general, contacts are available in a wide variety of sizes. The contacts in this catalog are size 22 (0.030 inches [0.76mm] in diameter). Contacts can be provided with multiple *termination* types, including wire *crimp* and solder; printed circuit board (pcb) solder, straight and right angle mount; and straight mount *compliant press-in.* A male crimp termination contact is shown in the example.

A2 – See definitions outlined in A1. A female crimp termination contact is shown in the example.

A3 – See definitions outlined in A1. A female right angle pcb solder termination is shown in the example.

A4 – See definitions outlined in A1. A female straight pcb solder termination is shown in the example.

B1 – Connector insert: The connector insulating element which also supports and positions the contacts in the connector system. Connectors can be supplied as a *free connector* or a *fixed connector.* Connector systems are available with a wide variety of *contact variants* and *termination types.* A 26 contact variant free connector for use with size 22 male crimp contacts is shown in the example.

B2 – See definitions outlined for B1. A 26 contact variant fixed connector with size 22 female contacts and right angle solder terminations is shown in the example.

B3 – A 26 contact variant free connector for use with size 22 male crimp contacts is shown in the example.

B4 – See definitions outlined for B1. A 26 contact variant fixed connector with size 22 female contacts and straight solder terminations is shown in the example.

B5 – See definitions outlined for B1. A 104 contact variant fixed bulkhead or panel mount connector for use with size 22 female crimp contacts is shown in the example.

B6 – A 104 contact variant free connector for use with size 22 male crimp contacts is shown in the example.

C1 – Male and female guides – Used to guide the mating of connector pairs and ensure proper alignment of contacts. A *polarized* guide system is shown in the example. Guide systems can also be used as a *coding device* for 75 and 104 variant connectors when used in corner position mounting holes.

C2 – Jackscrew system – A *locking device* which uses the mechanical advantage of male and female screw threads to couple and uncouple connector pairs. The system consists of a fixed jackscrew and a rotating jackscrew. A *polarized* jackscrew system is shown in the example. Jackscrew systems can also be used as a *coding device* for connectors.

C3 – Quick disconnect locking device – Device which allows for rapid connect and disconnect of connector pairs. The system shown in the example consists of fixed lock tabs and actuation levers.

C4 – Backshell – Connector accessory (commonly referred to as a "hood" or "cable adapter") which is used on *free connectors* to support cable or wires and to protect contact terminations. Backshell may be used with other accessories such as jackscrew and quick disconnect locking systems, guides, and connector housings as shown in the examples.

C5 – Connector Housing – Connector accessory (commonly referred to as a "shell" or "shroud") which protects the mating portion of the connector contacts. Connector housings are capable of serving as a *coding device* with the use of pin and slot system shown in this catalog, *see page 34 for details.*

C6 – Mounting bracket – Connector accessory used to mechanically fix a connector to a mounting surface. The example shows a mounting bracket used to secure a right angle solder connector to a pcb.

SUPPLEMENTAL DEFINITIONS

Male contact - Contact gender in which mechanical and electrical engagement is made on the outer surface of the contact.

Female contact – Contact gender in which mechanical and electrical engagement is made on the inner surface of the contact.

Size (contact) – A designation to differentiate one contact from another. Numbers are commonly used for this purpose. The designator numbers are associated with a specific male contact diameter; the smaller the designator, the larger the contact size.

Termination type - Means of making connection between the contact and external conductors.

Compliant press-in termination – A termination with a specially shaped section designed to provide an electrically secure solderless connection when pressed into a printed circuit board (pcb).

Crimp contact termination – A contact having a barrel which accepts a conductor and the barrel is designed to be crimped.

Free connector – The portion of connector system designed for attachment to the free end of wire or cable.

Fixed connector – The portion of connector system designed for attachment to a rigid surface.

Contact variant – The number, size, and arrangement of contacts.

Polarization (connector mating) - Integral feature within a connector system to ensure corresponding male and female contacts are engaged when the connectors are mated.

Coding device – Means of preventing the mating of a connector to any connector other than its intended mate. Also referred to as "keying".

Locking device (connector) – An accessory that provides mechanical retention of mated connectors.


Connector component terminology is based on I.E.C. (International Electrotechnical Commission) language. See http://www.electropedia.org/ for more information.

SGMC SERIES
INDUSTRIAL / MILITARY QUALITY
REMOVABLE CONTACTS

High
Density
Rectangular



- High reliability connectors with removable contacts.
- Contacts are high density size 22.
- Terminations: crimp, solder cup, straight solder and compliant press-in printed board mount.
  See pages 11- 14 for details.
- Female closed entry contacts utilize the "PosiBand®" system. See page 1 for details.
- Current ratings: signal level to 13 amperes.
  See temperature rise curves on page 2 for details.
- Eleven connector variants, 4 - 104 contacts.
- A multitude of polarization and connector coding (keying) options. See pages 30-34 for details.
- Intermateable with SGM and SMPL series.
  See page 15 for SGM series and page 23 for SMPL series.
- Thermocouple contact options available.
- A wide variety of options and accessories.



Connectors Qualified to:
- DSCC Drawing No. 86040 & 86078
- MIL-C-28748/13 & 28748/14

Contacts Qualified to:
- SAE AS39029/34 & 39029/35

Telecommunication:
- UL File # E49351

TECHNICAL CHARACTERISTICS

MATERIALS AND FINISHES:

Connector Insert: Glass filled DAP per ASTM-D-5948 type SDG-F. Green color is standard, black or grey available.

Removable Contacts: Precision machined copper alloy. 0.000015 inch [0.38 µ] gold over nickel. Other finishes available upon request, *see pages 11-14 for details.*

Polarizing Guides: Copper alloy with nickel plate or passivated stainless steel.

Jackscrew System: Passivated stainless steel.

Connector Housing (Shells): Aluminum with yellow anodize or black anodize1.

Backshell: Aluminum with yellow or black anodize.

Quick Disconnect Locking Device: Actuation lock lever and lock tab, copper alloy with nickel plate.

MECHANICAL CHARACTERISTICS:

Removable Contacts: Insert contact to rear face of connector insert, release from front face of connector insert. Size 22 contact, male contact - 0.030 inch [0.76mm] mating diameter. Female contact - PosiBand closed entry design, *see page 1 for details.*

Contact Retention in Connector Insert: 6 lbs. [26.5N] minimum.

continued on next page. . . .

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

TECHNICAL CHARACTERISTICS, continued

continued from previous page. . . .

MECHANICAL CHARACTERISTICS, continued:

Contact Termination: Crimp all wire sizes from 20 AWG [0.5 mm²] through 28 AWG [0.08 mm²].

Solder cup - 0.035 inch [0.89mm] hole diameter for 22 AWG [0.3mm²] wire maximum. 0.045 inch [1.14mm] hole diameter for 20 AWG [0.5mm²] wire maximum.

Straight printed board mount - 0.025 inch [0.64mm] termination diameter.

Compliant press-in termination.

Locking Systems: Friction, quick disconnect locking device and jackscrews.

Polarization: Polarized guides and jackscrew system.

Coding (Keying) Device: Pin and slot system; male and female guide system.

Mechanical Operations: 1000 operations

Jackscrews: Standard threads, 2-56 UNC on all sizes, except 75 and 104 connector variants, which use 6-32 UNC. Metric threads, M2X0.4 and M3X0.5 available.

ELECTRICAL CHARACTERISTICS:

Contact Current Rating, Tested per UL 1977:

13 amperes, 2 contacts energized.
10 amperes, 6 contacts energized.
6 amperes, 26 contacts energized.
5 amperes, 104 contacts energized

See temperature rise curves on page 2 for details.

Initial Contact Resistance: 0.004 ohms, maximum.

Flash over Voltage: 2200 V.AC (rms)

Test Voltage: 1000 V.AC (rms)

Insulation Resistance: 5 G ohms, minimum.

Clearance and Creepage Distance: 0.060 inch [1.52 mm], minimum.

Working Temperature: -55°C to 135°C

Working Voltage: 250 V.AC (rms)

THERMOCOUPLE CONTACTS:

Size 22 removable crimp contacts are available, *see page 12 for details*.


Straight printed circuit board mount contacts are available in SGM series, *see page 16 for details.*

Right angle (90°) printed circuit board mount contacts are available in SMPL series, *see page 24 for details.*


Visit our web site for the latest catalog updates and supplements at https://www.connectpositronic.com/catalogs/

Do you need 2-D drawings or 3-D models?

Once you have made a connector selection, contact Technical Sales if you would like a 2-D drawing or 3-D model. If we do not have your specific part number on file, we can create one for you. Or, please visit ***www.connectpositronic.com*** *and use the search function.*




2-D Drawing




3-D Model

CONNECTOR INSERT DIMENSIONS


MATING FACE VIEW OF FEMALE OR REAR FACE VIEW OF MALE




MALE AND FEMALE
PROFILE VIEW




SGMC 4




SGMC 7




SGMC 9




SGMC 14




SGMC 20




SGMC 26



SGMC 34



SGMC 44



SGMC 50

CONTACT HOLE PATTERNS:


For SGMC series contact hole patterns, refer to page 21 in SGM series.

For information regarding REMOVABLE CONTACTS, see contact illustration drawings and charts on pages 11-14.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

CONNECTOR INSERT DIMENSIONS

MATING FACE VIEW OF FEMALE OR REAR FACE VIEW OF MALE




SGMC 75 SGMC 104

CONTACT HOLE POSITION DIMENSIONS AND PRINTED BOARD HOLE PATTERN FOR CONTACT VARIANTS 75 AND 104

MATING FACE VIEW OF FEMALE OR REAR FACE VIEW OF MALE

For contact hole patterns for SGMC series sizes 4 - 50, refer to page 21 in SGM series.



SUGGESTED PRINTED BOARD HOLE SIZES:

Suggest 0.040 [1.01] Ø holes in printed board for contact terminations.

For information regarding REMOVABLE CONTACTS, see contact illustration drawings and charts on pages 11-14.

REMOVABLE CONTACT ORDERING ASSISTANCE CHART

SGMC SERIES
CRIMP AND SOLDER CUP CONTACT TERMINATIONS

TERMINATION TYPE	PAGE NUMBER REFERENCE IN CATALOG	CONTACT SIZE	FEMALE PART NUMBER	MALE PART NUMBER	WIRE SIZE AWG [mm²]
CRIMP	see page 11 for additional information	22	**FC422P2**	**MC422N**	22 / 24 / 26 / 28 [0.3/0.25/0.12/0.08]
			FC420P2	**MC420N**	20 [0.5]
MILITARY CRIMP	see page 12 for additional information	22	**M39029/35-441**	**M39029/34-440**	22 / 24 / 26 / 28 [0.3/0.25/0.12/0.08]
THERMOCOUPLE CRIMP	see page 12 for additional information	22	**FC422P2CH**	**MC422NCH**	22 / 24 / 26 [0.3/0.25/0.12]
			FC422P2AL	**MC422NAL**	
			FC422P2CU	**MC422NCU**	
			FC422P2CO	**MC422NCO**	
SOLDER CUP	see page 13 for additional information	22	**FS422P2**	**MS422N**	22 [0.3] max.
			FS420P2	**MS420N**	20 [0.5] max.

SGMC SERIES
PRINTED BOARD MOUNT CONTACT TERMINATIONS

TERMINATION TYPE	PAGE NUMBER REFERENCE IN CATALOG	CONTACT SIZE	FEMALE PART NUMBER	MALE PART NUMBER	USABLE TERMINATION LENGTH	TERMINATION DIMENSION
STRAIGHT SOLDER	see page 13 for additional information	22	**FDS425P2**	**MDS425N**	0.125 [3.18]	0.025 Ø [0.64]
			FDS456P2	**MDS456N**	0.156 [3.96]	0.025 Ø [0.64]
			FDS487P2	**MDS487N**	0.187 [4.75]	0.025 Ø [0.64]
COMPLIANT PRESS-IN	see page 14 for additional information	22	**FPF467P2**	**MPF467N**	N/A	0.048 Ø [1.22]

NOTE: Positronic recommends printed circuit board contacts be supplied installed in the connector. *Contact technical sales.*

For information regarding REMOVABLE CONTACTS, *see contact illustration drawings and charts on pages 11-14.*

For information regarding CRIMP TOOLS & CRIMPING TOOL TECHNIQUES, *see page 37.*

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

ORDERING INFORMATION - CODE NUMBERING SYSTEM

Specify Complete Connector By Selecting An Option From Step 1 Through 9

STEP	1	2	3	4	5	6	7	8	9		10
EXAMPLE	SGMC	14	S	0	ESS	0	0	0	0	—	-14

STEP 1 - BASIC SERIES

SGMC series

STEP 2 - CONNECTOR VARIANTS

4, 7, 9, 14, 20, 26, 34, 44, 50, 75, 104

STEP 3 - CONNECTOR GENDER

M - Male
S - Female - PosiBand closed entry contacts, *see page 1 for more information.*

STEP 4 - CONTACT TERMINATION TYPE

0 – Contacts are to be ordered separately, see contact ordering chart on page 9.

*1 STEP 5 - POLARIZING GUIDES AND JACKSCREW SYSTEMS

N – Polarizing guides.
NSS – Stainless steel polarizing guides.
T – Fixed jackscrews.
E – Rotating jackscrews with knobs.
E1 – Rotating jackscrews used with backshell only. Not offered on 75 and 104 variants.
ESS – Short rotating jackscrews.
0 – If no polarizing guides or jackscrews are required. Also use "0" if ordering backshell equipped with jackscrews, for variants 75 and 104, see STEP 8.

*1 STEP 6 - CONNECTOR HOUSING (SHELLS)

P – Male shell.
R – Female shell.
0 – If no connector housings are required.

*1 STEP 7 - CODING (KEYING) POSITIONS OF CONNECTOR HOUSING (SHELLS)

Select letter to designate position of male pin or female slot for coding system.

A, B, C, D, E, F, G
0 – If no coding is required or if no connector housings are required.

*1 STEP 8 - BACKSHELL

V – Side opening backshell equipped with stainless steel jackscrew system offered on 104 variant only.
Z – Top opening backshell equipped with stainless steel jackscrew system offered on 104 variants only.
J – Top opening backshell offered on all variants except 75 and 104.
0 – If no backshell are required.

*1 STEP 9 - ADDITIONAL FEATURES

B – For black anodized aluminum parts.
R – For yellow chromate coating on aluminum parts.
*2 V – Lock tab, not offered on 75 and 104 variants.
*2 VL – Actuation lock lever, not offered on 75 and 104 variants.
0 – If no additional options are required.
M – Jackscrews with metric threads.

STEP 10 - SPECIAL OPTIONS

FOR SPECIAL OPTIONS, SEE SPECIAL OPTIONS APPENDIX ON PAGE 41.

NOTE:

*1 For details of items listed in steps 5 through 9, see Accessories section on pages 30-36.

*2 Select '0' in Step 6 when selecting 'V' and 'VL' options.

Do you need 2-D drawings or 3-D models?
See page 6 for more information!

For information regarding CRIMP TOOLS & CRIMPING TOOL TECHNIQUES, *see page 37.*

REMOVABLE CONTACT TECHNICAL CHARACTERISTICS

SIZE 22 REMOVABLE CONTACT

MATERIALS AND FINISHES:

Precision machined copper alloy. 0.000015 inch [0.38 µ] gold over nickel. Other finishes available upon request, for details, see optional plating finishes below.

MECHANICAL CHARACTERISTICS:

Insert contact to rear face of connector insert, release from front face of connector insert. Size 22 contact, male - 0.030 inch [0.76mm] mating diameter. Female contact - PosiBand closed entry design, *see page 1 for details*. Terminations for 20, 22, 24, 26, and 28 AWG.

ELECTRICAL CHARACTERISTICS:

Contact Current Rating, Tested per UL 1977:

13 amperes, 2 contacts energized.
10 amperes, 6 contacts energized.
6 amperes, 26 contacts energized.
5 amperes, 104 contacts energized

See temperature rise curves on page 2 for details.

Initial Contact Resistance: 0.004 ohms, maximum.

OPTIONAL PLATING FINISHES

-14 0.000030 [0.76 µ] gold over nickel by adding "-14" suffix onto part number. *Example: FC422P2-14.*

-15 0.000050 inch [1.27µ] gold over nickel by adding "-15". *Example: FC422P2-15.*

REMOVABLE CRIMP CONTACT

FOR USE WITH SGMC SERIES CONNECTORS


SIZE 22

CLOSED CRIMP BARREL WITH INSULATION SUPPORT


Note: Connectors can be kitted with all applicable crimp/solder contacts, contact Technical Sales for connector part number.

FEMALE CONTACT

"CLOSED ENTRY" DESIGN



MALE CONTACT



FEMALE PART NUMBER	WIRE SIZE AWG [mm²]	ØA	ØB
FC422P2	22 / 24 / 26 / 28 [0.3/0.25/0.12/0.08]	0.056 [1.42]	0.035 [0.89]
FC420P2	20 [0.5]	N/A	0.045 [1.14]

MALE PART NUMBER	WIRE SIZE AWG [mm²]	ØA	ØB
MC422N	22 / 24 / 26 / 28 [0.3/0.25/0.12/0.08]	0.056 [1.42]	0.035 [0.89]
MC420N	20 [0.5]	N/A	0.045 [1.14]

For information regarding CRIMP TOOLS & CRIMPING TOOL TECHNIQUES, *see page 37.*

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

REMOVABLE MILITARY CRIMP CONTACT

FOR USE WITH SGMC SERIES CONNECTORS

SIZE 22

QUALIFIED TO SAE AS39029


Note: Connectors can be kitted with all applicable crimp/solder contacts, contact Technical Sales for connector part number.

***MILITARY SPECIFICATION CONTACTS**


STANDARD FINISH:
per SAE AS39029 specifications

COLOR CODE:
MALE CONTACT:
YELLOW/YELLOW/BLACK
FEMALE CONTACT:
YELLOW/YELLOW/BROWN

FEMALE CONTACT
"CLOSED ENTRY" DESIGN



MALE CONTACT



FEMALE PART NUMBER	WIRE SIZE AWG/[mm²]
*M39029/35-441	22 / 24 / 26 / 28 [0.3/0.25/0.12/0.08]

MALE PART NUMBER	WIRE SIZE AWG/[mm²]
*M39029/34-440	22 / 24 / 26 / 28 [0.3/0.25/0.12/0.08]


REMOVABLE THERMOCOUPLE CRIMP CONTACT

FOR USE WITH SGMC SERIES CONNECTORS


SIZE 22

Note: Connectors can be kitted with all applicable crimp/solder contacts, contact Technical Sales for connector part number.

FEMALE CONTACT
"CLOSED ENTRY" DESIGN



MALE CONTACT



TYPE	MATERIAL	FEMALE PART NUMBER	MALE PART NUMBER	COLOR CODE*	WIRE SIZE AWG [mm²]
K	CHROMEL (+) with gold flash	FC422P2CH	MC422NCH	WHITE	22 / 24 / 26 [0.3 / 0.25 / 0.12]
	ALUMEL (-)	FC422P2AL	MC422NAL	GREEN	22 / 24 / 26 [0.3 / 0.25 / 0.12]
T	COPPER (+)	FC422P2CU	MC422NCU	RED	22 / 24 / 26 [0.3 / 0.25 / 0.12]
	CONSTANTAN (-)	FC422P2CO	MC422NCO	YELLOW	22 / 24 / 26 [0.3 / 0.25 / 0.12]
E	CHROMEL (+)	FC422P2CH	MC422NCH	WHITE	22 / 24 / 26 [0.3 / 0.25 / 0.12]
	CONSTANTAN (-)	FC422P2CO	MC422NCO	YELLOW	22 / 24 / 26 [0.3 / 0.25 / 0.12]

For more information on the availability of Type J thermocouple contacts, please contact Technical Sales.

For more information about thermocouple contacts with printed circuit board solder termination, please contact Technical Sales.

Chromel® and Alumel® are registered trademarks of Hoskins Manufacturing Company

For information regarding CRIMP TOOLS & CRIMPING TOOL TECHNIQUES, *see page 37.*

REMOVABLE SOLDER CUP CONTACT


FOR USE WITH SGMC SERIES CONNECTORS

SIZE 22


Note: Connectors can be kitted with all applicable crimp/solder contacts, contact Technical Sales for connector part number.

FEMALE CONTACT

"CLOSED ENTRY" DESIGN



MALE CONTACT



FEMALE PART NUMBER	WIRE SIZE AWG/[mm²]	ØA	ØB
FS422P2	22 [3/0]	0.056 [1.42]	0.035 [0.89]
FS420P2	20 [0.5]	N/A	0.045 [1.14]

MALE PART NUMBER	WIRE SIZE AWG/[mm²]	ØA	ØB
MS422N	22 [3/0]	0.056 [1.42]	0.035 [0.89]
MS420N	20 [0.5]	N/A	0.045 [1.14]

REMOVABLE STRAIGHT SOLDER PRINTED BOARD MOUNT CONTACT*1


FOR USE WITH SGMC SERIES CONNECTORS*2

SIZE 22


Note: Connectors can be kitted with all applicable crimp/solder contacts, contact Technical Sales for connector part number.

FEMALE CONTACT

"CLOSED ENTRY" DESIGN



MALE CONTACT



FEMALE PART NUMBER	A	B *See below illustration*
FDS425P2	0.607 [15.42]	0.125 [3.18]
FDS456P2	0.638 [16.21]	0.156 [3.96]
FDS487P2	0.669 [16.99]	0.187 [4.75]

MALE PART NUMBER	A	B *See below illustration*
MDS425N	0.772 [19.61]	0.125 [3.18]
MDS456N	0.803 [20.40]	0.156 [3.96]
MDS487N	0.834 [21.18]	0.187 [4.75]

CONTACT HOLE PATTERNS:

For SGMC series contact hole patterns, refer to page 21 in SGM series.

NOTES: *1 Positronic recommends printed circuit board contacts be supplied installed in the connector. *Contact technical sales.*

*2 Positronic recommends the practice of using mounting hardware to secure connector to printed circuit board, see mounting hardware presentation on page 14.

For information regarding CRIMP TOOLS & CRIMPING TOOL TECHNIQUES, *see page 37.*

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.


REMOVABLE COMPLIANT PRESS-IN PRINTED BOARD MOUNT CONTACT*1

FOR USE WITH SGMC SERIES CONNECTORS*2

SIZE 22


FEMALE CONTACT

"CLOSED ENTRY" DESIGN



PART NUMBER: FPF467P2

MALE CONTACT



PART NUMBER: MPF467N

Note: Unless otherwise specified, compliant press-in contacts are not supplied with SGMC connectors and must be ordered separately. Contacts may be installed in connector to custom order.

SUGGESTED PRINTED BOARD HOLE SIZES:

Suggest 0.105 [2.66] Ø hole in printed board for connector mounting holes.

NOTE: For suggested printed board recommended drill hole sizes, plating and finished hole sizes for compliant contact termination positions, see page 40.

For compliant press-in connector installation tools, see page 39.

CONTACT HOLE PATTERNS:

For SGMC series contact hole patterns, refer to page 21 in SGM series.

NOTES: *1 Positronic recommends printed circuit board contacts be supplied installed in the connector. *Contact technical sales.*

*2 Positronic recommends the practice of using mounting hardware to secure connector to printed circuit board, see mounting hardware presentation below.


MOUNTING HARDWARE FOR PRINTED BOARD MOUNT CONNECTORS

FOR USE WITH SGMC OR SGM SERIES CONNECTORS


SGMC CONNECTOR INSERT SHOWN IN ILLUSTRATION FOR REFERENCE

*Positronic **recommends** the practice of **using mounting hardware.** Stresses that occur during coupling and uncoupling of connectors or through shock and vibration of systems can be transferred to printed circuit boards through compliant press-in connector terminations. Avoid concern over electrical integrity of the connector to board interface by using mounting screws.*

FEMALE



MALE




NOTE: *1 Stainless steel spacer available.


CONTACT TECHNICAL SALES FOR PART NUMBERS WITH LONG JACKSCREW OR NYLON SPACER*1 !

For information regarding CRIMP TOOLS & CRIMPING TOOL TECHNIQUES, *see page 37.*

SGM SERIES
INDUSTRIAL / MILITARY QUALITY
FIXED STRAIGHT PCB MOUNT / SOLDER CUP

High Density Rectangular







- High reliability connectors with fixed contacts.
- Contacts are high density size 22.
- Terminations: wire wrap, solder cup, straight solder and compliant press-in printed board mount. See pages 18-20 for details.
- Female closed entry contacts utilize the "PosiBand®" system. See page 1 for details.
- Current ratings: signal level to 13 amperes. See temperature rise curves on page 2 for details.
- Twelve connector variants, 4 - 50 contacts.
- A multitude of polarization and connector coding (keying) options. See pages 30-34 for details.
- Intermateable with SGMC and SMPL series. See page 5 for SGMC series and page 23 for SMPL series.
- Thermocouple contact options available.
- A wide variety of options and accessories.

Qualified to:
- MIL-DTL-28748/7 & 28748/8

Telecommunication:
- UL File # E49351

TECHNICAL CHARACTERISTICS

MATERIALS AND FINISHES:

Connector Insert: Glass filled DAP per ASTM-D-5948 type SDG-F. Grey color is standard, black or green available.

Fixed Contacts: Precision machined copper alloy. 0.000015 inch [0.38 µ] gold over nickel. Other finishes available upon request, *see page 41 for details*.

Polarizing Guides: Copper alloy with nickel plate or passivated stainless steel.

Jackscrew System: Passivated stainless steel.

Connector Housing (Shells): Aluminum with yellow anodize or black anodize.

Backshell: Aluminum with yellow or black anodize.

Quick Disconnect Locking Device: Actuation lock lever and lock tab, copper alloy with nickel plate.

MECHANICAL CHARACTERISTICS:

Fixed Contacts: Size 22, male contact 0.030 inch [0.76 mm] mating diameter. Female contact - PosiBand closed entry design, *see page 1 for details.*

Contact Retention in Connector Insert: 6 lbs. [26.5N] minimum.

Contact Termination: Solder cup contacts - 0.037 inch [0.94 mm] internal hole diameter for 22 AWG [0.3 mm^2] wire maximum.

Straight printed board mount - 0.025 inch [0.64 mm] termination diameter.

continued on next page. . . .

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

TECHNICAL CHARACTERISTICS, continued

continued from previous page. . . .

MECHANICAL CHARACTERISTICS, continued:

	Wire post - 0.025 inch [0.64 mm] square.
	Compliant press-in termination.
Locking Systems:	Friction, quick disconnect locking device and jackscrews.
Polarization:	Polarized guides and jackscrew system.
Coding (Keying) Device:	Pin and slot system; male and female guide system.
Mechanical Operations:	1000 operations per IEC 60512-5.
Jackscrews:	Standard threads, 2-56 UNC on all sizes, Metric threads, M2X0.4 and M3X0.5 available.

ELECTRICAL CHARACTERISTICS:

Contact Current Rating, Tested per UL 1977:

13 amperes, 2 contacts energized.
10 amperes, 6 contacts energized.
6 amperes, 26 contacts energized.
5 amperes, 104 contacts energized

See temperature rise curves on page 2 for details.

Initial Contact Resistance:	0.004 ohms, maximum.
Flash over Voltage:	2200 V.AC (rms)
Test Voltage:	1000 V.AC (rms)
Insulation Resistance:	5 G ohms, minimum.
Clearance and Creepage Distance:	0.028 inch [0.71 mm], minimum.
Working Temperature:	-55°C to 135°C
Working Voltage:	250 V.AC (rms)

THERMOCOUPLE CONTACTS:

Straight printed circuit board mount contacts are available, please contact Technical Sales for details.


Right angle (90°) printed circuit board mount contacts are available in SMPL series, *see page 24 for details.*

Size 22 removable crimp contacts are available in SGMC series, *see page 12 for details.*


Visit our web site for the latest catalog updates and supplements at https://www.connectpositronic.com/catalogs/

Do you need 2-D drawings or 3-D models?

Once you have made a connector selection, contact Technical Sales if you would like a 2-D drawing or 3-D model. If we do not have your specific part number on file, we can create one for you. Or, please visit ***www.connectpositronic.com*** *and use the search function.*




2-D Drawing




3-D Model

CONNECTOR INSERT DIMENSIONS FOR SGM AND SMPL SERIES


MATING FACE VIEW OF FEMALE OR REAR FACE VIEW OF MALE




MALE AND FEMALE
PROFILE VIEW




SGM 4
SMPL 4




SGM 5
SMPL 5




SGM 7
SMPL 7




SGM 9
SMPL 9




SGM 11
SMPL 11




SGM 14
SMPL 14




SGM 20
SMPL 20




SGM 26
SMPL 26




SGM 29
SMPL 29



SGM 34
SMPL 34



SGM 44
SMPL 44



SGM 50
SMPL 50


CONTACT HOLE PATTERNS:

For SGM series contact hole patterns, refer to page 21 in SGM series.
For SMPL series contact hole patterns, refer to page 26 in SMPL series.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

STRAIGHT SOLDER PRINTED BOARD MOUNT TERMINATION
CODE DS3, DS4, DS5 AND DS6

FEMALE



Typical Part Number:
SGM26SDS3T0000


CONTACT CODE	L
DS3	0.093 [2.36]
DS4	0.125 [3.18]
DS5	0.156 [3.96]
DS6	0.187 [4.75]

For straight solder contacts, specify contact code in Step 4 of ordering information.

SOLDER CUP TERMINATION
CODE SC


For solder cup contacts, specify contact code "SC" in Step 4 of ordering information.

FEMALE



Typical Part Number:
SGM26SSCN0000

MALE




Typical Part Number:
SGM26MSCN0000

SGM SERIES

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

WRAP POST TERMINATION
CODE WW1 OR CODE WW2

FEMALE



CONTACT CODE	L
WW1	0.225 [5.72]
WW2	0.355 [9.02]


For wrap post contacts, specify contact code in Step 4 of ordering information.

Typical Part Number:
SGM26SWW1T0000

COMPLIANT PRESS-IN PRINTED BOARD MOUNT TERMINATION*1
CODE 98


For compliant press-in contacts, specify contact code "98" in Step 4 of ordering information.

FEMALE



Typical Part Number:
SGM26S98T0000

MALE



Typical Part Number:
SGM26M98T0000

NOTES:

*1 Positronic recommends the practice of using mounting hardware to secure connector to printed circuit board.

*2 M2X0.4 metric thread available.

*3 Stainless steel spacer available.

CONTACT HOLE PATTERNS:

For compliant press-in connector contact hole patterns, see page 21.

SUGGESTED PRINTED BOARD HOLE SIZES:


Suggest 0.105 [2.66] Ø hole in printed board for connector mounting holes.

NOTE: For suggested printed board recommended drill hole sizes, plating and finished hole sizes for compliant contact termination positions, see page 40.


For compliant press-in connector installation tools, see page 39.

CONTACT HOLE POSITION DIMENSIONS AND PRINTED BOARD HOLE PATTERN FOR SGM AND SGMC SERIES


MATING FACE VIEW OF FEMALE OR REAR FACE VIEW OF MALE




SGM 4
SGMC 4




SGM 5




SGM 7
SGMC 7




SGM 9
SGMC 9




SGM 11




SGM 14
SGMC 14




SGM 20
SGMC 20




SGM 26
SGMC 26




SGM 29



SGM 34
SGMC 34



SGM 44
SGMC 44



SGM 50
SGMC 50

SUGGESTED PRINTED BOARD HOLE SIZES:

Suggest 0.105 [2.66] Ø holes in printed board for connector mounting holes
Suggest 0.040 [1.01] Ø holes in printed board for contact terminations

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

ORDERING INFORMATION - CODE NUMBERING SYSTEM

Specify Complete Connector By Selecting An Option From Step 1 Through 9

STEP	1	2	3	4	5	6	7	8	9		10
EXAMPLE	SGM	26	S	SC	N	0	0	J	0	—	-14

STEP 1 - BASIC SERIES

SGM series

STEP 2 - CONNECTOR VARIANTS

4, 5, 7, 9, 11, 14, 20, 26, 29, 34, 44, 50

STEP 3 - CONNECTOR GENDER

M - Male
S - Female - PosiBand closed entry contacts, *see page 1 for more information.*

STEP 4 - CONTACT TERMINATION TYPE

All female contacts "closed entry" design

DS3 – Straight solder 0.093 [2.36]
DS4 – Straight solder 0.125 [3.18]
DS5 – Straight solder 0.156 [3.96]
DS6 – Straight solder 0.187 [4.75]
SC – Solder cup
WW1 – Wrap post 0.225 [5.72]
WW2 – Wrap post 0.355 [9.02]
98 – Straight printed circuit board mount, compliant press-in.

*1 STEP 5 - POLARIZING GUIDES AND JACKSCREW SYSTEMS

N – Polarizing guides.
NSS – Stainless steel polarizing guides.
T – Fixed jackscrews.
E – Rotating jackscrews with knobs.
E1 – Rotating jackscrews used with backshell only.
ESS – Short rotating jackscrews.
0 – If no polarizing guides or jackscrews are required.

*1 STEP 6 - CONNECTOR HOUSING (SHELLS)

*2 P – Male shell.
*2 R – Female shell.
0 – If no connector housings are required.

*1 STEP 7 - CODING (KEYING) POSITIONS OF CONNECTOR HOUSING (SHELLS)

Select letter to designate position of male pin or female slot for coding system.

A, B, C, D, E, F, G
0 – If no coding is required or if no connector housings are required.

*1 STEP 8 - BACKSHELL

J – Top opening backshell offered on all variants except 5 and 11.
0 – If no backshell are required.

*1 STEP 9 - ADDITIONAL FEATURES

B – For black anodized aluminum parts.
R – For yellow chromate coating on aluminum parts.
*3 V – Lock tab.
*3 VL – Actuation lock lever.
M – Jackscrews with metric threads.
0 – If no additional options are required.

STEP 10 - SPECIAL OPTIONS

FOR SPECIAL OPTIONS, SEE SPECIAL OPTIONS APPENDIX ON PAGE 41.

NOTE:

*1 For details of items listed in steps 5 through 9, see Accessories section on pages 30-36.

*2 Contact Technical Sales for availability of 5, 11 and 29 connector variants.

*3 Select '0' in Step 6 when selecting 'V' and 'VL' options.

Do you need 2-D drawings or 3-D models?
See page 16 for more information!

SMPL SERIES
INDUSTRIAL / MILITARY QUALITY
FIXED RIGHT ANGLE PCB MOUNT TERMINATION

High Density Rectangular





- High reliability connectors with fixed contacts.
- Contacts are high density size 22.
- Terminations: right angle (90º) solder printed board mount.
  See pages 25 for details.
- Female closed entry contacts utilize the “PosiBand®” system.
  See page 1 for details.



- Current ratings: signal level to 13 amperes.
  See temperature rise curves on page 2 for details.
- Twelve connector variants, 4 - 50 contacts.
- A multitude of polarization and connector coding (keying) options. See pages 30-34 for details.
- Intermateable with SGMC and SGM series.
  See page 5 for SGMC series and page 15 for SGM series.
- Thermocouple contact options available.
- A wide variety of options and accessories.

Conforms to:
- MIL-DTL-28748

Telecommunication:
- UL File # E49351

TECHNICAL CHARACTERISTICS

MATERIALS AND FINISHES:

Connector insert: Glass filled DAP per ASTM-D-5948 type SDG-F. Grey color is standard, black or green available.

Fixed Contacts: Precision machined copper alloy. 0.000015 inch [0.38 µ] gold over nickel. Other finishes available upon request, *see page 41 for details*.

Polarizing Guides: Copper alloy with nickel plate or passivated stainless steel.

Jackscrew System: Passivated stainless steel.

Mounting Bracket: Phosphor bronze with zinc plate and chromate seal.

Alignment Bar: Nylon, black.

Quick Disconnect Locking Device: Actuation lock lever and lock tab, copper alloy with nickel plate.

MECHANICAL CHARACTERISTICS:

Fixed Contacts: Size 22, male 0.030 inch [0.76 mm] mating diameter. Female – PosiBand closed entry design, *see page 1 for details*.

Contact Retention in Connector Insert: 6 lbs. [26.5N] minimum.

Contact Termination: 0.020 inch [0.51 mm] termination diameter.

Locking Systems: Friction, quick disconnect locking device and jackscrews.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

continued on next page. . . .

TECHNICAL CHARACTERISTICS, continued

continued from previous page. . . .

MECHANICAL CHARACTERISTICS, continued:

Polarization: Polarized guides and jackscrew system.

Coding (Keying) Device: Pin and slot system; male and female guide system.

Mechanical Operations: 1000 operations per IEC 60512-5.

Jackscrews: Standard threads, 2-56 UNC. M2X0.4 metric threads available.

ELECTRICAL CHARACTERISTICS:

Contact Current Rating, Tested per UL 1977:

13 amperes, 2 contacts energized.
10 amperes, 6 contacts energized.
6 amperes, 26 contacts energized.
5 amperes, 104 contacts energized

See temperature rise curves on page 2 for details.

Initial Contact Resistance: 0.004 ohms, maximum.

Flash over Voltage: 2200 V.AC (rms)

Test Voltage: 1000 V.AC (rms)

Insulation Resistance: 5 G ohms, minimum.

Clearance and Creepage Distance: 0.028 inch [0.71 mm], minimum.

Working Temperature: -55°C to 135°C

Working Voltage: 250 V.AC (rms)

THERMOCOUPLE CONTACTS:

Right angle (90°) printed board mount contacts are available, please contact Technical Sales for details.


Straight printed board mount contacts are available in SGM series, *see page 16 for details.*

Size 22 removable crimp contacts are available in SGMC series, *see page 12 for details.*


Visit our web site for the latest catalog updates and supplements at https://www.connectpositronic.com/catalogs/

Do you need 2-D drawings or 3-D models?

Once you have made a connector selection, contact Technical Sales if you would like a 2-D drawing or 3-D model. If we do not have your specific part number on file, we can create one for you. Or, please visit ***www.connectpositronic.com*** *and use the search function.*




2-D Drawing



3-D Model

RIGHT ANGLE (90°) SOLDER PRINTED BOARD MOUNT TERMINATION
CODE 0



Typical Part Number:
SMPL29M0N0LB


NOTE:

Add 0.030 [0.76] to the hole location dimension 0.175 [4.48] when mounting bracket (Code LB) and locking tab (Code V) are used in combination on connector.

CONNECTOR INSERT DIMENSIONS:


For SMPL series connector insert dimensions, refer to page 17 in SGM series.

MOUNTING BRACKET
CODE LB



PART NUMBER	A	B	CONNECTOR VARIANTS
80213-0	0.105 [2.67]	0.205 [5.21]	4, 5, 7, 9
80213-1	0.140 [3.56]	0.240 [6.10]	11, 14, 20, 26, 29
80213-2	0.195 [4.95]	0.295 [7.49]	34, 44, 50

ALIGNMENT BAR DIMENSIONS




SIZE	A	B
5	0.314 [7.98]	0.290 [7.37]
7	0.394 [10.01]	0.290 [7.37]
9	0.488 [12.40]	0.290 [7.37]
11	0.364 [9.25]	0.415 [10.54]
14	0.456 [11.58]	0.415 [10.54]
20	0.646 [16.41]	0.415 [10.54]
26	0.832 [21.13]	0.415 [10.54]
29	0.926 [23.52]	0.415 [10.54]
34	0.864 [21.95]	0.550 [13.97]
44	1.112 [28.24]	0.550 [13.97]
50	1.240 [31.50]	0.550 [13.97]


DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

RIGHT ANGLE (90°) PRINTED BOARD HOLE PATTERN


HOLE IDENTIFICATION SHOWN FOR MALE CONNECTOR; USE MIRROR IMAGE FOR FEMALE CONNECTOR.




SMPL 4




SMPL 5




SMPL 7




SMPL 9




SMPL 11




SMPL 14




SMPL 20




SMPL 26




SMPL 29



SMPL 34



SMPL 44



SMPL 50

SUGGESTED PRINTED BOARD HOLE SIZES:

Suggest 0.105 [2.66] Ø holes in printed board for connector mounting holes
Suggest 0.040 [1.01] Ø holes in printed board for contact terminations
Add 0.030 [0.76] to the hole location dimension 0.175 [4.48] when mounting bracket (Code LB) and locking tab (Code V) are used in combination on connector.

ORDERING INFORMATION - CODE NUMBERING SYSTEM

Specify Complete Connector By Selecting An Option From Step 1 Through 7

STEP	1	2	3	4	5	6	7		8
EXAMPLE	SMPL	14	S	0	T	0	LB	—	-14

STEP 1 - BASIC SERIES

SMPL series.

STEP 2 - CONNECTOR VARIANTS

4, 5, 7, 9, 11, 14, 20, 26,
29, 34, 44, 50

STEP 3 - CONNECTOR GENDER

M - Male
S - Female - PosiBand closed entry contacts, *see page 1 for more information.*

STEP 4 - CONTACT TERMINATION TYPE

0 – Standard termination, right angle (90°).

*1 STEP 5 - POLARIZING GUIDES AND JACKSCREW SYSTEMS

N – Polarizing guides.
NSS – Stainless steel polarizing guides.
T – Fixed jackscrews.
0 – If no polarizing guides or jackscrews are required.

*1 STEP 6 - QUICK DISCONNECT LOCKING DEVICES

V – Lock tab.
VL – Actuation lock lever.
0 – If no locking devices are required.

STEP 7 - MOUNTING BRACKETS

LB – Mounting bracket.
0 – If no mounting bracket is required.

STEP 8 - SPECIAL OPTIONS

FOR SPECIAL OPTIONS, SEE SPECIAL OPTIONS APPENDIX ON PAGE 41.

NOTE:

*1 For details of items listed in steps 5 through 6, see Accessories section on pages 30-36.

Do you need 2-D drawings or 3-D models?
See page 24 for more information!

Visit our web site for the latest catalog updates and supplements at https://www.connectpositronic.com/catalogs/


U N I Q U E F E A T U R E S E C T I O N

Positronic®
THE SCIENCE OF CERTAINTY

Positronic is **known** around the world **for offering** our customers **flexibility** when choosing connectors.

In addition to allowing **customers** to **create** part numbers for **particular applications,** Positronic offers a **wide variety** of features and accessories within our products.


Positronic is **able** to modify existing products **to meet unique customer requirements.** We are also eager to develop **custom connectors** to customer requirements. If you do not find what you need in this catalog, please contact us for **assistance**.



LOW PROFILE SPACE SAVING HIGH RELIABILITY MEZZANINE CONNECTOR

SGM SERIES

*SGM connectors can be **used to stack multiple printed circuit boards** in applications requiring rugged, high density connectors.*




FOR DETAILED INFORMATION AND OPTIONS, CONTACT TECHNICAL SALES


CUSTOMER SPECIFIED CONTACT TERMINATION LENGTH

Positronic can supply High Density Retangular connectors with customer specified termination lengths. We have a wide variety of options available.

STRAIGHT PRINTED BOARD MOUNT




RIGHT ANGLE (90°) PRINTED BOARD MOUNT



"X" contact termination lengths can be custom designed to fit your application requirements.

CONTACT TECHNICAL SALES FOR MORE INFORMATION!


FLUSH PANEL CONNECTOR MOUNTING BRACKETS




PART NUMBER 80217-0

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

POLARIZATION & CODING (KEYING) OPTIONS






ACCESSORIES SECTION

PANEL CUT-OUT DIMENSIONS


FOR USE WITH SGMC OR SGM SERIES CONNECTORS



SIZE	A	B MIN.	C MIN.
4	0.562 [14.27]	0.390 [9.91]	0.215 [5.46]
5	0.482 [12.24]	0.315 [8.00]	0.215 [5.46]
7	0.562 [14.27]	0.397 [10.08]	0.215 [5.46]
9	0.656 [16.66]	0.495 [12.57]	0.215 [5.46]
11	0.531 [13.49]	0.401 [10.19]	0.285 [7.24]
14	0.625 [15.88]	0.510 [12.95]	0.285 [7.24]
20	0.814 [20.68]	0.700 [17.78]	0.285 [7.24]
26	1.000 [25.40]	0.885 [22.48]	0.285 [7.24]
29	1.094 [27.79]	0.959 [24.36]	0.285 [7.24]
34	1.032 [26.21]	0.867 [22.02]	0.395 [10.03]
44	1.281 [32.54]	1.105 [28.07]	0.395 [10.03]
50	1.408 [35.76]	1.235 [31.37]	0.395 [10.03]
75	1.375 [34.93]	1.145 [29.08]	0.755 [19.18]
104	1.750 [44.45]	1.520 [37.47]	0.755 [19.18]

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.


POLARIZING GUIDES
CODE N OR CODE NSS



POLARIZING GUIDES

STAINLESS STEEL POLARIZING GUIDES

FIXED AND ROTATING JACKSCREW SYSTEMS
CODE T, CODE E OR CODE ESS



FIXED JACKSCREWS

ROTATING JACKSCREWS

SHORT ROTATING JACKSCREWS

NOTE:
Recommended Jackscrew
mating torque 0.141 N m (1.25 in-lb)

POLARIZING GUIDE AND JACKSCREW THREAD AVAILABILITY CHART
CODE N, CODE NSS, CODE T, CODE E OR CODE ESS

THREAD OPTIONS	POLARIZING GUIDES				FIXED AND ROTATING JACKSCREWS					
	N		NSS		T		E		*1 ESS	
	4 - 50 VARIANTS	75 &104 VARIANTS	4 - 50 VARIANTS	75 &104 VARIANTS	4 - 50 VARIANTS	75 &104 VARIANTS	4 - 50 VARIANTS	75 &104 VARIANTS	4 - 50 VARIANTS	75 &104 VARIANTS
2-56 THREAD	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	- - -
M2x0.4 METRIC THREAD	AVAILABLE	- - -	AVAILABLE	- - -	AVAILABLE	- - -	AVAILABLE	- - -	AVAILABLE	- - -
6-32 THREAD	- - -	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	- - -	SUPPLIED AS STANDARD	CONTACT TECHNICAL SALES FOR AVAILABILITY	
M3x0.5 METRIC THREAD	- - -	AVAILABLE	- - -	AVAILABLE	- - -	AVAILABLE	- - -	AVAILABLE	CONTACT TECHNICAL SALES FOR AVAILABILITY	
MATERIAL AND FINISH	COPPER ALLOY WITH NICKEL PLATE		STAINLESS STEEL PASSIVATED		STAINLESS STEEL PASSIVATED					

NOTE: *1 ESS jackscrew is not offered in kits and must be factory installed on connectors.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.


POLARIZING GUIDE

FOR USE WITH 4 TO 50 CONTACTS VARIANTS

CODE N OR CODE NSS

QUALIFIED TO MIL-DTL-28748


N



POLARIZING GUIDES
BRASS

NSS

ON THE MALE CONNECTOR, THE FEMALE POLARIZING GUIDE IS POSITIONED AT CONTACT A



POLARIZING GUIDES
STAINLESS STEEL

NOTES:

Alternative lengths of polarizing guides are available as special options, contact Technical Sales.
M2x0.4 metric threads available, see chart on page 31.


POLARIZING GUIDE

FOR USE WITH SGMC 75 OR SGMC 104 CONTACT VARIANTS

CODE NSS

NSS

POLARIZING GUIDES
STAINLESS STEEL



NOTE:

*1 M3x0.5 metric threads available, see chart on page 31.


JACKSCREW SYSTEM

FOR USE WITH 4 TO 50 CONTACTS VARIANTS

CODE T, CODE E, CODE ESS, CODE ESS-756.2 OR CODE E-793.4


QUALIFIED TO MIL-DTL-28748

T




FIXED JACKSCREWS
STAINLESS STEEL

E




ROTATING JACKSCREWS
STAINLESS STEEL WITH ALUMINUM KNOBS

ESS



ROTATING JACKSCREWS
STAINLESS STEEL


ESS-756.2



ROTATING JACKSCREWS
STAINLESS STEEL

CONSULT TECHNICAL SALES FOR ORDERING INFORMATION

E-793.4



ROTATING JACKSCREWS
STAINLESS STEEL WITH STAINLESS STEEL KNOBS

CONSULT TECHNICAL SALES FOR ORDERING INFORMATION

NOTES:


Alternative lengths of jackscrews are available as special options, contact Technical Sales.
M3x0.5 metric threads available, see chart on page 31.

JACKSCREW SYSTEM

FOR USE WITH SGMC 75 OR SGMC 104 CONTACT VARIANTS


CODE T OR CODE E

T



FIXED JACKSCREWS
STAINLESS STEEL

E




ROTATING JACKSCREWS
STAINLESS STEEL

NOTE:

*1 M3x0.5 metric threads available, see chart on page 31.

**DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.**

FEMALE



CONNECTOR HOUSING (SHELLS)

CODE R OR CODE P

QUALIFIED TO MIL-DTL-28748

CODING (KEYING) DEVICE OPTIONS

Coding (keying) is accomplished with connector housings by a pin and slot system. Female connector housings are slotted to accept stainless steel polarizing pins mounted on the male connector housings.

There are seven coding positions available which are designated by the letters A, B, C, D, E, F or G. Non-coded connector housings are designated by "0" and are supplied without slot and pin. See ordering chart. For non Mil-Spec shells the polarization feature location shall be: slot to the left, pin to the right, when the connector is held vertically with contact position A or 1 at the top and the mating face visible.

FEMALE
CODE R

PART NUMBER	A MIN.	B MIN.	C MIN.	D MIN.	E	F	R
SG4000R000	0.875 [22.23]	0.305 [7.75]	0.230 [5.84]	0.430 [10.92]	0.562 [14.27]	0.437 [11.10]	0.031 [0.79]
SG7000R000	0.875 [22.23]	0.305 [7.75]	0.230 [5.84]	0.430 [10.92]	0.562 [14.27]	0.437 [11.10]	0.031 [0.79]
SG14000R000	0.975 [24.77]	0.375 [9.53]	0.300 [7.62]	0.530 [13.46]	0.625 [15.88]	0.437 [11.10]	0.062 [1.57]
SG20000R000	1.165 [29.59]	0.375 [9.53]	0.300 [7.62]	0.730 [18.54]	0.814 [20.68]	0.437 [11.10]	0.062 [1.57]
SG26000R000	1.350 [34.29]	0.375 [9.53]	0.300 [7.62]	0.910 [23.11]	1.000 [25.40]	0.437 [11.10]	0.062 [1.57]
SG34000R000	1.344 [34.14]	0.480 [12.19]	0.410 [10.41]	0.900 [22.86]	1.032 [26.21]	0.437 [11.10]	0.062 [1.57]
SG44000R000	1.595 [40.51]	0.480 [12.19]	0.410 [10.41]	1.140 [28.96]	1.281 [32.54]	0.437 [11.10]	0.062 [1.57]
SG50000R000	1.715 [43.56]	0.480 [12.19]	0.410 [10.41]	1.270 [32.26]	1.408 [35.76]	0.437 [11.10]	0.062 [1.57]
SG75000R000	1.775 [45.09]	0.840 [21.34]	0.770 [19.56]	1.180 [29.97]	1.375 [34.93]	0.512 [13.00]	0.062 [1.57]
SG104000R000	2.160 [54.86]	0.840 [21.34]	0.770 [19.56]	1.545 [39.24]	1.750 [44.45]	0.512 [13.00]	0.062 [1.57]

MALE
CODE P


PART NUMBER	A MAX.	B MAX.	C MIN.	D MIN.	E	F	R
SG4000P000	0.870 [22.10]	0.300 [7.62]	0.230 [5.84]	0.430 [10.92]	0.562 [14.27]	0.437 [11.10]	0.031 [0.79]
SG7000P000	0.870 [22.10]	0.300 [7.62]	0.230 [5.84]	0.430 [10.92]	0.562 [14.27]	0.437 [11.10]	0.031 [0.79]
SG14000P000	0.970 [24.64]	0.370 [9.40]	0.300 [7.62]	0.530 [13.46]	0.625 [15.88]	0.437 [11.10]	0.062 [1.57]
SG20000P000	1.160 [29.46]	0.370 [9.40]	0.300 [7.62]	0.730 [18.54]	0.814 [20.68]	0.437 [11.10]	0.062 [1.57]
SG26000P000	1.345 [34.16]	0.370 [9.40]	0.300 [7.62]	0.910 [23.11]	1.000 [25.40]	0.437 [11.10]	0.062 [1.57]
SG34000P000	1.340 [34.04]	0.480 [12.19]	0.410 [10.41]	0.900 [22.86]	1.032 [26.21]	0.437 [11.10]	0.062 [1.57]
SG44000P000	1.590 [40.39]	0.480 [12.19]	0.410 [10.41]	1.140 [28.96]	1.281 [32.54]	0.437 [11.10]	0.062 [1.57]
SG50000P000	1.710 [40.59]	0.480 [12.19]	0.410 [10.41]	1.270 [32.26]	1.408 [35.76]	0.437 [11.10]	0.062 [1.57]
SG75000P000	1.770 [44.96]	0.840 [21.34]	0.770 [19.56]	1.180 [29.97]	1.375 [34.93]	0.512 [13.00]	0.062 [1.57]
SG104000P000	2.145 [54.48]	0.840 [21.34]	0.770 [19.56]	1.545 [39.24]	1.750 [44.45]	0.512 [13.00]	0.062 [1.57]

ALUMINUM BACKSHELL

FOR USE WITH 4 TO 50 CONTACTS VARIANTS

CODE J

QUALIFIED TO MIL-DTL-28748




PART NUMBER	DIMENSIONS					CABLE OPENING	
	A	B	C	D	G	E	F
SG400000J0	0.943 [23.95]	0.750 [19.05]	0.250 [6.35]	0.780 [19.81]	0.410 [10.41]	0.255 [6.48]	0.188 [4.78]
SG700000J0	0.943 [23.95]	0.750 [19.05]	0.250 [6.35]	0.780 [19.81]	0.410 [10.41]	0.255 [6.48]	0.188 [4.78]
SG900000J0	1.087 [27.61]	0.750 [19.05]	0.272 [6.91]	0.880 [22.35]	0.550 [13.97]	0.375 [9.53]	0.190 [4.83]
SG1400000J0	1.087 [27.61]	0.750 [19.05]	0.340 [8.64]	0.886 [22.50]	0.550 [13.97]	0.375 [9.53]	0.255 [6.48]
SG2000000J0	1.087 [27.61]	0.750 [19.05]	0.340 [8.64]	1.062 [26.97]	0.550 [13.97]	0.375 [9.53]	0.250 [6.35]
SG2600000J0	1.076 [27.33]	0.750 [19.05]	0.340 [8.64]	1.250 [31.75]	0.550 [13.97]	0.406 [10.31]	0.250 [6.35]
SG2900000J0	1.087 [27.61]	0.750 [19.05]	0.340 [8.64]	1.344 [34.14]	0.550 [13.97]	0.406 [10.31]	0.250 [6.35]
SG3400000J0	1.077 [27.36]	0.750 [19.05]	0.453 [11.51]	1.250 [31.75]	0.710 [18.03]	0.750 [19.05]	0.375 [9.53]
SG4400000J0	1.527 [38.79]	1.190 [30.23]	0.450 [11.43]	1.500 [38.10]	0.710 [18.03]	0.750 [19.05]	0.380 [9.65]
SG5000000J0	1.527 [38.79]	1.190 [30.23]	0.450 [11.43]	1.620 [41.15]	0.710 [18.03]	1.000 [25.40]	0.388 [9.86]

ALUMINUM BACKSHELL WITH JACKSCREW SYSTEM

FOR USE WITH 4 TO 50 CONTACTS VARIANTS

CODE E1 (IN STEP 5) AND J (IN STEP 8)

QUALIFIED TO MIL-DTL-28748



PART NUMBER	DIMENSIONS					CABLE OPENING	
	A	B	C	D	G	E	F
SG400E100J0	1.561 [39.65]	0.750 [19.05]	0.250 [6.35]	0.780 [19.81]	0.410 [10.41]	0.255 [6.48]	0.188 [4.78]
SG700E100J0	1.561 [39.65]	0.750 [19.05]	0.250 [6.35]	0.780 [19.81]	0.410 [10.41]	0.255 [6.48]	0.188 [4.78]
SG900E100J0	1.561 [39.65]	0.750 [19.05]	0.272 [6.91]	0.880 [22.35]	0.550 [13.97]	0.375 [9.53]	0.190 [4.83]
SG1400E100J0	1.561 [39.65]	0.750 [19.05]	0.340 [8.64]	0.886 [22.50]	0.550 [13.97]	0.375 [9.53]	0.255 [6.48]
SG2000E100J0	1.561 [39.65]	0.750 [19.05]	0.340 [8.64]	1.062 [26.97]	0.550 [13.97]	0.375 [9.53]	0.250 [6.35]
SG2600E100J0	1.561 [39.65]	0.750 [19.05]	0.340 [8.64]	1.250 [31.75]	0.550 [13.97]	0.406 [10.31]	0.250 [6.35]
SG2900E100J0	1.561 [39.65]	0.750 [19.05]	0.340 [8.64]	1.344 [34.14]	0.550 [13.97]	0.406 [10.31]	0.250 [6.35]
SG3400E100J0	1.561 [39.65]	0.750 [19.05]	0.453 [11.51]	1.250 [31.75]	0.710 [18.03]	0.750 [19.05]	0.375 [9.53]
SG4400E100J0	2.001 [50.83]	1.190 [30.23]	0.450 [11.43]	1.500 [38.10]	0.710 [18.03]	0.750 [19.05]	0.380 [9.65]
SG5000E100J0	2.001 [50.83]	1.190 [30.23]	0.450 [11.43]	1.620 [41.15]	0.710 [18.03]	1.000 [25.40]	0.388 [9.86]

NOTE:

*1 M2x0.4 metric threads available, see chart on page 31.

**DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.**

FULL ACCESS ALUMINUM BACKSHELL WITH JACKSCREW SYSTEM

Hinged cover allows access to the inside of the hood while still installed on the connector

FOR USE WITH 104 CONTACTS VARIANTS

CODE Z OR CODE V

Z

TOP OPENING BACKSHELL




FIGURE 1

V

SIDE OPENING BACKSHELL




FIGURE 2

PART NUMBER	FIGURE	A	B	C	D	E	F	G	H	J
SG10400000Z0	1	2.100 [53.34]	0.812 [20.62]	1.750 [44.45]	2.100 [53.34]	0.500 [12.70]	0.860 [21.84]	1.110 [28.19]	2.645 [67.18]	–
SG10400000V0	2	2.100 [53.34]	0.812 [20.62]	1.750 [44.45]	2.100 [53.34]	0.500 [12.70]	0.860 [21.84]	1.110 [28.19]	2.645 [67.18]	1.050 [26.67]

NOTE:


*1 M3x0.5 metric threads available, see chart on page 31.

QUICK DISCONNECT LOCKING DEVICE

CODE V OR VL

V


LOCKING TABS



TYPICAL PART NUMBER:
SGMC14S0N000V

VL

ACTUATION LOCK LEVER ASSEMBLY



TYPICAL PART NUMBER:
SGMC14M0N000VL

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

APPLICATION TOOLS SECTION

*SGMC connectors are offered with **removable crimp contacts**.*



*Positronic recognizes the **importance of** supplying **application tooling** to support our customers' use of our products. Information on application tooling is **available** on our web site at*



https://www.connectpositronic.com/tooling/

*There you will find **downloadable PDF** cross reference charts for removable and compliant press-in contacts. These charts will **supply part numbers** for insertion, removal and crimping tools, along with **information regarding use** of tools and techniques.*

Connectors Designed To Customer Specifications

*Positronic **SGMC, SGM and SMPL series** connectors can be modified to customer specifications.*

Examples: select loading of contacts for cost savings or to gain creepage and clearance distances; longer printed circuit board terminations; customer specified hardware.

Contact Technical Sales with your particular requirements.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.

CONTACT APPLICATION TOOLS CROSS REFERENCE LIST


USE INDICATED POSITRONIC TOOLS FOR BEST RESULTS


Positronic Contact P/N	Handle & Positioner P/N	Hand Crimp Tool P/N	Mfg. Cross	Mil Equiv	Positioner	Mfg. Cross	Mil Equiv	Insertion Tool	Mfg. Cross	Mil Equiv	Removal Tool	Mfg. Cross	Mil Equiv
FC420P2	---	9507-0-0-0	AFM8	M22520/2-01	9502-13-0-0	K280	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FC422P2	---	9507-0-0-0	AFM8	M22520/2-01	9502-13-0-0	K280	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FC422P2** Thermocouple	---	9507-0-0-0	AFM8	M22520/2-01	9502-13-0-0	K280	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FDS425P2	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FDS456P2	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FDS487P2	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FPF467P2	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FS420P2	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
FS422P2	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
M39029/34-440	---	9507-0-0-0	AFM8	M22520/2-01	9502-12-0-0	K187	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
M39029/35-441	---	9507-0-0-0	AFM8	M22520/2-01	9502-13-0-0	K280	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MC420N	---	9507-0-0-0	AFM8	M22520/2-01	9502-12-0-0	K187	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MC422N	---	9507-0-0-0	AFM8	M22520/2-01	9502-12-0-0	K187	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MC422N** Thermocouple	---	9507-0-0-0	AFM8	M22520/2-01	9502-12-0-0	K187	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MDS425N	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MDS456N	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MDS487N	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MPF467N	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MS420N	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---
MS422N	---	---	---	---	---	---	---	9099-1-0-0	ITH 1056	M81969/18-02	9081-1-0-0	RTCO 2061	---

COMPLIANT PRESS-IN CONNECTOR INSTALLATION TOOLS

USE INDICATED POSITRONIC TOOLS FOR BEST RESULTS

Positronic offers expert assistance in adapting application tooling to your manufacturing environment. Contact our application tooling specialist for assistance.




Arbor Press

POSITRONIC RECOMMENDED TOOLS FOR COMPLIANT PRESS-IN CONNECTORS AND CONTACTS

CONNECTOR VARIANT (NUMBER OF CONTACTS)	SUPPORT TOOL	CONNECTOR SEATING TOOL WITH ARBOR PRESS SHAFT		CONNECTOR SEATING TOOL WITHOUT ARBOR PRESS SHAFT		ARBOR PRESS FOR SEATING TOOLS
		FEMALE P / N	MALE P / N	FEMALE P / N	MALE P / N	
4	9513-40-4-41	9513-42-4-41	9513-41-4-41	9513-44-4-41	9513-43-4-41	Use p / n **9530-1-0** 1 ton capacity 4 inch throat
5	9513-40-5-41	9513-42-5-41	9513-41-5-41	9513-44-5-41	9513-43-5-41	
7	9513-40-7-41	9513-42-7-41	9513-41-7-41	9513-44-7-41	9513-43-7-41	
9	9513-40-9-41	9513-42-9-41	9513-41-9-41	9513-44-9-41	9513-43-9-41	
11	9513-40-11-41	9513-42-11-41	9513-41-11-41	9513-44-11-41	9513-43-11-41	
14	9513-40-14-41	9513-42-14-41	9513-41-14-41	9513-44-14-41	9513-43-14-41	
20	9513-40-20-41	9513-42-20-41	9513-41-20-41	9513-44-20-41	9513-43-20-41	
26	9513-40-26-41	9513-42-26-41	9513-41-26-41	9513-44-26-41	9513-43-26-41	
29	9513-40-29-41	9513-42-29-41	9513-41-29-41	9513-44-29-41	9513-43-29-41	
34	9513-40-34-41	9513-42-34-41	9513-41-34-41	9513-44-34-41	9513-43-34-41	
44	9513-40-44-41	9513-42-44-41	9513-41-44-41	9513-44-44-41	9513-43-44-41	
50	9513-40-50-41	9513-42-50-41	9513-41-50-41	9513-44-50-41	9513-43-50-41	

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.


SUGGESTED PRINTED BOARD HOLE SIZES FOR COMPLIANT PRESS-IN CONNECTORS

Traditionally, tin-lead has been a popular plating for printed circuit boards (PCB) holes. However, many PCB hole platings must now be RoHS Compliant. Positronic is pleased to offer **PCB HOLE SIZE FOR RoHS** PCB plating as shown below.

OMEGA COMPLIANT PRESS-IN CONTACT HOLE				
BOARD TYPE	**CONTACT SIZE / TYPE**	**RECOMMENDED DRILL HOLE SIZE**	**RECOMMENDED PLATING**	**FINISHED HOLE SIZES**
TIN-LEAD SOLDER PCB	**22 OMEGA**	ø0.0453±0.0010 [ø1.150±0.025]	0.0006 [15µ] minimum solder over 0.0010 [25µ] min. copper	ø0.0394+0.0035-0.0024 [ø1.000+0.090-0.060]
RoHS PCB PLATING OPTIONS				
COPPER PCB	**22 OMEGA**	ø0.047±0.001 [ø1.19±0.025]	0.0010 [25µ] min. copper	ø0.043±0.002 [ø1.09±0.05]
IMMERSION TIN PCB	**22 OMEGA**	ø0.047±0.001 [ø1.19±0.025]	0.000033±0.000006 [0.85±0.15µ] immersion tin over 0.0010 [25µ] min. copper	ø0.043±0.002 [ø1.09±0.05]
IMMERSION SILVER PCB	**22 OMEGA**	ø0.047±0.001 [ø1.19±0.025]	0.000013±0.000007 [0.34±0.17µ] immersion silver over 0.0010 [25µ] min. copper	ø0.043±0.002 [ø1.09±0.05]
ELECTROLESS NICKEL / IMMERSION GOLD PCB	**22 OMEGA**	ø0.047±0.001 [ø1.19±0.025]	0.000002 [0.05µ] min. immersion gold over 0.000177±0.000059 [4.5±1.5µ] electroless nickel per IPC-4552 over 0.0010 [25µ] min. copper	ø0.043±0.002 [ø1.09±0.05]

"Omega" Termination
utilized on signal contacts





COMPLIANT PRESS-IN TERMINATION CONTACT HOLE

NOTE: For PCB plating compositions not shown, consult Technical Sales.

COMPLIANT PRESS-IN USER INFORMATION

When properly used, Positronic omega compliant press-in terminations provide reliable service even under severe conditions.

Connectors utilizing this leading technology compliant press-in contact are easy to install:

1. Inexpensive installation tooling is available from Positronic, to choose the proper installation tool refer to page 39 for part number ordering information.
2. Insert the connector into the P.C. board or backplane and seat connector fully.
3. Secure the connector to the P.C. board or backplane with supplied hardware.

MODIFICATION (MOS) SUFFIXES

Specify complete connector by selecting a base part number from the desired series **Ordering Information Page**.
Once base part number is selected, add desired modifications (MOS) number below to the end of the part number.

Example part number: SMPL34M0T0LB/AA-14-293.2 ***(Ordering information pages* can be found at the end of each series)**

SERIES	CONNECTOR VARIANT	GENDER	TERMINATION TYPE AVAILABLE	MODIFICATION OF STANDARD (MOS) SUFFIXES	DESCRIPTION OF MODIFICATION
SGMC SGM SMPL	ALL	F / M	ALL	**-14**	Allows connector with contacts installed, for contacts only to be plated 0.000030 [0.76 µ] gold over nickel.
SGMC SGM SMPL	ALL	F / M	ALL	**-15**	Allows connector with contacts installed, for contacts only to be plated 0.000050 inch [1.27µ] gold over nickel.
SGMC SGM SMPL	ALL	F / M	ALL	**-293.2**	Allows connector with any polarizing jackscrews to be supplied with jack-screw positions reversed.
SGMC	ALL	F / M	ALL	**-650.0**	Allows connector with any hardware to be supplied with MC422N or FC422P2 contacts kitted.
SGM	ALL	F / M	DS3, DS4, DS5, DS6	**-672.0**	Allows connector with straight solder contacts to have standard nylon hex nut and washer replaced with stainless steel hex nut and washer.
SGM	4, 5, 7, 9, 11, 14, 20, 26, 29, 34, 44, and 50	F / M	ALL	**-756.2**	Allows connector to be supplied with special length “ESS” jackscrews.
SGMC SGM	ALL	F / M	ALL	**-793.4**	Allows connector to be supplied with special rotating jackscrews with 0.078 [1.98] hex socket head.
SGMC SGM SMPL	ALL	F / M	ALL	**/AA**	Allows connector for environmental compliance per EU Directive 2002/95/EC (RoHS).

MANY OTHER SPECIAL OPTIONS ARE AVAILABLE CONSULT TECHNICAL SALES OR VISIT OUR WEB SITE AT WWW.CONNECTPOSITRONIC.COM

Connectors Designed To Customer Specifications

*Positronic **SGMC, SGM and SMPL series** connectors can be modified to customer specifications.*

Examples: select loading of contacts for cost savings or to gain creepage and clearance distances; longer printed circuit board terminations; customer specified hardware.

Contact Technical Sales with your particular requirements.

DIMENSIONS ARE IN INCHES [MILLIMETERS].
ALL DIMENSIONS ARE SUBJECT TO CHANGE.



Positronic® offers a variety of QPL connector products

RECTANGULAR CONNECTORS

MIL PREFIX	POSITRONIC SERIES
MIL-DTL-28748/3	GMCT
MIL-DTL-28748/4	GMCT
MIL-DTL-28748/5	GM
MIL-DTL-28748/6	GM
MIL-DTL-28748/7	SGM

MIL PREFIX	POSITRONIC SERIES
MIL-DTL-28748/8	SGM
MIL-C-28748/13	SGMC
MIL-C-28748/14	SGMC
SAE AS39029/34	SGMC, GMCT
SAE AS39029/35	SGMC, GMCT

D-SUBMINIATURE CONNECTORS

MIL PREFIX	POSITRONIC SERIES
MIL-DTL-24308/1	HDC
MIL-DTL-24308/2	RD, DD
MIL-DTL-24308/3	HDC
MIL-DTL-24308/4	RD, DD
MIL-DTL-24308/5	HDC
MIL-DTL-24308/6	RD, DD
MIL-DTL-24308/7	HDC
MIL-DTL-24308/8	RD, DD
MIL-DTL-24308/23	HDC, DD

MIL PREFIX	POSITRONIC SERIES
MIL-DTL-24308/24	HDC, DD
MIL-DTL-24308/25	HDC, RD, DD
MIL-DTL-24308/26	HDC, RD, DD
GSFC S-311-P4	SND, SDD, SCBC, SCBM
GSFC S-311-P10	SND, SCBM
SAE AS39029/57	DD
SAE AS39029/58	DD
SAE AS39029/63	RD
SAE AS39029/64	RD

For a complete QPL listing available to download in PDF format,
select 'SUPPORT' on the menu bar and pull to "QPL" on our website at:

www.connectpositronic.com

or enter the URL link below to download the QPL PDF file immediately!

https://www.connectpositronic.com/qpl/

LOCATIONS

Positronic®

THE SCIENCE OF CERTAINTY

Regional Headquarters

Positronic | Americas
423 N Campbell Ave
Springfield MO 65806 USA

+1 800 641 4054
info@connectpositronic.com

Positronic | Europe
Z.I. d'Engachies
46, route d'Engachies
F-32020 Auch Cedex 9 France

+33 5 6263 4491
contact@connectpositronic.com

Positronic | Asia
3014A Ubi Rd 1 #07-01
Singapore 408703

+65 6842 1419
singapore@connectpositronic.com

Sales Offices
Positronic has local sales representation all over the world. To find the nearest sales office, please visit **www.connectpositronic.com/locations**

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Positronic:

SGM11MSCESS0000 SGM11MSCN0000 SGM11MSCT0000/AA SGM14SDS3NSS0000 SGM14SSCN0000 SGM20MDS4N0000 SGM20MSCE0000 SGM20SDS6N0000-538.0 SGM20SDS6T0000 SGM26SSCE0000 SGM29MSCE0000 SGM44MSCE0000 SGM4MSCE0000 SGM4SSCE0000 SGM50MSCE0000 SGM50MSCE100J0 SGM50SDS6NSS0000 SGM7SSCESS0000/AA SGM7SSCT0000/AA SGM9MSCE0000 SGM9MSCT0000/AA SGM9SDS6T0000-538.0 SGM9SSCT0000 SGMC104M0EP000 SGMC14M0E0000 SGMC14M0N0000 SGMC14M0T0000 SGMC14M0T0000/AA SGMC14S0E0000 SGMC14S0E0000/AA SGMC14S0E100J0 SGMC20M000000 SGMC20M0E1P0J0 SGMC20M0T0000 SGMC20S0E0000 SGMC20S0E100J0/AA SGMC20S0T0000/AA SGMC34M0T0000/AA SGMC34S0T0000 SGMC44M0E100J0/AA SGMC4M0ESS0000/AA SGMC4M0T0000 SGMC50M0ESS0000 SGMC50M0T0000 SGMC50S0E100J0/AA SGMC50S0ESS0000 SGMC75M0E0000 SGMC7M0E0000 SGMC7S0E0000 SMPL14M0T0LB SMPL29M0000/AA-50 SMPL34S0T0LB SMPL44M0NSS0LB SMPL4M0T0LB SMPL50M0N0LB SMPL7M0T0LB SMPL7S0T0LB/AA SMPL9S0T0LB

Other:

SGM5SDS6T0000/AA SGM5SSCE0000 SGMC26M0T0000/AA SGMC26S0E0000/AA SGMC7S0T0000 SGMC9M0E100J0 SGM11MSCE0000/AA SGM11SDS4E0000 SGM14MDS6N0000 SGM14SDS6N0000 SGM14SSC00000 SGM14SSCE100J0 SGM20SDS300000 SGM29SDS4T0000 SGM34MDS600000 SGM34MSCESSP0J0/AA SGM9MDS6N0000 SGM9SDS6N0000 SGM9SSCNSS0000 SGMC104M0NSS0000 SGMC104S0NSS0000 SGMC20M0NSS0000 SGMC26M0NSSP000 SGMC34S0TRB0R/AA SGMC44M0E1PBJR/AA SGMC44M0NSS0000 SGMC44S0E0000 SGMC50S0TR000/AA SGMC75M0NSS0000 SGMC75S0NSS0000 SGMC7M0T00J0 SMPL5S0T0LB/AA

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP