

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.


- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PERFORMANCE MADE SMARTER



Ex repeater / power supply

5104B

- 1- or 2-channel version
- 3- / 5-port 3.75 kVAC galvanic isolation
- Loop supply > 17.1 V in hazardous area
- 20 programmable measurement ranges
- Universal supply by AC or DC


Application
- Supply voltage and safety barrier for 2-wire transmitters mounted in a hazardous area.
- Safety barrier for analog current / voltage signals from a hazardous area.
- 1 : 1 or signal conversion of analog current / voltage signals.

Technical characteristics
- The 20 factory-calibrated measurement ranges in the 5104B can be selected by the internal DIP-switches without the need for recalibration. Special measurement ranges can be delivered.
- PR5104B is based on microprocessor technology for gain and offset. The analog signal is transmitted at a response time of less than 25 ms.
- Inputs, outputs, and supply are floating and galvanically separated.
- The output can be connected either as an active current / voltage transmitter or as a 2-wire transmitter.

Mounting / installation
- Mounted vertically or horizontally on a DIN rail. By way of the 2-channel version up to 84 channels per meter can be mounted.

Note
- Not suitable for new installations requiring certification to the latest ATEX standards - see ATEX certificate DEMKO 99ATEX126013 and Declaration of conformity for details.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order :

Type	Input		Output		Channels	
5104B	0…20 mA	: A	Special	: 0	Single	: A
	4…20 mA	: B	0…20 mA	: 1	Double	: B
	0…10 V	: E	4…20 mA	: 2		
	2…10 V	: F	0…1 V	: 4		
	Special	: X	0.2…1 V	: 5		
			0…10 V	: 6		
			2…10 V	: 7		

Environmental Conditions

Operating temperature..... -20°C to +60°C
Calibration temperature..... 20...28°C
Relative humidity..... < 95% RH (non-cond.)
Protection degree..... IP20

Mechanical specifications

Dimensions (HxWxD)..... 109 x 23.5 x 130 mm
DIN rail type..... DIN 46277
Weight approx..... 225 g
Wire size..... 1 x 2.5 mm^2 stranded wire
Screw terminal torque..... 0.5 Nm
Vibration..... IEC 60068-2-6
2...13.2 Hz..... ±1 mm
13.2...100 Hz..... ±0.7 g

Common specifications

Supply

Supply voltage, universal..... 21.6...253 VAC, 50...60 Hz or 19.2...300 VDC
Fuse..... 400 mA SB / 250 VAC
Max. required power..... ≤ 3 W (2 channels)
Internal power dissipation..... ≤ 2 W (2 channels)

Isolation voltage

Isolation voltage, test / working..... 3.75 kVAC / 250 VAC
PELV/SELV..... IEC 61140

Auxiliary supplies

2-wire supply (pin 44...42 and 54...52)..... 28...17.1 VDC / 0...20 mA

Response time

Response time (0...90%, 100...10%)..... < 25 ms
Signal / noise ratio..... Min. 60 dB (0...100 kHz)
Accuracy..... Better than 0.1% of sel. range
EMC immunity influence..... < ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst..... < ±1% of span

Input specifications

Common input specifications

Max. offset..... 20% of max. value

Current input

Measurement range..... 0...20 mA
Min. measurement range (span)..... 16 mA
Input resistance..... Nom. 10 Ω + PTC 10 Ω

Voltage input

Measurement range..... 0...10 VDC
Min. measurement range (span)..... 8 VDC
Input resistance..... > 2 MΩ

Output specifications

Current output

Signal range..... 0...20 mA
Min. signal range..... 16 mA
Load (@ current output)..... ≤ 600 Ω
Load stability..... ≤ 0.01% of span / 100 Ω
Current limit..... ≤ 28 mA

Passive 2-wire mA output

Effect of external 2-wire supply voltage variation..... < 0.005% of span / V

Voltage output

Signal range..... 0...1 VDC / 0...10 VDC
Min. signal range..... 0.8 VDC / 8 VDC
Load (@ voltage output)..... ≥ 500 kΩ
External loop supply..... 29 VDC
of span..... = of the presently selected range

Observed authority requirements

EMC..... 2014/30/EU
LVD..... 2014/35/EU
EAC..... TR-CU 020/2011

Approvals

ATEX..... DEMKO 99ATEX126013, II (1) GD [EEx ia] IIC
c UL us, UL 913..... E233311
EAC Ex..... EAEU KZ 7500361.01.01.08756
DNV Marine..... TAA0000101

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP