

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

4210A Rubidium Frequency Standard

10MHz Rubidium Frequency Reference
1PPS Disciplining i/p Standard
Ultra Low Phase Noise (-130dBc at 10Hz)
RS 232 Monitor/Control
Convenient 2U bench or 19" rack mount



The ***ptf*** 4210A Rubidium Frequency Standard is a unique solution for providing a highly stable, low phase noise, frequency reference for applications requiring atomic reference stability performance.

The instrument contains a high performance rubidium module, with an extended life design, and very low aging rate, with high quality OCXO o/p for low phase noise.

For even better long term stability the unit will accept a 1PPS input that can be derived from a reference such as caesium or GPS.

An ideal laboratory or system frequency reference, which includes a range of options are available to enhance the functionality of the unit.

Specifications subject to change without notice

4210A Rubidium Frequency Standard

Specifications

Electrical

Output Level (standard)

10MHz	0.5 vrms into 50Ω
1PPS	5 v CMOS ±20 mA sink/source

Output Level (w/MOPS Option)

1MHz	1.0 vrms into 50Ω +13dBm ±1dBm
5MHz	1.0 vrms into 50Ω +13dBm ±1dBm
10MHz	1.0 vrms into 50Ω +13dBm ±1dBm
1PPS	4.2 v CMOS into 50Ω

Stability

Short-term:	1s	2E-11
	10s	1E-11
	100s	2E-12

Aging <5 E-11/month (after 30 days)
<5 E-10/year

Accuracy 5E-11 (at shipment)

Phase Noise, 1Hz b/w,

Offset from carrier	Phase Noise (dBc)
10Hz	-130
100Hz	-140

Spurious -130 dBc (100kHz bw)

Environmental & Physical

Power Requirements

AC Input (±15%)	120 or 230 VAC, <10W
DC Input (optional)	20 to 70 VDC, 10W

Dimensions

(HxWxD)	2U x 19” x 12”

Configuration Options

Option Description	Option #
Multiple RF Ouputs (1MHz, 5MHz, 10MHz)	MOPS
Front Panel Outputs	FPOC
1MHz Sinewave Output (X4)	RF01
5MHz Sinewave Output (X4)	RF05
10MHz Sinewave Output (X4)	RF10
Pulse Distribution (X4)	PULS
T1/ E1 Distribution (X4)	TELC
DC Power Supply	DCPS
Custom Options Available	



ptf 4210A rear view (w/MOPS option)

Specifications subject to change without notice

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP