ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *Protek 3003B* at our website: *Click HERE*

1805 Single Output Power Supply

- 0 to ±18 Volts with 0 to ±5Amps load current
- Excellent Load, Line and Ripple specs
- Fully Isolated outputs terminals
- 3 digit Led displays for both current and Voltage
- Small case size
- Front panel Indicators for constant current and constant voltage operation
- Short circuit and Reverse Voltage protected

3003B Single Output Power Supply

- 0 to ±30V with 0 to ±3 Amps Load current
- Constant Voltage and Constant current operation
- Units can be connected together in series for Higher output voltage
- Course and Fine controls for accurate Voltage settings
- Low noise and Linear supply for powering sensitive circuits
- Front panel push button switch disconnects power supply from Load



1805



3003B

SPECIFICATIONS

[1805]

Output Volts: 0 to ±18V DC
Output Amps: 0 to ±5A
Constant Voltage Mode:
Load Regulation: 0.05% + 5.6mV
Line Regulation: 0.05% + 5.6mV
Ripple and Noise: 0.5mV RMS
Constant Current Mode:
Load Regulation: 0.05% + 20mA
Line Regulation: 0.05% + 8mA
Ripple and Noise: 5mA RMS
Digital Display:
Type: 3 digit red LED
Resolution: Volts: 100mV; Amps: 10mA
Accuracy: Volts: ±(0.2% + 2d); Current: ±(1% + 3d)

General Specifications
AC Input Voltage: 120/220V selectable
Power Consumption: 170VA
Operating Temperature: 0 to 32°C (32 to 90°F)
Size: 6.3" (H) x 5.0" (W) x 13.0" (D)
Weight : 15 lbs
Supplied Accessories: Manual, Line cord, Test leads

[3003B]

Output Volts:
0 to ±30 V DC
Output Amps:
0 to ±3 Amps
Constant Voltage Mode:
Load and Line Regulation: 0.02% + 2mV
Ripple and Noise: 1mV RMS
Constant Current Mode:
Load Regulation: 0.05% + 5mA
Line Regulation: 0.05% + 0.25mA
Ripple and Noise: 2mA RMS
Digital Display Resolution:
Volts: 100mV; Amps: 10mA
Accuracy: ±(0.5% + 3d)

General Specifications
AC Input Voltage: 120/220V selectable
Power Consumption: 190VA
Operating Temperature: 0 to 32°C (32 to 90°F)
Size: 6.3" (H) x 5.0" (W) x 13.0" (D)
Weight : 15 lbs
Supplied Accessories: Manual, Line cord, Test leads

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP