

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

PRL-4505 1:8 DIFFERENTIAL FANOUT BUFFER SYSTEM, NECL AND TTL INPUTS, RS-422 OUTPUTS

APPLICATIONS

- Long Line Driver/Level Translator
- Reference Clock Distribution/Translation
- 1 PPS/IRIG-B Signal Distribution
- Test and System Integration



PRL-4505 Front View



PRL-4505 Rear View

FEATURES

- 1:8 Fanout with RS-422 Outputs
- Channel-to-channel Skew < 200 ps
- Unit-to-unit Skew < 300 ps[3]
- t_R= 1.6 ns Typ. @ 1.6 V Output into 50 Ω
- Back-terminated Differential 124 Ω Outputs Drive Long Lines into floating 124 Ω
- TTL and NECL Inputs (logically ORed)
- NECL Input can be driven differentially, single-ended, or AC-coupled for sinewave conversion
- Standard 19-in. Rack-Mount Chassis with optional slide rails

GENERAL DESCRIPTION

The PRL-4505 is a low-skew, 1:8 differential fanout buffer system with 8 RS-422 outputs and two inputs. The single-ended TTL input has a selectable 50 Ω or 1 KΩ to ground termination. The NECL input can be driven by single-ended NECL, differential NECL or AC-coupled sinewave signals. The TTL and NECL inputs are logically ORed; therefore a Hi level applied to either input can be used as a gate signal.

For the NECL input a toggle switch selects either single-ended or differential inputs. In the differential input mode both the NECL and $\overline{\text{NECL}}$ inputs and are terminated internally into 50 Ω/-2 V, and, therefore, either one or both inputs can accept AC-coupled signals as well.

In the single input mode, signal should be connected to the NECL input only. The $\overline{\text{NECL}}$ input is switched internally to V_{BB}, nominally -1.3 V, and termination resistor R_T for the $\overline{\text{NECL}}$ input channel is changed to a Hi Z value. In the single-input mode, therefore, the $\overline{\text{NECL}}$ input should not be used for receiving signals. If the NECL inputs are not connected to an active signal, the switch should be in the down position.

The input resistance of the TTL input can be selected to be either 50 Ω or 1 KΩ by a toggle switch. The 1 KΩ input is desirable when interfacing with low power circuits. The TTL input threshold voltage is 1.0 V minimum. When over-driven, the input voltage to the internal circuit is limited to 3.5 V through a current limiting 25 Ω series resistor.

The output swing is typically $2.3V_{PP}$ with a 1.1 V_{CMV} into a 124 Ω floating load.


All I/Os are DC coupled and have SMA connectors at the rear panel of the unit. The PRL-4505 is housed in a standard 19-in. rack-mountable enclosure with optional slide rails, powered by an internal power supply switchable for 120/240 VAC, 50-60 Hz operation.

1234 Francisco Street, Torrance, CA 90502
Tel: 310-515-5330 Fax: 310-515-0068
Email: sales@pulseresearchlab.com
www.pulseresearchlab.com

*SPECIFICATIONS (0 °C ≤ T_A ≤ 35 °C)

Unless otherwise specified, dynamic measurements are made with all rear-panel outputs terminated into floating 124 Ω, using precision-trimmed 18.0", phase-stable 50 Ω RF cables. Propagation delay measurements are made using a PRL-425T Differential Receiver with TTL outputs, and waveform measurements are made via either a PRL-860D 10X Differential Pickoff Tee, or a 50 Ω-input scope. Due to lack of suitable equipment with floating differential 124 Ω input termination, T_R and T_F are measured using a 50 Ω input scope

SYMBOL	PARAMETER	Min	Typ	Max	UNIT	Comment
R_{T1-1}	Input Resistance, NECL	49.5	50.0	50.5	Ω	Differential Input mode
R_{T2-1}	Input Resistance, TTL 50 Ω	49	50	51	Ω	
R_{T2-2}	Input Resistance, TTL 1 KΩ	0.95	1.00	1.05	KΩ	
V_{TT}	D Input Termination Voltage	-2.2	-2.0	-1.8	V	NECL input
V_{T1}	Input Termination Voltage	-1.25	-1.30	-1.35	V	Single-ended mode
V_{T2}	Input Termination Voltage	-2.20	-2.00	-1.80	V	Differential mode
V_{IH1}	TTL Input Hi Level	1.0		5.0	V	Internally limited to 3.5 V
V_{IL1}	TTL Input Lo Level	-0.5		0.5	V	
V_{IH2}	NECL Input Hi Level	-1.13	-0.90	-0.81	V	
V_{IL2}	NECL Input Lo Level	-1.95	-1.60	-1.48	V	
R_{OUT1}	Output Resistance	61.4	62	62.6	Ω	Single-ended
R_{OUT2}	Output Resistance	122.8	124	125.2	Ω	Differential
V_{OH1}	Output High Level		3.6		V	No Load
V_{OH2}	Output High Level	2.2	2.4	2.6	V	Terminated to 124 Ω
V_{OL1}	Output Low Level		-1		V	No Load
V_{OL}	Output Low Level	-0.1	0.1	0.25	V	Terminated to 124 Ω
V_{AC1}	AC Input Voltage, 120	108	115	127	V	
V_{AC2}	AC Input Voltage, 220	216	230	254	V	
V_{VA}	AC Input Power		28	31	VA	
T_{PROP1}	Prop. Delay to Output ↑, Diff. NECL Input	5.73	5.88	6.03	ns	See Notes 1, 2
T_{PROP2}	Prop. Delay to Output ↑, TTL Input, 50 Ω	5.82	5.97	6.12	ns	See Notes 1, 2
T_R	Rise Time (10%-90%)		1.6	2.2	ns	
T_F	Fall Time (10%-90%)		1.6	2.2	ns	
T_{SKEW1}	Ch./Ch. skew between any 2 True Outputs		100	200	ps	See Notes 1, 2
T_{SKEW2}	Unit/Unit skew between any 2 True Outputs		150	300	ps	See Notes 1, 2, 3
F_{MAX}	Max Clock Frequency	150	175		MHz	
	Size	19.0"W x 3.5"H x 16.5"D			in	Excluding slide rails
	Weight	13			lbs	



PRL-4505 Block Diagram (simplified)

Notes:

1. Skew measurements valid when using same input logic level. TTL-input measurements made with TTL input set to 50 Ω. ECL-input measurements made with ECL input set for differential mode.
2. T_{PROP} and T_{SKEW} measurements made via PRL-8505 Test Mux, which provides 50 MHz input clocks in ECL and TTL logic as well as a differential receiver and delay-matched ECL and TTL reference timing paths.
3. Unit-to-unit skew specification valid only for units within a single lot, purchased on a single PO.

1234 Francisco Street, Torrance, CA 90502
Tel: 310-515-5330 Fax: 310-515-0068
Email: sales@pulseresearchlab.com
www.pulseresearchlab.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP