



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com

Thermo Scientific Revco Elite Freezers

Our Revco Elite freezers are built to meet high standards for performance and safety. They feature microprocessor controls, alarm/monitor systems and rugged cabinet construction found throughout our entire freezer product line. Maximize the value of your freezer with our intelligent rack solutions and accessories.



Control System

- Microprocessor control system with touchpad data entry and digital display of all functions
- Key-operated switch for main power and alarm
- Independent operating temperature and high/low limit alarm functions with factory-set defaults for quick start-up, all setpoints adjustable in 1°C increments

Electrical System

- On-board power monitoring with digital readout of incoming line voltage
- Optional free-standing surge suppressor minimizes effect of voltage spikes from incoming electrical service



Alarm System

- A.I.M. (Automatic Incident Monitor) identifies any temperature deviation beyond alarm setpoints, with rapid flash for current event, slow flash if event was self-corrected; A.I.M. archives most deviated temperature
- Adjustable safety alarm with automatic, continuous charge battery backup provides full alarm function in case of power failure
- Power failure or temperature deviation triggers audible and visual warning
- Digital battery indicator displays battery capacity; flashing low battery indicator advises when to replace battery

- Touchpad alarm test function physically warms internal probe to simulate alarm condition
- RS-232 data port with system software package
- Exterior alarm contacts for connection to remote monitoring system

Monitoring System

- Voltage boost indicator advises of low source voltage below safe parameters and indicates voltage boost system is activated
- Clean filter indicator light advises when to remove and wash condenser filter



Revco Elite Upright Freezers

Temperature Range: -50°C to -86°C

Model No.	Cu.Ft. (L)	Electrical	Amps/ Breaker (Plug)	Interior Dimensions* H x D x W inches (mm)	Exterior Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
ULT-1386-5-A	13.4 (379)	115V 60Hz 1Ø	16/20 (P2)	50.5 x 19.5 x 23.5 (1280 x 500 x 600)	77.5 x 31.3 x 37.1 (1970 x 796 x 942)	655 (297)
ULT-1386-5-D	13.4 (379)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1386-5-V	13.4 (379)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1386-5-W	13.4 (379)	230V 50Hz 1Ø	12/13 (P8)			

Revco Elite Chest Freezers

Temperature Range: -50°C to -86°C

Model No.	Cu.Ft. (L)	Electrical	Amps/ Breaker (Plug)	Interior Dimensions* H x D x W inches (mm)	Exterior Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
ULT-390-5-A	3.1 (88)	115V 60Hz 1Ø	16/20 (P2)	17.0 x 17.0 x 19.0 (430 x 430 x 480)	44.5 x 29.9 x 30.2 (1156 x 760 x 766)	415 (188)
ULT-390-5-D	3.1 (88)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-390-5-V	3.1 (88)	230V 50Hz 1Ø	12/16 (P7)			
ULT-390-5-W	3.1 (88)	230V 50Hz 1Ø	12/13 (P8)			
ULT-790-5-A	6.8 (193)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 23.5 (670 x 480 x 600)	41.0 x 31.8 x 48.5 (1040 x 808 x 1230)	525 (238)
ULT-790-5-D	6.8 (193)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-790-5-V	6.8 (193)	230V 50Hz 1Ø	12/16 (P7)			
ULT-790-5-W	6.8 (193)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1090-5-A	10.3 (292)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 32.25 (670 x 480 x 900)	41.0 x 31.8 x 60.25 (1040 x 808 x 1530)	680 (308)
ULT-1090-5-D	10.3 (292)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1090-5-V	10.3 (292)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1090-5-W	10.3 (292)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1490-5-A	13.7 (388)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 47.0 (670 x 480 x 1190)	41.0 x 31.8 x 72.0 (1040 x 808 x 1830)	650 (295)
ULT-1490-5-D	13.7 (388)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1490-5-V	13.7 (388)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1490-5-W	13.7 (388)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1790-5-A	17.1 (484)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 58.75 (670 x 480 x 1490)	41.0 x 31.8 x 83.75 (1040 x 808 x 2130)	770 (350)
ULT-1790-5-D	17.1 (484)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1790-5-V	17.1 (484)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1790-5-W	17.1 (484)	230V 50Hz 1Ø	12/13 (P8)			
ULT-2090-5-A	20.5 (580)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 70.5 (670 x 480 x 1790)	41.0 x 31.8 x 95.5 (1040 x 808 x 2430)	940 (427)
ULT-2090-5-D	20.5 (580)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-2090-5-V	20.5 (580)	230V 50Hz 1Ø	12/16 (P7)			
ULT-2090-5-W	20.5 (580)	230V 50Hz 1Ø	12/13 (P8)			

*All dimensions and specifications subject to change without notice. External dimensions include allowances for cabinet door, hinges, latches, handles, and control panel protrusions.

Thermo Scientific Revco Freezers

Revco Elite Upright Freezers

Temperature Range: -10°C to -40°C						
Model No.	Cu.Ft. (L)	Electrical	Amps/ Breaker (Plug)	Interior Dimensions* H x D x W inches (mm)	Exterior Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
ULT-1340-5-A	13.4 (379)	115V 60Hz 1Ø	16/20 (P2)	50.5 x 19.5 x 23.5 (1280 x 500 x 600)	77.5 x 31.3 x 37.1 (1970 x 796 x 942)	595 (270)
ULT-1340-5-D	13.4 (379)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1340-5-V	13.4 (379)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1340-5-W	13.4 (379)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1740-5-A	17.2 (487)	115V 60Hz 1Ø	16/20 (P2)	50.5 x 25 x 23.5 (1280 x 640 x 600)	77.5 x 36.8 x 37.1 (1970 x 935 x 942)	630 (286)
ULT-1740-5-D	17.2 (487)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1740-5-V	17.2 (487)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1740-5-W	17.2 (487)	230V 50Hz 1Ø	12/13 (P8)			
ULT-2140-5-A	20.2 (572)	115V 60Hz 1Ø	16/20 (P2)	50.5 x 24.25 x 28.5 (1280 x 620 x 720)	77.5 x 36.1 x 42.2 (1970 x 91 x 1070)	680 (309)
ULT-2140-5-D	20.2 (572)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-2140-5-V	20.2 (572)	230V 50Hz 1Ø	12/16 (P7)			
ULT-2140-5-W	20.2 (572)	230V 50Hz 1Ø	12/13 (P8)			
ULT-2540-5-A	24.4 (691)	115V 60Hz 1Ø	16/20 (P2)	50.5 x 24.25 x 34.5 (1280 x 620 x 880)	77.5 x 36.1 x 48.1 (1970 x 916 x 1222)	770 (350)
ULT-2540-5-D	24.4 (691)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-2540-5-V	24.4 (691)	230V 50Hz 1Ø	12/16 (P7)			
ULT-2540-5-W	24.4 (691)	230V 50Hz 1Ø	12/13 (P8)			

Revco Elite Chest Freezers

Temperature Range: -10°C to -40°C						
Model No.	Cu.Ft. (L)	Electrical	Amps/ Breaker (Plug)	Interior Dimensions* H x D x W inches (mm)	Exterior Dimensions* H x D x W inches (mm)	Ship Weight lb (kg)
ULT-350-5-A	3.1 (88)	115V 60Hz 1Ø	16/20 (P2)	17.0 x 17.0 x 19.0 (430 x 430 x 480)	44.5 x 29.9 x 30.2 (1156 x 760 x 766)	355 (161)
ULT-350-5-D	3.1 (88)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-350-5-V	3.1 (88)	230V 50Hz 1Ø	12/16 (P7)			
ULT-350-5-W	3.1 (88)	230V 50Hz 1Ø	12/13 (P8)			
ULT-750-5-A	6.8 (193)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 23.5 (670 x 480 x 600)	41.0 x 31.8 x 48.5 (1040 x 808 x 1230)	470 (213)
ULT-750-5-D	6.8 (193)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-750-5-V	6.8 (193)	230V 50Hz 1Ø	12/16 (P7)			
ULT-750-5-W	6.8 (193)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1050-5-A	10.3 (292)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 32.25 (670 x 480 x 900)	41.0 x 31.8 x 60.25 (1040 x 808 x 1530)	500 (227)
ULT-1050-5-D	10.3 (292)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1050-5-V	10.3 (292)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1050-5-W	10.3 (292)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1450-5-A	13.7 (388)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 47.0 (670 x 480 x 1190)	41.0 x 31.8 x 72.0 (1040 x 808 x 1830)	650 (295)
ULT-1450-5-D	13.7 (388)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1450-5-V	13.7 (388)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1450-5-W	13.7 (388)	230V 50Hz 1Ø	12/13 (P8)			
ULT-1750-5-A	17.1 (484)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 58.75 (670 x 480 x 1490)	41.0 x 31.8 x 83.75 (1040 x 808 x 2130)	650 (295)
ULT-1750-5-D	17.1 (484)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-1750-5-V	17.1 (484)	230V 50Hz 1Ø	12/16 (P7)			
ULT-1750-5-W	17.1 (484)	230V 50Hz 1Ø	12/13 (P8)			
ULT-2050-5-A	20.5 (580)	115V 60Hz 1Ø	16/20 (P2)	26.5 x 19.0 x 70.5 (670 x 480 x 1790)	41.0 x 31.8 x 95.5 (1040 x 808 x 2430)	685 (311)
ULT-2050-5-D	20.5 (580)	208/230V 60Hz 1Ø	12/15 (P4)			
ULT-2050-5-V	20.5 (580)	230V 50Hz 1Ø	12/16 (P7)			
ULT-2050-5-W	20.5 (580)	230V 50Hz 1Ø	12/13 (P8)			

*All dimensions and specifications subject to change without notice. External dimensions include allowances for cabinet door, hinges, latches, handles, and control panel protrusions.



Artisan Technology Group is your source for quality new and certified-used/pre-owned equipment

- FAST SHIPPING AND DELIVERY
- TENS OF THOUSANDS OF IN-STOCK ITEMS
- EQUIPMENT DEMOS
- HUNDREDS OF MANUFACTURERS SUPPORTED
- LEASING/MONTHLY RENTALS
- ITAR CERTIFIED SECURE ASSET SOLUTIONS

SERVICE CENTER REPAIRS

Experienced engineers and technicians on staff at our full-service, in-house repair center

*InstraView*SM REMOTE INSPECTION

Remotely inspect equipment before purchasing with our interactive website at www.instraview.com ↗

WE BUY USED EQUIPMENT

Sell your excess, underutilized, and idle used equipment. We also offer credit for buy-backs and trade-ins. www.artisanng.com/WeBuyEquipment ↗

LOOKING FOR MORE INFORMATION?

Visit us on the web at www.artisanng.com ↗ for more information on price quotations, drivers, technical specifications, manuals, and documentation

Contact us: (888) 88-SOURCE | sales@artisanng.com | www.artisanng.com