

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

ROAL
living energy

HIGH POWER DENSITY MULTI OUTPUT SMPS
Model RHPS200

Special Features

644 Watt Output Power
1.5U x 3U Form Factor
Multiple Output
Wide Input Voltage Range
No Minimum Load required
Stand-by Output Voltage 5V@2A
Remote sense
Active Power Factor Corrector
Fan Status Monitoring
Multiphase buck synchronous rectification
Input harmonics conform to EN61000-3-2 and EN61000-3-3
RoHS-6 Compliant (Directive 2002/95/EC)



Applications

Test & Measurement Equipment (PXI Modular Instruments),
Industrial Equipment

Input Specifications

Input Voltage	110 Vac, 230 Vac (90 to 264 Vac Full Range), Single Phase
Input Frequency	50 Hz, 60 Hz, 400 Hz (47 to 440 Hz)
Maximum Input Current	10 A @ 90 Vac
Maximum Inrush Current	40 A peak
Power Factor Corrector	≥0.95 (Full Load @ 230 Vac)
Input Protection	Internal fuse, 12.5 A

Output Specification

Output Power (max) 644 W

	+3.3V	+5V	+12V	-12V	+12VFan	5Vaux
Output Voltage	0 to 40 A	0 to 59 A*	0 to 19 A*	0 to 4.5 A	0 to 3.7 A	0 to 2 A
Output Current	±2.5%	±2.5%	±2.5%	±2.5%	±5%	±5%
Voltage Regulation	<50 mV	<50 mV	<50 mV	<50 mV	<120 mV	<50 mV
Ripple						

*Total power +12V plus +5V = 403W

Efficiency (typ.) >80% (Full Load @ 230Vac)
Hold-up Time >20 ms (Full Load)

Protections

Output Over Voltage	Latch Mode with recovery when fault condition is removed and the Power Supply is cycled ON/OFF
Output Overload	Constant Current Mode
Output Short Circuit	Constant Current Mode
Over Temperature	The Power Supply shuts down to protect itself before excessive temperature causes damage; It restarts when the temperature decreases within acceptable range

Features

Soft Start	
Remote ON-OFF	
Remote sense	on Output Voltages: +3.3V, +5V,+12V, -12V
Auxiliary voltage	available on stand by +5V @ 2 A
Thermal shutdown alarm	
Fan Rotation detector	The Power Supply indicates the status of each fan via a logic signal on the connector

Environmental

Operating Temperature	0 to +60 °C Full Load
Storage Temperature	-40 to +70 °C
Relative Humidity	5% to 95% (non-condensing)
Cooling	Internal Fans (temperature controlled speed for low acoustic noise and extended life performances)
MTBF	>500000 h (Calculated @ 25 °C ambient temperature – Telcordia Issue 1)

Safety


Safety Agency Approvals	$_{C}UR_{US}$, D, CB Certificate
Safety Standards	IEC 60950-1 Ed1.0 (2001); UL 60950-1:2003,First Edition, CSA 22.2 No 60950-1-03 1st Ed. April,1 2003

EMC Compliance

Conducted Emissions	EN55022 Class B
Harmonic Distortion	EN61000-3-2
Flicker and Fluctuation	EN61000-3-3
Electrostatic Discharge	EN61000-4-2
Fast Transients/bursts	EN61000-4-4
Input Line Surges	EN61000-4-5
Voltage Dips	EN61000-4-11
Shock and Vibration Test	

Physical Specification

Case	Fully enclosed metal box
Dimensions (HxWxD)	1.5U x 3U x 313 mm = 63.5 mm x 127 mm x 313 mm = 2.5 in x 5.0 in x 12.3 in
Weight	2.8 kg = 6.2 lb



Roal Electronics, S.p.A. may change product specifications and accordingly the information presented in this document. Customers are responsible for their products and applications using Roal Electronics, S.p.A. products. Roal Electronics, S.p.A. assumes no liability from the use of its products outside of specifications. No license is granted to any intellectual property rights by this document. ROAL ELECTRONICS, S.P.A. DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

Eu and RoW

ROAL Electronics S.p.A
Via Jesina 56/A
60022 – Castelfidardo (AN) - Italy
Tel:+39 071 721461
Fax:+ 39 071 72146 480

www.roallivingenergy.com

North America

ROAL Electronics USA, Inc.
701, Main St. Suite 405
Stroudsburg, PA18360
Phone: + 1 570 421 5750
Fax: +1 570 421 5687

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP