ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Find the *RSF Elektronik MSA 170.63* at our website: *Click HERE*

MSA 170

Scale model	System resolution	Accuracy grades *	Grating pitch *	Max. velocity (Edge separation a_{min})
• **Sinusoidal voltage signals 1 V_{pp}**				
MSA 170.03	depending on external subdividing	±3, ±5, µm/m	20 µm	1 m/s
• **Sinusoidal micro-current signals**				
MSA 170.13	depending on external subdividing	±3, ±5, µm/m	20 µm	1 m/s
• **Square wave Line Driver signals with integrated Subdividing**				
MSA 170.23	5 µm	±3, ±5 µm/m	20 µm	1 m/s (3.3 µs)
MSA 170.63	1 µm	±3, ±5 µm/m	20 µm	1 m/s (500 ns)
MSA 170.73	0.5 µm	±3, ±5 µm/m	20 µm	1 m/s (300 ns)
MSA 170.53	0.2 µm	±3, ±5 µm/m	20 µm	0.6 m/s (300 ns)
MSA 170.83	0.1 µm	±3, ±5 µm/m	20 µm	0.3 m/s (300 ns)

* **Other accuracy grades or grating pitches (e.g. Inch) upon request**

Standard measuring lengths: (mm)
50, 70, 120, 170, 220, 270, 320, 370, 420, 470, 520,

Measuring type: glass scale

Reference mark (RI): selectable
MSA 170.xx **K**
Distance coded Reference Marks (**K**): after travelling 20 mm the absolute position will be shown on the display.

MSA 170.xx
One Reference Mark in the middle of the measuring length, or 10 mm from either end of the measuring length (excluding ML 50 mm).

Option:
One Reference mark at any location, or two or more Reference Marks separated by distances of n x 25 mm.

Required moving force: < 1 N

Environmental sealing DIN 40050:
IP 53 (with standard sealing lips)
IP 64 with DA300 (DA300 see page 45)

Permissible vibration: 100 m/s² (40 to 2000 Hz)
Permissible shock: 150 m/s² (8 ms)

Permissible temperature:
-20°C to +70°C (storage), 0°C to +50°C (operation)

Weight (approx.)
22 g/100 mm (scale spar) + 35 g (scanning head without cable)

Signal-outputs (optional):

• **Sinusoidal voltage signals**
MSA 170.03

Power supply:
+5V ±5%, max. 75 mA (unloaded)

Output signals:
Encoder signals: 0.6 to 1,2 Vpp, typical 1 Vpp
with terminating resistor Zo = 120 Ω
Reference pulse:
0.2 to 0.85 Vpp, typical 0.4 V (useable component)
with terminating resistor Zo = 120 Ω

Max. output frequency:
100 kHz (with 3 m cable)

• **Sinusoidal micro-current signals**
MSA 170.13

Power supply:
+5 V ±5%, max. 75 mA

Output signals:
Encoder signals: 7 to 16 µApp,
typical 11.5 µApp at 1 KΩ

Reference pulse: 2 to 8 µA,
typical 5 µA (useable component) at 1 KΩ

Max. output frequency:
50 kHz (with 3 m cable)

• **Square wave signals** (single ended)
with integrated Subdividing Electronics

• **Square wave signals** (differential)
via Line Driver RS 422 standard
with integrated Subdividing Electronics
MSA 170.23 = times1
MSA 170.63 = times5
MSA 170.73 = times10
MSA 170.53 = times25
MSA 170.83 = times50

Power supply:
+5 V ±5%, max. 120 mA (unloaded)

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP