

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction


All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

ELECTRONICS & DEFENSE

TSYNC TIME CODE PROCESSORS

BOARD LEVEL TIMING



Safran TSync time code processors are complete synchronization systems on circuit cards ready for easy integration into mission-critical applications.

Each board has an onboard clock/oscillator that can phase-lock to a wide variety of external timing references and provides 5 ns resolution to the timekeeping hardware. The user can prioritize multiple references so if one is lost the unit will automatically switch to the next. The oscillator can be its own reference when it "freewheels" in the absence of a valid external synchronization source.

For applications where accuracy in this "holdover" conditional is essential, an upgrade to a higher precision ovenized crystal oscillator (OCXO) is available.

Four user-programmable time tag inputs may be used for multiple event capture at 10,000 events per second. Additionally, four programmable time match outputs are provided. Key to the TSync functionality is the ability to generate interrupts. Using a Safran driver package available for the latest versions of popular operating systems, you may configure your board using interrupt-driven algorithms to support your unique applications.

Safran TSync boards offer a high degree of ruggedness, customization and field upgradability. If a new application or change in deployment requires a different feature set, we can usually accommodate it.

Safran Electronics & Defense is with you every step of the way, building in the intelligence that gives you a critical advantage in observation, decision-making and guidance.

SAFRAN

Technical Specifications

Form Factors

- PCIe, VPX
- Rugged design
- Conduction-cooled ready
- Conformal coating available

Available References

- GNSS synchronization (multi-constellation)
- SAASM GPS option
- IRIG timecode
- 1PPS
- Internal clock

Timing Function

- IRIG timecode generator
- 1PPS and programmable periodic output
- 10 MHz output
- Event time-tagging
- Time-match/alarm signal

Internal Timekeeping

Disciplined On-Board Clock
- Frequency: 200 MHz
- Resolution: 5 ns
- Sync Sources: GNSS, IRIG, 1 PPS inputs

Reference Inputs

GNSS Reference
- Frequency: GPS L1 (1575.42 MHz), GLONASS L1 (1602 MHz); contact the factory for compatibility with QZSS (1572.42 MHz), BeiDou (1561.1 MHz) and Galileo (1575.42 MHz)

Internal GNSS Receiver Option
- Front panel connector: SMA jack (+5 V at 30 mA max supplied to power antenna pre-amp)
- Antenna sold separately
- SMA to Type N adapter cable included

SAASM GPS Receiver Option (and VPX Only)
- Antenna sold separately
- SMA to Type N adapter cable included with convection cooled models
- See table for specs

IRIG

Code Format (AM or DCLS)
IRIG A, IRIG B, IRIG G, NASA36 (auto-detect), IEEE 1344/C37.118 (selectable)

AM
- Amplitude: 500 mV p-p min,10 V p-p max
- Modulation Ratio: 2:1 min, 6:1 max
- Input Impedance: >10 K Ohms
- Common mode voltage: 3150 V DC max
- Input stability: Better than 100 ppm

DCLS (Differential or Single Ended)
- Differential amplitude: 200 mV p-p min, 5 V p-p max - 7V to +12 V DC max common mode voltage (RS-485 compatible)
- Single ended amplitude: +1.3V VIL min, +2 V VIH max (TTL compatible)

1PPS Input
- Amplitude: 0 V to +5.5 V, +0.8 V VIL, +2.0 V VIH
- 1 Hz Pulse, rising edge or falling edge active (selectable)
- 100 ns minimum pulse width
- Input Impedence: <150 pF capacitive

General Inputs (x4)

Event Time-Tag Input
- Amplitude: 0 V to +5.5 V, +0.8 V VIL, +2.0 V VIH
- Polarity (selectable): Positive or negative
- Pulse width: 50 ns min
- Repetition rate: More than 10,000 events per second
- Resolution: 5 ns

Outputs

IRIG

Code Format (AM or DCLS)
IRIG A, IRIG B, IRIG E, IRIG G, NASA36, IEEE 1344

AM
- Amplitude (adjustable): 500 mV p-p min, 5 V p-p max into 50 ohms
- Modulation ratio: 3:1
- Output impedance: 50 Ohms

DCLS
- Differential amplitude: 1.5 V p-p min, 3.3V p-p max, 31.5 V min,1.8 V max common mode voltage (RS-485 compatible)
- Single ended amplitude: (100 Ohm Load) +0.5V VOL max, +2.5 V VOH min (TTL compatible)

1PPS
- Signal level: TTL compatible, 4.3 V minimum, base-to-peak into 50 (for PCIe only: TTL compatible, 2.2 V minimum, base-to-peak into high impedance)
- Pulse width: Configurable Pulse width (200 ms by default)
- Rise time:< 10 ns
- Accuracy: See table

General Outputs (x4)

Periodic Output
- Amplitude: TTL compatible, 4.3 V minimum, base-to-peak into 50 (for PCIe only: TTL compatible, 2.2 V minimum, base-to-peak into high impedance)
- Period: 100 ns min, 60 s max in 20 ns steps (10 MHz – 0.17 Hz)
- Pulse width: 20 ns min, 999 ms max in 20 ns steps
- Polarity (selectable): Positive or negative

Internal SAASM GPS Reference (VPX Only):

	Value
SAASM GPS Receiver	MPE-S Type II GB-GRAM
Frequency	L1 (1575.42 MHz) and L2 (1227.6 MHz) simultaneous L1- C/A, P(Y) L2 - P(Y)
Satellite Tracking	1 to 12
TTFF - Time to First Fix (Synchronization Time)	Cold Start (with almanac download): 15 minutes Cold Start (no almanac download): 5 minutes Warm Start: 90 seconds Hot Start: 10 seconds
TTSF - Time to Subsequent Fix (Reacquisition Time)	< 20 seconds, Off or Stby < 15 minutes < 25 seconds, Off or Stby < 60 minutes < 70 seconds, Off < 60 minutes
Antenna Connector	Convection Cooled: SMA Jack (+3.3 V @ 9 mA to 60 mA) Conduction Cooled: MMCX Jack (+3.3 V @ 9 mA to 60 mA)

10 MHz Frequency Output:

	TCXO	OCXO	OCXO Rugged Option (VPX only)
Accuracy (average over 24 hours when GPS locked)	$1x10^{-11}$	$5x10^{-12}$	$2x10^{-12}$
Medium Term Stability (without GPS after 2 weeks of GPS lock)	$1x10^{-8}$/day	$2x10^{-9}$/day	$5x10^{-10}$/day
Phase Noise (dBc/Hz)			
@1 Hz	—	-90	—
@10 Hz	—	-113	-120
@100 Hz	-110	-120	-135
@1 KHz	-135	-140	-135
@10 KHz	-140	-150	-145
Signal Waveform & Levels: +13 dBm ±3 dB into 50 ohm, BNC			

1 PPS Output:

	TCXO	OCXO	OCXO Rugged Option (VPX only)
Accuracy to UTC (1-sigma locked to GPS)	±50 ns	±50 ns	±25 ns
Holdover (constant temp after 2 weeks of GPS lock)			
After 4 hours	12 µs	3 µs	1 µs
After 24 hours	450 µs	100 µs	25 µs

Time-Match/Alarm Output
- Amplitude: TTL compatible, 4.3 minimum, base-to-peak into 50
- 2.2 V minimum, base-to-peak into high impedance)
- Range: 100 days in 5 ns steps

10 MHz Output (Sine Wave)
- Harmonics: < -40 dBc
- Spurious: < -70 dBc
- Other specifications: See table

10 MHz LVDS Clocks via P2 Connector (VPX only)
- Four (4) LVDS differential pairs
- Impedance: 100 ohm
- Duty cycle: 50%
- Rise time: < 10 ns

General

PCIe Specifications
- Full-height mounting bracket provided
- Bus interface: Low-profile PCIe x1, Rev 1.1

VPX Specifications
- 3U VPX form-factor compliant to VITA-46
- 3.9" x 6.3" (100 mm x 160 mm)
- Connectors to VITA 46.0 for P0, P1, and P2
- Bus interface: PCIe x1, Rev 1.1

Conduction Cooling (VPX only)
- Per VITA 46/IEEE 1101.2 (VPX)
- Thermal frame available by request
- Component elevations available for custom thermal frame design

Power
See table below.

Environmental

Temperature
- Operating: -40°C to 80°C (-40°F to +176°F) at card edge with conduction cooled frame
- Storage: -40°C to 85°C (-40°F to +185°F)

Humidity
- Operating & storage: 95% RH at 60°C for 5 cycles of 48 hours/ cycle

Physical


Weight (base configurations)
- PCIe: 4.3 oz/122 g
- PMC: 3.1 oz/88 g
- cPCI: 6.1 oz/173 g (without thermo frame), 11.4 oz/323 g (with thermo frame)
- VPX: 6.3 oz/179 g (without thermo frame), 11.6 oz/329 g (with thermo frame)
- PCI-104: 3.4 oz/96 g

Safety & EMI
Certifications: RoHS, CE, FCC Class A

Drivers
Linux* 64/32 bit, Windows 7 64/32 bit, Windows Embedded

*Contact sales for specific kernel versions

Timing Board Use Cases



Power:

	+5 VDC	+3.3 VDC	+12 VDC	-12 VDC
PCIe	—	±5% @ 0.7A typ	±8% @ 0.2A typ	—
VPX	Vs3: +5%/-2.5% @ 0.4A typical TCXO, OCXO options @ 0.6A typical rugged OCXO option @ 1.4A maximum rugged OCXO option warm-up	Vs2: +5%/-2% @ 0.85A typ	Vs1: ±5% @ 0.2A typ	12V_AUX: -±5% @ 0.2A typ

POWERED BY TRUST

safran-navigation-timing.com

SAFRAN

June 3, 2025

Safran Electronics & Defense may, at any time and without notice, make changes or improvements to the products and services offered and/or cease producing or commercializing them.

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP