

ARTISAN®
TECHNOLOGY GROUP

Your **definitive** source for quality pre-owned equipment.

Artisan Technology Group
(217) 352-9330 | sales@artisantg.com | artisantg.com

Full-service, independent repair center
with experienced engineers and technicians on staff.

We buy your excess, underutilized, and idle equipment
along with credit for buybacks and trade-ins.

Custom engineering
so your equipment works exactly as you specify.

- Critical and expedited services
- In stock / Ready-to-ship
- Leasing / Rentals / Demos
- ITAR-certified secure asset solutions

Expert team | Trust guarantee | 100% satisfaction

All trademarks, brand names, and brands appearing herein are the property of their respective owners.

Visit our website - *Click HERE*

Sanyo MCO-17AI Incubator

SPECIFICATIONS of the Sanyo MCO-17AI:

Name:	Sanyo CO2 Incubator
Type	MCO-17AI
Outer Dimensions	620W x 685D x 900H (mm)
Inner Dimensions	490W x 505D x 665H (mm)
Effective Capacity	164 liters
Shelf Dimensions	450W x 450D x 10H (mm)
Capacity of Shelves	5 (standard), 17 (maximum)
Exterior Cabinet	Baked-on acrylic finish on galvanized steel
Interior Cabinet	Stainless steel (SUS-304)
Door	Baked-on acrylic finish on galvanized steel
Inner Door	Tempered glass
Shelves	Stainless steel (SUS-304)
Insulation	Rigid polyurethane foam (NON-CFC) + Glass wool
Heating Method	Air jacket
Humidifier	Natural evaporation from humidifying pan
Temperature Control	PID Control
CO2 Control	ON-OFF automatic control (chopperless infrared sensor)
Convection in the Box	Gentle Draft
Fan	Turbo fan (polypropylene), Outer diameter 80 mm
Fan Motor	2 polarities, Output 1W
Filter	0.3*u*m, Efficiency 99.97%
Power Source	Local voltage
Heaters	Total 424W
Gas Control Valve	Solenoid valve
Warning Function	Temperature, CO2 and the other alarm diagnosis system
Temperature Warning Indication	More than ±1◦C, the all figure of temperature flickers
CO2 Density Warning Indication	More than ±1%, the all figure of CO2 flickers
Overheat Warning	Manual set(35 ˜ 51◦C), OVER HEAT lamp warning, heater OFF
Capacity of Contact Point for Remote Alarm	AC125V, 0.4A; DC30V, 2A
Output of Remote Recorder Terminal	0 ˜100mV (temperature, CO2 density)
CO2 Connecting Inlet	4 ˜6 mm dia. Tube
Sample Gas Collecting Outlet	4 ˜6 mm dia. Tube
Weight	91 kg

ATTACHMENTS

Stainless Steel Shelves	5
Supports	5 sets
Tube for Gas	1
Humidifying Pan	1

PERFORMANCE

Suitable Temperature of Environmental Surrounding	0˚C ~ 35˚C
Extent of Temperature in the Unit	Room temperature +5˚C ~ 50˚C
Control Range of Temperature in the Unit	±.01˚C
Distribution of Temperature in the Unit	±.02˚C
Extent of CO2 Density	0 ~ 20.0%
Range of CO2 Regulation	±0.15%˚C*
Humidity in the Unit	95% R.H. or more
Secondary Pressure of CO2	0.3 kg/cm2G
Total Power Consumption	440W (maximum)

*Value measured at 37˚C. CO2 density of 5.0%.Ambient temperature 20˚C

OPTIONS

Co2 Pressure Regulator	250 kg/cm2G (primary), 2kg/cm2G (secondary)
Stainless Steel Shelf	The same as the attached shelf, supplied with supports
Stack Kit	MCO-17PS

Artisan Technology Group - Quality Instrumentation ... Guaranteed | (888) 88-SOURCE | www.artisantg.com

Artisan Technology Group is an independent supplier of quality pre-owned equipment

Gold-standard solutions

Extend the life of your critical industrial, commercial, and military systems with our superior service and support.

We buy equipment

Planning to upgrade your current equipment? Have surplus equipment taking up shelf space? We'll give it a new home.

Learn more!

Visit us at **artisantg.com** for more info on price quotes, drivers, technical specifications, manuals, and documentation.

Artisan Scientific Corporation dba Artisan Technology Group is not an affiliate, representative, or authorized distributor for any manufacturer listed herein.

We're here to make your life easier. How can we help you today?

(217) 352-9330 | sales@artisantg.com | artisantg.com

ARTISAN® TECHNOLOGY GROUP