



Fibre Channel HBAs

2-Gigabit PMC Host Bus Adapters FC23 Series

Features

- 64-bit / 66 MHz PMC
- 200 MB/s half-duplex data transfer rate; up to 400 MB/s full-duplex
- Multiple initiator capable
- Fiber-optic and copper interface support
- SCSI initiator and IP protocol support on selected operating systems
- Unique high-bandwidth, low-latency firmware & software running on industry-standard QLogic® Fibre Channel 2300 controller chips
- Automatically negotiates 1- or 2-gigabit Fibre Channel bit rate allowing a FC23 card to be connected to a FC22 card
- Single chip engine includes enhanced RISC processor, Fibre Channel protocol manager, 2-gigabit transceivers, and on-chip frame buffers



SBS' 2-Gigabit Fibre Channel PMC Host Bus Adapters (HBAs)

and supporting software tools provide the high sustained throughput and low latency required for demanding real-time and storage applications. Engineered to take full advantage of industry standard Fibre Channel features and benefits, SBS HBAs incorporate unique value-added features such as a streamlined protocol engine.

Optimized device drivers for various operating systems are provided for standard file system and network support. Please contact SBS for additional information and driver availability.



2-Gigabit Fibre Channel HBAs

Specifications

Fibre Channel PMC HBA

- FC-AL-2
- FC-FS
- SCSI-FCP
- SCSI-FCP-2

PMC Host Bus

- PCI Local Bus revision 2.2
- PMC IEEE P1386.1
- CMC IEEE P1386

Fibre Channel Chip

- ISP2300

RISC RAM

- 256Kbytes

Frame Buffers

- 6K receive FIFO
- 4K transmit FIFO

Protocol Support

- SCSI, FC-Tape, IP, and VI concurrently

Weight

- 0.10kg (3.5 ounces)

Power Requirements +5VDC

- Copper: 0.9A max
- Optical: 1.2A max, 1.4A typical

Temperature

- Operating: 0° to 55° C
- Storage: -20° to 70° C

Relative Humidity

- 5% to 95% non-condensing

Software Support

- Windows NT 4.0
- Windows 2000/XP
- Linux 2.4
- LynxOS 4.0
- VxWorks 5.4



Operating Ranges over Fiber Optic Cable

Fiber Type	Range at 2.125-Gigabit Rate	Range at 1.0625-Gigabit Rate
62.5 micron MFF	100 meters	200 meters
50.0 micron MFF	300 meters	500 meters

Standard Cable Configurations

Length	Type	Model
3-meter	HSSDC	FCC-HH-03
	HSSDC to 9-pin D	FCC-HD-03
5-meter	HSSDC	FCC-HH-05
	HSSDC to 9-pin D	FCC-HD-05
	Multimode LC to LC duplex fiber-optic	FCF-LC-05
	Multimode SC to LC duplex fiber-optic	FCF-SC-LC-05
10-meter	HSSDC	FCC-HH-10
	HSSDC to 9-pin D	FCC-HD-10
	Multimode LC to LC duplex fiber-optic	FCF-LC-10
	Multimode SC to LC duplex fiber-optic	FCF-SC-LC-10
20-meter	HSSDC	FCC-HH-20
	HSSDC to 9-pin D	FCC-HD-20

Fiber-optic cable available in custom lengths up to 500 meters

Fibre Channel HBA Configurations

Model Number	Configuration
FC23-PMC-1C	PMC with one HSSDC port
FC23-PMC-1F	PMC with one fiber port
Custom configurations also available; call SBS at (651) 905-4700 for details.	



SBS Fibre Channel interfaces, software, and associated products are provided in cooperation with Delphi Fibre Gear LLC, Costa Mesa, CA. QLogic is a registered trademark of QLogic Corporation.

Corporate Headquarters

2400 Louisiana Blvd. NE, #5-600
Albuquerque, NM 87110-4316
Tel 505.875.0600 Fax 505.875.0400
Email info@sbs.com

European Headquarters

Memminger Str. 14
D-86159 Augsburg, Germany
Tel +49-821-5034-0 Fax +49-821-5034-119
Email sales@sbs-europe.com



For additional contact information, please visit our web site at www.sbs.com

Specifications subject to change without notice. All trademarks and logos are property of their respective owners.
©2003 SBS Technologies, Inc. 20030819